

STORMWATER NOTES


1. All roof collection components (ie gutters / DPs etc) are to be located / sized by the Developments Hydraulic Consultant for a 5% AEP event capacity.
2. All Trunk Drainage pipes, as shown on this plan are to be minimum of 90mm dia uno.
3. All pipes to be uPVC to AS 1254:2002.
4. All pipes to be laid at the grade required to match pit invert levels.
5. All pipes to be installed and laid in accordance with AS 3500.3:2003.
6. Thrust blocks to be installed to the trunk drainage pipes in accordance with AS 3500.3:2003.
7. All roof guttering / down pipes / valley gutters / box gutters etc are to be sized and installed in accordance with AS 3500.3:2003.
8. All pits are to be proprietary uv resistant polypropylene or similar unless noted (approved by the Engineer) and are to include a min 50mm sediment trap in the base and a maximesh screen laid at 45° across the pit to protect the outlet pipe.
9. All pits greater than 600mm in depth are to be proprietary precast concrete (approved by the Engineer).
10. All pits greater than 1000mm in depth are to have adequate access requirements in accordance with OH&S/Workcover requirements (ie; minimum dimensions 900x600mm with step irons).
11. All works are to be inspected and certified by the Principle Certifying Authority prior to backfilling.
12. All works requiring certification by the Engineer will require a works as executed survey prepared by a registered Surveyor detailing all levels etc as on the Engineering plans.
13. The system is too be flushed and cleaned of all sediment and debris annually.
14. The system will require regular cleaning and maintenance to ensure its ability to function is maintained.
15. To ensure the system's ability to function is maintained it is to be inspected and certified as operating effectively by a licensed plumber every 5 years, and a engineer every 20yrs.
16. All existing predevelopment catchment area run-off conditions exiting the site are to be maintained with no run-off flows being diverted from the predevelopment condition.

STORMWATER MANAGEMENT PLAN

~ 1:100

All new drainage including gutters, dps, pipes etc are to be sized and installed to AS3500.3 requirements by a licensed plumber with the outlet to the on site dispersion system.
dp + rwh - down pipe + rain water head
Note - residence structure to be suspended above ngls for potential floodwater ingress
NOTE - NO ON SITE DETENTION REQUIRED AS DISPOSAL DIRECTLY TO CAREEL CREEK
GENERAL STORMWATER QUALITY REQUIREMENTS ACHIEVED UTILIZING BIOSWALE


0 1 2 3 4 5



TYPICAL PIPE & TRENCH DETAIL


~ 1 : 20

Note -
Bedding / overlay to be -
a) sand, free from rock, hard or sharp objects
b) max 14mm crushed rock or gravel
c) the excavated material free of rock, hard or sharp objects and broken up with no soil lumps > 75mm dia



DISPERSION TRENCH DETAIL

~ 1 : 20



TYPICAL PIT DETAIL

NTS

ISSUE:
DA 21. 03. 2025 Issued for DA submission

Barrenjoey Consulting Engineers Pty Ltd
Stormwater Structural Civil
PO Box 672
Avalon NSW 2107
M: 0818 620 330
E: lucas@bce@bigpond.com
ABN: 15124694917
ACN: 124694917


PROJECT:
PROPOSED NEW RESIDENCE
12A JOHN STREET
AVALON

DRAWING :
STORMWATER MANAGEMENT
& ASSETS PLAN

Job No :
18100525-12A
Document Certification
Barrenjoey Consulting Engineers Pty Ltd
per
Lucas Molloy MEA OP Eng NER Director

Drawing No
SW1 DA

A1




2.0m2 BIORETENTION SYSTEM PLAN

~ 1:50


WSUD SITE AREA BREAK-UP 12A & 12B John Street, Avalon

November 29, 2023



12A JOHN STREET
 ROOF: 213m²
 DRIVEWAY: 48m²
 LANDSCAPE: 333m²
 PATH: 35m²
 PAVERS: 20m²
 BYPASS LANDSCAPE: 51m²
 TOTAL AREA: 700m²

12B JOHN STREET
 ROOF: 215m²
 DRIVEWAY: 53m²
 LANDSCAPE: 227m²
 PATH: 33m²
 PAVERS: 11m²
 BYPASS LANDSCAPE: 75m²
 TOTAL AREA: 614m²




	Source	Roadload	% Reduction
Flow (ML/yr)	1.08	0.934	13.3
Total Suspended Solids (kg/yr)	77.1	3.99	94.8
Total Phosphorus (kg/yr)	0.228	0.0284	87.5
Total Nitrogen (kg/yr)	3.1	0.632	79
Gross Pollutants (kg/yr)	10.2	9	100

MUSIC MODEL SUMMARY


by OCEAN PROTECT MUSIC Version 6.3.0

Rainfall Station 66062 Sydney Observatory Hill, 6 Minute Time Step 1981 To 1985
 utilizing modified % impervious area, rainfall threshold, soil properties & pollutant concentration
 No drainage routing between nodes.
 85% Total Suspended Solids Reduction
 65% Total Phosphorus Reduction
 45% Total Nitrogen Reduction
 90% Gross Pollutant Reduction




BIOSWALE LONG SECTION

~ 1:20




BIOSWALE OUTLET / DISPERSION TRENCH DETAIL

~ 1:20



BIORETENTION SYSTEM CROSS SECTION


~ 1:20



- GENERAL NOTES**
1. THE MINIMUM CLEARANCE DEPENDS ON THE CONFIGURATION (SEE NOTE 2) AND THE LOCAL COUNCIL REQUIREMENTS.
 2. CLEARANCE FOR ANY PIT WITHOUT AN INLET PIPE (ONLY USED FOR SURFACE FLOW CANALS) AS LOW AS 100mm FOR 150mm DIA. THE RECOMMENDED CLEARANCE SHOULD BE GREATER OR EQUAL TO THE PIPE DIAMETER TO AVOID THE PIPE BEING OVERFLOWED.
 3. OCEAN PROTECT PROVIDES TWO FILTRATION BAG TYPES: 200 MICRON BAGS FOR HIGHER WATER QUALITY FILTERING AND A COARSE BAG FOR TARGETING GROSS POLLUTANTS.
 4. DIMENSIONS NOT TO SCALE.



OCEAN PROTECT
 OCEANGUARD
 TYPICAL ARRANGEMENTS
 SPECIFICATION DRAWING



FILTERRA BIOSCAPE SYSTEM

by OCEAN PROTECT

ISSUE:
 DA 21. 03. 2025 Issued for DA submission


Barrenjoey Consulting Engineers Pty Ltd
 Stormwater Structural Civil
 PO Box 672
 Avalon NSW 2107
 M: 0818 620 930
 E: lucas@bcebigpond.com
 ABN: 131 246 949 17
 ACN: 124 694 917

PROJECT:
 PROPOSED NEW RESIDENCE
 12A JOHN STREET
 AVALON

DRAWING :
 STORMWATER MANAGEMENT
 BIOSWALE PLANS & DETAIL



Job No :
 18100525-12A
 Document Certification
 Barrenjoey Consulting Engineers Pty Ltd
 per
 Lucas Molloy MEA OPEN NER Director

Drawing No
 SW2DA




SEDIMENT & EROSION CONTROL PLAN

All excavation works to be carried out in a safe building manner in accordance with NCC and industry standards etc.
Sediment and erosion control measures to be installed before any excavation works and monitored / improved continually to prevent sediment leaving the site, including immediate cleaning of spillage etc from vehicles leaving the property.
All material stock piles to be protected from rainfall and runoff at all times.



SEDIMENT FENCE

- SEDIMENT FENCE CONSTRUCTION NOTES:
1. CONSTRUCT SEDIMENT FENCES AS CLOSE AS POSSIBLE TO BEING PARALLEL TO THE CONTOURS OF THE SITE, BUT WITH SMALL RETURNS AS SHOWN IN THE DRAWING TO LIMIT THE CATCHMENT AREA OF ANY ONE SECTION. THE CATCHMENT AREA SHOULD BE SMALL ENOUGH TO LIMIT WATER FLOW.
 2. CUT A 150mm DEEP TRENCH ALONG THE UPSLOPE LINE OF THE FENCE FOR THE BOTTOM OF THE FABRIC TO BE ENTRENCHED.
 3. DRIVE 1.5m LONG STAR PICKETS INTO GROUND @ 2.5m INTERVALS (MAX.) AT THE DOWNSLOPE EDGE OF THE TRENCH. ENSURE ANY STAR PICKETS ARE FITTED WITH SAFETY CAPS.
 4. FIX SELF-SUPPORTING GEOTEXTILE TO THE UPSLOPE SIDE OF THE POSTS ENSURING IT GOES TO THE BASE OF THE TRENCH. FIX THE GEOTEXTILE WITH WIRE TIES OR AS RECOMMENDED BY THE MANUFACTURER. ONLY USE GEOTEXTILE SPECIFICALLY PRODUCED FOR SEDIMENT FENCING. THE USE OF SHADE CLOTH FOR THIS PURPOSE IS NOT SATISFACTORY.
 5. JOIN SECTIONS OF FABRIC AT A SUPPORT POST WITH A 150mm OVERLAP.
 6. BACKFILL THE TRENCH OVER THE BASE OF THE FABRIC AND COMPACT IT THOROUGHLY OVER THE GEOTEXTILE.



STOCKPILE CONSTRUCTION NOTES:

1. PLACE STOCKPILES MORE THAN 2 (PREFERABLY 5) METRES FROM EXISTING VEGETATION, CONCENTRATED WATER FLOW, ROADS AND HAZARD AREAS.
2. CONSTRUCT ON THE CONTOUR AS LOW, FLAT, ELONGATED MOUNDS.
3. WHERE THERE IS SUFFICIENT AREA, TOPSOIL STOCKPILES SHALL BE LESS THAN 2 METRES IN HEIGHT.
4. WHERE THEY ARE TO BE PLACED FOR MORE THAN 10 DAYS, STABILISE FOLLOWING THE APPROVED E.S.C.P. OR S.W.M.P. TO REDUCE THE C-FACTOR TO LESS THAN 0.10.
5. CONSTRUCT EARTH BANKS ON THE UPSLOPE SIDE TO DIVERT WATER AROUND STOCKPILES AND SEDIMENT FENCES 1 TO 2 METRES DOWNSLOPE.

STOCKPILES

SCALE N.T.S.

TEMPORARY CONSTRUCTION ACCESS
SEDIMENT TRAP

- NOTES:
1. THIS DEVICE IS TO BE LOCATED AT ALL EXITS FROM CONSTRUCTION SITE.
 2. THIS DEVICE IS TO BE REGULARLY CLEANED OF DEPOSITED MATERIAL SO AS TO MAINTAIN A 50mm DEEP SPACE BETWEEN PLANKS.
 3. ANY UNSEALED ROAD BETWEEN THIS DEVICE AND NEAREST ROADWAY IS TO BE TOPPED WITH 100mm THICK 40-70mm SIZE AGGREGATE.
 4. ALTERNATIVELY, THREE(3) PRECAST CONCRETE CATTLE GRIDS (AS MANUFACTURED BY HUMES CONCRETE MAY BE USED. 1, 2 & 3 ABOVE ALSO APPLY.

ISSUE:			Barrenjoey Consulting Engineers ptly ltd			PROJECT:		DRAWING :		Job No :		Drawing No	
DA			Stormwater Avalon NSW 2107 M 0418 620 530 E lucashee@bigpond.com ABN 15124694917 ACN 124694917			PROPOSED NEW RESIDENCE 12A JOHN STREET AVALON		SEDIMENT & EROSION CONTROL PLAN / DETAILS		18100525-12A		CIV1 DA	
										Document Certification Barrenjoey Consulting Engineers ptly ltd per Lucas Molloy MEA OP Eng NER Director			