

Technical specifications

Height Five standard heights: -800/1300 mm (lowered position/raised position)

- 1200/2100 mm (max width 2000 mm)

Width vertical profiles 31 mm.

Height horizontal profiles 15 mm.

Operation: Manual or electrical operation.

Glass 5 mm laminated glass in the moving part. The lower fixed part is supplied with 6 mm laminated glass in standard performance but can be supplied with other materials such as aluminium or wood.

Surface coating Satin anodized aluminium in standard performance. Others surface coatings are available at an additional cost, such as powder coating wet painting or anodizing

Svalson AB reserve the rights to make product changes without prior notice. This drawing is indicative only and may differ from the actual

|                 |                   | View Placeme    | View Placement |  |
|-----------------|-------------------|-----------------|----------------|--|
| section drawing |                   |                 | (              |  |
| <u> </u>        | N                 |                 |                |  |
|                 | View from outside | Drawn/Design    | Scale          |  |
| u Lä            | View from inside  | <sup>≜</sup> CM | 1:10           |  |
| Drawing Number  |                   | Rev.            | Sheet          |  |
| 14.GC           |                   | 04              | 1 (4)          |  |





| View Placement |  | nt                |              |       |
|----------------|--|-------------------|--------------|-------|
| S              | section drawing $\leftarrow \rightarrow +$ |                   |              |       |
|                |  | View from outside | Drawn/Design | Scale |
| aι             | u Lä                                       | View from inside  | CM           | 1:10  |
|                | Drawing Number                             |                   | Rev.         | Sheet |
| 3              | 14.GC                                      |                   | 04           | 3 (4) |









