
## NOTES

ALL DIMENSIONS SHOULD BE VERIFIED ON SITE BY THE BUILDER WHO WILL BE RESPONSIBLE FOR THE ACCURATE SETTING OUT OF THE JOB

ALL CONSTRUCTION IS TO COMPLY WITHTHE RELEVANT BUILDING CODES AND LOCAL COUNCIL REQUIREMENTS ALL DIMENSIONS THAT RELATE TO SITE BOUNDARIES AND EASEMENTS ARE SUBJECT TO VERIFICATION BY A SITE SURVEY ROOF WATER AND SUBSOIL DRAINAGE TO BE DISPODED OF IN THE APPROVED MANNER OR AS DIRECTED DOWN PIPE LOCATION TO BE DETERMINED BY THE ROOF PLUMBER ELECTRICAL, POWER AND LIGHT OUTLETS TO BE DETERMINED BY THE OWNER STRUCTURAL DETAIL AND DESIGN TO BE APPROVED BY A STRUCTURAL ENGINEER ANY ADDITIONAL DETAILING SHALL BE RESOLVED BETWEEN THE OWNER AND THE BUILDER ALL LEVELS TO AUSTRALIAN HEIGHT DATUM



14.4.21 DELETE SECONDARY DWELLING / REDUCE FRONT DECK

PROPOSED ALTERATIONS & ADDITIONS WISEMAN RESIDENCE 63 MARINE PARADE AVALON BEACH

DWG 0319 1/5 SHIMDESIGN architectural design and drafting k2shimeld@gmail.com

12.5.20 POOL DECK DELETED/ CONDITIONS OF CONSENT FOR C.C.


24-11-14 REDUCE ROOF TO DECK DELETE CABANA ROOF


FREESTANDING GARAGE IN LIEU


10-12-14 MODIFICATION TO DA NO 263/14


**MARCH 2019 (MOD APRIL 2022)** 

PERGOLA IN LIEU









## NATIONAL CONSTRUCTION REQUIREMENTS

PEST CONTROL TO COMPLY WITH NCC PART 3.1.3 AS3660.1-2000/20014
BATHROOM WINDOW GLAZING TO BE TOUGHENED GLASS
STAIR CONSTRUCTION TO COMPLY WITH NCC PART 3.9.1
BALUSTRADES AND HANDRAILS TO COMPLY WITH NCC PART 3.9
SMOKE ALARMS AS INDICATED ON PLAN TO COMPLY WITH NCC PART 3.7.2

## **BASIX NOTES**

SWIMMING POOL TO BE OUTDOORS, CAPACITY NOT GREATER THAN 16 KILOLITRES , TO HAVE POOL COVER AND POOL PUMP TIMER AND SOLAR HEATING WITH GAS BOOSTER

SPA CAPACITY NOT GREATER THAN 2.7 KILOLITRES, MUST HAVE SPA COVER AND SPA PUMP TIMER. SPA HEATER TO BE GAS

A RAINWATER TANK WITH MINIMUM 1181LTS CAPACITY TO BE INSTALLED, COLLECTING AT LEAST 256 M2 OF ROOF AREA OF RAINWATER RUNOFF AND CONNECTED TO AT LEAST ONE TAP LOCATED WITHIN 10M OF THE EDGE OF THE POOL/SPA

EXTERNAL FRAMED WEATHERBOARD CLAD WALLS TO HAVE MIN. R1.3 INSULATION (R1.7 INC. CONSTRUCTION) SUSPENDED FLOOR WITH ENCLOSED SUBFLOOR TO HAVE MIN. R0.6 INSULATION (R1.30 INC. CONSTRUCTION) ROOF WITH DARK SOLAR ABSORPTANCE TO HAVE FOIL SARKING AND CEILINGS WITH R3.0 CEILING INSULATION

BATHROOM AND KITCHEN TAPS AND SHOWER TO HAVE MINIMUM 3 STAR RATING/MAX 9LTRS PER MINUTE TOILETS TO HAVE MINIMUM 3 STAR RATING, MAXIMUM 4 LTR FLUSH MINIMUM 40% NEW OR ALTERED LIGHT FITTINGS TO BE FLUORESCENT, COMPACT FLURO OR LED LAMPS. WINDOWS 1-18 IN ACCORDANCE WITH BASIX CERTIFICATE A 506514 DATED 08 SEPT 2023

