BASIX°Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A378097 03

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Thursday, 02, July 2020

To be valid, this certificate must be lodged within 3 months of the date of issue.



Description of project

Project address				
Project name	25 The Outlook_03			
Street address	25 The Outlook Road Bilgola Plateau 2107			
Local Government Area	Northern Beaches Council			
Plan type and number	Deposited Plan 16902			
Lot number	190			
Section number				
Project type				
Dwelling type	Separate dwelling house			
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and does not include a pool (and/or spa).			

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Daniel Raymond Architect

ABN (if applicable): 612713425

BASIX Certificate number: A378097_03 page 2 / 6

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		✓	✓
Fixtures	<u>.</u>		
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		✓	✓
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		✓	✓
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		✓	

BASIX Certificate number: A378097_03 page 3 / 6

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check		
Insulation requirements							
The applicant must construct the new or altered the table below, except that a) additional insular is not required for parts of altered construction	√	√	✓				
Construction	Additional insulation required (R-value) Other specifications						
suspended floor with open subfloor: framed (R0.7).	R0.8 (down) (or R1.50 including construction)						
external wall: cavity brick	nil						
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)						

BASIX Certificate number: A378097_03

Glazing requ	uirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows and	d glazed do	ors							
					nading devices, in accordance with reach window and glazed door.	the specifications listed in the table below.	✓	~	✓
The following r	equirements i	must also	be satisfi	ed in relation	n to each window and glazed door:			✓	✓
have a U-value	Each window or glazed door with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.							✓	✓
For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.							✓	✓	✓
Pergolas with p	oolycarbonate	roof or si	milar tran	slucent mate	erial must have a shading coefficien	t of less than 0.35.		✓	✓
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.							✓	✓	
Windows a			lazing r	equireme					
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	Distance (m)	Shading device	Frame and glass type			
W01	S	1	0	0	awning (adjustable) >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W02	N	0.8	0	0	awning (adjustable) >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W03	E	2.7	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W04	E	1.5	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W05	Е	1.5	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			

BASIX Certificate number: A378097_03 page 5 / 6

Glazing requi	irements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	Distance (m)	Shading device	Frame and glass type			
D01	Е	3.2	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			

BASIX Certificate number: A378097_03

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.