page 1 / 7

BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A401580 02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv Date of issue: Thursday, 04, March 2021

To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project address	
Project name	Bell_02
Street address	45 Ernest Street Balgowlah Heights 2093
Local Government Area	Northern Beaches Council
Plan type and number	Deposited Plan 12817
Lot number	3
Section number	
Section number Project type	
	Separate dwelling house

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Rapid Plans

ABN (if applicable): 43150064592

Pool and Spa	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Rainwater tank			
The applicant must install a rainwater tank of at least 1003 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rainwater runoff from at least 76.3 square metres of roof area.		\checkmark	\checkmark
The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool.		\checkmark	\checkmark
Outdoor swimming pool			
The swimming pool must be outdoors.	\checkmark	\checkmark	
The swimming pool must not have a capacity greater than 35.2 kilolitres.	\checkmark	\checkmark	\checkmark
The swimming pool must have a pool cover.		\checkmark	~
The applicant must install a pool pump timer for the swimming pool.		\checkmark	~
The applicant must install the following heating system for the swimming pool that is part of this development: electric heat pump.		\checkmark	\checkmark

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Fixtures	1		
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		\checkmark	~
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		\checkmark	~
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		\checkmark	

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
	tion is not required where the area of new con	is) in accordance with the specifications listed in struction is less than 2m2, b) insulation specified	~	~	~
Construction	Additional insulation required (R-value)	Other specifications			
concrete slab on ground floor.	nil				
external wall: concrete block/plasterboard	R1.18 (or R1.70 including construction)				

	uirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows and	d glazed do	ors						1	1
					hading devices, in accordance with r each window and glazed door.	the specifications listed in the table below.	~	\checkmark	~
The following re	equirements i	must also	be satisfi	ed in relation	n to each window and glazed door:			~	\checkmark
have a U-value must be calcula	e and a Solar ated in accord	Heat Gair dance with	n Coefficie h National	ent (SHGC) Fenestratio	no greater than that listed in the tabl	ar glazing, or toned/air gap/clear glazing must le below. Total system U-values and SHGCs a. The description is provided for information		~	~
					f each eave, pergola, verandah, bal than 2400 mm above the sill.	cony or awning must be no more than 500 mm	~	~	~
Dennelse uddies	a a lu ca a rha a ra a ta								
Pergolas with p	oolycarbonate	e roof or s	imilar tran	slucent mate	erial must have a shading coefficien	t of less than 0.35.		\checkmark	\checkmark
Pergolas with fi	ixed battens r	must have	e battens	parallel to th	Ũ	t of less than 0.35. ch they are situated, unless the pergola also	_	\checkmark	~
Pergolas with fi shades a perpe Windows ar	ixed battens r endicular wind	must have dow. The doors g	e battens spacing b lazing r	parallel to th etween batte	e window or glazed door above whic ens must not be more than 50 mm.			~	~
Pergolas with fi shades a perpe	ixed battens r endicular wind	must have dow. The doors g	e battens spacing b lazing r	parallel to th etween batte equireme	e window or glazed door above whic ens must not be more than 50 mm.			~	~
Pergolas with fi shades a perpe Windows an Window / door no.	ixed battens r endicular wind	must have dow. The doors g Area of glass inc. frame	e battens spacing b lazing r Oversha Height	parallel to th etween batte equireme adowing Distance	e window or glazed door above whic ens must not be more than 50 mm. nts	ch they are situated, unless the pergola also		~	~
Pergolas with fi shades a perpe Windows an Window / door no.	ixed battens r endicular wind nd glazed o Orientation	must have dow. The doors g Area of glass inc. frame (m2)	e battens spacing b lazing r Oversha Height (m)	parallel to th etween batte equireme adowing Distance (m)	e window or glazed door above whic ens must not be more than 50 mm. nts Shading device	ch they are situated, unless the pergola also Frame and glass type improved aluminium, single clear, (U-value:		~	~
Pergolas with fi shades a perpe Windows ar Window / door	ixed battens r endicular wind nd glazed o Orientation W	must have dow. The doors g Area of glass inc. frame (m2) 0.6	e battens spacing b lazing r Oversha Height (m) 0	parallel to the etween batte equireme adowing Distance (m) 0	e window or glazed door above whiteens must not be more than 50 mm.	Frame and glass type improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75) improved aluminium, single pyrolytic low-e,			× •

BASIX Certificate number: A401580_02

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
"
"
"
"
"
"
"
"
"
"
Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " / " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.