BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1241650S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Friday, 10 December 2021 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project summary	
Project name	5 NORMANDY ROAD, ALLAMBIE HEIGHTS
Street address	5 NORMANDY Road ALLAMBIE HEIGHTS 2100
Local Government Area	Northern Beaches Council
Plan type and plan number	deposited 752038
Lot no.	2358
Section no.	-
Project type	separate dwelling house - secondary dwelling
No. of bedrooms	1
Project score	
Water	✓ 40 Target 40
Thermal Comfort	V Pass Target Pass
Energy	V 50 Target 50

Certificate Prepared by

Name / Company Name: rkdesigns

ABN (if applicable): 39330033053

Description of project

Project a	address
-----------	---------

Project name	5 NORMANDY ROAD, ALLAMBIE HEIGHTS			
Street address	5 NORMANDY Road ALLAMBIE HEIGHTS 2100			
Local Government Area	Northern Beaches Council			
Plan type and plan number	Deposited Plan 752038			
Lot no.	2358			
Section no.	-			
Project type				
Project type	separate dwelling house - secondary dwelling			
No. of bedrooms	1			
Site details				
Site area (m²)	1057			
Roof area (m ²)	75			
Conditioned floor area (m2)	39.58			
Unconditioned floor area (m2)	4.65			
Total area of garden and lawn (m2)	50			
Roof area (m2) of the existing dwelling	225			
No. of bedrooms in the existing dwelling	4			

Assessor details and thermal lo	bads
Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m ² .year)	n/a
Area adjusted heating load (MJ/m ² .year)	n/a
Ceiling fan in at least one bedroom	n/a
Ceiling fan in at least one living room or other conditioned area	n/a
Project score	
Water	V 40 Target 40
Thermal Comfort	V Pass Target Pass
Energy	✓ 50 Target 50

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 3 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 3 star in the kitchen in the development.		 	
The applicant must install basin taps with a minimum rating of 3 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 1000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 74.8 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
all toilets in the development		 Image: A second s	~
 the cold water tap that supplies each clothes washer in the development 		 Image: A second s	~

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - other/undecided	2.40 (including construction)	
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 3.5 (up), roof: foil/sarking	framed; medium (solar absorptance 0.475-0.70)

• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.

Note • In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	 Image: A set of the set of the	~
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	 Image: A set of the set of the	~
The following requirements must also be satisfied in relation to each window and glazed door:	~	 Image: A set of the set of the	~
• For the following glass and frame types, the certifier check can be performed by visual inspection.			-
- Aluminium single clear			
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			
 Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column. 	~	~	~

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North-East facing					
W02	700	2400	aluminium, single, clear	eave 450 mm, 850 mm above head of window or glazed door	>4 m high, <2 m away
W03	700	2400	aluminium, single, clear	eave 450 mm, 850 mm above head of window or glazed door	>4 m high, 2-5 m away
W04	700	2400	aluminium, single, clear	eave 450 mm, 850 mm above head of window or glazed door	>4 m high, 2-5 m away
W09	700	610	aluminium, single, clear	eave 450 mm, 850 mm above head of window or glazed door	>4 m high, 2-5 m away
South-East facing	1				
W05	3048	2400	aluminium, single, clear	eave 2500 mm, 600 mm above head of window or glazed door	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
South-West facing					
W06	700	2400	aluminium, single, clear	eave 450 mm, 740 mm above head of window or glazed door	>4 m high, <2 m away
W07	400	1810	aluminium, single, clear	eave 450 mm, 280 mm above head of window or glazed door	>4 m high, <2 m away
W08	1200	610	aluminium, single, clear	eave 450 mm, 280 mm above head of window or glazed door	>4 m high, <2 m away

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric heat pump with a performance of 36 to 40 STCs or better.	~	v	~
Cooling system			
The living areas must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		~	~
The bedrooms must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		~	~
Heating system			
The living areas must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	~
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		 Image: A set of the set of the	~
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		 Image: A set of the set of the	~
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		 Image: A set of the set of the	~
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		v	~
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
 at least 1 of the bedrooms / study; dedicated 		 Image: A second s	~
 at least 1 of the living / dining rooms; dedicated 		 Image: A set of the set of the	~
the kitchen; dedicated		_	~

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
all bathrooms/toilets; dedicated		>	~
the laundry; dedicated		~	~
all hallways; dedicated		~	~
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.	~	>	~
Other			
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.		~	
The applicant must install a fixed indoor or sheltered clothes drying line as part of the development.		_	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a vi in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a vi in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a vi in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.