

Nationwide House Energy Rating Scheme

NatHERS Certificate No. 0006666317

Generated on 12 Oct 2021 using BERS Pro v4.4.0.6 (3.21)

Property

Address Ingleside Road , Ingleside , NSW , 2101
Lot/DP 10/12130
NCC Class* 1A
Type New Dwelling

Plans

Main Plan BROWN
Prepared by Stothard Projects

Construction and environment

Assessed floor area (m²)*	Exposure Type
Conditioned* 263.0	Suburban
Unconditioned* 57.0	NatHERS climate zone
Total 319.0	56
Garage 37.0	



Accredited assessor


Name Daniel.Warda
Business name Energi Thermal Assessors Pty Ltd
Email daniel@energiassessments.com.au
Phone 0452504125
Accreditation No. 101182
Assessor Accrediting Organisation
ABSA
Declaration of interest Declaration not completed

National Construction Code (NCC) requirements

The NCC's requirements for NatHERS-rated houses are detailed in 3.12.0(a)(i) and 3.12.5 of the NCC Volume Two. For apartments the requirements are detailed in J0.2 and J5 to J8 of the NCC Volume One.

In NCC 2019, these requirements include minimum star ratings and separate heating and cooling load limits that need to be met by buildings and apartments through the NatHERS assessment. Requirements additional to the NatHERS assessment that must also be satisfied include, but are not limited to: insulation installation methods, thermal breaks, building sealing, water heating and pumping, and artificial lighting requirements. The NCC and NatHERS Heating and Cooling Load Limits (Australian Building Codes Board Standard) are available at www.abcb.gov.au.

State and territory variations and additions to the NCC may also apply.



Thermal performance

Heating	Cooling
39.4	25.9
MJ/m²	MJ/m²

About the rating

NatHERS software models the expected thermal energy loads using information about the design and construction, climate and common patterns of household use. The software does not take into account appliances, apart from the airflow impacts from ceiling fans.

Verification

To verify this certificate, scan the QR code or visit [hstar.com.au/QR/Generate?](http://hstar.com.au/QR/Generate?p=1jzrYHDda)

[p=1jzrYHDda](http://hstar.com.au/QR/Generate?p=1jzrYHDda).
When using either link, ensure you are visiting hstar.com.au



Certificate check

Ensure the dwelling is designed and then built as per the NatHERS Certificate. While you need to check the accuracy of the whole Certificate, the following spot check covers some important items impacting the dwelling's rating.

Genuine certificate

Does this Certificate match the one available at the web address or QR code in the verification box on the front page? Does the set of NatHERS-stamped plans for the dwelling have a Certificate number on the stamp that matches this Certificate?

Ceiling penetrations*

Does the 'number' and 'type' of ceiling penetrations (e.g. downlights, exhaust fans, etc) shown on the stamped plans or installed, match what is shown in this Certificate?

Windows

Does the installed window meet the substitution tolerances (SHGC and U-value) and window type, of the window shown on this Certificate?

Apartment entrance doors

Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.

Exposure*

Has the appropriate exposure level (terrain) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".

Provisional* values

Have provisional values been used in the assessment and, if so, noted in "additional notes" below?

Additional notes

Window and glazed door *type and performance*

Default* windows

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

Custom* windows

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
WID-006-04 A	WID-006-04 A AI Residential Sliding Window SG 638mm Comfort Plus	4.5	0.46	0.44	0.48
WID-001-04 A	WID-001-04 A AI Residential Awning Window SG 638mm Comfort Plus	5.0	0.40	0.38	0.42
WID-005-04 A	WID-005-04 A AI Residential Internal Sliding Door SG 638mm Comfort Plus	4.4	0.44	0.42	0.46

Window and glazed door *schedule*

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orientation	Window shading device*
Laundry	WID-006-04 A	n/a	600	2100	n/a	45	SW	No
Entry	WID-001-04 A	n/a	2400	800	n/a	00	NE	No
Media	WID-001-04 A	n/a	2100	2710	n/a	30	NE	No
Kitchen/Living	WID-001-04 A	n/a	2100	3610	n/a	30	NE	No
Kitchen/Living	WID-001-04 A	n/a	2100	3070	n/a	30	NE	No
Kitchen/Living	WID-005-04 A	n/a	2700	3576	n/a	60	SE	No
Kitchen/Living	WID-005-04 A	n/a	2700	3576	n/a	60	SE	No
Scullery	WID-006-04 A	n/a	600	1810	n/a	45	SW	No
Powder	WID-006-04 A	n/a	600	1810	n/a	45	SW	No
Bedroom 1	WID-005-04 A	n/a	2100	3576	n/a	60	SE	No
Bedroom 1	WID-005-04 A	n/a	2100	2410	n/a	45	NE	No
B1 WIR	WID-001-04 A	n/a	1800	600	n/a	90	SE	No
Ensuite	WID-001-04 A	n/a	1414	850	n/a	90	SE	No
Living	WID-001-04 A	n/a	1457	1810	n/a	45	SW	No
Living	WID-005-04 A	n/a	2100	2410	n/a	90	NE	No
Living	WID-005-04 A	n/a	2100	2410	n/a	90	NE	No
Living	WID-001-04 A	n/a	714	2410	n/a	00	NE	No Shading
Living	WID-001-04 A	n/a	714	2410	n/a	00	NE	No Shading
Bedroom 2	WID-001-04 A	n/a	1500	2710	n/a	30	NE	No
Bedroom 3	WID-001-04 A	n/a	1500	2710	n/a	30	NE	No
Bedroom 4	WID-001-04 A	n/a	1450	2650	n/a	30	NW	No
Bath	WID-001-04 A	n/a	1457	1810	n/a	45	SW	No
Bedroom 5	WID-006-04 A	n/a	857	2650	n/a	45	SW	No

Roof window *type and performance*

Default* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

Custom* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
VEL-011-01 W	Glass	2.6	0.24	0.23	0.25

Roof window schedule

Location	Window ID	Window no.	Opening %	Height (mm)	Width (mm)	Orientation	Outdoor shade	Indoor shade
Kitchen/Living	VEL-011-01 W	n/a	0	1180	550	SW	No	No

Skylight type and performance

Skylight ID	Skylight description
GEN-04-008a	Double-glazed clear, Timber and Aluminium Frame

Skylight schedule

Location	Skylight ID	Skylight No.	Skylight shaft length (mm)	Area (m ²)	Orientation	Outdoor shade	Diffuser	Skylight shaft reflectance
Study	GEN-04-008a	n/a	500	0.60	NE	None	No	0.50
Living	GEN-04-008a	n/a	500	0.60	SW	None	No	0.50
Living	GEN-04-008a	n/a	500	0.60	SW	None	No	0.50

External door schedule

Location	Height (mm)	Width (mm)	Opening %	Orientation
Garage 1	2340	5000	90	NE
Entry	2340	1200	90	NE

External wall type

Wall ID	Wall type	Solar absorptance	Wall shade (colour)	Bulk insulation (R-value)	Reflective wall wrap*
EW-1	Single Skin Brick	0.50	Medium	No insulation	No
EW-2	Brick Veneer	0.50	Medium	Bulk Insulation R2	No
EW-3	Fibro Cavity Panel Direct Fix	0.50	Medium	Anti-glare foil with bulk no gap R2	No

External wall schedule

Location	Wall ID	Height (mm)	Width (mm)	Orientation	Horizontal shading feature* maximum projection (mm)	Vertical shading feature (yes/no)
Garage 1	EW-1	2600	6100	NE	1400	NO
Garage 1	EW-2	2600	800	SE	14500	YES
Garage 1	EW-2	2600	6095	NW	100	NO
Laundry	EW-2	2600	3695	SW	100	NO
Laundry	EW-2	2600	1795	NW	100	NO
Mudroom	EW-2	2600	500	SE	100	YES
Mudroom	EW-2	2600	3595	SW	100	NO
Entry	EW-2	2600	2390	NE	2200	YES

Location	Wall ID	Height (mm)	Width (mm)	Orientation	Horizontal shading feature* maximum projection (mm)	Vertical shading feature (yes/no)
Entry	EW-2	2600	2290	SW	100	YES
Media	EW-2	3200	2200	NW	8600	YES
Media	EW-3	3200	3895	NE	1500	NO
Kitchen/Living	EW-3	3200	8095	NE	1500	NO
Kitchen/Living	EW-3	3200	9400	SE	100	NO
Kitchen/Living	EW-2	3200	6295	SW	100	NO
Scullery	EW-2	3200	2295	SW	100	NO
Scullery	EW-2	3200	600	NW	100	YES
Powder	EW-2	3200	2290	SW	100	YES
Bedroom 1	EW-3	2600	4095	SE	2300	NO
Bedroom 1	EW-3	2600	800	NW	14600	YES
Bedroom 1	EW-3	2600	4600	NE	600	NO
B1 WIR	EW-3	2600	2095	SE	2300	NO
B1 WIR	EW-3	2600	1900	SW	600	YES
Ensuite	EW-3	2600	2595	SE	600	YES
Ensuite	EW-3	2600	2695	SW	600	NO
Living	EW-3	2600	2290	SW	600	NO
Living	EW-3	2600	6690	NE	2500	YES
Bedroom 2	EW-3	2600	3895	NE	600	NO
Bedroom 2	EW-3	2600	800	SE	13600	YES
Bedroom 3	EW-3	2600	4795	NW	600	NO
Bedroom 3	EW-3	2600	3395	NE	600	NO
Bedroom 4	EW-3	2600	4095	SW	600	NO
Bedroom 4	EW-3	2600	3995	NW	600	NO
Bath	EW-3	2600	3190	SW	600	NO
Bedroom 5	EW-3	2600	4390	SW	600	NO

Internal wall type

Wall ID	Wall type	Area (m ²)	Bulk insulation
IW-1 - Cavity wall, direct fix plasterboard, single gap		30.00	Bulk Insulation, No Air Gap R2
IW-2 - Cavity wall, direct fix plasterboard, single gap		263.00	No insulation

Floor type

Location	Construction	Area (m ²)	Sub-floor ventilation	Added insulation (R-value)	Covering
Garage 1	Waffle pod slab 300 mm 100mm	36.70	None	Waffle Pod 300mm	Bare
Laundry	Waffle pod slab 300 mm 100mm	6.40	None	Waffle Pod 300mm	Ceramic Tiles 8mm

Location	Construction	Area (m ²)	Sub-floor ventilation	Added insulation (R-value)	Covering
Mudroom	Waffle pod slab 300 mm 100mm	6.20	None	Waffle Pod 300mm	Ceramic Tiles 8mm
Entry	Waffle pod slab 300 mm 100mm	16.40	None	Waffle Pod 300mm	Ceramic Tiles 8mm
Media	Waffle pod slab 300 mm 100mm	18.20	None	Waffle Pod 300mm	Ceramic Tiles 8mm
Kitchen/Living	Waffle pod slab 300 mm 100mm	69.00	None	Waffle Pod 300mm	Ceramic Tiles 8mm
Scullery	Waffle pod slab 300 mm 100mm	7.00	None	Waffle Pod 300mm	Ceramic Tiles 8mm
Powder	Waffle pod slab 300 mm 100mm	5.60	None	Waffle Pod 300mm	Ceramic Tiles 8mm
Hall	Waffle pod slab 300 mm 100mm	5.80	None	Waffle Pod 300mm	Ceramic Tiles 8mm
Bedroom 1/Kitchen/Living	AAC Above Plasterboard 75mm	20.40		No Insulation	Carpet+Rubber Underlay 18mm
B1 WIR/Kitchen/Living	AAC Above Plasterboard 75mm	7.20		No Insulation	Carpet+Rubber Underlay 18mm
Ensuite/Kitchen/Living	AAC Above Plasterboard 75mm	6.30		No Insulation	Ceramic Tiles 8mm
Ensuite/Scullery	AAC Above Plasterboard 75mm	0.50		No Insulation	Ceramic Tiles 8mm
Study/Media	AAC Above Plasterboard 75mm	2.80		No Insulation	Carpet+Rubber Underlay 18mm
Study/Kitchen/Living	AAC Above Plasterboard 75mm	5.10		No Insulation	Carpet+Rubber Underlay 18mm
Study/Hall	AAC Above Plasterboard 75mm	0.90		No Insulation	Carpet+Rubber Underlay 18mm
Living/Entry	AAC Above Plasterboard 75mm	10.40		No Insulation	Carpet+Rubber Underlay 18mm
Living/Media	AAC Above Plasterboard 75mm	12.20		No Insulation	Carpet+Rubber Underlay 18mm
Living/Kitchen/Living	AAC Above Plasterboard 75mm	1.60		No Insulation	Carpet+Rubber Underlay 18mm
Living/Hall	AAC Above Plasterboard 75mm	2.50		No Insulation	Carpet+Rubber Underlay 18mm
Living	Suspended AAC (75mm) 75mm	1.60	Totally Open	No Insulation	Carpet+Rubber Underlay 18mm
Upper Hall/Garage 1	AAC Above Plasterboard 75mm	4.40		No Insulation	Carpet+Rubber Underlay 18mm
Upper Hall/Entry	AAC Above Plasterboard 75mm	2.00		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2/Garage 1	AAC Above Plasterboard 75mm	6.40		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2/Entry	AAC Above Plasterboard 75mm	2.30		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Suspended AAC (75mm) 75mm	6.20	Totally Open	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 3/Garage 1	AAC Above Plasterboard 75mm	11.60		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 3	Suspended AAC (75mm) 75mm	4.60	Totally Open	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 4/Garage 1	AAC Above Plasterboard 75mm	9.60		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 4/Laundry	AAC Above Plasterboard 75mm	4.70		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 4/Mudroom	AAC Above Plasterboard 75mm	0.50		No Insulation	Carpet+Rubber Underlay 18mm
Bath/Garage 1	AAC Above Plasterboard 75mm	2.10		No Insulation	Ceramic Tiles 8mm
Bath/Mudroom	AAC Above Plasterboard 75mm	3.90		No Insulation	Ceramic Tiles 8mm
Bath/Entry	AAC Above Plasterboard 75mm	1.70		No Insulation	Ceramic Tiles 8mm
WC/Garage 1	AAC Above Plasterboard 75mm	1.50		No Insulation	Ceramic Tiles 8mm
Bedroom 5/Kitchen/Living	AAC Above Plasterboard 75mm	0.80		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 5/Scullery	AAC Above Plasterboard 75mm	5.30		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 5/Powder	AAC Above Plasterboard 75mm	5.80		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 5/Hall	AAC Above Plasterboard 75mm	2.60		No Insulation	Carpet+Rubber Underlay 18mm

Ceiling type

Location	Construction material/type	Bulk insulation R-value (may include edge batt values)	Reflective wrap*
Garage 1	AAC Above Plasterboard	No Insulation	No
Laundry	Plasterboard	Bulk Insulation R4	No
Laundry	AAC Above Plasterboard	No Insulation	No
Mudroom	Plasterboard	Bulk Insulation R4	No
Mudroom	AAC Above Plasterboard	No Insulation	No
Entry	AAC Above Plasterboard	No Insulation	No
Media	Plasterboard	Bulk Insulation R4	No
Media	AAC Above Plasterboard	No Insulation	No
Kitchen/Living	Plasterboard	Bulk Insulation R4	No
Kitchen/Living	AAC Above Plasterboard	No Insulation	No
Scullery	Plasterboard	Bulk Insulation R4	No
Scullery	AAC Above Plasterboard	No Insulation	No
Powder	AAC Above Plasterboard	No Insulation	No
Hall	AAC Above Plasterboard	No Insulation	No
Bedroom 1	Plasterboard	Bulk Insulation R4	No
B1 WIR	Plasterboard	Bulk Insulation R4	No
Ensuite	Plasterboard	Bulk Insulation R4	No
Study	Plasterboard	Bulk Insulation R4	No
Living	Plasterboard	Bulk Insulation R4	No
Upper Hall	Plasterboard	Bulk Insulation R4	No
Bedroom 2	Plasterboard	Bulk Insulation R4	No
Bedroom 3	Plasterboard	Bulk Insulation R4	No
Bedroom 4	Plasterboard	Bulk Insulation R4	No
Bath	Plasterboard	Bulk Insulation R4	No
WC	Plasterboard	Bulk Insulation R4	No
Bedroom 5	Plasterboard	Bulk Insulation R4	No

Ceiling penetrations*

Location	Quantity	Type	Diameter (mm ²)	Sealed/unsealed
WC	1	Exhaust Fans	300	Sealed

Ceiling fans

Location	Quantity	Diameter (mm)
Kitchen/Living	1	1200
Living	1	1200

Roof type

Construction	Added insulation (R-value)	Solar absorptance	Roof shade
Corrugated Iron	Bulk, Reflective Side Down, No Air Gap Above R1.3	0.50	Medium

Explanatory notes

About this report

A NatHERS rating is a comprehensive, dynamic computer modelling evaluation of a home, using the floorplans, elevations and specifications to estimate an energy load. It addresses the building layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings), but does not cover the water or energy use of appliances or energy production of solar panels.

Ratings are based on a unique climate zone where the home is located and are generated using standard assumptions, including occupancy patterns and thermostat settings. The actual energy consumption of a home may vary significantly from the predicted energy load, as the assumptions used in the rating will not match actual usage patterns. For example, the number of occupants and personal heating or cooling preferences will vary.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparing different dwelling designs and to demonstrate that the design meets the energy efficiency requirements in the National Construction Code. Homes that are energy efficient use less energy, are warmer on cool days, cooler on hot days and cost less to run. The higher the star rating the more thermally efficient the dwelling is.

Accredited assessors

To ensure the NatHERS Certificate is of a high quality, always use an accredited or licenced assessor. NatHERS accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

Australian Capital Territory (ACT) licensed assessors may only produce assessments for regulatory purposes using software for which they have a licence endorsement. Licence endorsements can be confirmed on the ACT licensing register

AAOs have specific quality assurance processes in place, and continuing professional development requirements, to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any ongoing training requirements.

Any questions or concerns about this report should be directed to the assessor in the first instance. If the assessor is unable to address these questions or concerns, the AAO specified on the front of this certificate should be contacted.

Disclaimer

The format of the NatHERS Certificate was developed by the NatHERS Administrator. However the content of each individual certificate is entered and created by the assessor to create a NatHERS Certificate. It is the responsibility of the assessor who prepared this certificate to use NatHERS accredited software correctly and follow the NatHERS Technical Notes to produce a NatHERS Certificate.

The predicted annual energy load in this NatHERS Certificate is an estimate based on an assessment of the building by the assessor. It is not a prediction of actual energy use, but may be used to compare how other buildings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, indoor air temperature and local climate.

Not all assumptions that may have been made by the assessor while using the NatHERS accredited software tool are presented in this report and further details or data files may be available from the assessor.

Glossary

Annual energy load	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
Assessed floor area	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
Ceiling penetrations	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, rangehoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
Conditioned	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
Custom windows	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
Default windows	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
Entrance door	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
Exposure category – exposed	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
Exposure category – open	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
Exposure category – suburban	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
Exposure category – protected	terrain with numerous, closely spaced obstructions over 10m e.g. city and industrial areas.
Horizontal shading feature	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
National Construction Code (NCC) Class	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at www.abcb.gov.au .
Opening percentage	the openability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
Provisional value	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at www.nathers.gov.au
Reflective wrap (also known as foil)	can be applied to walls, roofs and ceilings. When combined with an appropriate airgap and emissivity value, it provides insulative properties.
Roof window	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
Shading device	a device fixed to windows that provides shading e.g. window awnings or screens but excludes eaves.
Shading features	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
Solar heat gain coefficient (SHGC)	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
Skylight (also known as roof lights)	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.
U-value	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
Unconditioned	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions.
Vertical shading features	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).