

General Notes

READ ARCHITECTURAL DRAWINGS IN CONJUNCTION WITH OTHER CONSULTANTS DRAWINGS, DOCUMENTATION AND COORDINATE WITH OTHER INSTRUCTIONS THAT ARE ISSUED DURING THE COURSE OF THE WORKS.

VERIFY SET-OUT DIMENSIONS AND LEVELS ON SITE PRIOR TO COMMENCEMENT OF WORKS

DETAIL DRAWINGS TO LARGER SCALES TAKE PRECEDENCE OVER SMALLER SCALE DRAWINGS

EXECUTE THE WORKS IN COMPLIANCE WITH THE CURRENT EDITION OF THE BUILDING CODE OF AUSTRALIA (AS AMMENDED), CURRENT OF THE BUILDING CODE OF AUSTRALIAN STANDARDS (AS AMMERDED), CURRE EDITIONS OF RELEVANT AUSTRALIAN STANDARDS (AS AMENDED) AND THE CURRENT REQUIREMENTS OF OTHER AUTHORITIES RELEVANT TO THE EXECUTION OF THE WORKS.

Levels

(XXX)????? (RL) RELATIVE LEVEL ???? (SSL) STRUCTURAL SLAB LEVEL ???? (FFL) FINISHED FLOOR LEVEL ???? (GND) FINISHED GROUND LEVEL ????

10,000 EXISTING SITE LEVELS TRANSPOSED FROM SITE SURVEY FOR REFERENCE.

EXISTING SITE LEVELS EXTRAPOLATED BY BH DESIGN FROM SITE SURVEY INFORMATION. EXTRAPOLATED LEVEL MAY BE LIMITED IN THEIR ACCURACY. -000

BASIX Compliance

LIGHTING

LIGHTING ENSURE A MIN.40% OF NEW OR ALTERED LIGHT FIXTURES ARE FITTED W/ FILIORESCENT, COMPACT FLUORESCENT, OR LIGHT-EMITTING-DIODE LAMPS.

EXCLURES INSTALL GAS INSTANTANEOUS HOT WATER SYSTEM. DISURE NEW OR ALTERED SHOWERHEADS HAVE A FLOW RATE NO GREATER THAN SLAWN OR A 3 STAR WATER RATING. ENSURE NEW RATERED FLOTES HAVE A FLOW RATE NO GREATER THAN DISURE NEW RATERED AND A MIN. 3 STAR WATER RATING. AL/AVERAGE FLUSH OR A MIN. 3 STAR WATER RATING. ENSURE NEW OR ALTERED TAPS HAVE A FLOW RATE NO GREATER THAN 9L/MIN OR A MIN. 3 STAR WATER RATING.

Insulation requirements Floor Above Existing of Helling or Building – Nil External Wall: Brick Veneer – R1.16 (or R1.70 including construction). External Wall: Framed – R1.30 (or R1.70 including construction). FLAT CEILING, PITCHED ROOF - CEILING R2.50 (UP), ROOF: FOIL/SARKING. MEDIUM SOLAR ABSORPTANCE 0.475-0.70. RAKED CEILING, PITCHED/SKILLION ROOF: FRAMED - CEILING R2.50 (UP), ROOF: FOIL/SARKING. MEDIUM SOLAR ABSORPTANCE 0.475-0.70.

<u>WINDOWS AND GLAZED DOORS</u> INSTALL ALL WINDOWS, GLAZED DOORS & SHADING DEVICES IN A/W BASIX CERTIFICATE.

CRUTIFICATE. For projections described in MM, the leading edge of each eave, pergola, Vernandah, balcony or anning must be no more than sooiam above the Head of the window or glazed door and no more than 2400mm above the

SULL. Overshadowing Buildings or vegetation must be of the height & distance from the centre & the base of the window & glazed door, as specified in the basix certificate.

This design is not to be used, copied or reproduced

Do not scale from drawings. Confirm dimensions on site

This drawing is only to be used for its designated purpose

Unless otherwise stated this drawing is not to be used for

prior to commencement of works. Where a discrepancy arrises seek direction prior to proceeding with the works.

without authority

construction.

<u>GLAZING REQUIREMENTS</u> EXCH SKYLGHT MAY ETHER MATCH THE DESCRIPTION, OR, HWE A U-VALLE AND A SING NO GREATE THAN THAT LISTED IN THE BASIX CERTIFICATE. EXTERNAL, ANNINGS & LOUVRES MIST FULLY SHADE THE SKYLGHT ABOVE WHICH THEY ARE STURDED WHEN FULLY DOWNIN OR CLOSED.

A

