BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A352835 02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv Date of issue: Tuesday, 21, April 2020 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project address	
Project name	Pilling on Bellevue_02
Street address	6 Bellevue Place North Curl Curl 2099
Local Government Area	Northern Beaches Council
Plan type and number	Deposited Plan 514865
Lot number	6
Section number	
Project type	
Project type Dwelling type	Separate dwelling house

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Sally Gardner Design and Draft

ABN (if applicable): 17 751 732 195

Pool and Spa	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Outdoor swimming pool			
The swimming pool must be outdoors.	\checkmark	\checkmark	\checkmark
The swimming pool must not have a capacity greater than 13.1 kilolitres.	\checkmark	\checkmark	\checkmark
The swimming pool must have a pool cover.		~	\checkmark
The applicant must install a pool pump timer for the swimming pool.		~	\checkmark
The applicant must not incorporate any heating system for the swimming pool that is part of this development.		 	\checkmark

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		\checkmark	\checkmark
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		\checkmark	\checkmark
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		\checkmark	

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
nsulation requirements					
The applicant must construct the new or alter the table below, except that a) additional insu- is not required for parts of altered construction	~	~	~		
suspended floor with enclosed subfloor:	R0.60 (down) (or R1.30 including				
framed (R0.7).	construction)				
	construction)R1.16 (or R1.70 including construction)				

	uirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows an	d glazed do	ors							
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.							~	 	~
The following requirements must also be satisfied in relation to each window and glazed door:								\checkmark	\checkmark
have a U-value must be calcul	e and a Solar lated in accord	Heat Gair dance with	n Coefficie n National	ent (SHGC) r Fenestration	no greater than that listed in the tabl	ar glazing, or toned/air gap/clear glazing must le below. Total system U-values and SHGCs s. The description is provided for information		~	~
For projections least that show			he ratio of	the projection	on from the wall to the height above	the window or glazed door sill must be at	\checkmark	\checkmark	\checkmark
Overshadowing buildings or vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column in the table below.							/	1	
					it and distance from the centre and	the base of the window and glazed door, as	~	×	×
specified in the	e 'overshadow	ving' colun	nn in the t	able below.			- ×	v	~
specified in the Windows a	e 'overshadow nd glazed o	ring ['] colun doors g	nn in the t	able below. equireme		Frame and glass type		~	~
specified in the Windows a Window / doo no.	e 'overshadow nd glazed o	ving [°] colun doors g Area of glass inc. frame	nn in the t lazing r Oversha Height	able below. equiremen adowing Distance	nts				~
specified in the Windows a Window / doo no.	e 'overshadow nd glazed (r Orientation	ring ^r colun doors g Area of glass inc. frame (m2)	nn in the t lazing r Oversha Height (m)	able below. equiremen adowing Distance (m)	nts Shading device	Frame and glass type improved aluminium, single clear, (U-value:			~
specified in the Windows a Window / doo no. W1	e 'overshadow nd glazed (r Orientation S	ring ^r colum doors g Area of glass inc. frame (m2) 6.3	nn in the t lazing r Oversha Height (m) 0	able below. equirement adowing Distance (m) 0	nts Shading device	Frame and glass type improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75) improved aluminium, clear/air gap/clear,			~
specified in the Windows a Window / doo no. W1 W2	e 'overshadow nd glazed o r Orientation S N	ring ^r colum doors g Area of glass inc. frame (m2) 6.3 1.48	nn in the t lazing r Oversha Height (m) 0	able below. equirement adowing Distance (m) 0 0	nts Shading device none none	Frame and glass type improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75) improved aluminium, clear/air gap/clear, (U-value: 4.12, SHGC: 0.66) improved aluminium, single clear, (U-value:			
specified in the Windows a Window / doo no. W1 W2 W3	e 'overshadow nd glazed (r Orientation S N N	ving ^r colum doors g Area of glass inc. frame (m2) 6.3 1.48 0.78	nn in the t Iazing r Oversha Height (m) 0 0	able below. equirement adowing Distance (m) 0 0 0 0	nts Shading device none none none projection/height above sill ratio	Frame and glass type improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75) improved aluminium, clear/air gap/clear, (U-value: 4.12, SHGC: 0.66) improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75) improved aluminium, single clear, (U-value:			

Glazing requirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Window / door Orientation no.	glass F	Dvershad Height m)	lowing Distance (m)	Shading device	Frame and glass type			
					(U-value: 4.48, SHGC: 0.46)			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
"
"
"
"
"
"
"
"
"
"
Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " / " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.