

All structural components shall be in strict accordance to details and specifications as prepared by a structural engineer. All existing structures need to be examined for structural adequacy, and it is the Contractor's responsibility to ensure that a certificate of structural adequacy is available prior to the start of any work.


(1)

SON	EMMELKAMP	



NOTES

1. SOIL AND EROSION CONTROL MEASURES: i) NO PARKING OR STOCKPILING OF MATERIAL IS PERMITTED ON FOOTPATH. ii) ACCESS IS TO BE GAINED VIA TEMPORARY ENTRY ii) SILT STOP FENCING TO BE PLACED ALONG THE NORTH, SOUTH AND WEST BOUNDARIES. PROVIDE SILT STOP FENCING ON THE EASTERN SIDE WHERE SHOWN ON PLAN. 2. MAINTENANCE PROCEDURES DURING CONSTRUCTION: i) ALL EROSION CONTROL MEASURES ARE TO BE MAINTAINED AT ALL TIMES SO THAT THOSE MEASURES ARE FULLY FUNCTIONAL/OPERATIONAL DURING THE CURRENCY OR WORKS. ALL SUCH CONTROLS MUST ALSO BE FULLY FUNCTIONAL/ OPERATIONAL SHOULD WORK OPERATIONS CEASE TEMPORARILY. (eg WEEKENDS, ROSTERED DAYS OFF, etc.) ii) ALL FILTER BARRIERS ARE TO BE REGULARLY INSPECTED, PARTICULARLY FOLLOWING RUNOFF EVENTS, SO THAT DISLODGED OR BROKEN BALES/BAGS CAN BE IMMEDIATELY REPLACED. SEDIMENT ACCUMULATION BEHIND STRAWBALE SANDBAGS SHALL BE REMOVED. iii) RESPREAD MATERIAL GAINED DURING MAINTENANCE OPERATION OR ALTERNATIVELY PLACE ON STOCKPILES. 3. MINIMISE DISTURBED AREAS. 4. ALL STOCKPILES TO BE CLEAR FROM DRAINS, GUTTERS AND FOOTPATH. 5. ROADS AND FOOTPATHS TO BE SWEPT DAILY. 6. ALL TRUCK LOADS ARE TO BE COVERED WHEN ENTERING AND EXITING THE SITE SO AS TO AVOID SPILLAGE DEMOLISH & REMOVE FROM THE SITE. AS PER THE SPECIFICATION, THE COUNCIL REQUIREMENTS & AS. 2601 ALL THE EXISTING BUILDINGS, CARPORT, FENCES, DRIVEWAY, PATHS AND THE LIKE, AS SHOWN HATCHED AND/OR AS REQUIRED TO ACHIEVE THE PROPOSED WORK. DISCONNECT, CAP OFF & SEAL ALL REDUNDANT SERVICES PRIOR TO THE COMMENCEMENT OF DEMOLITION METHOD OF SUPPORT OF EXCAVATION ADJACENT TO ADJOINING PROPERTIES TO ENG'S DETAILS AND IT IS TO BE CERTIFIED BY A CERTIFIER ACCREDITED IN CIVIL ENGINEERING ANY DAMAGE TO EXISTING &/OR ADJOINING PROPERTY &/OR SERVICES IS TO BE MADE GOOD WITH MINIMAL IF ANY INCONVENIENCE TO ALL PROPRIETORS. IF ANY DAMAGE IS DUE TO NEGLIGENCE, IT IS TO BE RECTIFIED AT THE COST OF THE NEGLIGENT PARTY WHICH CAUSED THAT DAMAGE. VEHICLES CARRYING LOOSE BUILDING MATERIALS TO BE COVERED IN COMPLIANCE WITH ROAD TRAFFIC REGULATIONS. SAFE ACCESS FOR HEAVY EQUIPMENT PLANT AND MATERIALS DELIVERY. LEGEND - TO BE DEMOLISHED IMPORTANT NOTE THESE DRAWINGS HAVE BEEN ISSUED FOR DEVELOPMENT APPLICATION PURPOSES ONLY. THEY ARE NOT ISSUED FOR CONSTRUCTION OR CONSTRUCTION CERTIFICATE OR FOR THE PURPOSES OF PRICING BY ANY CONTRACTOR 6/7 Parkes Street Parramatta NSW 2150 www.rkdesigns.com.au dmin@rkdesigns.com.au 02 9633 4797 ACCREDITED abn. 393 300 330 53 BUILDING DESIGNER spaces designed for life DEMOLITION PLAN project no date sheet no. scale @ A3 issue drawn DESIGNS 19-103 18/12/19 .1 of 1 1:200 A RK





All existing structures needs to be examined for structural adequacy, and it is the Contractor's responsibility to ensure that a certificate of structural adequacy is available prior to the start of any work.


 $(\mathbf{1})$


GENERAL NOTES


1:200














GENERAL NOTES

. All dimensions are to be confirmed on site by the builder/subcontractor, any incongruencies must be reported to the Designer before commencement of any work . No Survey has been made on the boundaries, all bearings, distances and areas have been taken from the contour survey plan. A Survey must be carried out to

Confirm the exact boundary locations. No construction work shall commence until a site survey confirming the site boundaries has been completed. The contractor is to ensure that the boundary setbacks are confirmed the contractor is to ensure that the boundary setbacks take precedence over all other dimensions. The Survey work must be performed by a registered Survey. In the event of encountering any discrepancies on these drawings, specification or subsequent instructions issued, the Builder/Subcontractor shall contact the

. In the event of encountering any discrepancies on these drawings, specification or subsequent instructions issued, the Builder/Subcontractor shall contact the designer before proceeding further with any work. All construction, control joints and expansion joints in the wall, floors, other locations shall be in strict accordance with the Structural Engineering details. No joints or breaks other than specified, are allowed without written permission from the Engineer. Measurements for the fabrication of secondary components such as, windows, doors, internal frames, structural steel components and the like, are not to be taken from these documents. Measurements must be taken on site to suit the work as constructed. All existing structures need to be examined for structural adequacy, and it is the Contractor's responsibility to ensure that a certificate of structural adequacy is available prior to the start of any work.

drawn	date	issue	amendment	project		
EU	18/12/19	12/19 A ISSUE FOR DA	ISSUE FOR DA	PROPOSED CONSTRUCTION OF A GRANNY FLA GILLES CRESENT, BEACON HILL LOT 11 DP222		Ĺ
					true north	drawin
				Bungalow Homes		project 19-10

