


DESIGN TO BE FINALISED UPON SITE INSPECTION AND REVIEW OF EQUIPMENT SCHEDULE  
ALL WORKS TO BE COMPLETED IN ACCORDANCE WITH AS1668.2-2012



- 600x250 EXHAUST DUCTWORK FITTED WITH CONNECTION SPIGOTS TO DISHWASHER. CONNENCTION SPIGOTS SIZE TO BE DETERMINED BY MANUFACTURERS DESIGN SPECIFICATION
- 250x250 EXHAUST DUCTWORK - ALL HORIZONTAL. DUCTWORK TO BE INSTALLED WITH 5° FALL BACK TOWARDS HOOD AND BE FITTED WITH DUCT MOUNTED ACCESS PANELS EVERY 3m OR CHANGE OF DIRECTION
- EXHAUST MOTOR 2  
MOUNTED ON TOP OF 350x350 RISER DUCTWORK
- HOOD 2:  
1100x1100x700  
400 L/S
- MAKE UP AIR INLET  
MULTI PEAK FILTERS
- SQUARE TO ROUND
- 1200 LONG 6300 OPEN TYPE/UNPODDED OUTLET NOISE ATTENUATOR  
MAKE UP AIR MOTOR - FITTED EITHER SIDE WITH FLEXIBLE CONNECTIONS, MOUNTED ON ROOF PLATFORM
- 1200 LONG 6300 OPEN TYPE/UNPODDED INLET NOISE ATTENUATOR  
SQUARE TO ROUND
- INTERNALLY INSULATED MAKE UP AIR DUCTWORK.  
450x450 INTERNAL OPENING OR EQUIVALENT
- 2500 FLEXIBLE DUCTWORK  
2500 SPIGOTS
- 500x600 EXHAUST PLENUM OR EQUIVALENT
- HOOD 1:  
4500x1350x700  
2000 L/S EXH / 1600 L/S MUA
- EXHAUST MOTOR 1

NOTE:

1. ALL FIRE RATING REQUIREMENTS AT CLIENTS OWN EXPENSE.
2. ANY ACOUSTIC REQUIREMENTS BELOW dBA STATED AT CLIENTS OWN EXPENSE.
3. THE FAN MOTOR MUST BE PROVIDED WITH CURRENT OVERLOAD PROTECTION AND MUST ALSO BE PROVIDED WITH DIFFERENTIAL ACTION SINGLE PHASE PROTECTION. SUPPLIED BY OTHERS. IF THE ABOVE PROTECTIVE MEASURES ARE NOT TAKEN WARRANTY WILL BE VOID.
4. DESIGNED IN ACCORDANCE WITH AS1668-2:1991
5. COPYRIGHT OF DESIGN SHOWN HEREIN IS RETAINED BY THIS OFFICE. AUTHORITY IS REQUIRED FOR ANY REPRODUCTION.

General Notes

1	FOR DISCUSSION	19/03/16
No.	Revision/Issue	Date

**SPEEDY VENTILATION PTY LTD**  
A.B.N. 69 114 607 466  
13 Moorlands Road  
Ingleburn NSW 2565  
PH: (02) 9629 8680  
FAX: (02) 9629 8681  
MOBILE: 0418 242312  
EMAIL: [speedy@speedyvent.com.au](mailto:speedy@speedyvent.com.au)

Project Name and Address

Newport Arms Hotel  
2 Kalinya Street,  
Newport, NSW, 2106

Drawn By: *Rugam Walsb* DRAWING NO:

Date: 19/03/16

3886-01

Scale: 1:100@A2 Sheet 1 OF 3



EXHAUST MOTOR 1 DETAIL

Performance - Required


Air Flow:	2000 L/s	Air Flow:	2301 L/s
Static Pressure:	200 Pa	Static Pressure:	265 Pa
Selection Pressure:	200 Pa	Total Pressure:	265 Pa
Installation Type:	n/a		
Air Density:	1.204 kg/m³		
Atmos. Temp.:	20 °C		
Altitude: m	0 m		
Humidity:	0.0 %		

Actual

Air Flow:	2000 L/s	Air Flow:	2301 L/s
Static Pressure:	200 Pa	Static Pressure:	265 Pa
Selection Pressure:	200 Pa	Total Pressure:	265 Pa
Installation Type:	n/a		
Air Density:	1.204 kg/m³		
Atmos. Temp.:	20 °C		
Altitude: m	0 m		
Humidity:	0.0 %		

Fan Data

Catalogue Code:	CHD636
Description:	Heritage Series
Diameter:	630 mm
Impeller Type:	Centrifugal
Blade Material:	-
Speed:	960 RPM
Power, Abs:	0.85
Efficiency Total:	-
Fan Weight:	78.0 kg



Motor Data (at STP)

Motor Type:	Electrical Supply:	415V 3ph 50Hz
Motor Frame:	D90L	
Motor Power:	1.10kW	
FLC/Start:	3.00A / 16.80A	
Motor Speed:	6 pole	
Motor Efficiency:	81.4%	


Energy Efficiency, NCC/BCA Vol. 1, Table J6.2 compliant

+ 2006 - 2009  
+ 2010 - 2012  
+ 2013 - 2014

Sound Data

Spectrum (Hz):	63	125	250	500	1K	2K	4K	8K	dBW	dB(A) @ 3m
Inlet (dB):	89	90	85	75	73	71	69	69	93	61

Sound levels are quoted as in-duct values. dB(A) values are average spherical free-field for comparative use only.



EXHAUST MOTOR 1 DETAIL

Performance - Required


Air Flow:	600 L/s	Air Flow:	650 L/s
Static Pressure:	150 Pa	Static Pressure:	176 Pa
Selection Pressure:	150 Pa	Total Pressure:	176 Pa
Installation Type:	n/a		
Air Density:	1.204 kg/m³		
Atmos. Temp.:	20 °C		
Altitude: m	0 m		
Humidity:	0.0 %		

Actual

Air Flow:	600 L/s	Air Flow:	650 L/s
Static Pressure:	150 Pa	Static Pressure:	176 Pa
Selection Pressure:	150 Pa	Total Pressure:	176 Pa
Installation Type:	n/a		
Air Density:	1.204 kg/m³		
Atmos. Temp.:	20 °C		
Altitude: m	0 m		
Humidity:	0.0 %		


Fan Data

Catalogue Code:	CHD354
Description:	Heritage Series
Diameter:	350 mm
Impeller Type:	Centrifugal
Blade Material:	-
Speed:	1440 RPM
Power, Abs:	0.30
Efficiency Total:	-
Fan Weight:	26.0 kg



Motor Data (at STP)

Motor Type:	Electrical Supply:	415V 3ph 50Hz
Motor Frame:	D80	
Motor Power:	0.55kW	
FLC/Start:	1.40A / 7.84A	
Motor Speed:	4 pole	
Motor Efficiency:	72.2%	



Sound Data

Spectrum (Hz):	63	125	250	500	1K	2K	4K	8K	dBW	dB(A) @ 3m
Inlet (dB):	80	78	74	71	62	64	63	53	83	52

Sound levels are quoted as in-duct values. dB(A) values are average spherical free-field for comparative use only.

MAKE UP AIR MOTOR DETAIL

Performance - Required


Air Flow:	1600 L/s	Air Flow:	1629 L/s
Static Pressure:	250 Pa	Static Pressure:	259 Pa
Selection Pressure:	250 Pa	Total Pressure:	276 Pa
Installation Type:	TYPE D		
Air Density:	1.204 kg/m³		
Atmos. Temp.:	20 °C		
Altitude: m	0 m		
Humidity:	0.0 %		

Actual

Air Flow:	1600 L/s	Air Flow:	1629 L/s
Static Pressure:	250 Pa	Static Pressure:	259 Pa
Selection Pressure:	250 Pa	Total Pressure:	276 Pa
Installation Type:	TYPE D		
Air Density:	1.204 kg/m³		
Atmos. Temp.:	20 °C		
Altitude: m	0 m		
Humidity:	0.0 %		

Fan Data

Catalogue Code:	AP0634AP10/14 (AP0634AP10B007)
Description:	AP Series In-Line Direct Drive
Diameter:	630 mm
Impeller Type:	Axial
Blade Material:	GRP
Speed:	1440 RPM
Power, Abs:	0.69
Efficiency Total:	64.6%
Fan Weight:	43.9 kg



Motor Data (at STP)

Motor Type:	Standard
Electrical Supply:	415V 3ph 50Hz
Motor Frame:	D80
Motor Power:	0.83kW (AOM)
FLC/Start:	2.31A (AOM) / 12.80A (2.10A FL IEC)
Motor Speed:	4 pole
Motor Efficiency:	82.5%


Energy Efficiency, NCC/BCA Vol. 1, Table J6.2 compliant

+ 2006 - 2009  
+ 2010 - 2012  
+ 2013 - 2014

Sound Data

Spectrum (Hz):	63	125	250	500	1K	2K	4K	8K	dBW	dB(A) @ 3m
Inlet (dB):	66	68	77	91	84	76	69	61	92	69
Outlet (dB):	76	78	84	88	84	79	74	63	91	68

Sound levels are quoted as in-duct values. dB(A) values are average spherical free-field for comparative use only.



NOTE:

1. ALL FIRE RATING REQUIREMENTS AT CLIENTS OWN EXPENSE.
2. ANY ACOUSTIC REQUIREMENTS BELOW dBA STATED AT CLIENTS OWN EXPENSE.
3. THE FAN MOTOR MUST BE PROVIDED WITH CURRENT OVERLOAD PROTECTION AND MUST ALSO BE PROVIDED WITH DIFFERENTIAL ACTION SINGLE PHASE PROTECTION, SUPPLIED BY OTHERS. IF THE ABOVE PROTECTIVE MEASURES ARE NOT TAKEN WARRANTY WILL BE VOID.
4. DESIGNED IN ACCORDANCE WITH AS1668-2:1991
5. COPYRIGHT OF DESIGN SHOWN HEREIN IS RETAINED BY THIS OFFICE. AUTHORITY IS REQUIRED FOR ANY REPRODUCTION.

General Notes

1	FOR DISCUSSION	19/03/16
No.	Revision/Issue	Date

SPEEDY VENTILATION PTY LTD


A.B.N. 69 114 607 466  
13 Moorlands Road  
Ingleburn NSW 2565  
PH: (02) 9629 8680  
FAX: (02) 9629 8681  
MOBILE: 0418 242312  
EMAIL: speedy@speedyvent.com.au

Project Name and Address

Newport Arms Hotel  
2 Kalina Street,  
Newport, NSW, 2106

Drawn By:	3ugan Wabsh	DRAWING NO:
Date:	19/03/16	3886-01
Scale:	1:100@A2	Sheet 3 OF 3





## TYPICAL HOOD DETAIL



CAT 5 CONNECTION BETWEEN  
CONTROL UNIT AND DISPLAY UNIT  
MAX. 6M LENGTH



DISPLAY UNIT

POSITION TO BE CONFIRMED  
(GENERALLY IN WORK AREA)

CONTROL UNIT

POSITION TO BE CONFIRMED  
(GENERALLY IN SERVICE AREA)

## SPEED CONTROLLER DETAIL

### HOOD 2 DISHWASHER CANOPY

NOTE:

- ALL FIRE RATING REQUIREMENTS AT CLIENTS OWN EXPENSE.
- ANY ACOUSTIC REQUIREMENTS BELOW dBA STATED AT CLIENTS OWN EXPENSE.
- THE FAN MOTOR MUST BE PROVIDED WITH CURRENT OVERLOAD PROTECTION AND MUST ALSO BE PROVIDED WITH DIFFERENTIAL ACTION SINGLE PHASE PROTECTION, SUPPLIED BY OTHERS. IF THE ABOVE PROTECTIVE MEASURES ARE NOT TAKEN WARRANTY WILL BE VOID.
- DESIGNED IN ACCORDANCE WITH AS1668-2:1991
- COPYRIGHT OF DESIGN SHOWN HEREIN IS RETAINED BY THIS OFFICE. AUTHORITY IS REQUIRED FOR ANY REPRODUCTION.

General Notes

No.	Revision/Issue	Date
1	FOR DISCUSSION	19/03/16

**SPEEDY VENTILATION PTY LTD**  
A.B.N. 69 114 607 466  
13 Moorlands Road  
Ingleburn NSW 2565  
PH: (02) 9629 8680  
FAX: (02) 9629 8681  
MOBILE: 0418 242312  
EMAIL: [speedy@speedyvent.com.au](mailto:speedy@speedyvent.com.au)

Project Name and Address

Newport Arms Hotel  
2 Kalinya Street,  
Newport, NSW, 2106

Drawn By: <i>Ryan Walsh</i>	DRAWING No: <b>3886-01</b>
Date: 19/03/16	Sheet: 2 OF 3
Scale: 1:100@A2	