BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A357249

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv

Date of issue: Monday, 09, September 2019 To be valid, this certificate must be lodged within 3 months of the date of issue.



Project name	Bloomfield-Shearer
Street address	2 Epacris Avenue Forestville 2086
Local Government Area	Northern Beaches Council
Plan type and number	Deposited Plan 274447
Lot number	19
Section number	
Project type	
Dwelling type	Separate dwelling house
Type of alteration and addition	My renovation work is valued at \$50,000 or mo and includes a pool (and/or spa).

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: JAH Design Services

ABN (if applicable): 22630690834

S **đ**1

Pool and Spa	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Rainwater tank			
The applicant must install a rainwater tank of at least 1268 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rainwater runoff from at least 30 square metres of roof area.		\checkmark	\checkmark
The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool.		\checkmark	\checkmark
Outdoor swimming pool			
The swimming pool must be outdoors.	\checkmark	\checkmark	
The swimming pool must not have a capacity greater than 36 kilolitres.	\checkmark	\checkmark	\checkmark
The swimming pool must have a pool cover.		\checkmark	\checkmark
The applicant must install a pool pump timer for the swimming pool.		\checkmark	\checkmark
The applicant must install the following heating system for the swimming pool that is part of this development: electric heat pump.		\checkmark	\checkmark

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Fixtures	1		
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		\checkmark	\checkmark
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		\checkmark	\checkmark
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		\checkmark	

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
	tion is not required where the area of new con	s) in accordance with the specifications listed in struction is less than 2m2, b) insulation specified	 ✓ 	~	~
Construction	Additional insulation required (R-value)	Other specifications			
external wall: external insulated façade system (EIFS)(façade panel: 70 mm)	nil				

	equirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows a	and glazed do	ors					1	l	
					nading devices, in accordance with r each window and glazed door.	the specifications listed in the table below.	~	\checkmark	~
The following	g requirements	must also	be satisf	ed in relatior	n to each window and glazed door:			~	\checkmark
have a U-va	lue and a Solar	Heat Gair	n Coefficie	ent (SHGC) r		ed glass may either match the description, or, le below. Total system U-values and SHGCs s.		~	~
					f each eave, pergola, verandah, bal than 2400 mm above the sill.	lcony or awning must be no more than 500 mm	~	\checkmark	~
Porgolac wit	the malu carbonate				and the second				
reigulas wit	in polycarbonate	e root or s	imilar trar	islucent mate	erial must have a shading coefficien	nt of less than 0.35.		✓	✓
Pergolas wit	th fixed battens	must have	e battens	parallel to the	C C	ch they are situated, unless the pergola also		~	~
Pergolas wit shades a pe	th fixed battens	must have dow. The	e battens spacing b	parallel to the	e window or glazed door above whi ens must not be more than 50 mm.	ch they are situated, unless the pergola also	-	~	~
Pergolas wit shades a pe Windows	th fixed battens a erpendicular wind	must have dow. The doors g	e battens spacing b	parallel to the between batte equireme l	e window or glazed door above whi ens must not be more than 50 mm.	ch they are situated, unless the pergola also		~	~
Pergolas wit shades a pe Windows Window / do no.	th fixed battens erpendicular wind and glazed	must have dow. The doors g Area of glass inc. frame	e battens spacing b lazing r Oversha Height	parallel to the etween batte equireme adowing Distance	e window or glazed door above whi ens must not be more than 50 mm. nts	ch they are situated, unless the pergola also		~	~
Pergolas wit shades a pe Windows Window / do no.	th fixed battens erpendicular wind and glazed (oor Orientation	must have dow. The doors g Area of glass inc. frame (m2)	e battens spacing b lazing r Oversha Height (m)	parallel to the between batte equireme adowing Distance (m)	e window or glazed door above whi ens must not be more than 50 mm. nts Shading device eave/verandah/pergola/balcony	Frame and glass type standard aluminium, single clear, (or		~	~
Pergolas wit shades a pe Window / do no.	th fixed battens erpendicular wind and glazed (oor Orientation E	must have dow. The doors g Area of glass inc. frame (m2) 2.916	e battens spacing b lazing r Oversha Height (m) 0	parallel to the between batter adowing Distance (m) 0	e window or glazed door above whi ens must not be more than 50 mm. nts Shading device eave/verandah/pergola/balcony >=900 mm	Frame and glass type standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.