

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1009119S_03

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

BASIX

Date of issue: Friday, 18 October 2019

To be valid, this certificate must be lodged within 3 months of the date of issue.



| Project summary | | | |
|---------------------------|---|--|--|
| Project name | Tim & Jacqueline Maguire (SMALLER WI_03 | | |
| Street address | 89 Carawa Road Cromer 2099 | | |
| Local Government Area | Northern Beaches Council | | |
| Plan type and plan number | deposited 361178 | | |
| Lot no. | В | | |
| Section no. | - | | |
| Project type | separate dwelling house | | |
| No. of bedrooms | 2 | | |
| Project score | | | |
| Water | ✓ 40 Target 40 | | |
| Thermal Comfort | Pass Target Pass | | |
| Energy | ✓ 100 Target 50 | | |

| Certificate Prepared by |
|-----------------------------------|
| Name / Company Name: Action Plans |
| ABN (if applicable): 17118297587 |

Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1009119S_03 Friday, 18 October 2019 page 1/9

Description of project

| Project address | | | | |
|------------------------------------|---|--|--|--|
| Project name | Tim & Jacqueline Maguire (SMALLER WI_03 | | | |
| Street address | 89 Carawa Road Cromer 2099 | | | |
| Local Government Area | Northern Beaches Council | | | |
| Plan type and plan number | Deposited Plan 361178 | | | |
| Lot no. | В | | | |
| Section no. | - | | | |
| Project type | | | | |
| Project type | separate dwelling house | | | |
| No. of bedrooms | 2 | | | |
| Site details | | | | |
| Site area (m²) | 696 | | | |
| Roof area (m²) | 103 | | | |
| Conditioned floor area (m2) | 55.14 | | | |
| Unconditioned floor area (m2) | 4.39 | | | |
| Total area of garden and lawn (m2) | 342 | | | |

| Assessor details and thermal loads | | | | | | |
|---|-------------|-------------|--|--|--|--|
| Assessor number | n/a | | | | | |
| Certificate number | n/a | | | | | |
| Climate zone | n/a | | | | | |
| Area adjusted cooling load (MJ/m².year) | n/a | | | | | |
| Area adjusted heating load (MJ/m².year) | n/a | | | | | |
| Project score | | | | | | |
| Water | 4 0 | Target 40 | | | | |
| Thermal Comfort | ✓ Pass | Target Pass | | | | |
| Energy | 1 00 | Target 50 | | | | |

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1009119S_03 Friday, 18 October 2019 page 2/9

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

| Water Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|--|------------------|------------------------------|-----------------|
| Landscape | | | |
| The applicant must plant indigenous or low water use species of vegetation throughout 100 square metres of the site. | ~ | ~ | |
| Fixtures | | | |
| The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development. | | ~ | ~ |
| The applicant must install a toilet flushing system with a minimum rating of 6 star in each toilet in the development. | | ~ | ~ |
| The applicant must install taps with a minimum rating of 6 star in the kitchen in the development. | | ~ | |
| The applicant must install basin taps with a minimum rating of 6 star in each bathroom in the development. | | V | |
| Alternative water | | | |
| Rainwater tank | | | |
| The applicant must install a rainwater tank of at least 3500 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities. | ~ | ~ | ~ |
| The applicant must configure the rainwater tank to collect rain runoff from at least 103.44 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam). | | ~ | ~ |
| The applicant must connect the rainwater tank to: | | | |
| all toilets in the development | | ~ | • |
| at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) | | ✓ | ~ |

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1009119S_03 Friday, 18 October 2019 page 3/9

| Thermal Comfort Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|---|---------------------|------------------------------|-----------------|
| General features | | | |
| The dwelling must not have more than 2 storeys. | V | ~ | - |
| The conditioned floor area of the dwelling must not exceed 300 square metres. | V | ~ | V |
| The dwelling must not contain open mezzanine area exceeding 25 square metres. | V | ~ | V |
| The dwelling must not contain third level habitable attic room. | V | V | V |
| Floor, walls and ceiling/roof | | | |
| The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below. | V | V | ~ |

| Construction | Additional insulation required (R-Value) | Other specifications |
|---|--|---|
| floor - suspended floor above open subfloor, framed | 0.8 (or 1.5 including construction) (down) | |
| external wall - framed (weatherboard, fibre cement, metal clad) | 2.00 (or 2.40 including construction) | |
| ceiling and roof - raked ceiling / pitched or skillion roof, framed | ceiling: 4 (up), roof: foil/sarking | framed; medium (solar absorptance 0.475-0.70) |

| Note | Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia. |
|------|--|
| Note | • In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials. |

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1009119S_03 Friday, 18 October 2019 page 4/9

| Thermal Comfort Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check | | | |
|---|---------------------|------------------------------|-----------------|--|--|--|
| Windows, glazed doors and skylights | | | | | | |
| The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door. | V | ~ | V | | | |
| The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table. | V | ~ | V | | | |
| The following requirements must also be satisfied in relation to each window and glazed door: | ~ | V | V | | | |
| • For the following glass and frame types, the certifier check can be performed by visual inspection. | | | | | | |
| - Aluminium single clear | | | | | | |
| - Aluminium double (air) clear | | | | | | |
| - Timber/uPVC/fibreglass single clear | | | | | | |
| - Timber/uPVC/fibreglass double (air) clear | | | | | | |
| For other glass or frame types, each window and glazed door must be accompanied with certification showing a U value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range of those listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. Frame and glass types shown in the table below are for reference only. | | | ~ | | | |

| Window/glazed door no. | Maximum height (mm) | Maximum width (mm) | Туре | Shading Device (Dimension within 10%) | Overshadowing |
|------------------------|------------------------|--------------------|--------------------------|--|------------------|
| North facing | | | | | |
| D01 | 2100 | 2200 | aluminium, single, clear | eave 749 mm, 318 mm above head of window or glazed door | not overshadowed |
| W01 | 1100 | 1800 | aluminium, single, clear | eave 749 mm, 318 mm above head of window or glazed door | not overshadowed |
| W09 | 1000 | 2000 | aluminium, single, clear | eave 3174 mm, 214 mm above head of window or glazed door | not overshadowed |
| W11 | 400 | 2600 | aluminium, single, clear | eave 934 mm, 211 mm above head of window or glazed door | not overshadowed |
| W10 | 400 | 2900 | aluminium, single, clear | eave 934 mm, 211 mm above head of window or glazed door | not overshadowed |

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1009119S_03 Friday, 18 October 2019 page 5/9

| Window/glazed door no. | Maximum height (mm) | Maximum width (mm) | Туре | Shading Device (Dimension within 10%) | Overshadowing |
|------------------------|------------------------|--------------------|--|--|------------------|
| East facing | | | | | |
| W03 | 400 | 1800 | aluminium, single, clear | eave 600 mm, 1094 mm above head of window or glazed door | not overshadowed |
| W02 | 400 | 1800 | aluminium, single, clear | eave 965 mm, 417 mm above head of window or glazed door | not overshadowed |
| South facing | <u>'</u> | | | | |
| D02 | 2100 | 3000 | U-value: 5.6, SHGC: 0.324 - 0.396 (aluminium, single, Lo-Tsol Low-e) | eave 595 mm, 941 mm above head of window or glazed door | not overshadowed |
| W04 | 1100 | 1800 | aluminium, single, clear | eave 595 mm, 941 mm above head of window or glazed door | not overshadowed |
| W05 | 600 | 600 | aluminium, single, clear | eave 595 mm, 941 mm above head of window or glazed door | not overshadowed |
| West facing | | | | | |
| W06 | 600 | 600 | aluminium, single, clear | eave 600 mm, 1170 mm above head of window or glazed door | not overshadowed |
| W08 | 400 | 900 | aluminium, single, clear | eave 600 mm, 1053 mm above head of window or glazed door | not overshadowed |
| W07 | 400 | 900 | aluminium, single, clear | eave 600 mm, 1129 mm above head of window or glazed door | not overshadowed |

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1009119S_03 Friday, 18 October 2019 page 6/9

| Energy Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|--|------------------|------------------------------|-----------------|
| Hot water | | | |
| The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric nstantaneous. | ~ | V | ~ |
| Cooling system | | | |
| The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 3 Star | | ~ | ~ |
| The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 3 Star | | ~ | V |
| Heating system | | | |
| The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 3 Star | | ~ | V |
| The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 3 Star | | ~ | V |
| Ventilation | | | |
| The applicant must install the following exhaust systems in the development: | | | |
| At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off | | ~ | - |
| Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off | | ✓ | V |
| Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off | | • | V |
| Artificial lighting | | | |
| The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or ight emitting diode (LED) lamps: | | | |
| at least 2 of the bedrooms / study; | | | |
| • at least 2 of the living / dining rooms; | | j | J |
| • the kitchen; | | Ĭ | |

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1009119S_03 Friday, 18 October 2019 page 7/9

| Energy Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|---|---------------------|------------------------------|-----------------|
| all bathrooms/toilets; | | ~ | V |
| • the laundry; | | ✓ | ~ |
| • all hallways; | | ~ | V |
| Natural lighting | | | |
| The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting. | V | ~ | - |
| Alternative energy | | | |
| The applicant must install a photovoltaic system with the capacity to generate at least 3000 peak kilowatts of electricity as part of the development. The applicant must connect this system to the development's electrical system. | • | ~ | - |

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1009119S_03 Friday, 18 October 2019 page 8/9

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1009119S_03 Friday, 18 October 2019 page 9/9