BASIX™Certificate

Building Sustainability Index www.planningportal.nsw.gov.au/development-and-assessment/basix

Single Dwelling

Certificate number: 1794096S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.planningportal.nsw.gov.au/definitions

Secretary

Date of issue: Tuesday, 06 May 2025

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



Project summary		
Project name	2 Cherana Crescent Forestville 208	7
Street address	2 CHERANA Crescent FORESTVII	LLE 2087
Local Government Area	Northern Beaches Council	
Plan type and plan number	Deposited Plan DP840790	
Lot no.	12	
Section no.	-	
Project type	dwelling house (detached) - second	lary dwelling
No. of bedrooms	2	
Project score		
Water	✓ 41	Target 40
Thermal Performance	✓ Pass	Target Pass
Energy	√ 74	Target 68
Materials	✓ -41	Target n/a

Certificate Prepared by
Name / Company Name: GRACE LEUNG
ABN (if applicable):

Version: 4.03 / EUCALYPTUS_03_01_0

Description of project

Project address	
Project name	2 Cherana Crescent Forestville 2087
Street address	2 CHERANA Crescent FORESTVILLE 2087
Local Government Area	Northern Beaches Council
Plan type and plan number	Deposited Plan DP840790
Lot no.	12
Section no.	-
Project type	
Project type	dwelling house (detached) - secondary dwelling
No. of bedrooms	2
Site details	
Site area (m²)	962
Roof area (m²)	123
Conditioned floor area (m²)	47.5
Unconditioned floor area (m²)	12.5
Total area of garden and lawn (m²)	348
Roof area of the existing dwelling (m²)	253
Number of bedrooms in the existing dwelling	3

Assessor details and therma	al loads	
NatHERS assessor number	n/a	
NatHERS certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m².year)	n/a	
Area adjusted heating load (MJ/m².year)	n/a	
Project score		
Water	✓ 41	Target 40
	✓ 41✓ Pass	Target 40 Target Pass
Water		

Certificate No.: 1794096S

BASIX

Version: 4.03 / EUCALYPTUS_03_01_0

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape	-4		
The applicant must plant indigenous or low water use species of vegetation throughout 100 square metres of the site.	~	~	
Fixtures	_		
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 5 star in each toilet in the development.		>	~
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		×	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		>	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 2000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 123 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
all toilets in the development		~	-
the cold water tap that supplies each clothes washer in the development		~	-

Version: 4.03 / EUCALYPTUS_03_01_0

Department of Planning, Housing and Infrastructure

	DA plans	Show on CC/CDC plans & specs	Certifier check
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	~

page 4/12

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Do-it-yourself Method			
General features	=-		
The dwelling must be a Class 1 dwelling according to the National Construction Code, and must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	~
The applicant must adopt one of the options listed in the tables below to address thermal bridging in metal framed floor(s), walls and ceiling/roof of the dwelling.	~	~	~
The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the tables below.			~

Construction	Area - m²	Additional insulation required	Options to address thermal bridging	Other specifications
floor - concrete slab on ground, conventional slab.	60	nil;not specified	nil	
garage floor - concrete slab on ground.	20	none	nil	
external wall: brick veneer; frame: timber - H2 treated softwood.	all external walls	2.44 (or 3.00 including construction);fibreglass batts or roll + reflective foil in the cavity	nil	wall colour: Medium (solar absorptance 0.48-0.7)

Department of Planning, Housing and Infrastructure

Construction	Area - m²	Additional insulation required	Options to address thermal bridging	Other specifications
internal wall shared with garage: single skin masonry; frame: no frame.	25.7	nil;none	nil	
internal wall: plasterboard; frame: timber - H2 treated softwood.	14.1	fibreglass batts or roll	nil	
ceiling and roof - flat ceiling / pitched roof, framed - terracotta tiles , timber - untreated softwood.	123	ceiling: 4.7 (up), roof: foil/ sarking ;ceiling: fibreglass batts or roll; roof: foil/sarking.	nil	roof space ventilation: unventilated; roof colour: light (solar absorptance 0.38-0.47); 0.5 to \leq 1.0% of ceiling area uninsulated

Note	Insulation specified in this Certificate must be installed in accordance with the ABCB Housing Provisions (Part 13.2.2) of the National Construction Code.
Note	If the additional ceiling insulation listed in the table above is greater than R3.0, refer to the ABCB Housing Provisions (Part 13.2.3 (6)) of the National Construction Code.
Note	In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.
Note • Thermal breaks must be installed in metal framed walls and applicable roofs in accordance with the ABCB Housing Provisions of the National Construction Code.	

BASIX

Certificate No.: 1794096S

page 6/12

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Ceiling fans			
The applicant must install at least one ceiling fan in at least one daytime habitable space, such as living room.	~	~	~
The minimum number and diameter of ceiling fans in a daytime habitable space must be installed in accordance with the ABCB Housing Provisions (Part 13.5.2) of the National Construction Code .	~	>	~

Department of Planning, Housing and Infrastructure

BASIX

Certificate No.: 1794096S

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Glazed windows, doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each glazed window and door.	~	~	~
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	~
The following requirements must also be satisfied in relation to each window and glazed door:	~	~	~
• The applicant must install windows and glazed doors in accordance with the height and width, frame and glazing types listed in the table.	~	~	~
• Each window and glazed door must have a U- value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.		~	~
The applicant must install the skylights described in the table below, in accordance with the specifications listed in the table. Total skylight area must not exceed 3 square metres (the 3 square metre limit does not include the optional additional skylight of less than 0.7 square metres that does not have to be listed in the table).	~	~	~

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing		
North facing							
W01	1200.00	1080.00	aluminium, single glazed (U-value: <=3.0, SHGC: 0.18 - 0.22)	none	not overshadowed		
East facing							
W02	600.00	2000.00	aluminium, single glazed (U-value: <=2.5, SHGC: 0.18 - 0.22)	none	not overshadowed		
South facing							
W03	1200.00	1500.00	aluminium, single glazed (U-value: <=2.5, SHGC: 0.18 - 0.22)	none	not overshadowed		

Department of Planning, Housing and Infrastructure

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing	
W04	1200.00	1500.00	aluminium, single glazed (U-value: <=2.5, SHGC: 0.18 - 0.22)	none	not overshadowed	
D1	2400.00	3300.00	aluminium, single glazed (U-value: <=2.5, SHGC: 0.18 - 0.22)	eave 450 mm, 2700 mm above head of window or glazed door	not overshadowed	
West facing						
W06	1200.00	1500.00	aluminium, single glazed (U-value: <=7.5, SHGC: 0.40 - 0.49)	solid overhang 3120 mm, 2700 mm above head of window or glazed door	not overshadowed	

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric boosted solar with a performance of more than 45 STCs.	~	~	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning - ducted; Energy rating: 5 star (average zone)		~	~
The bedrooms must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		~	~
Heating system			
The living areas must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	~
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	~
Ventilation	-		
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: please select		~	-
Kitchen: individual fan, ducted to façade or roof; Operation control: interlocked to light		~	-
Laundry: individual fan, ducted to façade or roof; Operation control: interlocked to light		~	-
Artificial lighting			
The applicant must ensure that a minimum of 80% of light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~

Department of Planning, Housing and Infrastructure

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.		~	>
Other			
The applicant must install a fixed outdoor clothes drying line as part of the development.		~	

BASIX

Certificate No.: 1794096S

Legend

BASIX

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.

Department of Planning, Housing and www.basix.nsw.gov.au Version: 4.03 / EUCALYPTUS_03_01_0 Certificate No.: 1794096S Tuesday, 06 May 2025 page 12/12 Infrastructure