

CHILDREN'S VILLAGE - CHILDCARE CENTRE & OOSHC

S4.56 SUBMISSION



LOCALITY AERIAL
NOT TO SCALE

SOURCE : SIX MAPS

DRAWING SCHEDULE		
DRG No.	DRAWING TITLE	REV.
C1.00 Arrangement and Overview Plans		
C1.01	Cover Sheet	3
C1.02	Specification Notes	3
C2.00 Sediment and Erosion Control		
C2.01	Sediment and Erosion Control Plan	4
C2.02	Sediment and Erosion Control Details	4
C6.00 Stormwater Drainage		
C6.01	Stormwater Layout Plan	4
C6.02	Stormwater Catchment Plan	3
C6.03	Roof Drainage Plan	3
C6.04	Roof Catchment Plan	3
C6.05	OSD Tank Plan	3
C6.06	OSD Tank Sections	3
C6.07	Stormwater Drainage Details	3
C6.08	Stormwater360 Treatment Device Typical Details	3

3

Rev: 10/11/2021 09:28:48, Log: Name: au, Cad File: T:\6118000\Drawings\Sub\CHC\Design\CHC\Development\app\sheet\01_Cover_Sheet.dwg

CLIENT	LODESTONE HQ
PROJECT MANAGER	MOSTYN COPPER GROUP
ARCHITECT	LIQUID DESIGN



WARREN SMITH CONSULTING ENGINEERS PTY LTD		SINCE 1981.	NSW	VIC
ACN 002 197 088	ABN 36 300 430 126	wsp@warrensmith.com.au	Level 9, 233 Castlereagh St Sydney 2000 NSW Australia	Level 20/485 La Trobe St Melbourne 3000 Vic Australia
■ Hydraulic ■ Fire ■ Civil ■ Utilities Infrastructure		www.warrensmith.com.au	PH +61 (2) 9299 1312	PH +61 (3) 8648 9942



**Serving the
Construction
Industry
since 1981.**

COVER SHEET				
SCALE	DRAWN	DESIGNED	CHECKED	APPROVED
AS SHOWN	L.SI.	L.SI.	J.G.	M.C.
JOB No.	DRAWING No.		ISSUE	
6118000	C1.01		3	
DATE	STATUS			
NOVEMBER 2021	S4.56 SUBMISSION			

GENERAL

- G1. DESIGN HEREIN HAS BEEN PREPARED BY WARREN SMITH AND PARTNERS PTY LTD CONSULTING CIVIL ENGINEERS...
G2. THE DRAWINGS HEREIN SHALL BE READ AS REQUIRED IN CONJUNCTION WITH ARCHITECT DRAWINGS BY LIQUID DESIGN...
G3. ALL DIMENSIONS IN MILLIMETRES UNO. REDUCED LEVELS AND CHAINAGES ARE IN METRES. DO NOT SCALE DRAWINGS. USE FIGURED DIMENSIONS.
G4. THE PROPOSED WORKS DETAILED HEREIN SHALL BE CONSTRUCTED TO THE REQUIREMENTS OF COUNCIL GENERALLY AS DETAILED HEREUNDER.
G5. ALL EXISTING SERVICES SHALL BE VERIFIED FOR DEPTH AND HORIZONTAL POSITION BY PHYSICAL MEANS PRIOR TO EXCAVATION. ANY DISCREPANCIES SHALL BE BROUGHT FORTHWITH TO THE PROJECT MANAGER'S ATTENTION.
G6. REFERENCE SHALL BE MADE TO THE CONSTRUCTION MANAGEMENT PLAN FOR ALL SITE WORKS DETAILED HEREIN.

STORMWATER & SUB-SOIL DRAINAGE MATERIALS:

- STW1. PIPES AND FITTINGS FOR STORMWATER DRAINAGE SHALL BE AS FOLLOWS UNO ON THE DRAWINGS:
A. SEWER GRADE uPVC (SN8) WITH SOLVENT WELDED JOINTS FOR BELOW GROUND DRAINAGE UP TO 225mm. FIBRE REINFORCED CEMENT WITH RUBBER RINGS, CLASS 3, FOR PIPE DIA'S GREATER THAN 225mm. UNO. REINFORCED CONCRETE WHERE REQUIRED BY AS 3500 FOR EXCESSIVE DEPTH.
B. INSTALL IN ACCORDANCE WITH AUSTRALIAN STANDARD AS3500 EXCEPT WHERE VARIED BY THE CONTRACT DOCUMENTS.
STW2. PIPES & FITTINGS FOR SUBSOIL DRAINAGE SHALL BE SLOTTED POLYVINYL CHLORIDE (PVC) WITH SOLVENT WELDED JOINTS. MIN. 150mm DIAMETER.
STW3. IN GROUND DRAINAGE PIPEWORK SERVING DP'S SHALL BE MINIMUM 150mm DIA. UNO.
STW4. GRATED DRAINS SHALL BE 150mm NOM.
A. 150mm NOM. WIDTH IN NON TRAFFICABLE AREAS.
B. 225mm NOM. WIDTH IN TRAFFICABLE AREAS.
STW5. STORMWATER PITS ARE AS SHOWN & SPECIFIED ON THE PLANS. PRECAST TYPE ACCEPTABLE WITH STEP IRONS FOR DEPTH GREATER THAN 1200. BENCH ALL PITS MIN. 50mm & FORM SMOOTH TRANSITION FROM INLET TO OUTLET.
STW6. SELECT FILL SHALL BE MATERIAL OBTAINED FROM EXCAVATION OF THE PIPE TRENCH OR IMPORTED WITH A PARTICLE SIZE FOR ROCK NOT GREATER THAN 75mm OR FOR OTHER THAN ROCK NOT GREATER THAN 150mm.
STW7. IMPORTED FILL SHALL BE EITHER AND GENERALLY CONSIST OF SINGLE SIZED AGGREGATE WITH PARTICLE SIZE NOT GREATER THAN 5mm WRAPPED ALL ROUND WITH GEOTEXTILE FILTER FABRIC OR APPROVED HIGH COMPACTION SAND OR APPROVED CRUSHED ROAD GRAVEL CONFORMING TO RTA FORM 3051 OR SIMILAR.
STW8. STORMWATER PITS AND GRATES TO CONFORM WITH STANDARD COUNCIL REQUIREMENTS, WHERE ON PUBLIC LAND. GRATES TO BE SUPPLIED IN CLASS SHOWN ON THE DRAWINGS.
INSTALLATION REQUIREMENTS:
STW9. PIPES SHALL BE TRUE TO GRADES SHOWN AND ALIGNED SO THAT THE CENTRES OF THE INLET PIPES INTERSECT WITH THE CENTRE OF THE OUTLET PIPE AT THE DOWNSTREAM FACE OF THE PIT.
STW10. MINIMUM GRADES FOR GRAVITY STORMWATER DRAINAGE SHALL CONFORM TO AS3500 PART3 AS FOLLOWS, UNO:
1% FOR 100 AND 150 mm DIA.
0.5% FOR 225 mm DIA
0.5% FOR 300 mm DIA
0.4% FOR 375 mm DIA
STW11. MINIMUM DEPTH OF COVER SHALL BE :-
- 300mm IN PRIVATE PROPERTY (NON VEHICULAR TRAFFIC).
- 450mm IN PUBLIC AREAS.
- 600mm IN VEHICULAR TRAFFICABLE AREAS

- STW12. (FOOTWAY/ROADWAY) BED ALL PIPES FIRMLY AND EVENLY ONTO IMPORTED BEDDING FILL MATERIAL.
STW13. LAY AND JOINT ALL PIPES IN ACCORDANCE WITH THE MANUFACTURERS RECOMMENDATIONS AND AS 3725-1989 BURIED FLEXIBLE PIPELINES AS 2566-1998 LOADS ON BURIED FLEXIBLE PIPELINES AS 1597.2-1996 PRECAST REINFORCED CONCRETE BOX CULVERTS.
AS 3500-1990 NATIONAL PLUMBING & DRAINAGE CODE. PART 2, SANITARY PLUMBING AND SANITARY DRAINAGE. SYDNEY WATER REQUIREMENTS.
STW14. ALLOW TO TEST ALL PIPES AND PITS TO MANUFACTURERS REQUIREMENTS.

CONCRETE WORKS

- C1. ALL WORKMANSHIP AND MATERIALS SHALL BE IN ACCORDANCE WITH AS3600, THE STANDARDS ASSOCIATION AUSTRALIA, STANDARDS CITED IN AS3600, THE DRAWINGS AND THE SPECIFICATION.
C2. ALL CONCRETE SHALL BE 80mm NOMINAL SLUMP, 20mm MAXIMUM AGGREGATE WITH NO ADMIXTURES OR FLY ASH, UNLESS OTHERWISE APPROVED. ALL CONCRETE WORK IN CONTACT WITH SEWER TO HAVE TYPE SL PORTLAND CEMENT, OTHERWISE TYPE A CEMENT FOR BRIDGE WORKS, A MAXIMUM 56 DAYS SHRINKAGE OF 600 MICROSTRAIN, A MINIMUM CEMENT CONTENT 350kg/m3 AND MAXIMUM WATER-CEMENT RATIO OF 0.40.
C3. STRENGTH GRADE OF CONCRETE SHALL BE : 25 MPa (KERBS, EDGE STRIPS & CONCRETE ENCASMENT) AND 32 MPa ELSEWHERE.
C4. CONSTRUCTION JOINTS SHALL BE PROPERLY FORMED AND USED ONLY WHERE SHOWN OR APPROVED. GENERALLY FOR HAND PLACED KERB & GUTTER 6mm THICK APPROVED BITUMINOUS MASTIC JOINTING MATERIAL SHALL BE PROVIDED AT INTERVALS NOT EXCEEDING 6m. FOR MACHINE PLACED KERB & GUTTER 6mm THICK APPROVED BITUMINOUS MASTIC JOINTING MATERIAL SHALL BE PROVIDED AT INTERVALS NOT EXCEEDING 12m & GUILLOTINED DUMMY GROOVED JOINTS, 25mm IN DEPTH, SHALL BE FORMED EVERY 3m OF GUTTER. JOINTS ARE ALSO REQUIRED AT EACH END OF GUTTER CROSSING AND GULLY PITS. JOINTS SHALL BE SET VERTICAL AND SQUARE TO THE KERB.
C5. REINFORCEMENT IS REPRESENTED DIAGRAMMATICALLY AND IS NOT NECESSARILY SHOWN IN TRUE PROJECTION.
C6. ELDDING OR SPLICES IN REINFORCEMENT SHALL BE USED ONLY IN POSITIONS APPROVED BY THE ENGINEER.
C7. CONCRETE CURING SHALL BE IN ACCORDANCE WITH AS3600. CURING SHALL BE COMMENCED WITHIN TWO HOURS OF FINISHING OPERATIONS AND SHALL BE CONTINUED FOR A MINIMUM OF SEVEN DAYS BY AN APPROVED PROPRIETARY COMPOUND OR BY KEEPING CONTINUOUSLY WET.
C8. FORMWORK SHALL BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH AS3610. FORMWORK SHALL NOT BE STRIPPED NOR PROPS REMOVED WITHOUT APPROVAL.
C9. FABRIC LAP DETAILS SHALL BE IN ACCORDANCE WITH FIG.13.2.4 OF AS3600.
C10. HOOKS, LAPS AND BENDS SHALL BE IN ACCORDANCE WITH AS3600 UNO.
C11. ALL CHEMICAL ANCHORS SHALL BE EITHER 'CHEMSET' BY 'RAMSET' WITH THE GLASS CAPSULE SYSTEM INSTALLED IN STRICT ACCORDANCE WITH MANUFACTURERS INSTRUCTIONS OR HILTI HVU ADHESIVE ANCHOR WITH FOIL CAPSULE SYSTEM INSTALLED IN STRICT ACCORDANCE WITH MANUFACTURERS INSTRUCTION.
C12. ALL CHEMICAL ANCHORS SHALL BE HOT DIPPED GALVANIZED AND BE MIN M16 DIA. U.N.O.

GENERAL EARTHWORKS, SITEWORKS & FILLING: FILLING:

- SGE1. THESE CLAUSES SHALL BE READ IN CONJUNCTION WITH GEOTECHNICAL REPORTS FOR THE SITE.
SGE2. THE RECOMMENDATIONS CONTAINED IN THE GEOTECH REPORT SHALL OVERRIDE THE CLAUSES PRESENTED HEREIN.
SGE3. STRIP ALL TOPSOIL AND UNDERLYING FILL AND STOCKPILE TOPSOIL FOR LATER REUSE FOR LANDSCAPING PURPOSES.
SGE4. NEW FILL REQUIRED TO REINSTATE CUT LEVELS TO PROPOSED BENCHING LEVELS SHALL BE SOURCED FROM OTHER PARTS OF THE EXCAVATION AS SELECT FILL OR IMPORTED FILL AS SPECIFIED BELOW IN SGE 5 AND SGE 6.

- SGE5. SELECT FILL SHALL CONSIST OF LOCALLY DERIVED OR CUT NATURAL CLAYS.
SGE6. IMPORTED FILL SHALL CONSIST OF RIPPED SANDSTONE OR SHALE OR SIMILAR MATERIAL WITH MAXIMUM PARTICLE SIZE NOT GREATER THAN 120mm AND A MOISTURE CONTENT WITHIN 2-3% OF STANDARD OPTIMUM.
SGE7. ALL FILL (COHESIVE SOIL) SHALL BE PLACED IN LAYERS OF 200mm MAXIMUM THICKNESS, COMPACTED BY MACHINE ROLLING TO ACHIEVE A DRY DENSITY RATIO OF NOT LESS THAN 98% STANDARD MAXIMUM AT A CORRESPONDING MOISTURE CONTENT WITHIN 2-3% OF STANDARD OPTIMUM.
SGE8. IN AREAS WHERE HIGH IMPACT ROLLING IS USED TEST EACH FINAL LAYER OF NOT GREATER THAN 300mm TO 400mm TO ACHIEVE A DRY DENSITY SGE8. RATIO OF NOT LESS THAN 98% STANDARD MAXIMUM AT A CORRESPONDING MOISTURE CONTENT WITHIN 2-3% OF STANDARD OPTIMUM.
EXCAVATION BATTERS:
SGE9. ALL TEMPORARY BATTERS CUT IN CLAY SUBSTRATE SHALL BE 1 HORIZ : 1 VERT. ALL LONG TERM EXPOSED BATTERS CUT IN CLAY SUBSTRATE SHALL BE 2 HORIZ : 1 VERT. ALL DETENTION BASIN BATTERS IN CLAY SUBSTRATE SHALL BE 3 HORIZ : 1 VERT. ALL DETENTION BASIN BATTERS IN ROCK SUBSTRATE SHALL BE NEAR VERTICAL.
SGE10. GEOTECHNICAL TESTING IS TO BE UNDERTAKEN AT AT LEAST LEVEL 1 CONTROL OF FILL COMPACTION STANDARD, AS DEFINED IN AS. 3738 AS FOLLOWS
FOR GENERAL FILL OR CUT AREAS OVER THE AREA PROVIDE ONE (1) TEST PER 200mm LAYER, OVER AN AREA NOT GREATER THAN 500 m²
FOR GENERAL FILL AREAS IN CONCENTRATED AREAS ADJACENT TO AND BEHIND THE STRUCTURE AND ADJACENT TO AND BEHIND RETAINING WALLS PROVIDE ONE (1) TEST PER 200mm LAYER, OVER AN AREA NOT GREATER THAN 50m²
SGE11. SUBMIT ALL GEOTECHNICAL TEST RESULTS TO WARREN SMITH & PARTNERS FOR REVIEW PRIOR TO CONTINUATION WITH SUBSEQUENT SECTION OF WORK.

EARTH WORKS FOR SERVICES

- E1. EXCAVATE TRENCHES AND STOCKPILE ALL MATERIAL FOR INSPECTION WITH REGARD TO RE-USE FOR TRENCH BACKFILL. REMAINING MATERIAL TO BE REMOVED FROM SITE.
E2. BEDDING MATERIAL SHALL CONSIST OF IMPORTED FILL ONLY. THICKNESS OF BEDDING LAYER SHALL BE 75mm IN O.T.R. AND 200mm IN ROCK.
E3. EMBED ALL PIPES WITH IMPORTED FILL. PROVIDE 200mm SIDE SUPPORT AND 150mm OVERLAY ABOVE PIPE CROWN.
E4. TRENCH FILL ABOVE THE EMBEDMENT ZONE TO THE UNDERSIDE OF THE ROAD PAVEMENT OR FOOTWAY FILL MATERIAL SHALL BE AS FOLLOWS :

UNDER ROADWAY

TRENCH FILL MATERIAL SHALL CONSIST OF IMPORTED FILL AS SPECIFIED HEREIN OF EITHER HIGH GRADE COMPACTION SAND OR APPROVED CRUSHED ROAD GRAVEL CONFORMING TO RTA FORM 3051 OR SIMILAR.

OTHER THAN ROADWAY

TRENCH FILL MATERIAL EXCAVATED SHALL CONSIST OF SELECT FILL AS SPECIFIED HEREIN AND SHALL NOT CONTAIN MORE THAN 20% OF STONES OF SIZE BETWEEN 75mm & 150mm AND NONE LARGER THAN 150mm. PRIOR TO THE USE OF THE EXCAVATED MATERIAL IT SHALL BE INSPECTED AND APPROVED BY THE CONSULTANT.

- E5. COMPACT BEDDING, EMBEDMENT AND TRENCH FILL MATERIALS AS FOLLOWS:
EMBEDMENT:-
FOR GRANULAR FILL MATERIAL (NON-COHESIVE SOILS) EG. COARSE AGGREGATE FILL, HIGH GRADE COMPACTION SAND, THE DENSITY INDEX (ID) SHALL BE NOT LESS THAN 70%.
TRENCH FILL:-
FOR GRANULAR MATERIAL (NON-COHESIVE SOILS), THE DENSITY INDEX (ID) SHALL BE NOT LESS THAN 70%.
FOR NON-GRANULAR FILL MATERIAL (COHESIVE SOILS), THE DRY DENSITY RATIO (RD) SHALL BE NOT LESS THAN 95%.
E6. MEASURE OF COMPACTION:-
THE DEGREE OF COMPACTION SHALL BE MEASURED BY ONE OF THE FOLLOWING PARAMETERS :-

- GRANULAR FILL (NON-COHESIVE SOILS). THE DENSITY INDEX (ID) DETERMINED IN ACCORDANCE WITH AS 1289.E6.1 BASED ON THE MAXIMUM AND MINIMUM DRY DENSITIES IN ACCORDANCE WITH AS 1289.E5.1 AND THE FIELD DRY DENSITY IN ACCORDANCE WITH AS 1289.5.3.2, AS 1289.E3.5 OR AS 1289.E8.1.
NON-GRANULAR FILL (COHESIVE SOILS). THE DRY DENSITY RATION (RD) DETERMINED IN ACCORDANCE WITH AS 1289.5.4.1 BASED ON THE FIELD DRY DENSITY IN ACCORDANCE WITH AS 1289.5.3.2 AND THE MAXIMUM DRY DENSITY IN ACCORDANCE WITH AS 1289.5.1.1
E7. GEOTECHNICAL TESTING IS TO BE UNDERTAKEN TO AT LEAST LEVEL 1 CONTROL OF FILL COMPACTION STANDARD, AS DEFINED IN AS. 3738 AS FOLLOWS:
TEST EACH 300mm LAYER ABOVE PIPE CROWN. TEST BASE & SUB-BASE LAYERS WHERE APPLICABLE. TESTS SHALL BE REQUIRED AT EACH 50m CENTRES WHERE THE LENGTH OF TRENCH IS WITHIN THE 50m REQUIREMENT.
E8. SUBMIT ALL GEOTECHNICAL TEST RESULTS TO WARREN SMITH & PARTNERS FOR REVIEW PRIOR TO CONTINUATION WITH SUBSEQUENT SECTION OF WORK.

RESTORATION:

- RES1. RESTORE ALL TRAFFIC AREAS TO PRE EXISTING CONDITION.
RES2. FOR ALL SURFACES OTHER THAN IN TRAFFIC AREAS RESTORE DISTURBED SURFACES TO PRE-EXISTING CONDITIONS AND COMPACT AS SPECIFIED.
RES3. RESTORE ALL AUTHORITY OWNED AREAS TO COUNCIL STANDARDS

ROAD WORKS, DRIVEWAYS & CARPARKS

- R1. ALLOW FOR LEVEL 2 TESTING AND SUB-GRADE CONDITIONS & PAVEMENT THICKNESS TO BE VERIFIED BY GEOTECHNICAL CONSULTANT AFTER INSPECTION OF PRELIMINARY BOXING.
R2. ALLOW FOR ANY SUB-GRADE REPLACEMENT WORK TO BE DETERMINED AS REQUIRED BY GEOTECHNICAL CONSULTANT AT THE TIME OF PAVEMENT CONSTRUCTION.
R3. MINIMUM DRY DENSITY RATIOS (AS 1289.3.4.1-1993) TO BE:
BASE COURSE: 98% MODIFIED
SUB-BASE: 95% MODIFIED
SUB-GRADE: 100% STANDARD
SUB-GRADE REPLACEMENT: 100% STANDARD
R4. PAVEMENT MATERIALS TO COMPLY WITH RMS SPECIFICATION No. 3051 OR SIMILAR AS APPROVED BY GEOTECHNICAL CONSULTANT.
R5. PROVIDE (1) TEST FOR EACH LAYER NOT EXCEEDING 250mm THICK BEING BASECOURSE, SUB-BASE & SUB-GRADE OVER AN AREA NOT GREATER THAN 500m²
R6. SUBMIT ALL GEOTECHNICAL TEST RESULTS TO WARREN SMITH & PARTNERS FOR REVIEW PRIOR TO CONTINUATION WITH SUBSEQUENT SECTION OF WORK.

APPROVALS

- A1. THE AS CONSTRUCTED WORKS SHALL BE INSPECTED BY DESIGN CONSULTANT. MINIMUM 48 HOURS NOTICE SHALL APPLY TO ALL INSPECTIONS.
A2. THE DESIGN PLANS HEREIN ARE SUBJECT TO LOCAL COUNCIL APPROVAL PRIOR TO CONSTRUCTION. OBTAIN EXPRESS (WRITTEN) ADVICE TO PROCEED FROM PROJECT MANAGER PRIOR TO COMMENCEMENT.
A3. SUBMIT WORK-AS-EXECUTED DRAWINGS IN CIVILCAD OR DXF DIGITAL FORMAT AND HARD COPY FORMAT. VERIFY ALL CONSTRUCTION WORKS SHOWN HEREON.
A4. CERTIFY THAT THE AS CONSTRUCTED SYSTEM HAS BEEN BUILT IN ACCORDANCE WITH THE APPROVED PLANS ISSUED FOR CONSTRUCTION.

SERVICES UNDER ROAD SURFACES

- S1. ALL OTHER SERVICES INCLUDING BUT NOT LIMITED TO WATER, HYDRANT, GAS, SEWER, ELECTRICAL AND COMMUNICATIONS CONDUITS OR CABLES SHALL BE LAID WITH MINIMUM 600mm U.N.O. COVER BELOW PROPOSED ROAD SURFACE OR APPROVED OTHER MEANS TO PROTECT DURING CONSTRUCTION.

ROAD SIGNS & LINE MARKING

- RS1. ALL SIGNS AND LINEMARKING SHALL BE TO ROADS & TRAFFIC AUTHORITY STANDARDS AND SPECIFICATIONS

- RS2. AND AS.1742, MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES
ALL LINEMARKING SHALL BE AUGMENTED BY RETROREFLECTIVE RAISED PAVEMENT MARKERS (RRPMs) AND ALL SHALL BE TO AS 1742.2 - 1994 AND AS 1742.2 /AMDT /11997-10-05
RS3. ALL ROAD SIGNS AND POSTS SHALL BE TO AS 1742.2 - 1994 AND AS 1742.2 /AMDT /11997-10-05

PROTECTION OF FLORA - REFER SPECIFICATION

- 1. ANY TRENCHES WITHIN 3m OF TREES SHALL BE HAND DUG TO AVOID DAMAGE TO TREE ROOTS.
2. IF IT IS CONSIDERED NECESSARY TO PERFORM ANY WORK ON TREES, INCLUDING TRIMMING, LOPPING, ROOT CUTTING, REPAIR AND REMOVAL, APPLICATION IN WRITING SHALL BE MADE BY THE CONTRACTOR TO THE SUPERINTENDENT. ANY WORK PERMITTED TO BE DONE ON TREES TO BE RETAINED SHALL BE PERFORMED IN ACCORDANCE WITH THE ARBORISTS REPORT.
3. MATURE TREES AND SHRUBS ARE TO BE REMOVED IN ACCORDANCE WITH THE ARBORISTS REPORT.

AUTHORITY STANDARDS

- LGA 1. THE DRAWINGS HEREIN SHALL BE READ IN CONJUNCTION WITH WARRINGAH CITY COUNCIL STANDARDS & SPECIFICATIONS WHICH SHALL OVERRIDE SPECIAL DETAILS SHOWN ON THE DRAWINGS.

TRAFFIC NOTE:

- 1. A TRAFFIC CONTROL PLAN IS TO BE PREPARED BY AN ACCREDITED RMS 1. TRAFFIC CONTROLLER AND SUBMITTED TO COUNCIL. THIS TRAFFIC PLAN IS TO BE CERTIFIED BY AND IMPLEMENTED TO THE SATISFACTION OF AN ACCREDITED RMS TRAFFIC CONTROLLER

PRIOR TO COMMENCEMENT OF WORK

- 2. ALL TRAFFIC CONTROL WORKS SHALL ONLY BE CARRIED OUT BY 2. ACCREDITED RMS TRAFFIC CONTROLLERS.

CLOSED CIRCUIT COLOUR TV (CCTV)

- CCTV 1. UNDERTAKE A CCTV INSPECTION OF ALL THE COMPLETED DRAINAGE IN ACCORDANCE WITH THE GUIDELINES OF THE AUSTRALIAN CONDUIT CONDITION EVALUATION MANUAL (ACCEN)
CCTV 2. APPLY THE FOLLOWING REQUIREMENTS TO THE CCTV INSPECTION:-
A. USE DATA CAPTURE SOFTWARE APPROVED BY SYDNEY WATER
B. USE CERTIFIED CCTV OPERATORS C. THE CCTV FOOTAGE SHALL BE OF QUALITY TO ALLOW ACCURATE ASSESSMENT OF THE INTERNAL CONDITION OF THE PIPE. FURNISH TO THE DESIGN CONSULTANT:-
CCTV 3. A. VIDEOS IN MPG FORMAT
B. CCTV REPORT AND SURVEY DATA IN PDF FORMAT

Scale: 1:1000 (A1)
Date: 10/11/2021 09:16:14
Project Name: you
Client File: T:\6118000\Drawings\AutoCAD\Civil\Design\Civil_2D\Development\application\C1.02_Specification Notes.dwg

DO NOT SCALE FROM DRAWINGS, CHECK & VERIFY ALL DIMENSIONS & LEVELS BEFORE COMMENCEMENT OF ANY WORK.
THIS DRAWING IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM WARREN SMITH CONSULTING ENGINEERS.

Table with 3 columns: REVISION, AMENDMENT, DATE. Contains 3 rows of revision data.

Table with 3 columns: REVISION, AMENDMENT, DATE. Contains 3 rows of revision data.

CLIENT: LODESTONE HQ
PROJECT: CHILDREN'S VILLAGE - CHILDCARE CENTRE & OOSH

WARREN SMITH CONSULTING ENGINEERS PTY LTD
NSW 9/233 Castlereagh St, Sydney 2000 NSW Australia
VIC 20/485 La Trobe St, Melbourne 3000 VIC Australia
PH +61 (2) 9299 1312
wsp@warrensmith.com.au
www.warrensmith.com.au


TITLE: SPECIFICATION NOTES
SCALE: AS SHOWN
DRAWN: I.K.
DESIGNED: R.X.
CHECKED: J.G.
APPROVED: M.C.
JOB No: 6118000
DRAWING No: C1.02
ISSUE: 3
DATE: NOVEMBER 2021
STATUS: S4.56 SUBMISSION

LEGEND

- SITE FENCE
- SITE GATE
- SEDIMENT FENCE
- GEOTEXTILE INLET FILTER
- DROP INLET SEDIMENT TRAP
- SEDIMENT TRAP FOR KERB INLETS
- VEHICLE ENTRY SHAKER GRID
- SITE STOCKPILE (LOCATIONS TO BE AGREED ON SITE)

NOTES



- GEOTEXTILE INLET FILTER BAGS TO BE FITTED IN ALL STORMWATER GRATED PITS WITHIN THE DEVELOPMENT AREA.
- STOCKPILE LOCATION IS INDICATIVE ONLY AND SHALL BE DETERMINED ON SITE DURING CONSTRUCTION STAGE.



PRELIMINARY - NOT FOR CONSTRUCTION

DO NOT SCALE FROM DRAWINGS, CHECK & VERIFY ALL DIMENSIONS & LEVELS BEFORE COMMENCEMENT OF ANY WORK.

THIS DRAWING IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM WARREN SMITH CONSULTING ENGINEERS.



REVISION	AMENDMENT	DATE	REVISION	AMENDMENT	DATE
1	ISSUE FOR INFORMATION	12/04/18			
2	DEVELOPMENT APPLICATION	20/04/18			
3	DEVELOPMENT APPLICATION	01/05/18			
4	S4.56 SUBMISSION	12/11/21			

CLIENT
LODESTONE HQ

PROJECT
**CHILDREN'S VILLAGE -
CHILD CARE CENTRE &
OOSHC**

PREPARED BY

WARREN SMITH CONSULTING ENGINEERS PTY LTD
SINCE 1981.


NSW 9/233 Castlereagh St, Sydney 2000 NSW Australia
VIC 20/485 La Trobe St, Melbourne 3000 VIC Australia
PH +61 (2) 9299 1312 PH +61 (3) 8648 9942
www.warrensmith.com.au
www.warrensmith.com.au
ACN 002 197 088 ABN 36 300 430 126

Hydraulic Fire Civil Utilities Infrastructure


TITLE
SEDIMENT AND EROSION CONTROL PLAN

SCALE AS SHOWN	DRAWN I.K.	DESIGNED R.X.	CHECKED J.G.	APPROVED M.C.
JOB No. 6118000	DRAWING No. C2.01		ISSUE 4	
DATE NOVEMBER 2021	STATUS S4.56 SUBMISSION			


Path: X:\6118000\Sub\Drawings\48 18000-048_C2.01_Sediment and Erosion Control Plan.dwg
 Plot Date: 10/11/2021 09:16:30 Login Name: jnu C:\p\1818000\Drawings\48 18000-048_C2.01_Sediment and Erosion Control Plan.dwg




SEDIMENT CONTROL FENCE
NTS




GEOTEXTILE FILTER FABRIC DROP INLET
NTS




HESSIAN BAG DROP INLET
NTS




NEW/EXISTING GRATED KERB ENTRY PIT
NTS




STABILIZED CONSTRUCTION SITE
VEHICLE ENTRY/EXIT
NTS




SEDIMENT FENCE DETAIL FOR ROCKY GROUND
NTS



SEDIMENT FENCE LAYOUT PLAN
NTS




EXCAVATED SEDIMENT TRAP
NTS



GEOTEXTILE FILTER BAGS
NTS

- SITE ENTRY/EXIT NOTES:-**
- ALL VEHICLE ENTRANCES & EXITS TO THE CONSTRUCTION SITE MUST BE STABILIZED TO PREVENT THEM BECOMING A SOURCE OF SEDIMENT, BY PROVIDING A VEHICLE SHAKE AREA. THIS MAY CONSIST OF A TIMBER, CONCRETE OR STEEL SHAKER GRID OR RUBBLE AREA.
 - THE VEHICLE EXIT AREA IS TO BE MAINTAINED IN A CLEAN & SERVICEABLE CONDITION DURING THE TOTAL TIME OF USAGE.
 - ANY UNSEALED ROAD BETWEEN THE DEVICE AND COUNCILS ROADWAY IS TO BE TOPPED WITH 100mm THICK, 4.0mm NOMINAL SIZE AGGREGATE.
 - PUBLIC ROADS MUST BE KEPT FREE OF DIRT AND MUD. SEDIMENT TRACKED ONTO THE PUBLIC ROADWAY BY VEHICLES LEAVING THE CONSTRUCTION SITE IS TO BE SWEEPED UP IMMEDIATELY.
 - FENCES SHOULD BE ERECTED TO ENSURE VEHICLES CAN NOT BYPASS THE STABILIZED ACCESS POINTS, UNLESS COMING FROM A STABILIZED AREA.



VEHICLE SHAKER GRID
NTS

- SITE ENTRY/EXIT CONSTRUCTION NOTES:-**
- STRIP TOP SOIL & LEVEL SITE. PROVIDE CATCH DRAIN AT SIDES TO DIRECT RUNOFF WATER TO SEDIMENT TRAPS.
 - COMPACT SUBGRADE AND REMOVE ANY HIGH POINTS.
 - COVER AREA WITH GEOTEXTILE FABRIC. THIS MAY BE WOVEN OR NEEDLE PUNCHED PRODUCT WITH A MINIMUM CBR BURST STRENGTH (AS3706.4-90) OF 2500 N.
 - CONSTRUCT 200mm THICK RUBBLE PAD OVER GEOTEXTILE USING ROAD BASE OR 30-40mm AGGREGATE. MINIMUM LENGTH 15 METRES OR TO BUILDING ALIGNMENT. MINIMUM WIDTH 3 METRES. CONSTRUCT 300mm HIGH HUMP IMMEDIATELY WITHIN BOUNDARY TO DIVERT WATER TO A SEDIMENT TRAP.
 - WHERE GRIDS ARE USED FIRST CONSTRUCT A 150 THICK PAD OVER GEOTEXTILE FABRIC. LEVEL THIS IN BOTH DIRECTIONS. LOWER GRID ON TO THE PREPARED BASE AND ENSURE THAT NO PART IS SITTING ON ANY HIGH POINTS. BACKFILL THE SPACES BETWEEN THE GRIDS TO WITHIN 50mm OF THE TOP.


- WHERE GRIDS ARE USED FIRST CONSTRUCT A 150 THICK PAD OVER GEOTEXTILE FABRIC. LEVEL THIS IN BOTH DIRECTIONS. LOWER GRID ON TO THE PREPARED BASE AND ENSURE THAT NO PART IS SITTING ON ANY HIGH POINTS. BACKFILL THE SPACES BETWEEN THE GRIDS TO WITHIN 50mm OF THE TOP.**
- PROVIDE RAMPS AT ENDS AND SIDE OF GRIDS. IF DEPRESSIONS OCCUR IN THE RAMPS DURING USE. ADD ADDITIONAL MATERIAL.

- MAINTENANCE REQUIREMENTS:-**
- ACCUMULATED SILT & SEDIMENT MUST BE REMOVED AT REGULAR INTERVALS AND AFTER EACH MAJOR STORM.
 - SILT & SEDIMENT MUST BE REMOVED FROM OFF THE SITE OR TO A COUNCIL APPROVED LOCATION WITHIN THE SITE, WHERE IT WILL NOT ERODE.
 - THE SEDIMENT FENCES, BALES & TRAPS SHALL BE REGULARLY INSPECTED, ESPECIALLY AFTER RAIN AND KEPT IN GOOD REPAIR AND FUNCTIONING CONDITION AT ALL TIMES.
 - CONSTRUCTION OPERATIONS SHALL BE CARRIED OUT IN SUCH A MANNER THAT SEDIMENT, EROSION & WATER POLLUTION SHALL BE MINIMIZED.
 - THE SEDIMENT TRAPS SHALL BE REMOVED AND THE AREA STABILIZED WHEN THE CONSTRUCTION AREA HAS BEEN PROPERLY STABILIZED.


- SEDIMENT FENCE NOTES:-**
- CONSTRUCT SEDIMENT FENCE AS CLOSE AS POSSIBLE TO PARALLEL TO THE CONTOURS OF THE SITE OR AT THE TOE OF A SLOPE.
 - DRIVE 1.5 METRE LONG STAR PICKETS INTO GROUND SUFFICIENT TO PROVIDE RIGID SUPPORT, 3 METERS APART, WHERE THERE IS INSUFFICIENT SOIL DEPTH OVER ROCK, HOLES ARE TO BE DRILLED INTO ROCK TO ACCEPT THE STAR PICKETS.
 - ON SOFT GROUND MATERIALS, DIG A 150mm DEEP TRENCH ALONG THE UPSLOPE LINE OF THE FENCE FOR THE BOTTOM OF THE FABRIC TO BE ENTRENCHED. BACKFILL TRENCH OVER BASE OF FABRIC & COMPACT.
 - FIX SELF-SUPPORTING GEOTEXTILE TO UPSLOPE SIDE OF POSTS WITH WIRE TIES OR AS RECOMMENDED BY THE GEOTEXTILE MANUFACTURER. USE A REINFORCEMENT BACKING WITH NON SELF-SUPPORTING GEOTEXTILE FABRIC.
 - JOIN SECTIONS OF FABRIC AT A SUPPORT POST WITH A 150mm OVERLAP.
 - ON HARD OR ROCKY GROUND, SMOOTH A 500mm WIDE STRIP UPSLOPE OF THE FENCE LINE. TURN THE BOTTOM 500mm OF THE FABRIC UPSLOPE AND ANCHOR IN PLACE WITH SUITABLE AGGREGATE.
 - WHERE A SEDIMENT FENCE IS CONSTRUCTED DOWN SLOPE FROM A DISTURBED BATTER THE FENCE SHOULD BE LOCATED 1.5 TO 2.0 METERS DOWN SLOPE FROM THE TOE OF THE BATTER.

- EXCAVATED SEDIMENT TRAP NOTES:-**
- REMOVE THE SEDIMENT WHEN IT HAS ACCUMULATED TO HALF THE DESIGN DEPTH OF THE TRAP AND RESTORE THE TRAP TO ITS ORIGINAL DIMENSIONS.
 - PROVIDE 50 cu.m/Ha OF SEDIMENT STORAGE VOLUME.
 - REFER TO THE MAINTENANCE REQUIREMENTS.


- SEDIMENT BARRIER FOR PITS & PIPES, NOTES:-**
- SLEEVES ARE TO BE MADE FROM GEOTEXTILE FABRIC LONGER THEN THE LENGTH OF THE INLET PIT.
 - FILL SLEEVE WITH 5 OR 10mm CLEAN GRAVEL.
 - PLACE THE SLEEVE AT THE OPENING OF THE KERB INLET LEAVING A 100mm GAP TO ACT AS AN EMERGENCY OVERFLOW.
 - SLEEVE MUST BE PLACED AGAINST THE KERB TO PREVENT BYPASS.
 - FIT SLEEVE TO ALL INLETS DOWNSTREAM OF THE WORKS.
 - FOR DRAINAGE WORKS FIT GEOTEXTILE FABRIC OR GEO BAGS TO UPSLOPE FACE OF ALL OPEN PIPES.
 - MAINTAIN AN OPENING AT THE TOP OF THE PIPE OF 1/3 OF THE PIPE DIAMETER.
 - THE FILTERS ARE TO BE CLEANED AND MAINTAINED DAILY.
 - ALL CARE SHOULD BE TAKEN TO MINIMIZE SEDIMENT REACHING THE STORMWATER SYSTEM BY MINIMIZING EXCAVATION WORKS AND PREVENTING EXCESS WATER FLOW THROUGH WORKS.




TYPICAL STRAW BALE SECTION
NTS



TYPICAL STRAW BALE DETAIL
NTS




VIEW OF CHECK DAM
NTS



DIVERSION DRAIN (LOW FLOW)
NTS

- DIVERSION DRAIN NOTES:-**
- CONSTRUCT WITH GRADIENT OF 1 PER CENT TO 5 PER CENT.
 - AVOID REMOVING TREES AND SHRUBS IF POSSIBLE.
 - DRAINS TO BE OF CIRCULAR, PARABOLIC OR TRAPEZOIDAL CROSS SECTION NOT V-SHAPED.
 - EARTH BANKS TO BE ADEQUATELY COMPACTED IN ORDER TO PREVENT FAILURE.
 - PERMANENT OR TEMPORARY STABILIZATION OF THE EARTH BANK TO BE COMPLETED WITHIN 10 DAYS OF CONSTRUCTION.
 - ALL OUTLETS FROM DISTURBED LANDS ARE TO FEED INTO A SEDIMENT BASIN OR SIMILAR.
 - DISCHARGE RUN OFF COLLECTED FROM UNDISTURBED LANDS ONTO EITHER A STABILIZED OR AN UNDISTURBED DISPOSAL SITE WITHIN THE SAME SUBCATCHMENT AREA FROM WHICH THE WATER ORIGINATED.
 - COMPACT BANK WITH A SUITABLE IMPLEMENT IN SITUATIONS WHERE THEY ARE REQUIRED TO FUNCTION FOR MORE THAN FIVE DAYS.
 - EARTH BANKS TO BE FREE OF PROJECTIONS OR OTHER IRREGULARITIES THAT WILL IMPEDE NORMAL FLOW.




TYPICAL STRAW BALE LAYOUT PLAN
NTS

CHECK DAM SPACING TABLE


LONGITUDINAL GRADE (%)	SPACING (METERS)
0 - 5	40
5 - 10	30
10 - 15	20
GREATER THAN 15	10

STRAW BALE CHECK DAM DETAILS
NTS

- STRAW BALE NOTES:-**
- CONSTRUCT STRAW BALE FILTER AS CLOSE AS POSSIBLE TO PARALLEL TO THE CONTOURS OF THE SITE OR AT THE TOE OF A SLOPE.
 - PLACE BALES LENGTHWISE IN A ROW WITH ENDS TIGHTLY ABUTTING. USE STRAW TO FILL ANY GAPS BETWEEN BALES, STRAWS TO BE PLACED PARALLEL TO GROUND.
 - MAXIMUM HEIGHT OF FILTER IS ONE BALE.
 - ON SOFT MATERIALS, EMBED EACH BALE IN THE GROUND 75mm TO 100mm AND ANCHOR WITH TWO 1.2 METRE STAR PICKETS. ANGLE THE FIRST STAKE IN EACH BALE TOWARDS THE PREVIOUSLY LAID BALE. DRIVE STAKES 600mm INTO THE GROUND AND FLUSH WITH THE TOP OF THE BALES.
 - WHERE A STRAW BALE FILTER IS CONSTRUCTED DOWN SLOPE FROM A DISTURBED BATTER THE BALES SHOULD BE LOCATED 1.5 TO 2.0 METERS DOWN SLOPE FROM THE TOE OF THE BATTER.
 - WHERE REQUIRED WRAP GEOTEXTILE FILTER FABRIC AROUND BALES AND STAPLE IN POSITION.



CHECK DAM SECTION
NTS



CHECK DAM PLAN
NTS

DO NOT SCALE FROM DRAWINGS, CHECK & VERIFY ALL DIMENSIONS & LEVELS BEFORE COMMENCEMENT OF ANY WORK.

THIS DRAWING IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM WARREN SMITH CONSULTING ENGINEERS.

REVISION	AMENDMENT	DATE	REVISION	AMENDMENT	DATE
1	ISSUE FOR INFORMATION	12/04/18			
2	DEVELOPMENT APPLICATION	20/04/18			
3	DEVELOPMENT APPLICATION	01/05/18			
4	S4.56 SUBMISSION	12/11/21			

CLIENT	PROJECT
LODESTONE HQ	CHILDREN'S VILLAGE - CHILD CARE CENTRE & OOSHC

PREPARED BY	TITLE
Warren Smith Consulting Engineers	SEDIMENT AND EROSION CONTROL DETAILS

SCALE	DRAWN	DESIGNED	CHECKED	APPROVED
AS SHOWN	I.K.	R.X.	J.G.	M.C.

JOB No.	DRAWING No.	ISSUE
6118000	C2.02	4


DATE: NOVEMBER 2021 STATUS: S4.56 SUBMISSION

PRELIMINARY - NOT FOR CONSTRUCTION

LEGEND

	PROPOSED PIPE DIAMETER AND DIRECTION OF FLOW		GRADED TRENCH DRAIN
	STORMWATER PIPE		PIPE CONTINUATION
	EXISTING PIPE DIAMETER AND DIRECTION OF FLOW		CLEAROUT
	EXISTING STORMWATER PIPE		KERB ONLY
	GRADED INLET PIT		PROPOSED FINISHED LEVEL
	JUNCTION PIT		PROPOSED GRATE LEVEL
	INDICATIVE OVERLAND FLOW ROUTE		PROPOSED TOP OF KERB LEVEL
			DIRECTION AND GRADE OF FALL

NOTES:
 1. ALL GRADED INLET PITS TO BE FITTED WITH ENVIPOD FILTER BASKETS SUPPLIED BY OCEAN PROTECT, INCLUDING THE GRADED LID ON THE OSD TANK.
 2. ALL GRATES WITHIN TRAFFICABLE AREAS ARE TO BE HEELSAFE.
 3. REFER TO HYDRAULIC ENGINEERS DRAWINGS FOR DOWNPIPE LOCATIONS AND DETAILS.




PRELIMINARY - NOT FOR CONSTRUCTION

No. 141 19000-16, 141 19000-17, 141 19000-18, 141 19000-19, 141 19000-20, 141 19000-21, 141 19000-22, 141 19000-23, 141 19000-24, 141 19000-25, 141 19000-26, 141 19000-27, 141 19000-28, 141 19000-29, 141 19000-30, 141 19000-31, 141 19000-32, 141 19000-33, 141 19000-34, 141 19000-35, 141 19000-36, 141 19000-37, 141 19000-38, 141 19000-39, 141 19000-40, 141 19000-41, 141 19000-42, 141 19000-43, 141 19000-44, 141 19000-45, 141 19000-46, 141 19000-47, 141 19000-48, 141 19000-49, 141 19000-50, 141 19000-51, 141 19000-52, 141 19000-53, 141 19000-54, 141 19000-55, 141 19000-56, 141 19000-57, 141 19000-58, 141 19000-59, 141 19000-60, 141 19000-61, 141 19000-62, 141 19000-63, 141 19000-64, 141 19000-65, 141 19000-66, 141 19000-67, 141 19000-68, 141 19000-69, 141 19000-70, 141 19000-71, 141 19000-72, 141 19000-73, 141 19000-74, 141 19000-75, 141 19000-76, 141 19000-77, 141 19000-78, 141 19000-79, 141 19000-80, 141 19000-81, 141 19000-82, 141 19000-83, 141 19000-84, 141 19000-85, 141 19000-86, 141 19000-87, 141 19000-88, 141 19000-89, 141 19000-90, 141 19000-91, 141 19000-92, 141 19000-93, 141 19000-94, 141 19000-95, 141 19000-96, 141 19000-97, 141 19000-98, 141 19000-99, 141 19000-100

DO NOT SCALE FROM DRAWINGS, CHECK & VERIFY ALL DIMENSIONS & LEVELS BEFORE COMMENCEMENT OF ANY WORK. THIS DRAWING IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM WARREN SMITH CONSULTING ENGINEERS.	 NORTH	 SCALE 1:200 AT SHEET	REVISION 1: ISSUE FOR INFORMATION 11/04/18 REVISION 2: DEVELOPMENT APPLICATION 20/04/18 REVISION 3: DEVELOPMENT APPLICATION 01/05/18 REVISION 4: S4.56 SUBMISSION 12/11/21	REVISION 1: REVISION 2: REVISION 3: REVISION 4:	CLIENT: LODESTONE HQ PROJECT: CHILDREN'S VILLAGE - CHILDCARE CENTRE & OOSH	PREPARED BY: 	WARREN SMITH CONSULTING ENGINEERS PTY LTD SINCE 1981. NSW: 9/23 Castlereagh St, Sydney 2000 NSW Australia VIC: 20/485 La Trobe St, Melbourne 3000 VIC Australia PH +61 (0) 9299 1312 PH +61 (0) 8648 9942 www.warrensmith.com.au www.warrensmith.com.au ACN 002 197 088 ABN 36 300 430 126 ■ Hydraulic ■ Fire ■ Civil ■ Utilities Infrastructure	TITLE: STORMWATER LAYOUT PLAN SCALE: AS SHOWN DRAWN: I.K. DESIGNED: R.X. CHECKED: J.G. APPROVED: M.C. JOB No. 6118000 DRAWING No. C6.01 ISSUE 4 DATE: NOVEMBER 2021 STATUS: S4.56 SUBMISSION			

Scenario	20% AEP Storm Event (L/Sec)	5% AEP Storm Event (L/Sec)	1% AEP Storm Event (L/Sec)
Pre-Development Discharge	65	110	167
Post Development Discharge	56	72	88





PRELIMINARY - NOT FOR CONSTRUCTION

Path: X:\118000\Sub\Drawings\118000-AB_Level3_118000-TP_A14_X4118000-AB_Schedule_X4118000-AB_External Works (Orion)
 File Name: 118000-AB_Level3_118000-TP_A14_X4118000-AB_Schedule_X4118000-AB_External Works (Orion)
 Date: 11/11/2021 10:02:38 AM
 User: jason

DO NOT SCALE FROM DRAWINGS, CHECK & VERIFY ALL DIMENSIONS & LEVELS BEFORE COMMENCEMENT OF ANY WORK.

THIS DRAWING IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM WARREN SMITH CONSULTING ENGINEERS.



REVISION	AMENDMENT	DATE	REVISION	AMENDMENT	DATE
1	DEVELOPMENT APPLICATION	20/04/18			
2	DEVELOPMENT APPLICATION	01/05/18			
3	S4.56 SUBMISSION	12/11/21			

CLIENT
LODESTONE HQ

PROJECT
**CHILDREN'S VILLAGE -
CHILD CARE CENTRE &
OOSHC**

PREPARED BY

WARREN SMITH CONSULTING ENGINEERS PTY LTD
SINCE 1981.

NSW
9/23 Castlereagh St,
Sydney 2000 NSW Australia
PH +61 (2) 9299 1312

VIC
20/485 La Trobe St,
Melbourne 3000 VIC
Australia
PH +61 (3) 8648 9942


www.warrensmith.com.au
ACN 002 197 088 ABN 36 300 430 126

Hydraulic Fire Civil Utilities Infrastructure

TITLE				
STORMWATER CATCHMENT PLAN				
SCALE	DRAWN	DESIGNED	CHECKED	APPROVED
AS SHOWN	I.K.	R.X.	J.G.	M.C.
JOB No.	DRAWING No.		ISSUE	
6118000	C6.02		3	
DATE	STATUS			
NOVEMBER 2021	S4.56 SUBMISSION			

0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

LEGEND	
$\overline{\text{Ø300}}$	PIPE DIAMETER AND DIRECTION OF FLOW (IN-GROUND DRAINAGE)
$\overline{\text{SW}}$	PROPOSED STORMWATER PIPE (IN-GROUND DRAINAGE)
$\overline{\text{Ø150}}$	PIPE DIAMETER AND DIRECTION OF FLOW (SUSPENDED DRAINAGE)
$\overline{\text{SW}}$	PROPOSED STORMWATER PIPE (SUSPENDED DRAINAGE)
$\overline{\text{GD}}$	GRATED TRENCH DRAIN
\rhd	DROPPER
S	PIPE CONTINUATION
RWO	SPS 150mm SUPERFLO RAINWATER OUTLET w/ CLASS D HEAVY DUTY FLAT GRATE (SIA150F)
\bullet DPS	Ø100 DOWNPIPE SPREADER
\bullet DP1	Ø100 DOWNPIPE
\bullet DP2	Ø150 DOWNPIPE





PRELIMINARY - NOT FOR CONSTRUCTION

Path: X:\11800018_A41\11800018_A41\11800018_C6.03\11800018_C6.03_Roof Drainage Plan.dwg
 Plot Date: 11/11/2021 09:12:43
 User: Name: you
 Plot File: 11800018_A41\11800018_A41\11800018_C6.03\11800018_C6.03_Roof Drainage Plan.dwg

DO NOT SCALE FROM DRAWINGS, CHECK & VERIFY ALL DIMENSIONS & LEVELS BEFORE COMMENCEMENT OF ANY WORK.

THIS DRAWING IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM WARREN SMITH CONSULTING ENGINEERS.



REVISION	AMENDMENT	DATE	REVISION	AMENDMENT	DATE
1	DEVELOPMENT APPLICATION	20/04/18			
2	DEVELOPMENT APPLICATION	01/05/18			
3	S4.56 SUBMISSION	12/11/21			

CLIENT
WARD CIVIL

PROJECT
BARANGAROO STATION

PREPARED BY

WARREN SMITH CONSULTING ENGINEERS PTY LTD
SINCE 1981.

NSW 9/233 Castlereagh St, Sydney 2000 NSW Australia	VIC 20/485 La Trobe St, Melbourne 3000 VIC Australia
PH +61 (2) 9299 1312	PH +61 (3) 8648 9942
www.warrensmith.com.au	
ACN 002 197 088 ABN 36 300 430 126	

Hydraulic Fire Civil Utilities Infrastructure


TITLE
ROOF DRAINAGE PLAN

SCALE	DRAWN	DESIGNED	CHECKED	APPROVED
AS SHOWN	L.S.I.K.	R.X	J.G.	J.G.

JOB No. **7350000** DRAWING No. **C6.03** ISSUE **3**

DATE **NOVEMBER 2021** STATUS **ISSUE FOR INFORMATION**

0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



OSD PLAN
SCALE 1:50

PRELIMINARY - NOT FOR CONSTRUCTION

Path: X:\18000\18000_01_A11.dwg
 Plot Date: 11/11/2021 09:17:26:32
 User Name: you
 Call File: 18118000\Drawings\AutoCAD\Design\Civil 3D\Development Applications\OSD1 Tank Plan.dwg

DO NOT SCALE FROM DRAWINGS, CHECK & VERIFY ALL DIMENSIONS & LEVELS BEFORE COMMENCEMENT OF ANY WORK.

THIS DRAWING IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM WARREN SMITH CONSULTING ENGINEERS.

REVISION	AMENDMENT	DATE	REVISION	AMENDMENT	DATE
1	DEVELOPMENT APPLICATION	20/04/18			
2	DEVELOPMENT APPLICATION	01/05/18			
3	S4.56 SUBMISSION	12/11/21			

CLIENT
LODESTONE HQ

PROJECT
**CHILDREN'S VILLAGE -
CHILD CARE CENTRE &
OOSHC**

PREPARED BY



WARREN SMITH CONSULTING ENGINEERS PTY LTD
SINCE 1981.

NSW
9/23 Castlereagh St,
Sydney 2000 NSW Australia
PH +61 (2) 9299 1312


VIC
20/485 La Trobe St,
Melbourne 3000 VIC
Australia
PH +61 (3) 8648 9942

www.warrensmith.com.au
ACN 002 197 088 ABN 36 300 430 126




Hydraulic Fire Civil Utilities Infrastructure

TITLE				
OSD TANK PLAN				
SCALE	DRAWN	DESIGNED	CHECKED	APPROVED
AS SHOWN	I.K.	R.X.	J.G.	M.C.
JOB No.	DRAWING No.		ISSUE	
6118000	C6.05		3	
DATE	STATUS			
NOVEMBER 2021	S4.56 SUBMISSION			



SECTION A
SCALE: 1:30



SECTION B
SCALE: 1:30

PRELIMINARY - NOT FOR CONSTRUCTION

Path: X:\180000\Drawings\AutoCAD\Design\Civil 2D\Development Applications\OSD Tank Plans.dwg
 Plot Date: 11/11/2021 09:12:33
 Login Name: you
 Call File: 181180000\Drawings\AutoCAD\Design\Civil 2D\Development Applications\OSD Tank Plans.dwg

DO NOT SCALE FROM DRAWINGS, CHECK & VERIFY ALL DIMENSIONS & LEVELS BEFORE COMMENCEMENT OF ANY WORK.
THIS DRAWING IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM WARREN SMITH CONSULTING ENGINEERS.

REVISION	AMENDMENT	DATE	REVISION	AMENDMENT	DATE
1	DEVELOPMENT APPLICATION	20/04/18			
2	DEVELOPMENT APPLICATION	01/05/18			
3	S4.56 SUBMISSION	12/11/21			

CLIENT
LODESTONE HQ

PROJECT
**CHILDREN'S VILLAGE -
CHILD CARE CENTRE &
OOSHC**

PREPARED BY



WARREN SMITH CONSULTING ENGINEERS PTY LTD
SINCE 1981.

NSW
9/23 Castlereagh St,
Sydney 2000 NSW Australia
PH +61 (2) 9299 1312





VIC
20/485 La Trobe St,
Melbourne 3000 VIC
Australia
PH +61 (3) 8648 9942

www.warrensmith.com.au
www.warrensmith.com.au
ACN 002 197 088 ABN 36 300 430 126

Hydraulic Fire Civil Utilities Infrastructure





OSD TANK SECTIONS				
SCALE	DRAWN	DESIGNED	CHECKED	APPROVED
AS SHOWN	I.K.	R.X.	J.G.	M.C.
JOB No.	DRAWING No.		ISSUE	
6118000	C6.06		3	
DATE	STATUS			
NOVEMBER 2021	S4.56 SUBMISSION			

0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



NOTES:

1. TRENCH WIDTH MAY NEED TO BE INCREASED SUBJECT TO ACHIEVING ADEQUATE COMPACTION.
2. MINIMUM PIPE COVER NOT UNDER ROADS = 450mm UNO.
3. THE CONTRACTOR SHALL ENSURE THAT THE SHORING OF TRENCHES IS INSTALLED AS REQUIRED BY STATUTORY REQUIREMENTS.
4. ENSURE BACKFILLING COMPACTION MEETS THE RELEVANT STANDARDS:
 - A) TRENCHES UNDER PAVED AREAS & BUILDINGS - 100% SMDD.
 - B) TRENCHES NOT UNDER PAVEMENTS - 95% SMDD.



PRELIMINARY - NOT FOR CONSTRUCTION

Path: X:\18000\18_01_A14
 File: 1818000\Drawings\AutoCAD\Civil\Design\Civil_2D\development\applications\C6.07 Stormwater Drainage Details.dwg
 Plot Date: 10/11/2021 09:16:18:46
 Login Name: you

DO NOT SCALE FROM DRAWINGS, CHECK & VERIFY ALL DIMENSIONS & LEVELS BEFORE COMMENCEMENT OF ANY WORK.

THIS DRAWING IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM WARREN SMITH CONSULTING ENGINEERS.

REVISION	AMENDMENT	DATE	REVISION	AMENDMENT	DATE
1	DEVELOPMENT APPLICATION	20/04/18			
2	DEVELOPMENT APPLICATION	01/05/18			
3	S4.56 SUBMISSION	12/11/21			

CLIENT
LODESTONE HQ

PROJECT
**CHILDREN'S VILLAGE -
CHILD CARE CENTRE &
OOSHC**

PREPARED BY

WARREN SMITH CONSULTING ENGINEERS PTY LTD
SINCE 1981.



NSW
9/23 Castlereagh St,
Sydney 2000 NSW Australia
PH +61 (2) 9299 1312

VIC
20/485 La Trobe St,
Melbourne 3000 VIC
Australia
PH +61 (3) 8648 9942

www.warrensmith.com.au
www.warrensmith.com.au
ACN 002 197 088 ABN 36 300 430 126

Hydraulic Fire Civil Utilities Infrastructure

TITLE				
STORMWATER DRAINAGE DETAILS				
SCALE	DRAWN	DESIGNED	CHECKED	APPROVED
AS SHOWN	I.K.	R.X.	J.G.	M.C.
JOB No.	DRAWING No.		ISSUE	
6118000	C6.07		3	
DATE	STATUS			
NOVEMBER 2021	S4.56 SUBMISSION			



PRELIMINARY - NOT FOR CONSTRUCTION

Path: X:\190000\B_A\H...
 Cell File: 16118000\Drawings\AutoCAD\Design\Civil_2D\Development Application\C6.08 Stormwater360 Treatment Device Typical Details.dwg
 Login Name: you
 Plot Date: 11/11/2021 09:17:28.36

DO NOT SCALE FROM DRAWINGS, CHECK & VERIFY ALL DIMENSIONS & LEVELS BEFORE COMMENCEMENT OF ANY WORK.

THIS DRAWING IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM WARREN SMITH CONSULTING ENGINEERS.

REVISION	AMENDMENT	DATE	REVISION	AMENDMENT	DATE
1	DEVELOPMENT APPLICATION	20/04/18			
2	DEVELOPMENT APPLICATION	01/05/18			
3	S4.56 SUBMISSION	12/11/21			

CLIENT
LODESTONE HQ

PROJECT
**CHILDREN'S VILLAGE -
CHILD CARE CENTRE &
OOSHC**

PREPARED BY



WARREN SMITH CONSULTING ENGINEERS PTY LTD
SINCE 1981.

NSW 9/233 Castlereagh St, Sydney 2000 NSW Australia	VIC 20/485 La Trobe St, Melbourne 3000 VIC Australia
PH +61 (2) 9299 1312	PH +61 (3) 8648 9942
wsp@warrensmith.com.au	
www.warrensmith.com.au	
ACN 002 197 088 ABN 36 300 430 126	

Hydraulic Fire Civil Utilities Infrastructure



TITLE				
STORMWATER360 TREATMENT DEVICE TYPICAL DETAILS				
SCALE	DRAWN	DESIGNED	CHECKED	APPROVED
AS SHOWN	I.K.	R.X.	J.G.	M.C.
JOB No.	DRAWING No.		ISSUE	
6118000	C6.08		3	
DATE	STATUS			
31/03/17	S4.56 SUBMISSION			

0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150