page 1/6

BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A401580 04

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv

Date of issue: Thursday, 17, November 2022 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project address		
Project name	Bell_04	
Street address	45 Ernest Street Balgowlah Heights 2093	
Local Government Area	Northern Beaches Council	
Plan type and number	Deposited Plan 12817	
Lot number	3	
Section number		
Section number Project type		
	Separate dwelling house	

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Rapid Plans

ABN (if applicable): 43150064592

Pool and Spa	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Rainwater tank			
The applicant must install a rainwater tank of at least 1006 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rainwater runoff from at least 76.3 square metres of roof area.		\checkmark	\checkmark
The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool.		\checkmark	\checkmark
Outdoor swimming pool			
The swimming pool must be outdoors.	\checkmark	\checkmark	
The swimming pool must not have a capacity greater than 35.4 kilolitres.	\checkmark	\checkmark	\checkmark
The swimming pool must have a pool cover.		\checkmark	\checkmark
The applicant must install a pool pump timer for the swimming pool.		\checkmark	\checkmark
The applicant must install the following heating system for the swimming pool that is part of this development: electric heat pump.		\checkmark	\checkmark

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Fixtures	1		
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		\checkmark	\checkmark
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		\checkmark	\checkmark
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		\checkmark	

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
	tion is not required where the area of new con	s) in accordance with the specifications listed in struction is less than 2m2, b) insulation specified	~	~	~
Construction	Additional insulation required (R-value)	Other specifications			
concrete slab on ground floor.	nil				
external wall: concrete block/plasterboard	R1.18 (or R1.70 including construction)				

Glazing requ	irements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows and	d glazed do	ors							
					hading devices, in accordance with r each window and glazed door.	the specifications listed in the table below.	~	 	~
The following r	equirements r	must also	be satisfi	ed in relation	n to each window and glazed door:			~	~
have a U-value must be calcula	and a Solar	Heat Gair lance with	Coefficie National	ent (SHGC) Fenestratio	no greater than that listed in the tab	ar glazing, or toned/air gap/clear glazing must le below. Total system U-values and SHGCs s. The description is provided for information		~	~
For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.					~	\checkmark	~		
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.							\checkmark	\checkmark	
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.							\checkmark	~	
Windows ar	nd glazed o	doors gl	azing r	equireme	nts		-		
			ershadowing	Shading device	Frame and glass type				
10.		inc. frame (m2)	Height (m)	Distance (m)					
W1	W	0.6	0	0	none	improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75)			
W2	N	3.3	0	0	eave/verandah/pergola/balcony >=450 mm	improved aluminium, single pyrolytic low-e, (U-value: 4.48, SHGC: 0.46)			
W3	W	0.23	0	0	none	improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75)			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
"
"
"
"
"
"
"
"
"
"
Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " / " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.