BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1130171S_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary Date of issue: Friday, 29 April 2022 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project summary			
Project name	Harbord Bowling Club_02		
Street address	4/0 Bennett Street Curl Curl 2096		
Local Government Area	Northern Beaches Council		
Plan type and plan number	deposited 601758		
Lot no.	4		
Section no.	-		
Project type	separate dwelling house		
No. of bedrooms	0		
Project score			
Water	V 40 Target 40		
Thermal Comfort	V Pass Target Pass		
Energy	V 70 Target 50		

Name / Company Name: Rapid Plans

ABN (if applicable): 43150064592

Description of project

Project address

Harbord Bowling Club_02
4/0 Bennett Street Curl Curl 2096
Northern Beaches Council
Deposited Plan 601758
4
-
separate dwelling house
0
2800
269
51.88
52.8
1000

Assessor details and thermal lo	ads	
Assessor number	n/a	
Certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m ² .year)	n/a	
Area adjusted heating load (MJ/m².year)	n/a	
Ceiling fan in at least one bedroom	n/a	
Ceiling fan in at least one living room or other conditioned area	n/a	
Project score		
Water	V 40	Target 40
Thermal Comfort	V Pass	Target Pass
Energy	70	Target 50

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 500 square metres of the site.	~	~	
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 6 but <= 7.5 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		 	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		 Image: A set of the set of the	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 6000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 297.77 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
 the cold water tap that supplies each clothes washer in the development 		✓	~
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		 Image: A second s	~

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - cavity brick	0.50 (or 1.17 including construction)	
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 3.5 (up), roof: foil backed blanket (75 mm)	framed; medium (solar absorptance 0.475-0.70)

• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.

Note • In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	~	~
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	~
The following requirements must also be satisfied in relation to each window and glazed door:	~	 Image: A set of the set of the	~
• For the following glass and frame types, the certifier check can be performed by visual inspection.			~
- Aluminium single clear			
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North-East facing					
W3	1200	2700	aluminium, single, clear	eave 1500 mm, 1125 mm above head of window or glazed door	not overshadowed
South-East facing					
D5	2100	1800	aluminium, single, clear	eave 750 mm, 878 mm above head of window or glazed door	not overshadowed
South-West facing					
W6	500	1800	aluminium, single, clear	eave 150 mm, 550 mm above head of window or glazed door	not overshadowed
W4	500	1800	aluminium, single, clear	eave 150 mm, 550 mm above head of window or glazed door	not overshadowed
W5	500	600	aluminium, single, clear	eave 150 mm, 550 mm above head of window or glazed door	not overshadowed
North-West facing			·	·	·

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
W7	900	2700	aluminium, single, clear	eave 3050 mm, 952 mm above head of window or glazed door	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: solar (electric boosted).	~	v	~
Cooling system			
The living areas must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		~	~
The bedrooms must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		~	~
Heating system			
The living areas must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	~
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	~
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: no mechanical ventilation (ie. natural); Operation control: n/a		 Image: A second s	~
Kitchen: no mechanical ventilation (ie. natural); Operation control: n/a		 Image: A second s	~
Laundry: natural ventilation only, or no laundry; Operation control: n/a		v	-
Artificial lighting	1		1
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
 at least 1 of the bedrooms / study; dedicated 		~	-
 at least 1 of the living / dining rooms; dedicated 		 Image: A second s	-
the kitchen; dedicated		_	~

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
all bathrooms/toilets; dedicated		v	~
the laundry; dedicated		v	~
all hallways; dedicated		~	~
Alternative energy			
The applicant must install a photovoltaic system with the capacity to generate at least 1 peak kilowatts of electricity as part of the development. The applicant must connect this system to the development's electrical system.	~	 	~
Other			
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		 	
The applicant must install a fixed outdoor clothes drying line as part of the development.		~	
The applicant must install a fixed indoor or sheltered clothes drying line as part of the development.		~	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a vi in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a vi in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a vi in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.