

Memorandum

To	Henroth Investments Pty Ltd	Dan Maurici	dan@henroth.com.au
From	Scott Easton	Date	5 December 2016
Subject	Groundwater Measurements 3-12 Boondah Road, Warriewood	Project No.	85749.00

This provides the factual results of groundwater monitoring undertaken for the proposed Bulky Goods Centre at 3-12 Boondah Road, Warriewood. The monitoring was carried out at the request of Henroth Investments Pty Ltd (Henroth).

Four boreholes (BH1 to BH4) were drilled at the locations nominated by Henroth (see attached Drawing 1). The boreholes were drilled to depths of between 4.5 m and 6.0 m using a bobcat sized and truck mounted drilling rig. Groundwater monitoring wells comprising Class 18 machine slotted PVC were installed in each of the boreholes. Steel protective covers were installed at the surface.

The borehole logs are attached and show the soil profile encountered and the monitoring well construction details. The boreholes were logged on site by a geotechnical engineer. The surface levels at each of the boreholes were measured using optical survey equipment relative to State Survey Mark (PM6869, RL2.603 m relative to Australia Height Datum [AHD]).

A summary of the measured groundwater levels within the monitoring wells is provided in Table 1.

Table 1: Summary of Groundwater Measurements in Monitoring Wells

Borehole (Well)	Surface RL (m, AHD)	Well Depth (m)	Measured Depth (m) and RL (m, AHD) to Groundwater in Monitoring Wells 23 November 2016
1	2.4	4.9	1.6 (RL0.8)
2	2.3	4.0	1.2 (RL1.1)
3	4.1	5.8	2.7 (RL1.4)
4	2.1	4.0	1.4 (RL0.7)

Measured water levels vary from RL0.8 m to RL1.0 m over most of the site (BH1 to BH3) and rise slightly to RL1.4 m on the elevated northern end part of the site (BH4). Groundwater levels will fluctuate and may temporarily rise by at least 1 m (or higher and up to flood levels) following prolonged rainfall. Further monitoring would be required to assess fluctuations in groundwater levels.

We trust the above satisfies your present requirements. Please contact the undersigned should you have any queries.

Yours faithfully,
Douglas Partners Pty Ltd



Scott Easton
Principal

Reviewed by



Ray Blinman
Principal

Attached: About this Report
 Borehole Logs
 Drawing 1 – Location of Boreholes

About this Report

Douglas Partners



Introduction

These notes have been provided to amplify DP's report in regard to classification methods, field procedures and the comments section. Not all are necessarily relevant to all reports.

DP's reports are based on information gained from limited subsurface excavations and sampling, supplemented by knowledge of local geology and experience. For this reason, they must be regarded as interpretive rather than factual documents, limited to some extent by the scope of information on which they rely.

Copyright

This report is the property of Douglas Partners Pty Ltd. The report may only be used for the purpose for which it was commissioned and in accordance with the Conditions of Engagement for the commission supplied at the time of proposal. Unauthorised use of this report in any form whatsoever is prohibited.

Borehole and Test Pit Logs

The borehole and test pit logs presented in this report are an engineering and/or geological interpretation of the subsurface conditions, and their reliability will depend to some extent on frequency of sampling and the method of drilling or excavation. Ideally, continuous undisturbed sampling or core drilling will provide the most reliable assessment, but this is not always practicable or possible to justify on economic grounds. In any case the boreholes and test pits represent only a very small sample of the total subsurface profile.

Interpretation of the information and its application to design and construction should therefore take into account the spacing of boreholes or pits, the frequency of sampling, and the possibility of other than 'straight line' variations between the test locations.

Groundwater

Where groundwater levels are measured in boreholes there are several potential problems, namely:

- In low permeability soils groundwater may enter the hole very slowly or perhaps not at all during the time the hole is left open;

- A localised, perched water table may lead to an erroneous indication of the true water table;
- Water table levels will vary from time to time with seasons or recent weather changes. They may not be the same at the time of construction as are indicated in the report; and
- The use of water or mud as a drilling fluid will mask any groundwater inflow. Water has to be blown out of the hole and drilling mud must first be washed out of the hole if water measurements are to be made.

More reliable measurements can be made by installing standpipes which are read at intervals over several days, or perhaps weeks for low permeability soils. Piezometers, sealed in a particular stratum, may be advisable in low permeability soils or where there may be interference from a perched water table.

Reports

The report has been prepared by qualified personnel, is based on the information obtained from field and laboratory testing, and has been undertaken to current engineering standards of interpretation and analysis. Where the report has been prepared for a specific design proposal, the information and interpretation may not be relevant if the design proposal is changed. If this happens, DP will be pleased to review the report and the sufficiency of the investigation work.

Every care is taken with the report as it relates to interpretation of subsurface conditions, discussion of geotechnical and environmental aspects, and recommendations or suggestions for design and construction. However, DP cannot always anticipate or assume responsibility for:

- Unexpected variations in ground conditions. The potential for this will depend partly on borehole or pit spacing and sampling frequency;
- Changes in policy or interpretations of policy by statutory authorities; or
- The actions of contractors responding to commercial pressures.

If these occur, DP will be pleased to assist with investigations or advice to resolve the matter.

About this Report

Site Anomalies


In the event that conditions encountered on site during construction appear to vary from those which were expected from the information contained in the report, DP requests that it be immediately notified. Most problems are much more readily resolved when conditions are exposed rather than at some later stage, well after the event.

Information for Contractual Purposes

Where information obtained from this report is provided for tendering purposes, it is recommended that all information, including the written report and discussion, be made available. In circumstances where the discussion or comments section is not relevant to the contractual situation, it may be appropriate to prepare a specially edited document. DP would be pleased to assist in this regard and/or to make additional report copies available for contract purposes at a nominal charge.

Site Inspection

The company will always be pleased to provide engineering inspection services for geotechnical and environmental aspects of work to which this report is related. This could range from a site visit to confirm that conditions exposed are as expected, to full time engineering presence on site.



Locality Plan

NOTE:
1: Base image from Nearmap.com
(Dated 17 November 2016)
2: Test locations are approximate only and are shown
with reference to existing features.



LEGEND
Borehole location



CLIENT: Henroth Investments Pty Ltd	
OFFICE: Sydney	DRAWN BY: PSCH
SCALE: 1:2500 @ A3	DATE: 25.11.2016

TITLE: **Location of Boreholes**
Proposed Bulky Goods Centre
3-12 Boondah Road, WARRIEWOOD




PROJECT No:	85749.00
DRAWING No:	1
REVISION:	0

BOREHOLE LOG

CLIENT: Henroth Investments Pty Ltd
PROJECT: Proposed Bulky Goods Centre
LOCATION: 3-12 Boondah Road, Warriewood

SURFACE LEVEL: 2.39 AHD^
EASTING: 342229.8
NORTHING: 6270135
DIP/AZIMUTH: 90°/--

BORE No: 1
PROJECT No: 85749.00
DATE: 21/11/2016
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing				Water	Well Construction Details	
				Type	Depth	Sample	Results & Comments			
2		FILLING - red-brown, silty sand filling, humid						23-11-16		
	0.5m: with a trace of shell fragments									
1	1.2m: damp to moist									
1.9	1.6m: saturated									
2		SAND - grey fine to coarse sand with a trace of clay, saturated								
0										
3										
4										
5.1		SANDY CLAY - dark grey sandy clay, saturated								
5.5	Bore discontinued at 5.5m - target depth reached									
6										
7										
8										
9										

Douglas Partners
Geotechnics / Environment / Groundwater

BOREHOLE LOG

CLIENT: Henroth Investments Pty Ltd
PROJECT: Proposed Bulky Goods Centre
LOCATION: 3-12 Boondah Road, Warriewood

SURFACE LEVEL: 2.25 AHD^

EASTING: 342226.4
NORTHING: 6270495.7
DIP/AZIMUTH: 90°/--

BORE No: 2
PROJECT No: 85749.00
DATE: 21/11/2016
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing			Water	Well Construction Details	
				Type	Depth	Sample			Results & Comments
2		FILLING - orange-brown, silty fine to medium sand filling with a trace of shells and terracotta fragments, humid		A	0.1				Gatic cover
					0.2				Backfill 0.0-0.4m
				A	0.4				
	0.7				0.5				Bentonite 0.4-0.7m
		SAND - grey, fine to coarse sand with some clay, moist		A	0.9				
		1.2m: saturated			1.0				
	1.4								
		CLAYEY SAND - dark grey clayey sand, saturated		A	1.4				Gravel 0.7-4.0m
					1.5				
	1.9								
		SANDY CLAY - dark grey, sandy clay, saturated, slight organic odour		A/E	1.9				
					2.0				
				A	2.4				Machine slotted PVC screen 1.0-4.0m
					2.5				
	3.8								
		CLAY - light brown clay with some fine sand, MC>PL							End cap
	4.5			A	4.4				
		Bore discontinued at 4.5m - target depth reached			4.5				


Douglas Partners
Geotechnics | Environment | Groundwater

BOREHOLE LOG

CLIENT: Henroth Investments Pty Ltd
PROJECT: Proposed Bulky Goods Centre
LOCATION: 3-12 Boondah Road, Warriewood

SURFACE LEVEL: 4.1 AHD^
EASTING: 342177
NORTHING: 6270617
DIP/AZIMUTH: 90°/--

BORE No: 3
PROJECT No: 85749.00
DATE: 21/11/2016
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing				Water	Well Construction Details
				Type	Depth	Sample	Results & Comments		
4		FILLING - grey-brown sand filling with some fine gravel and a trace of charcoal, damp		A	0.1				 Gatic cover Backfill 0.0-0.1m Bentonite 0.1-0.3m Gravel 0.8-5.8m Machine slotted PVC screen 0.8-5.8m End cap
				A	0.2				
				A	0.4				
				A	0.5				
				A/E	0.9				
1.2		SAND - orange-brown, slightly clayey sand, damp to moist		A	1.4				
				A	1.5				
1.7		CLAY - orange clay with a trace of sand, MC~PL							
		2.2m: becoming orange-grey with a trace of ironstone gravel		A	1.9				
				A	2.0				
				A	2.4				
				A	2.5				
2.8		CLAY - grey mottled red-brown clay with a trace of sand and fine ironstone gravel, MC~PL		A	2.9				
				A	3.0				
				A	3.9				
				A	4.0				
4.7		SILTY CLAY - light brown, silty clay with a trace of sand, MC>PL		A	4.9				
				A	5.0				
				A	5.9				
6.0		Bore discontinued at 6.0m - target depth reached		A	6.0				

RIG: Scout 1

DRILLER: W Gartside

LOGGED: A McIntyre

CASING: Uncased

TYPE OF BORING: Solid flight auger (TC-bit) to 6.0m

WATER OBSERVATIONS: Free groundwater observed in well at 2.67m on 23/11/16

REMARKS: ^Co-ordinates obtained by Nearmaps, RL by Survey

SAMPLING & IN SITU TESTING LEGEND			
A	Auger sample	G	Gas sample
B	Bulk sample	P	Piston sample
BLK	Block sample	U	Tube sample (x mm dia.)
C	Core drilling	W	Water sample
D	Disturbed sample	W	Water seep
E	Environmental sample	W	Water level
		PID	Photo ionisation detector (ppm)
		PL(A)	Point load axial test Is(50) (MPa)
		PL(D)	Point load diametral test Is(50) (MPa)
		pp	Pocket penetrometer (kPa)
		S	Standard penetration test
		V	Shear vane (kPa)



Douglas Partners
Geotechnics | Environment | Groundwater

BOREHOLE LOG

CLIENT: Henroth Investments Pty Ltd
PROJECT: Proposed Bulky Goods Centre
LOCATION: 3-12 Boondah Road, Warriewood

SURFACE LEVEL: 2.1 AHD[^]
EASTING: 342425.7
NORTHING: 6270502.7
DIP/AZIMUTH: 90°/--

BORE No: 4
PROJECT No: 85749.00
DATE: 23/11/2016
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing				Water	Well Construction Details	
				Type	Depth	Sample	Results & Comments			
2	0.3	FILLING - brown silty sand filling with some terracotta fragments (50mm), humid		A	0.1			23-11-16 ▼		
				A/E	0.2					
		FILLING - dark grey fine to coarse sand filling with some clay and fine basalt gravel, humid to damp			0.4					
					0.5					
1	0.8	SAND - grey fine to coarse sand with a trace of silt, damp to moist		A	0.9					
					1.0					
		1.3m: wet		A	1.4					
		1.6m: saturated			1.5					
2	1.7	CLAYEY SAND - dark grey, slightly clayey fine to coarse sand, saturated, organic odour		A	1.9					
					2.0					
				A	2.4					
					2.5					
3				A	2.9					
					3.0					
					3.9					
		4.0m: becoming more clayey		A	4.0					
5				A	4.9					
					5.0					
6	5.8	CLAY - light grey clay with a trace of sand, MC<PL		A	5.9					
		Bore discontinued at 6.0m - target depth reached			6.0					
7										
8										
9										

RIG: Bobcat

DRILLER: G Marino

LOGGED: A McIntyre

CASING: Uncased

TYPE OF BORING: Solid flight auger (TC-bit) to 6.0m

WATER OBSERVATIONS: Free groundwater observed in well at 1.43m on 23/11/16

REMARKS: ^Co-ordinates obtained by Nearmaps, RL by Survey

SAMPLING & IN SITU TESTING LEGEND

A	Auger sample	G	Gas sample	PID	Photo ionisation detector (ppm)
B	Bulk sample	P	Piston sample	PL(A)	Point load axial test Is(50) (MPa)
BLK	Block sample	U	Tube sample (x mm dia.)	PL(D)	Point load diametral test Is(50) (MPa)
C	Core drilling	W	Water sample	pp	Pocket penetrometer (kPa)
D	Disturbed sample	W	Water seep	S	Standard penetration test
E	Environmental sample	W	Water level	V	Shear vane (kPa)



Douglas Partners
 Geotechnics | Environment | Groundwater