

BROWN

CONCEPT STORMWATER MANAGEMENT PLAN PROPOSED RESIDENTIAL SUBDIVISION AT SECTOR 5 WARRIEWOOD VALLEY

Prepared For
DENIS LEECH & ASSOCIATES PTY LTD

Report N°: X04023-01
SEPTEMBER 2004



People & Systems
TO ENGINEER YOUR FUTURE

Brown Consulting (NSW) Pty Ltd

Consulting Environmental, Engineers & Managers ABN 30 109 434 513

Telephone 02 9900 1000 Facsimile 02 9900 1099

Level 2, 82 Waterloo Road Macquarie Park PO Box 1484 Macquarie Centre North Ryde NSW 2113

E-mail sydney@wpbrown.com.au Website www.wpbrown.com.au

SYDNEY CANBERRA BRISBANE MELBOURNE SUNSHINE COAST SINGAPORE BRUNEI

COMMERCIAL IN CONFIDENCE

All intellectual property rights, including copyright, in designs developed and documents created by the group of companies listed below remain the property of those companies. Any use made of such design or document without the prior written approval of the Group will constitute an infringement of the rights of the companies which reserves all legal rights and remedies in respect of any such infringement.

The information, including any intellectual property, contained in this proposal is confidential and proprietary to the Group. It may only be used by the person to whom it is provided for the stated purpose for which it is provided and must not be imparted to any third person without the prior written approval of the Group. The Group reserves all legal rights and remedies in relation to any infringement of its rights in respect of its confidential information.

©

Brown Consulting (NSW) Pty Ltd

SEPT 2004

DOCUMENT CONTROL

X04023-01A

Issue	Date	Issue Details	Author	Checked	Approved
01	SEPT 04	Stormwater Management Report	JL	JL/ RP	RP

G:\0004 - Macquarie\X04023\WATER SECTION\Current\WPB\Reports\Stormwater Management Report_V1.doc



7.2.1	Estimated Flows	18
7.2.2	Estimate of Design Flood Levels – Sector 5 overland Flow Path	19
7.3	Stormwater Outlet Concept Design	19
8.0	RECOMMENDATIONS	21
9.0	REFERENCES.....	21

APPENDICIES

Appendix A	HEC-RAS Results – Design Geometry
Appendix B	Water Quality Details

CONCEPT STORMWATER MANAGEMENT PLAN

SECTOR 5 – WARRIEWOOD VALLEY

1.0 INTRODUCTION

Brown Consulting (NSW) Pty Ltd has been commissioned to provide a stormwater management plan for a development application at Sector 5 Warriewood Valley in the Pittwater local government area. This report and its associated drawings provide concept detail as to the stormwater management for the proposed residential development.

The following drawings should be read in conjunction with this stormwater management plan:

- D01 Existing Survey and Flood Extents
- D02 Stormwater Drainage Concept Plan
- D03 OSD Tanks and Sand Filter Details
- D04 Bio-retention Basin & Design Creek Details
- D10 Narrabeen Creek Design Plan & HEC-RAS Cross Sections
- D11 Narrabeen Creek Existing & Design Long Section
- D12 Narrabeen Creek Design Cross Sections – Sheet 1
- D13 Narrabeen Creek Design Cross Sections – Sheet 2
- D14 Narrabeen Creek Design Cross Sections – Sheet 3
- D20 Overland Flowpath – Sector 5
- D21 Overland Flowpath Long Section – Sector 5
- D22 Overland Flowpath Cross Sections – Sheet 1
- D23 Overland Flowpath Cross Sections – Sheet 2

1.1 Site Location & Description

The site is located in the upper reaches of Narrabeen Creek, with the proposed development located to the south of Narrabeen Creek, which flows in an easterly direction. The site currently contains glasshouses and is predominantly cleared. Most riparian vegetation on Sector 5 is predominantly weed species and significant incision (up to 2 m depth) of the creek channel has occurred in places as a result of channel instability. In its existing condition, this section of Narrabeen Creek is considered a Class 3 fish habitat ‘Minimal Fish Habitat’, although with riparian restoration would be considered a Class 2 habitat ‘Moderate Fish Habitat’.



7.2.1	Estimated Flows	18
7.2.2	Estimate of Design Flood Levels – Sector 5 overland Flow Path	19
7.3	Stormwater Outlet Concept Design	19
8.0	RECOMMENDATIONS	21
9.0	REFERENCES	21

APPENDICIES

Appendix A	HEC-RAS Results – Design Geometry
Appendix B	Water Quality Details

CONCEPT STORMWATER MANAGEMENT PLAN

SECTOR 5 – WARRIEWOOD VALLEY

1.0 INTRODUCTION

Brown Consulting (NSW) Pty Ltd has been commissioned to provide a stormwater management plan for a development application at Sector 5 Warriewood Valley in the Pittwater local government area. This report and its associated drawings provide concept detail as to the stormwater management for the proposed residential development.

The following drawings should be read in conjunction with this stormwater management plan:

- D01 Existing Survey and Flood Extents
- D02 Stormwater Drainage Concept Plan
- D03 OSD Tanks and Sand Filter Details
- D04 Bio-retention Basin & Design Creek Details
- D10 Narrabeen Creek Design Plan & HEC-RAS Cross Sections
- D11 Narrabeen Creek Existing & Design Long Section
- D12 Narrabeen Creek Design Cross Sections – Sheet 1
- D13 Narrabeen Creek Design Cross Sections – Sheet 2
- D14 Narrabeen Creek Design Cross Sections – Sheet 3
- D20 Overland Flowpath – Sector 5
- D21 Overland Flowpath Long Section – Sector 5
- D22 Overland Flowpath Cross Sections – Sheet 1
- D23 Overland Flowpath Cross Sections – Sheet 2

1.1 Site Location & Description

The site is located in the upper reaches of Narrabeen Creek, with the proposed development located to the south of Narrabeen Creek, which flows in an easterly direction. The site currently contains glasshouses and is predominantly cleared. Most riparian vegetation on Sector 5 is predominantly weed species and significant incision (up to 2 m depth) of the creek channel has occurred in places as a result of channel instability. In its existing condition, this section of Narrabeen Creek is considered a Class 3 fish habitat 'Minimal Fish Habitat', although with riparian restoration would be considered a Class 2 habitat 'Moderate Fish Habitat'.

A steep bushland catchment of 4.12 ha drains through the site in a northerly direction through a low point that is ill-defined as it extends through the proposed development area on Sector 5. Drainage from this catchment is currently conveyed through the site by a series of small earth drains and pipe culverts, and in places the drainage line would only exist as sheet overland flow. This drainage discharges into Narrabeen Creek near the creek crossing with Jubilee Avenue.

The ephemeral drainage line passing through Sector 5 is considered a Class 4 fish habitat "Unlikely Fish Habitat" by the NSW Department of Primary Industry (Fisheries) due to the ephemeral nature of this drainage line, lack of vegetation, significant modification of the drainage line and the absence of any upstream or downstream significant aquatic habitat.

1.2 Warriewood Valley Stormwater Management Specification

This study has been developed in accordance with Pittwater Councils (2001) Stormwater Management Specification for the Warriewood Valley Urban Release Area. The key issues outlined by this specification include:

Stormwater Quantity Management

- Developed hydrograph must be within $\pm 10\%$ of the pre-developed hydrograph at any location on the rising or falling limb,
- Peak flow from the sector to be within $\pm 5\%$ of the peak flow given in Appendix A of the specification.
- Developed peak flow to be no greater than pre-developed conditions,
- All OSD aboveground structures to be located above the 100 year ARI flood level,
- Stormwater reuse to be utilised for the development

Flooding

- Estimation of flood levels for pre and post development,
- Floor levels to be +500 mm above the 1% AEP flood,
- The 50% AEP flood to be conveyed within the creek banks,
- Walkways & cycleways to be above 20% AEP flood level,
- Water quality control devices to be above the 20% AEP flood level,
- Flood hazard and evacuation associated with the PMF to be considered if it flows through residential areas.

Stormwater Quality

- Load based modelling of pre and post development using a daily load model for 90th, 50th and 10th percentile rainfall years,
- Ensure post developed pollutant loads do not exceed existing loads,
- Concept design of stormwater treatment facilities,

Water Balance

- Water balance modelling for pre and post development,

Watercourse & Creekline Preservation

- Establish baseline conditions by survey every 25 m,
- 1% AEP flood to be conveyed in creekline for post-development conditions,
- Use of natural channels in the design sections of the creek,
- 50% AEP flood to be conveyed below bank-full levels,
- Stormwater discharges to be adequately stabilised,

1.3 The Development Proposal

The DA is for the construction of 75 residential dwellings in Sector 5 Warriewood Valley, as shown in **Drawing D02**. A total of 55 dwellings are proposed adjacent to Narrabeen Creek, denoted Site A in this study. A further 20 dwellings are proposed in the south-east corner of Sector 5, denoted Site B.

The development of Sector 5 will utilise stormwater quality and quantity controls in accordance with industry 'best practice management', and more specifically to meet the objectives of Pittwater Council's "*Water Management Specification*". This will include stormwater reuse for each dwelling in accordance with the NSW government's BASIX, in addition to utilising stormwater treatments such as bio-retention, sand filters and gross pollutant traps. The development will also provide on-site detention to maintain existing flow regimes, provide rehabilitation of Narrabeen Creek through Sectors 5 & 6 and provide a landscaped overland flow path for overland flows passing across Sector 5.

2.0 EXISTING CONDITIONS

The hydrology of the proposed development area has been previously modelled by Lawson & Treloar Pty Ltd for Pittwater Council using the *XP-RAFTS* hydrological model. This model was a broad scale model covering most of the catchment of Narrabeen Creek, including Sector 5.

2.1 Hydrology

2.1.1 Narrabeen Creek

The existing peak flow at the upstream and downstream end of Sector 5 & 6 for various design floods as estimated by Lawson & Treloar Pty Ltd is shown in Table 2.1.

Table 2.1 Peak Flows Upstream & Downstream of Sectors 5 & 6

Sector 5	PMF	1% AEP	2% AEP	5% AEP	20% AEP	50% AEP
Upstream	62.8	14.1	11.5	8.6	4.2	1.3
Downstream	75.0	17.0	13.6	10.1	5.0	1.5

These flows relate to the runoff contributed from both Sectors 5 and 6.

2.1.2 Drainage Line through Bisecting Sector 5

A small ephemeral drainage line passes through the proposed subdivision. This drainage line has a catchment area of 4.12 ha upstream of the proposed subdivision. The catchment landuse is bushland and the average slope in this area is 15%.

The peak 100 year ARI flow from this catchment has been estimated using the RAFTS component of DRAINS as being 1.54 m³/s. This flow was estimated using a Manning's value of 0.06 representing the bushland conditions and the same initial and continuing losses as adopted in the RAFTS model developed for Narrabeen Creek by Lawson & Treloar Pty Ltd.

2.2 Existing Flood Conditions in Narrabeen Creek

Flood levels for existing conditions were established by Lawson & Treloar for Pittwater Council from four cross sections through the site. The estimated 100 year ARI flood level varied from 20.77 to 19.79 m AHD through Sector 5. These flood levels were revised as part of this study using a more detailed survey through the site, which was taken at 25 m spacings along the creek and extended further onto the floodplain.

The HEC-RAS boundary condition adopted was the known surface water level as derived from the modelling undertaken by Lawson & Treloar Pty Ltd for each design flood (eg 17.92 m AHD for the 100 y ARI flood). The model was run in sub-critical mode.

Drawing D01 shows the PMF, 20 and 100 year ARI flood extents through Sector 5. **Table 2.2** shows that the revised 100 year ARI flood level varies from approximately 20.86 to 18.91 m AHD through the site. All floods except the PMF are completely contained within the existing channel of Narrabeen Creek.

Table 2.2 Existing 100 year ARI Flood Levels

Section	Q Total (m ³ /s)	Flood Level (m, AHD)	Channel Velocity (m/s)	Froude	Mannings		
					LOB	Channel	ROB
11	14.1	20.86	1.89	0.65	0.1	0.045	0.1
10	14.1	20.4	2.55	0.91	0.1	0.045	0.1
9	14.1	20.29	1.55	0.49	0.1	0.045	0.1
8	14.1	20.14	1.61	0.5	0.1	0.045	0.1
7	14.1	19.98	1.75	0.51	0.05	0.045	0.1
6	14.1	19.65	2.32	0.8	0.05	0.045	0.1
5	14.1	19.66	1.35	0.39	0.05	0.045	0.1
4	14.1	19.6	1.18	0.33	0.05	0.045	0.1
3	14.1	19.55	1.13	0.35	0.05	0.045	0.1
2	14.1	18.99	2.85	1.01	0.05	0.045	0.1
1	17	18.91	1.59	0.49	0.05	0.045	0.1
0	Bridge						

2.3 Narrabeen Creek Corridor through Sector 5

Narrabeen Creek is considerably degraded adjacent to Sector 5, showing signs of scour and containing many weed species in the riparian area. Proposed creek works will aid in stabilising the creek and provide a revegetated riparian corridor.

Drawing D10 and **Drawing D11** show the existing creek survey information in section and plan.

3.0 WATER BALANCE FOR SECTOR 5

A daily water balance model was developed for pre and post development of the site using a spreadsheet model. This type of approach is recommended by the EPA (1997) for estimating flows and pollutant loads at the development application stage.

3.1 Model Assumptions

This model used daily rainfall data from the Bureau of meteorology Station at Mona Vale to estimate daily runoff volumes. The period of record covered 31 years from January 1972 to the end of 2002. Evaporation data used were daily averages for each month.

Volumetric runoff coefficients and initial rainfall loss used in the model for each landuse included:

Existing Site	15%	4 mm
Roof Areas	100%	0 mm
Roads	85%	1 mm
Lots	18%	4 mm

For developed conditions, the stormwater reuse was assumed to occur only if no greater than 1 mm of rainfall had occurred that day, as although the water will be available for domestic use it is assumed most of the water will be used for irrigation. Daily rainwater demand was assumed to be 450 L/d/dwelling if available (for irrigation, washing machines and toilet flushing), which is conservative given that if >1 mm of rainfall occurred it is assumed there is no water demand from the rainwater tanks. Total rainwater storage for each dwelling is 8,000 L of storage.

Evaporation losses from the bio-retention basin were also considered in the modelling using average daily evaporation for each month in Sydney. Such losses were only applied while water was held in the bio-retention basin.

3.2 Water Balance Summary

The water balance modelling estimated the following total rainfall depths for statistically representative rainfall years:

▪ 10 th Percentile Rainfall Year	744 mm
▪ Average rainfall year	1,090 mm
▪ 90 th Percentile rainfall year	1,537 mm

The water balance model results are shown in Table 3.1.

Table 3.1 Water Balance Modelling Results

Site	Pre-development Runoff (ML/y)		Post-Development Runoff with Stormwater Re-use (ML/y)	
	A	B	A	B
10 th Percentile Rainfall Year	5.88	0.84	2.66	0.52
Average rainfall year	8.60	1.23	4.69	0.75
90 th Percentile rainfall year	14.26	2.03	9.86	1.21

The model shows that development of Sector 5 would not increase runoff volumes from that of existing conditions. This has been achieved by incorporating a substantial stormwater reuse component for each dwelling. However, environmental flows to Narrabeen Creek will not be reduced as the rainwater reuse is only from roof areas of the site and all roads and lot areas will continue to flow to Narrabeen Creek through the water quality treatment devices and on-site detention.

Figure 2.1 shows the storage in the rainwater tanks associated with the stormwater demand for an average rainfall year on Site A. It can be seen that for approximately 30% of the year stormwater would be unavailable for reuse on Site A.




Figure 2.1 Rainwater Tank Storage - Site A

4.0 STORMWATER DRAINAGE CONCEPT PLAN (SDCP)

A requirement of Pittwater Council is to provide a Stormwater Drainage Concept Plan (SDCP). This plan is shown in **Drawing D02**, which identifies:

- Location & size of SQIDS
- Location of diversion drains,
- Location and size of the OSD systems,
- 1% AEP and PMF extents – post development
- Creekline corridors – post development
- Piped drainage system
- Onsite retention facilities
- Surface overland flowpaths

5.0 STORMWATER QUALITY MANAGEMENT

5.1 Modelling Methodology

Stormwater quality was analysed using the daily water balance model developed for this study, coupled with a water quality model component, as recommended by Pittwater Council's (2001) *Warriewood Valley Water Management Specification*. It was necessary to combine the two models as the reduction in runoff volumes through water reuse would also reduce pollutant loads from the catchment. Such a relationship is not yet adequately modelled by water quality models such as MUSIC, which can only accommodate simplistic reuse from ponds.

The event mean concentrations (EMC) used for establishing the existing conditions for the site were taken from the average results of water quality sampling data for the 'Wet Conditions' classification at the McPherson Street Bridge, being:

- | | |
|-------|-----------|
| ▪ TN | 1.85 mg/L |
| ▪ TP | 0.74 mg/L |
| ▪ TSS | 131 mg/L |

For developed conditions, the catchment was subdivided into roof, landscaped and road areas. The EMC values used for these landuses were taken from Australian Runoff Quality-DRAFT (2003) which were adopted from Duncan (1999) and are shown in **Table 5.1**.

Table 5.1 Pollutant EMC Values & Runoff Coefficients

Landuse	TSS (mg/L)	TP (mg/L)	TN (mg/L)
Roof Areas	35	0.13	0.60
Landscaped Areas	150	0.40	1.85
Roads	250	0.25	1.12

Note: TN for landscaped areas was assigned as 1.85 mg/L which is greater than Duncan (1999)

5.2 Existing Pollutant Loads from Sector 5

The existing pollutant loads off Site A and B as estimated by the model are shown in Table 5.2.

Table 5.2 Existing pollutant Loads

Percentile Year	TSS kg/y	TN kg/y	TP kg/y
Site A			
10 th	771	10.89	1.18
mean	1127	15.91	1.72
90 th	1869	26.37	2.85
Site B			
10 th	109	1.55	0.62
mean	160	2.27	0.90
90 th	266	3.76	1.50

5.3 Proposed Stormwater Treatment Strategy – Site A

The water quality treatment for Site A will consist of:

- Stormwater re-use of dwelling roof runoff by utilising 8,000 L rainwater tanks,
- Gross pollutant traps to pre-treat road and lot drainage, and
- Two bio-retention basins which will receive flows from the gross pollutant trap.

The pollutant removal rates adopted for stormwater treatment devices are shown in Table 5.3. Data from Melbourne Water in Appendix B indicates that bio-retention basins may achieve higher pollutant removal rates than adopted in this study. The performance of sand filters was adopted from the *Water Sensitive Planning Guide for the Sydney Region*.

Table 5.3 Pollutant Load Reductions for Stormwater Treatments

	TSS	TP	TN
Bio-retention Basins	85%	77%	70%
GPT's	50-75%	20%	0%
Sand Filter	65%	58%	50%

5.3.1 Post Development Pollutant Loads – Site A

The estimates of pollutant loads from Site A with stormwater treatment are shown in Table 5.4.

Table 5.4 Site A - Pollutant Loads with Treatment

Percentile Year	TSS kg/y	TN kg/y	TP kg/y
10th	96	3.62	0.60
mean	160	5.81	0.98
90th	337	12.31	2.07
Mean Reduction	86%	64%	43%

5.3.2 Bio-retention Basin Concept Design

The design of the bio-retention basins was in accordance with Melbourne Waters WSUD Manual and other similar procedures. The design assumptions include:

Bio-retention Basin Sizing

Filter Media depth	750 mm
Filter Media Surface Area	317 m ² (Total)
Extended Detention Depth	300 mm
Total Basin Volume	95 m ³ (Total)
Adopted Saturated Hydraulic Conductivity	36 mm/h (adopted long term k)
Maximum Time to Drain Basin	24 hours

Filter Media Specification

Filter Media Type	Sandy Loam (0.45 mm)
Maximum Hydraulic Conductivity	180 mm/h
Sub-surface Drain Type	Perforated PVC (min 0.5% grade)

Surface Treatment on Filter Media

Plants selected for use in bio-retention systems need to be able to tolerate periods of inundation, as these systems can be expected to have a proportion of the soil profile saturated for several days. The selection of a sandy loam soil with a hydraulic conductivity in the range of 40-180mm/h will normally ensure soils are not waterlogged, which has been accommodated in the concept design.

Plants with extensive fibrous root systems are generally preferred as they prevent the filter media from clogging. Plants with a spreading, rhizomatous or suckering habit are also preferred. The filter must be planted to ensure it does not clog, and a stone layer at the surface could be used if required, although no mulch should be placed on the filter.

Sub-surface Drainage

100 mm PVC perforated pipes will be placed in a 150-200 mm thick fine gravel layer below a 100 mm thick sand transition layer located immediately below the filter media. The grading of the transition layer should be:

- 1.4 mm 100% passing
- 1.0 mm 80%
- 0.7 mm 44%
- 0.5 mm 8.4% passing

The maximum spacing of the perforated PVC pipes is to be maximum 2 m spacings centre to centre.

5.4 Proposed Stormwater Treatment Strategy – Site B

The water quality treatment for Site B will consist of:

- Stormwater re-use from dwelling roof runoff using 8,000L rainwater tanks,
- Gross pollutant traps to treat road and lot drainage, and
- Sand filters which will receive runoff from the gross pollutant trap and treat to remove nutrients, grease and hydrocarbons. These will discharge runoff to the OSD tanks.

5.4.1 Post Development Pollutant Loads – Site B

The model estimates of pollutant loads from Site B on Sector 5 are shown in Table 5.5.

Table 5.5 Site B - Pollutant Loads with Treatment

Percentile Year	TSS kg	TN kg	TP kg
10th	14.5	0.32	0.05
mean	28.3	0.55	0.09
90th	39.0	0.80	0.12
Mean Reduction	82%	76%	90%

5.4.2 Concept Water Quality Treatment Device Sizing – Site B

The GPT's will be sized to treat the 3 month ARI peak flow from the catchment. The sand filter will receive flows directed to it via the GPT's, effectively making them off-line, and has been sized based on the following assumptions:

Combined Runoff Volume (first 15 mm)	36.5 m ³
Combined Filter SA	57 m ²
Filter depth	600 mm
Filter Media	Clean, washed aggregate

6.0 ONSITE DETENTION - SECTOR 5

The Warriewood Valley Water Management Specification provides site storage requirements (SSR) and permissible site discharge (PSD) for Sector 5. These were estimated from the *RAFTS* modelling undertaken by Lawson & Treloar for Pittwater Council. These factors were determined as being:

SSR for 1% AEP 1 hr Storm	368 m ³ /ha = 740 m ³ for Site A
PSD for 1% AEP 1 hr Storm	0.331 m ³ /s
PSD for 1% AEP 2 hr Storm	0.390 m ³ /s

The PSD and SSR were verified using the *RAFTS* hydrological component of the *DRAINS* model for both catchments A and B in Sector 5. This software has a more advanced detention basin modelling component than *RAFTS* that allows multiple orifices to be modelled and hydrographs examined. Initial and continuing losses adopted were those used in the flood study by Lawson & Treloar Pty Ltd for Pittwater Council.

6.1 Onsite Detention Calculations for Site A

The hydrological parameters adopted for the existing catchment conditions were the same as for the *RAFTS* modelling undertaken by Lawson & Treloar, being:

Existing Mannings 'n'	0.05
Developed Mannings 'n'	0.025
Slope	5%
Contributing catchment area	2.01 ha
Impervious percentage	50%

Exceptions from the parameters used in the existing *RAFTS* model were the catchment area modelled, where it is proposed to develop only 2.01 ha of Site A and hydrologically isolate the remaining upslope catchment area from the rest of the site.

The proposed OSD system for Site A is shown in **Drawing D03**. The OSD system will utilise 560 m³ of storage located in storage provided under the access road. An additional 220 m³ of storage will be provided within the rainwater tanks for each dwelling, equating to 4 m³ of OSD storage per dwelling. It should be noted that BASIX states that 50% of the rainwater tank capacity can be counted towards OSD storage if the rainwater tank is connected into the household water supply, which is proposed. Therefore, the downpipes for each dwelling and inter-allotment drainage will be required to convey the roof runoff from the 100 year ARI storm.

The *DRAINS* modelling has estimated that the development of Site A would not increase the peak flow from that of existing conditions when using OSD, as shown in Table 6.1.

Table 6.1 Summary of Peak Flows - Site A

ARI Storm	Critical Storm (min)	Existing Conditions	PSD	Developed With OSD
5	120	0.346	0.346	0.322
20	120	0.499	0.499	0.488
100	120	0.673	0.784	0.687

Note: The PSD of 0.784 for the 100y ARI storm is from the Warriewood Valley Water Management Specification

The concept outlet arrangement from the OSD tank is:

- Low level orifice 458 mm at centre RL 20.17 m
- High level Orifice 310 mm at centre RL 20.89 m
- Overflow weir at RL 21.35 m (Q100 level 21.37 m)
- Outlet using a 900 mm RCP at IL 19.04 m

The OSD system has been designed to ensure that there is no pronounced 'tail' on the falling limb of the hydrograph and that the times of peak and hydrograph shapes are similar (Figure 6.1). Furthermore, the system has been designed to account for the hydraulic grade line in the outlet pipe due to flooding in Narrabeen Creek.




Figure 6.1
2 hour 100 year ARI Storm Hydrograph - Site A




Figure 6.2
2 hour 5 year ARI Storm Hydrograph - Site A

6.2 Onsite Detention Calculations for Site B

This catchment was modelled in *DRAINS* using the *ILSAX* hydrological component, as a smaller sub-catchment in the *RAFTS* component will alter the peak flows from the catchment.

The upslope bushland catchment was excluded from the model as flows from this catchment will be diverted around the site and into the drainage line that is proposed to flow through Site A.

The existing peak flows for each design storm were adopted as the PSD for the site, except for the 100 year ARI storm where the PSD given in the Warriewood Water Management Specification was used. The PSD and results are shown in Table 6.2.

Table 6.2
Summary of Peak Flows - Site B

ARI Storm	Critical Duration (min)	Existing Conditions (m³/s)	Developed Site With OSD (m³/s)
5	90	0.182	0.176
20	120	0.254	0.224
100	120	0.338 (PSD = 0.275)*	0.273

*PSD adopted from the Warriewood Valley Urban Release Area Water Management Specification (2001)

The proposed OSD system utilises two underground tanks to provide a combined storage of 232 m³ including 80 m³ of OSD storage in rainwater tanks in the dwellings draining to the OSD system. It is proposed that the tanks will be located underneath the roads in this area as shown in Drawing D03.

Concept design details for the OSD on Site B are provided below:

Tank 1 – Catchment area 0.377 ha

- Total OSD Storage (incl Rainwater tanks) 107 m³
- Low level outlet – 220 mm orifice with Centre at RL 25.5m
- High level outlet – weir at RL 27 m

Tank 2 – Catchment area 0.453 ha

- Total OSD Storage (incl rainwater tanks) 125 m³
- Low level outlet – 265 mm orifice with centre at RL 21.5m
- High level outlet – weir at RL 23 m

Unlike most conventional OSD systems, there is no sustained base-flow resulting from the attenuation of peak flows for all storms up to the 100 year ARI.

WATERCOURSE RESTORATION & FLOOD PROTECTION

6.3 Narrabeen Creek

Narrabeen Creek will be rehabilitated by providing revegetation of the riparian zone along with earthworks to stabilise the existing creek and manage flooding. The existing creek channel will be stabilised by creating benching in accordance with natural channel design principles. Small natural sandstone retaining walls of 300 mm height will extend above the bank full flow section of the channel throughout some sections of the creek. The creek bank above these retaining wall sections is proposed to be battered at a 1 in 6 grade to other 300 mm high benches until the design or natural surface level is reached. Concept creek design sections are shown in Drawings D10, D11, D12, D13, D14 and D04.

We have been advised that the section of Narrabeen Creek on Sector 6 will have straight 1 in 3 batters, which has been adopted for the hydraulic modelling. Therefore, flood levels through this section of Narrabeen Creek will need to be re-viewed in the context of proposed works on the other side of the creek that fronts Sector 6 for the detailed design. In either case, changes to the flood levels estimated in this study are expected to be minimal for the detailed design.

6.3.1 Estimate of Design Flood Levels – Narrabeen Creek

Flood levels in Narrabeen Creek adjacent to Sector 5 were estimated using HEC-RAS, the cross sectional geometry from the proposed creek design and the estimate of flows derived by Lawson & Treloar for Sectors 5 & 6. The hydraulic modelling results are given in Table 7.1.

Section	PMF (m, AHD)	100 y ARI (m, AHD)	100 y ARI Velocity (m/s)	20 y ARI (m, AHD)	2 y ARI (m, AHD)	Flood Planning Level * (m, AHD)
11	21.85	20.35	3.07	20.04	19.41	20.85
10	21.56	20.08	2.03	19.8	19.19	20.58
9	21.56	20.0	1.60	19.7	19.03	20.50
8	21.32	19.81	1.98	19.52	18.88	20.31
7	21.21	19.65	2.05	19.36	18.73	20.15
6	21.15	19.51	1.98	19.22	18.57	20.01
5	21.12	19.43	1.79	19.13	18.45	19.93
4	20.97	19.22	2.13	18.91	18.28	19.72
3	20.98	19.09	1.97	18.77	18.12	19.59
2	20.96	18.96	1.91	18.62	17.91	19.46
1	20.9	18.83	2.11	18.54	17.77	19.33
0	Bridge					

*Flood Planning Level = (Q100+500 mm for minimum floor level for adjacent buildings)

Mannings values adopted for the flood study included:

- 0.08 for overbanks (representing dense planting within the riparian zone), and
- 0.045 for the channel (representing scattered vegetation with rushes and macrophytes).

Hydraulic controls included the road bridge immediately downstream of Sector 5.

Drawing D11 shows the design 100 year ARI flood levels along this section of creek. It can be seen that the design of the creek reduces flood levels from that of existing conditions as a consequence of increasing the conveyance capacity of Narrabeen Creek.

6.4 Overland Flow Path through Site A

A minor overland flow path is proposed to pass through the site in Site A. An ephemeral landscaped corridor has been provided to pass overland flows from the upstream 4.12 ha catchment, in addition to conveying the flows from the 0.81 ha catchment upslope of Site B.

6.4.1 Estimated Flows

The 100 year ARI flow from the total 4.93 ha upstream catchment is estimated as being $1.91 \text{ m}^3/\text{s}$, of which $0.389 \text{ m}^3/\text{s}$ is diverted from the upslope catchment of Site B. A box culvert under the access road is proposed to convey these flows into the designated overland flow path through Site A. Two box culverts of 1800 mm width and 600 mm height will convey this flow without overtopping of the access road when 50% blocked. Their combined capacity without blockage is estimated at $2.84 \text{ m}^3/\text{s}$ at a headwater depth of 0.6 m. With blockage the culvert capacity is estimated at $2.0 \text{ m}^3/\text{s}$ at the same headwater depth, which exceeds the estimated 100 year ARI flow at this location.

The total peak flow arriving at the downstream end of the overland flow path is estimated at $2.01 \text{ m}^3/\text{s}$ for the 100 year ARI storm. Flows from this overland flow path will be piped in a 1,050 mm diameter RCP, where they will combine with flows from the OSD system for Site A, continue through a 1200 mm RCP and discharge into a stabilised energy dissipater at Narrabeen Creek. The access road will form an overland flow path for floods above the 100 year ARI.

This corridor consists of an overland flow path that leads to a series of self draining rock weirs. It should be noted that this structure is not designed to retain water, although in large storms ponding of water will occur behind the weirs and at the inlet to the pipe culvert.

A 300 mm high rock retaining wall will form a hard edge to the overland flow path. This will aid in reducing mosquito larvae development and preventing scour in extreme floods. All batters below and above the edge wall will be a maximum of 1(V) in 6(H).

6.4.2 Estimate of Design Flood Levels – Sector 5 overland Flow Path

The HEC-RAS hydraulic model was used to estimate flood levels in the proposed overland flow path through Sector 5. The model used a downstream boundary condition of a known surface water level, as the permeable rock weirs located across the overland flow path act as a hydraulic control for the water level in each section of the overland flow path. Therefore the results shown in Table 7.2 do not extend beyond Section OF10.

Drawings D20, D21, D22 and D23 show long sections and cross sections of this overland flow path along with the 100 year ARI flood level, which in the lower sections of the overland flow path is controlled by the inlet capacity of the pipe that conveys runoff to Narrabeen Creek. It can be seen that all adjacent dwellings are located a minimum of 500 mm above the 100 year ARI flood level. Furthermore, all dwellings fronting the access road have sufficient freeboard.

For storms greater than the 100 year ARI, or if significant blockage of the culvert occurred, the adjacent road would act as an overland flow path for those overflows allowing runoff to reach Narrabeen Creek. Dwellings adjacent to the road have sufficient freeboard provided.

Table 7.2 100 Year ARI flood Levels in the Overland Flow Path

Section	Chainage	100 Y ARI Flood Level (m, AHD)	Energy Grade Elevation (m, AHD)	100 Y ARI Channel Velocity (m/s)
1	90	28.49	28.72	2.14
2	85	28.08	28.28	1.97
3	80	27.90	28.17	2.32
4	75	27.64	27.76	1.57
5	70	27.07	27.36	2.39
6	65	26.74	26.89	1.72
7	60	26.36	26.55	1.93
8	55	25.85	26.09	2.17
9	50	25.58	25.70	1.54
10	40	25.01	25.16	1.67

6.5 Stormwater Outlet Concept Design

A single stormwater outlet to Narrabeen Creek is proposed. This outlet will contain a 1200 mm RCP discharging through a headwall situated in the riparian zone. The DRAINS model has estimated the flow velocity in the pipe to be a maximum of 2.75 m/s.

The outlet will incorporate a natural rip rap energy dissipater in accordance with a *Type A - Roads & Traffic Authority* dissipater to force a hydraulic jump and allow flow to return to subcritical. A total dissipater length of 10 m has been provided to prevent scour at the confluence of this outlet and Narrabeen Creek. The proposed creek design will require that this stormwater outlet be surrounded by a sandstone boulder retaining wall that will mesh with the proposed benched creek design.

7.0 RECOMMENDATIONS

The stormwater management plan for Sector 5 Warriewood Valley has been prepared in accordance with Pittwater Councils Water Management Specification. The stormwater components used in the development will meet five principle objectives being:








- Ensuring that peak flows are maintained at a rate not exceeding that of existing conditions, while maintaining a similar design storm hydrograph,
- Improving water quality in discharge from the site so that it is no worse than that of existing conditions,
- Ensuring that the average annual flows from the site are no greater than that of existing conditions,
- Promoting WSUD in the design,
- Rehabilitating the creek corridor along Narrabeen Creek ensuring long term channel stability and promoting revegetated benched riparian zones.



8.0 REFERENCES

- Duncan H.P. (1999). *"Urban Stormwater Quality: A Statistical Overview"*. CRC for Catchment Hydrology.
- Institution of Engineers Australia (2004) Australian Runoff Quality – DRAFT.
- Melbourne Water (2004). WSUD Engineering Procedures: Stormwater DRAFT.
- NSW EPA (1997a). Managing Urban Stormwater: Council Handbook.
- NSW EPA (1997b). Managing Urban Stormwater: Treatment Techniques.
- Pittwater Council (2001). Warriewood Valley Urban Land Release Water Management Specification. Prepared by Lawson & Treloar Pty Ltd.

APPENDIX A

HEC-RAS RESULTS






APPENDIX B

WATER QUALITY



Melbourne (reference site) Bioretention TSS Removal



Melbourne (reference site) Bioretention TP Removal




Figure 6.3 Bioretention system TP removal performance in Melbourne



Melbourne (reference site) Bioretention TN Removal





Figure 6.4 Bioretention system TN removal performance in Melbourne

[illegible][illegible]

DP 361070
1338Hs
1/1000 (AS 1400)




0 20 40 60 80 100 120 140 160 180 200
SCALE 1:500 (AS 1400)

REV	DATE	DESCRIPTION	BY	CHK	APP
01	22/05/04	ISSUED FOR DA APPROVAL	AK	JL	RAP
AMENDMENTS					

Decline and Copyright:
ALL DIMENSIONS TO BE CHECKED
ON SITE BY SUPERINTENDANT
PRIOR TO CONSTRUCTION. USE
WRITTEN DIMENSIONS ONLY. DO
NOT SCALE.

© 2004 W F Brown & Partners Pty Ltd



Brown Consulting (NSW) Pty Ltd
Level 2, 82 Waterloo Road Macquarie Park NSW Australia 2113
Telephone: 02 9900 1000 Facsimile: 02 9900 1099


INITIALS	SIGNATURE	DATE
AK		16/10/04
JL		16/10/04
RAP		16/10/04
APPROVED		16/10/04

Architects:
DENIS LEECH & ASSOCIATES PTY LTD
Project:
Sector 5
Warriewood Valley

EXISTING FLOOD EXTENTS
AND SURVEY
- SECTOR 5

PRELIMINARY

Drawn by: AK
Design by: JL
Project No: X04023
Drawing No: D01
Rev: 01




LEGEND

- BIORETENTION BASIN
- OSD STORAGE (UNDERGROUND)
- SAND FILTER
- DIVERSION DRAIN
- EXISTING TREES
- GPT (INTS)
- PIT (INTS)
- DROP PIT (INTS)
- HEADWALL (INTS)

NOTE:

- ALL DWELLINGS TO UTILISE 9000L RAINWATER TANKS (50% OSD CONTRIBUTION)
- DIVERSION DRAINS SIZED TO CONVEY 100YR ARI PEAK FLOW
- RIPARIAN ZONE TO BE RE-VEGETATED IN ACCORDANCE WITH LANDSCAPE ARCHITECT & DIPNR REQUIREMENTS



ALL DIMENSIONS TO BE CHECKED ON SITE BY SUPERINTENDANT PRIOR TO CONSTRUCTION. USE WRITTEN DIMENSIONS ONLY. DO NOT SCALE.

Brown Consulting (NSW) Pty Ltd
Level 2, 82 Waterloo Road Macquarie Park NSW Australia 2113
Telephone: 02 9900 1000 Facsimile: 02 9900 1099

DATE	SIGNATURE	INITIALS	VERIFICATION
18/10/04	AK	AK	DRAFTING
18/10/04	JL	JL	DESIGN
18/10/04	RAP	RAP	CHECKING
18/10/04	RAP	RAP	APPROVED


DENIS LEECH & ASSOCIATES PTY LTD

SECTOR 5
WARRIEWOOD VALLEY


STORMWATER DRAINAGE
CONCEPT PLAN

PRELIMINARY

Drawn by:	AK	Sheet:	2 of 12
Design by:	JL	Scale:	1:500
Project No:	X04023		
Drawing No:	D02	Rev:	01



OSD TANK 2 - SITE B
SECTION 3
SCALE 1:20



OSD TANK 1 & SAND FILTER - SITE B
SECTION 
SCALE 1:20

**PRIOR TO CONSTRUCTION, USE
WRITTEN DIMENSIONS ONLY, DO
NOT SCALE.**

ALL DIMENSIONS TO BE CHECKED
ON SITE BY SUPERINTENDANT
PRIOR TO CONSTRUCTION. USE
WRITTEN DIMENSIONS ONLY, DO
NOT SCALE.

©2004 W P Brown & Partners Pty Ltd

Architect		Project:	
VERIFICATION		INITIALS	SIGNATURE
DRAFTING	AK		16/1904
DESIGN	JL		16/1904
VERIFY	RAP		16/1904
APPROVED	RAP		16/1904

Brown Consulting (NSW) Pty Ltd
Level 2, 82 Waterloo Road Macquarie Park NSW Australia 2113
Telephone: 02 9900 1000 Facsimile: 02 9900 1099

BROWN

©2004 W P Brown & Partners Pty Ltd

DENIS LEECH & ASSOCIATES PTY LTD


**SECTOR 5
WARRIEWOOD VALLEY**

OSD TANKS AND SAND FILTER CONCEPT DETAILS


PRELIMINARY

Drawn by: AK	Sheet: 3 of 12
Design by: JL	Scale: 1:20
Project No: X04023	
Drawing No: D03	Rev:


Drawing No: D03




TYPICAL EDGE TREATMENT
NARRABEEN CREEK
SCALE 1:20



TYPICAL EDGE TREATMENT
OVERLAND FLOW PATH
SCALE 1:20



PLAN
BIORETENTION BASIN OUTLET STRUCTURE - SITE A
SCALE 1:20



SECTION
BIORETENTION BASIN FILTER AND OUTLET STRUCTURE - SITE A
SCALE 1:20

PRELIMINARY


**BIORETENTION BASIN AND
DESIGN CREEK
DETAILS**

DENIS LEECH & ASSOCIATES PTY LTD

SECTOR 5
WARRIEWOOD VALLEY

VERIFICATION			
	INITIALS	SIGNATURE	DATE
DRAFTING	AK		16/19/04
DESIGN	JL		16/19/04
VERIFY	RAP		16/19/04
APPROVED	RAP		16/19/04

Brown Consulting (NSW) Pty Ltd
Level 2, 82 Waterloo Road Macquarie Park NSW Australia 2113
Telephone: 02 9900 1000 Facsimile: 02 9900 1099




Disclaimer and Copyright:
ALL DIMENSIONS TO BE CHECKED
ON SITE BY SUPERINTENDANT
PRIOR TO CONSTRUCTION. USE
WRITTEN DIMENSIONS ONLY, DO
NOT SCALE.


© 2004 W P Brown & Partners Pty Ltd

[illegible]

Drawing No: D04 Rev: 01



A1



LOT B
DP 361070

PRELIMINARY

Drawn by:	AK	Sheet:	4 OF 12
Design by:	JL	Scale:	1:250
Project No:	X04023		
Drawing No:	D10	Rev:	01

NARRABEEN CREEK
DESIGN PLAN
AND
HEC RAS SECTIONS


DENIS LEECH & ASSOCIATES PTY LTD
SECTOR 5
WARRIEWOOD VALLEY

INITIALS	SIGNATURE	DATE
AK		15/10/04
JL		16/10/04
RAP		16/10/04


Brown Consulting (NSW) Pty Ltd
Level 2, 82 Waterloo Road Macquarie Park NSW Australia 2113
Telephone: 02 9900 1000 Facsimile: 02 9900 1099
Sydney
Canberra
Brisbane
Melbourne
Perth
Singapore

ALL DIMENSIONS TO BE CHECKED
ON SITE BY SUPERINTENDANT
PRIOR TO CONSTRUCTION. USE
WRITTEN DIMENSIONS ONLY. DO
NOT SCALE.

REV	DATE	ISSUED FOR	DESCRIPTION	APPROVED
01	22/08/04	FOR DIA APPROVAL		



NOTE:
POOLS AND RIFFLES AREAS WILL BE
INCORPORATED INTO THE CREEK DESIGN
BASED ON OBTAINING AN APPROXIMATE
GRADE OF 0.6%



PRELIMINARY

**NARRABEEN CREEK
DESIGN LONGSECTION**

DENIS LEECH & ASSOCIATES PTY LTD

**SECTOR 5
WARRIWOOD VALLEY**

INITIALS	SIGNATURE	DATE
DRAFTING	AK	16/1904
DESIGN	JL	16/1904
VERIFY	RAP	16/1904
APPROVED	RAP	16/1904

Brown Consulting (NSW) Pty Ltd
Level 2, 82 Waterloo Road Macquarie Park NSW Australia 2113
Telephone: 02 9900 1000 Facsimile: 02 9900 1099




BROWN

© 2004 W P Brown & Partners Pty Ltd

ALL DIMENSIONS TO BE CHECKED
ON SITE BY SUPERINTENDANT
PRIOR TO CONSTRUCTION. USE
WRITTEN DIMENSIONS ONLY, DO
NOT SCALE.

REV	DATE	DESCRIPTION	AK	JL	RAP	
BY	VER	APP	AMENDMENTS			
U1	22/03/04	ISSUED FOR DA APPROVAL				

姓名	性别	年龄	籍贯	民族	文化程度	职业	婚姻	子女	备注
王德胜	男	45	山东	汉族	高中	教师	已婚	2	
李秀英	女	38	河北	汉族	初中	工人	已婚	1	
张国强	男	52	河南	汉族	小学	农民	已婚	3	
刘小红	女	28	江苏	汉族	大学	医生	未婚	0	
陈为民	男	60	浙江	汉族	小学	退休	已婚	2	
赵大刚	男	35	四川	汉族	高中	工程师	已婚	1	
周丽娟	女	42	湖南	汉族	初中	售货员	已婚	2	
吴永强	男	55	湖北	汉族	小学	农民	已婚	3	
孙小芳	女	30	广东	汉族	大学	教师	未婚	0	
郑为民	男	48	广西	汉族	高中	工人	已婚	1	
马大伟	男	58	陕西	汉族	小学	农民	已婚	2	
林小梅	女	33	福建	汉族	初中	售货员	已婚	1	
徐国强	男	40	江西	汉族	高中	教师	已婚	2	
黄小红	女	25	安徽	汉族	大学	医生	未婚	0	
周为民	男	50	山西	汉族	小学	退休	已婚	1	
吴大刚	男	38	四川	汉族	高中	工程师	已婚	1	
周丽娟	女	45	湖南	汉族	初中	售货员	已婚	2	
吴永强	男	55	湖北	汉族	小学	农民	已婚	3	
孙小芳	女	30	广东	汉族	大学	教师	未婚	0	
郑为民	男	48	广西	汉族	高中	工人	已婚	1	
马大伟	男	58	陕西	汉族	小学	农民	已婚	2	
林小梅	女	33	福建	汉族	初中	售货员	已婚	1	
徐国强	男	40	江西	汉族	高中	教师	已婚	2	
黄小红	女	25	安徽	汉族	大学	医生	未婚	0	
周为民	男	50	山西	汉族	小学	退休	已婚	1	
吴大刚	男	38	四川	汉族	高中	工程师	已婚	1	
周丽娟	女	45	湖南	汉族	初中	售货员	已婚	2	
吴永强	男	55	湖北	汉族	小学	农民	已婚	3	
孙小芳	女	30	广东	汉族	大学	教师	未婚	0	
郑为民	男	48	广西	汉族	高中	工人	已婚	1	
马大伟	男	58	陕西	汉族	小学	农民	已婚	2	
林小梅	女	33	福建	汉族	初中	售货员	已婚	1	
徐国强	男	40	江西	汉族	高中	教师	已婚	2	
黄小红	女	25	安徽	汉族	大学	医生	未婚	0	
周为民	男	50	山西	汉族	小学	退休	已婚	1	
吴大刚	男	38	四川	汉族	高中	工程师	已婚	1	
周丽娟	女	45	湖南	汉族	初中	售货员	已婚	2	
吴永强	男	55	湖北	汉族	小学	农民	已婚	3	
孙小芳	女	30	广东	汉族	大学	教师	未婚	0	
郑为民	男	48	广西	汉族	高中	工人	已婚	1	
马大伟	男	58	陕西	汉族	小学	农民	已婚	2	
林小梅	女	33	福建	汉族	初中	售货员	已婚	1	
徐国强	男	40	江西	汉族	高中	教师	已婚	2	
黄小红	女	25	安徽	汉族	大学	医生	未婚	0	
周为民	男	50	山西	汉族	小学	退休	已婚	1	
吴大刚	男	38	四川	汉族	高中	工程师	已婚	1	
周丽娟	女	45	湖南	汉族	初中	售货员	已婚	2	
吴永强	男	55	湖北	汉族	小学	农民	已婚	3	
孙小芳	女	30	广东	汉族	大学	教师	未婚	0	
郑为民	男	48	广西	汉族	高中	工人	已婚	1	
马大伟	男	58	陕西	汉族	小学	农民	已婚	2	
林小梅	女	33	福建						



PRELIMINARY

NARRABEEN CREEK
DESIGN CROSS SECTIONS
SHEET 2

Drawn by: AK
Design by: J.L.
Project No: X04023
Drawing No: D13
Rev: 01

SECTOR 5
WARRIEWOOD VALLEY

Denis Leech & Associates Pty Ltd

BROWN

Level 2, 82 Waterloo Road Macquarie Park NSW Australia 2113
Telephone: 02 9900 1000 Facsimile: 02 9900 1099




©2004 W.P. Brown & Partners Pty Ltd


ALL DIMENSIONS TO BE CHECKED
ON SITE BY SUPERINTENDANT
PRIOR TO CONSTRUCTION. USE
WATER DIMENSIONS ONLY. DO
NOT SCALE.

ISSUED FOR DA APPROVAL

REV	DATE	DESCRIPTION
01	22/06/04	ISSUED FOR DA APPROVAL

AK	JL	BP
BY	VER	APP

[illegible]



PRELIMINARY

OVERLAND FLOWPATH
LONGSECTION
SECTOR 5

DENIS LEECH & ASSOCIATES PTY LTD

SECTOR 5
WARRIEWOOD VALLEY

DATE	SIGNATURE	INITIALS
16/19/04		AK
16/19/04		JL
16/19/04		RAP
16/19/04		RAP

Brown Consulting (NSW) Pty Ltd
Level 2, 82 Waterloo Road Macquarie Park NSW Australia 2113
Telephone: 02 9900 1000 Facsimile: 02 9900 1099






BROWN
Telephone: 02

Disclaimer and Copyright:
ALL DIMENSIONS TO BE CHECKED
ON SITE BY SUPERINTENDANT
PRIOR TO CONSTRUCTION. USE
WRITTEN DIMENSIONS ONLY, DO
NOT SCALE.

© 2004 W P Brown & Partners Pty Ltd

01	22/08/04	ISSUED FOR DA APPROVAL	AK	JL	RAP
REV	DATE	DESCRIPTION	BY	VER	APP

[illegible]



PRELIMINARY

OVERLAND FLOWPATH CROSS SECTIONS

SHEET 2

DENIS LEECH & ASSOCIATES PTY LTD

SECTOR 5
WARRIEWOOD VALLEY

Brown Consulting (NSW) Pty Ltd
Level 2, 82 Waterloo Road Macquarie Park NSW Australia 2113
Telephone: 02 9900 1000 Facsimile: 02 9900 1099

ALL DIMENSIONS TO BE CHECKED
ON SITE BY SUPERINTENDANT
PRIOR TO CONSTRUCTION. USE
WRITTEN DIMENSIONS ONLY. DO
NOT SCALE.

© 2004 W P Brown & Partners Pty Ltd

REV	DATE	ISSUED FOR	DESCRIPTION	BY	VER	APP
01	20/04/04	ISSUED FOR DA APPROVAL	AMENDMENTS	AK	JL	RAP

INITIALS	SIGNATURE	DATE
DRAFTING	AK	15/04/04
DESIGN	JL	16/04/04
VERIFY	RAP	16/04/04
APPROVED	RAP	18/04/04

Drawn by:	AK	Sheet:	11 OF 12
Design by:	JL	Scale:	1:200 (H) 1:50 (V)
Project No:	X04023	Drawing No:	D23
Rev:	01		