Local Government Area Northern Be	VORKS 2 rworks Road Ingleside 2101 eaches Council Plan DP 11594
Project type Dwelling type Separate dv Type of alteration and My renovation	welling house ion work is valued at \$50,000 or mon of include a pool (and/or spa).
Certificate Prepared by (please core)	gliete before submitting to Council or PCA)
	Certificate Prepared by please com

Fixtures and systems

Show on DA Plans Systems

Hot water

The applicant must install the following hot water system in the development: gas instantaneous.

Lighting

The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) tamps.

Fixtures

The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.

The applicant must ensure new or altered toilets have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.

The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
	d construction (floor(s), walls, and ceilings/roofs) tition is not required where the area of new const where insulation already exists.		✓	✓	✓
Construction	Additional insulation required (R-value)	Other specifications			
concrete slab on ground floor.	nil				
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				
external wall: brick veneer	R1.16 (or R1.70 including construction)				
internal wall shared with garage: single skin masonry (R0.18)	nil				
flat ceiling, pitched roof	ceiling: R0.95 (up), roof: foil backed blanket (75 mm)	medium (solar absorptance 0.475 - 0.70)			

BASIX Certificate number: A447921 Glazing requirements Windows and glazed doors The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door. The following requirements must also be satisfied in relation to each window and glazed door: Each window or glazed door with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. 1 Each window or glazed door with improved frames, or pyrolytic low-e glass, or clear/air gap/clear glazing, or toned/air gap/clear glazing must have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. The description is provided for information only. Alternative systems with complying U-value and SHGC may be substituted. For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill. Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35. Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm. Pergolas with adjustable shading may have adjustable blades or removable shade cloth (not less than 80% shading ratio). Adjustable blades Windows and glazed doors glazing requirements eave/verandah/pergola/balcony standard aluminium, single clear, (or >=900 mm U-value: 7.63, SHGC: 0.75) 1.7 0 0 eave/verandah/pergola/balcony standard aluminium, single clear, (or >=900 mm U-value: 7.63, SHGC: 0.75) S Planning, Industry & Environment Building Sustainability Index www.basix.nsw.gov.au BASIX Certificate number: A447921 page 5/6 3.2 eave/verandah/pergola/balcony standard aluminium, single clear, (or >=600 mm U-value: 7.63, SHGC: 0.75) 1.8 eave/verandah/pergola/balcony standard aluminium, single clear, (or >=600 mm U-value: 7.63, SHGC: 0.75) eave/verandah/pergola/balcony >=900 mm improved aluminium, single clear, (U-value 6.44, SHGC: 0.75) 1.5 1.7 0 eave/verandah/pergola/balcony >=900 mm standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) 7.5 0 pergola (adjustable shade) >=900 improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75) Planning, Industry & Environment Building Sustainability Index www.basix.nsw.gov.au

Arty CAD ADDITION - PROJECT MANAGEMENT	DESIGNED: ZK		Project	: PRO	POSED DEVELOPMENT	Demolition of existing garage/utility Alteration and addition	
A Beacon AvenueBeacon Hill NSW 2100 Mob: 0414 813 5Elhali: artyc@optusnet.com.au Copy Right of Arty CAD. Figured dimensions are to be taken in preference of scaling. Contractor is to check oil site levels and dimensions and must verify those before commencing work or malding any shop drawing.	DRAWN: MK		Adress	240 F NSW LOT 1	2101	to existing dwelling Owners: T & D Cvijetic	9
and must verify mose before commencing work or making any stop drawing.	ZK			BASI	BASIX COMMITMENTS		
B 04. 02. 22 ISSUED FOR D.A. A 15. 12. 21 FOR REVIEW Rev.: Rev. Date : Description :	DATE: 2021	SCALE 1: '	: 100(@A3)	SHEET: A3	2114/ A-10	6	Revision: B