BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A420866

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv Date of issue: Thursday, 01, July 2021 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

	Project address			
	Project name	Hall Outdoor room		
	Street address	82 Pitt Road North Curl Curl 2099		
	Local Government Area	Northern Beaches Council		
	Plan type and number	Deposited Plan 10571		
	Lot number	61		
	Section number			
Project type				
1	Dwelling type	Separate dwelling house		
	Type of alteration and addition	My renovation work is valued at \$50,000 or more and does not include a pool (and/or spa).		

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Site Specific Designs

ABN (if applicable): 28464402548

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		\checkmark	~
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		\checkmark	~
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		\checkmark	

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements			1		1
The applicant must construct the new or altere the table below, except that a) additional insula is not required for parts of altered construction	~	~	~		
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				
flat ceiling, flat roof: framed	ceiling: R0.90 (up), roof: foil backed blanket (55 mm)	light (solar absorptance < 0.475)			

Glazing re	quirements		_				Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows a	ind glazed do	oors					1		
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.					~	\checkmark	~		
The following requirements must also be satisfied in relation to each window and glazed door:						\checkmark	\checkmark		
Each window or glazed door with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.							 	~	
For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.					~	\checkmark	\checkmark		
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.						\checkmark	\checkmark		
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.						\checkmark	\checkmark		
Windows	and glazed	doors g	lazing r	equireme	nts				
Window / do no.	oor Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	adowing Distance (m)	Shading device	Frame and glass type			
W1	S	10.8	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
Skylights									
The applicant must install the skylights in accordance with the specifications listed in the table below.				\checkmark	\checkmark	\checkmark			
The following requirements must also be satisfied in relation to each skylight:						\checkmark	\checkmark		
Each skylight may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below.						 	\checkmark		
External awnings and louvres must fully shade the skylight above which they are situated when fully drawn or closed.						\checkmark	\checkmark		

Glazing requirements						Certifier Check
Skylights glaz	Skylights glazing requirements					
Skylight number	Area of glazing inc. frame (m2)	Shading device	Frame and glass type			
S1	1.68	external adjustable awning or blind	timber, double clear/air fill, (or U-value: 4.3, SHGC: 0.5)			
S2	1.68	external adjustable awning or blind	timber, double clear/air fill, (or U-value: 4.3, SHGC: 0.5)			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.