

Nationwide House Energy Rating Scheme®

NatHERS® Certificate No. 0011831328

Generated on 03 Apr 2025 using BERS Pro v5.2.4 (3.23)

Property

Address 13 Garden Street,
NORTH NARRABEEN , NSW , 2101

Lot/DP Lot 1 DP 24227

NCC class* 1a

Floor/all Floors G of 2 floors

Type New Home

Plans

Main plan 2023-15

Prepared by Blue Sky Building Designs

Construction and environment

Assessed floor area [m2]*	Exposure type
Conditioned* 259.6	Suburban
Unconditioned* 21.5	NatHERS climate zone
Total 286.5	56 Mascot (Sydney Airport)
Garage 5.4	



Accredited assessor

Name Joseph Lorriman

Business name Evergreen Energy Consultants Pty Ltd

Email enquiries@evergreenec.com.au

Phone 1300 584 010

Accreditation No. DMN/16/1742

Assessor Accrediting Organisation

Design Matters National

Declaration of interest Declaration completed: no conflicts

NCC Requirements

NCC provisions Volume Two

State/Territory variation Yes

National Construction Code (NCC) requirements


The NCC allows the use of NatHERS accredited software to comply with the energy efficiency requirements for houses (Class 1 buildings) and apartments (Class 2 sole-occupancy units and Class 4 parts of buildings). The applicable requirements for houses are detailed in Specification 42 of NCC Volume Two. For apartments the requirements are detailed in clauses J3D3 and J3D15 of NCC Volume One.

NCC 2022 includes enhanced thermal performance requirements for houses and apartments. It also includes a new whole-of-home annual energy use budget which applies to the major equipment in the home.

The NCC, and associated ABCB Standards and support material, can be accessed at www.abcb.gov.au.

Note, variations and additions to the NCC energy efficiency requirements may apply in some states and territories.

Thermal performance Star rating



Thermal performance [MJ/m²]

Limits taken from ABCB Standard 2022

	Heating	Cooling
Modelled	11.4	15.3
Load limits	N/A	N/A

Features determining load limits

Floor Type (lowest conditioned area)	CSOG
NCC climate zone 1 or 2	No
Outdoor living area	No
Outdoor living area ceiling fan	No

Whole of Home performance rating

No Whole of Home
performance rating
generated for this
certificate.

Verification

To verify this certificate,
scan the QR code or visit
[hstar.com.au/QR/Generate?
p=wtiOyFyXE](http://hstar.com.au/QR/Generate?p=wtiOyFyXE) .
When using either link,
ensure you are visiting
hstar.com.au



About the ratings

Thermal performance rating

NatHERS thermal software models the expected heating and cooling energy loads using information about the design, construction, climate and common patterns of household use. The thermal performance rating (shown as a star rating on this Certificate) does not take into account appliances, apart from the airflow impacts from ceiling fans.

Whole of Home performance rating

NatHERS Whole of Home software uses the heating and cooling energy loads combined with the energy performance of the home's appliances (heating, cooling, hot water, lighting, pool/spa pump and onsite renewable energy generation and storage) and models the expected energy value* of the whole home. The Whole of Home performance rating is shown as a score out of 100 on this Certificate.

Heating & Cooling Load Limits

Additional information

In some locations under the NCC NatHERS pathway, separate heating and cooling load limits may apply. Minimum required star ratings in northern parts of Australia may also be affected by the presence or absence of an outdoor living area and/or an outdoor living area ceiling fan. Refer to the *ABC Standard 2022: NatHERS heating and cooling load limits* for details or contact the relevant local building regulating authority, noting that State and Territory variations may also apply.

Setting Options:

Floor Type:

CSOG – Concrete Slab on Ground
SF – Suspended Floor (or a mixture of CSOG and SF)
NA – Not Applicable

NCC Climate Zone 1 or 2:

Yes
No
NA – Not Applicable

Outdoor Living Area:

Yes
No
NA – Not Applicable

Outdoor Living Area Ceiling Fan:

Yes
No
NA – Not Applicable



Predicted onsite renewable energy impact

No Whole of Home performance assessment conducted for this certificate.

Predicted Whole of Home annual impact by appliance

Energy use

No Whole of Home performance assessment conducted for this certificate

Greenhouse gas emissions

No Whole of Home performance assessment conducted for this certificate

Cost

No Whole of Home performance assessment conducted for this certificate

Certificate check

The checklist covers important items impacting the dwelling's ratings. It is recommended that the accuracy of the whole certificate is checked.

Note: The boxes indicate when and by whom each item should be checked. It is not mandatory to complete this checklist.

	Approval Stage		Construction Stage		Occupancy/Other
	Assessor checked	Consent Authority/ Surveyor checked	Builder checked	Consent Authority Surveyor checked	
Genuine certificate check					
Does this Certificate match the one available at the web address or QR code verification link on the front page?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the NatHERS certificate number on the NatHERS-stamped plans match the number on this Certificate?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Thermal performance check					
Windows and glazed doors					
Does the window size, opening type and location shown on the NatHERS-stamped plans or as installed match what is shown in 'Window and glazed door schedule' and 'Roof window schedule' tables on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the installed windows meet the substitution tolerances (AFRC* based SHGC* and U-values*) as shown in the 'Window and glazed door type and performance' and 'Roof window type and performance' tables on this Certificate?			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
External walls					
Does the external wall bulk insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the External wall type table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the external wall shade (colour) match what is shown in the 'External wall type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Floor					
Does the floor insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Floor type' table on this certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Ceiling penetrations*					
Does the 'quantity' and 'type' of ceiling penetrations* (e.g. downlights, exhaust fans, etc) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling penetrations' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Ceiling					
Does the ceiling insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Roof					
Does the external roof shade (colour) on the NatHERS stamped plans or as installed match what is shown in the 'Roof type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Apartment entrance doors (NCC Class 2 assessments only)					
Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>
Exposure*					
Has the appropriate exposure type (terrain) (shown on page 1) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>
Heating and cooling load limits*					
Do the load limits settings (shown on page 1) match what is shown	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>



Certificate check

Continued

	Approval Stage		Construction Stage		
	Assessor checked	Consent Authority/ Surveyor checked	Builder checked	Consent Authority Surveyor checked	Occupancy/Other

Additional NCC requirements for thermal performance (not included in the NatHERS assessment)

Thermal bridging

Does the dwelling meet the NCC requirement for thermal bridging?

☐ ☐ ☐ ☐

Insulation installation method

Has the insulation been installed according to the NCC requirements?

☐ ☐ ☐

Building sealing

Does the dwelling meet the NCC requirements for Building Sealing?

☐ ☐ ☐ ☐

Whole of Home performance check (not applicable if a Whole of Home performance assessment is not conducted)

Appliances

Does the cooling appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the Appliance schedule on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the heating appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the hot water system type and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the pool pump efficiency/performance shown on the NatHERS-stamped plans or as installed match the minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the onsite renewable energy system type, orientation and system size or generation capacity shown on the NatHERS stamped plans or installed match the 'Onsite Renewable Energy schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Additional NCC Requirements for Services (not included in the NatHERS assessment)

Does the lighting meet the artificial lighting requirements specified in the NCC?

☐ ☐ ☐ ☐

Does the hot water system meet the additional requirements specified in the NCC?

☐ ☐ ☐ ☐

Provisional values* check

Have provisional values* been used in the assessment and, if so, are they noted in 'Additional notes' table below?

☐ ☐ ☐ ☐

Other NCC requirements

Note: This Certificate only covers the energy efficiency requirements in the NCC. Additional requirements that must also be satisfied include, but are not limited to: condensation, structural and fire safety requirements and any state or territory variations to the NCC energy efficiency requirements.

Additional notes

Room schedule

Room	Zone Type	Area [m ²]
Kitchen/Living	Kitchen/Living	87.46
Pantry	Daytime	6.75
Laundry	Unconditioned	6.02
Bath	Unconditioned	5.37
Powder	Unconditioned	3.38
Guest Bed	Bedroom	17.46
Home Gym	Daytime	13.48
Storage	Garage	5.38
Master Bed	Bedroom	30.64
Rumpus	Living	24.29
Bedroom 2	Bedroom	16.14
Bedroom 3	Bedroom	14.43
Bedroom 4	Bedroom	14.26
Bathroom	Unconditioned	5.04
Ensuite	Nighttime	7.26
Void	Unconditioned	9.5
Parent Retreat	Nighttime	15.67
Hall	Daytime	11.78
WC	Unconditioned	1.66

Window and glazed door type and performance

Default windows*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

Custom windows*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
ALS-037-018	Aluminium Sliding Door DG LB Clr 4/10/4	2.8	0.48	0.46	0.51
ALS-039-019	Aluminium Double Hung Window DG LB Clr 4/10/4	3.2	0.46	0.44	0.48



Custom windows*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
ALS-028-019	Aluminium Fixed Window DG LB Clr 4/10/4	2.2	0.53	0.51	0.56
ALS-090-009	Aluminium Sliding Window DG LB Clr 4/10/4	2.9	0.49	0.47	0.51
ALS-056-013	Aluminium Casement Window DG LB Clr 4/16/4	4.1	0.36	0.34	0.37
ALS-025-019	Aluminium Awning Window DG LB Clr 4/10/4	3.2	0.45	0.43	0.47

Window and glazed door schedule

Location	Window ID	Window no.	Height [mm]	Width [mm]	Window type	Opening %	Orientation	Window shading device*
Kitchen/Living	ALS-037-018-001	W28	2400	3600	Sliding	60	E	No
Kitchen/Living	ALS-039-019-001	W19	2000	1200	Double Hung	45	N	No
Kitchen/Living	ALS-037-018-001	W23	2400	6000	Sliding	60	E	No
Kitchen/Living	ALS-028-019-001	W30	600	2700	Fixed	00	S	No
Kitchen/Living	ALS-039-019-001	W29	2000	1200	Double Hung	45	N	No
Kitchen/Living	ALS-037-018-001	n/a	2400	2400	Sliding	45	N	No
Pantry	ALS-090-009-001	W20	600	1600	Sliding	45	S	No
Laundry	ALS-056-013-001	W26	2100	820	Casement	90	S	No
Bath	ALS-039-019-001	W21	1400	900	Awning	90	S	No
Guest Bed	ALS-090-009-001	W22	1400	1800	Sliding	45	S	No
Home Gym	ALS-037-018-001	W14	2400	2600	Sliding	60	N	No
Master Bed	ALS-090-009-001	W6	1300	3000	Sliding	10	E	No
Master Bed	ALS-025-019-001	W7	1300	600	Awning	90	E	No
Master Bed	ALS-090-009-001	W25	1300	1500	Sliding	10	N	No
Rumpus	ALS-090-009-001	n/a	1300	3300	Sliding	30	N	No
Bedroom 2	ALS-090-009-001	n/a	1300	2700	Sliding	10	W	No
Bedroom 3	ALS-090-009-001	W13	1300	2700	Sliding	10	W	No
Bedroom 3	ALS-090-009-001	n/a	1300	2700	Sliding	10	N	No
Bedroom 4	ALS-090-009-001	W2	1300	2700	Sliding	10	N	No

* Refer to glossary.



Location	Window ID	Window no.	Height [mm]	Width [mm]	Window type	Opening %	Orientation	Window shading device*
Bathroom	ALS-090-009-001	W9	1300	1500	Sliding	45	S	No
Ensuite	ALS-090-009-001	W8	1300	1500	Sliding	45	S	No
Parent Retreat	ALS-090-009-001	W4	1300	2700	Sliding	30	N	No
Parent Retreat	ALS-090-009-001	W5	1300	3600	Sliding	60	E	No
Hall	ALS-025-019-001	W32	1300	900	Awning	90	W	No
WC	ALS-025-019-001	W31	1300	900	Awning	90	S	No

Roof window* type and performance value

Default roof windows*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
DG-Generic-02 A	DG-Generic-02 A Clear AI DG DEFAULT ROOF WINDOW System 02	4.2	0.72	0.68	1.40

Custom roof windows*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
VEL-011-01 W	VEL-011-01 W VELUX FS - Fixed Skylight DG 3mm LoE 366 / 8.5mm Argon Gap / 5.36mm Clear La	2.6	0.24	0.23	0.25

Roof window* schedule

Location	Window ID	Window no.	Opening %	Height [mm]	Width [mm]	Orientation	Outdoor shade	Indoor shade
Master Bed	VEL-011-01 W	S10	0	1800	600	S	Yes	Yes
Master Bed	DG-Generic-02 A	S11	0	1800	600	S	Yes	Yes
Master Bed	DG-Generic-02 A	S12	0	1800	600	S	Yes	Yes
Ensuite	DG-Generic-02 A	S5	0	1200	800	S	Yes	Yes
Void	DG-Generic-02 A	S13	0	1800	600	S	Yes	Yes
Void	DG-Generic-02 A	S14	0	1800	600	S	Yes	Yes
Void	DG-Generic-02 A	S15	0	1800	600	S	Yes	Yes
Hall	DG-Generic-02 A	S9	0	600	600	S	Yes	Yes

Skylight* type and performance

Skylight ID	Skylight description	Skylight shaft reflectance
No Data Available		

Skylight* schedule

Location	Skylight ID	Skylight No.	Skylight shaft length [mm]	Area [m ²]	Orientation	Outdoor shade	Diffuser
No Data Available							

External door schedule

Location	Height [mm]	Width [mm]	Opening %	Orientation
Kitchen/Living	2100	920	90	W
Storage	2040	2500	90	W

External wall type

Wall ID	Wall type	Solar absorptance	Wall shade [colour]	Bulk insulation [R-value]	Reflective wall wrap*
EW-1	Fibro Timber Stud Frame Panel Direct Fix	0.30		Bulk Insulation, Air Gap R2.7	No
EW-2	Metal Clad Timber Stud Frame Direct Fix	0.30		Bulk Insulation, Air Gap R2.7	No

External wall schedule

Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature [yes/no]
Kitchen/Living	EW-1	2700	3700	E	600	No
Kitchen/Living	EW-1	2701	600	E	5900	No
Kitchen/Living	EW-1	2700	1800	N	600	No
Kitchen/Living	EW-1	2700	7100	E	4100	Yes
Kitchen/Living	EW-1	2700	5995	S	600	No
Kitchen/Living	EW-2	1350	3900	S	5200	No
Kitchen/Living	EW-1	2700	1295	W	2800	No
Kitchen/Living	EW-1	2700	3900	N	7400	No
Kitchen/Living	EW-1	2700	595	W	6700	No
Kitchen/Living	EW-1	2700	1400	W	10400	No
Kitchen/Living	EW-1	2700	6100	N	700	No



Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature [yes/no]
Pantry	EW-1	2700	1890	S	600	No
Laundry	EW-1	2700	1690	S	600	No
Bath	EW-1	2700	1990	S	600	No
Guest Bed	EW-1	2700	3890	S	600	No
Guest Bed	EW-1	1350	1295	W	0	No
Guest Bed	EW-2	1350	1295	W	2300	No
Home Gym	EW-1	2700	3495	W	6700	No
Home Gym	EW-1	2700	3695	N	2100	No
Storage	EW-1	1350	1695	S	0	No
Storage	EW-2	1350	1695	S	600	No
Storage	EW-1	1350	3300	W	0	No
Storage	EW-2	1350	3300	W	600	No
Storage	EW-1	1350	1695	N	0	No
Storage	EW-2	1350	1695	N	10000	No
Master Bed	EW-1	750	5900	E	0	No
Master Bed	EW-2	3450	5900	E	600	No
Master Bed	EW-2	200	4895	S	0	No
Master Bed	EW-1	2300	4895	S	600	No
Master Bed	EW-1	2700	1800	N	600	No
Rumpus	EW-1	2500	4490	N	475	No
Bedroom 2	EW-2	2500	3895	S	1100	No
Bedroom 2	EW-2	400	4195	W	0	No
Bedroom 2	EW-1	2100	4195	W	600	No
Bedroom 3	EW-1	2700	1300	S	600	No
Bedroom 3	EW-1	2500	4300	W	600	No
Bedroom 3	EW-1	2500	3395	N	450	No
Bedroom 4	EW-1	2500	3390	N	475	No
Bathroom	EW-2	200	2090	S	0	No
Bathroom	EW-1	2300	2090	S	600	No
Ensuite	EW-2	200	2990	S	0	No
Ensuite	EW-1	2300	2990	S	600	No

Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature [yes/no]
Parent Retreat	EW-2	200	3695	N	0	No
Parent Retreat	EW-1	2300	3695	N	500	No
Parent Retreat	EW-1	2700	4295	E	600	No
Hall	EW-1	2500	1190	W	600	No
WC	EW-2	200	1595	S	0	No
WC	EW-1	2300	1595	S	600	No
WC	EW-1	2700	500	W	4500	No

Internal wall type

Wall ID	Wall type	Area [m ²]	Bulk insulation
IW-001	Timber Stud Frame, Direct Fix Plasterboard	254.84	No insulation
IW-002	Timber Stud Frame, Direct Fix Plasterboard	0.00	Bulk Insulation, No Air Gap R2.7

Floor type

Location	Construction	Area [m ²]	Sub-floor ventilation	Added insulation [R-value]	Covering
Kitchen/Living	Suspended 35mm Fibre-Reinforced Concrete Floor Timber Frame 42mm	87.46	Very Open	No Insulation	Cork Tiles or Parquetry 8mm
Pantry	Suspended 35mm Fibre-Reinforced Concrete Floor Timber Frame 42mm	6.75	Very Open	No Insulation	Ceramic Tiles 8mm
Laundry	Suspended 35mm Fibre-Reinforced Concrete Floor Timber Frame 42mm	6.02	Very Open	No Insulation	Ceramic Tiles 8mm
Bath	Suspended 35mm Fibre-Reinforced Concrete Floor Timber Frame 42mm	5.37	Very Open	No Insulation	Ceramic Tiles 8mm
Powder	Suspended 35mm Fibre-Reinforced Concrete Floor Timber Frame 42mm	3.38	Very Open	No Insulation	Ceramic Tiles 8mm
Guest Bed	Suspended 35mm Fibre-Reinforced Concrete Floor Timber Frame 42mm	17.46	Very Open	No Insulation	Cork Tiles or Parquetry 8mm
Home Gym	Suspended 35mm Fibre-Reinforced Concrete Floor Timber Frame 42mm	13.48	Very Open	No Insulation	Cork Tiles or Parquetry 8mm
Storage	Concrete Slab on Ground 100mm	5.38	None	No Insulation	Bare



Location	Construction	Area [m ²]	Sub-floor ventilation	Added insulation [R-value]	Covering
Master Bed / Kitchen/Living	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	30.64		No Insulation	Carpet+Rubber Underlay 18mm
Rumpus / Kitchen/Living	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	13.22		No Insulation	Carpet+Rubber Underlay 18mm
Rumpus / Home Gym	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	7.66		No Insulation	Carpet+Rubber Underlay 18mm
Rumpus	Suspended 35mm Fibre-Reinforced Concrete Floor Timber Frame 42mm	2.48	Totally Open	Bulk Insulation in Contact with Floor R1	Carpet+Rubber Underlay 18mm
Bedroom 2 / Kitchen/Living	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	4.83		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2 / Guest Bed	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	11.06		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 3	Suspended 35mm Fibre-Reinforced Concrete Floor Timber Frame 42mm	14.43	Totally Open	Bulk Insulation in Contact with Floor R1	Carpet+Rubber Underlay 18mm
Bedroom 4 / Home Gym	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	4.28		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 4	Suspended 35mm Fibre-Reinforced Concrete Floor Timber Frame 42mm	9.62	Totally Open	Bulk Insulation in Contact with Floor R1	Carpet+Rubber Underlay 18mm
Bathroom / Laundry	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	4.03		No Insulation	Ceramic Tiles 8mm
Bathroom / Bath	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	0.43		No Insulation	Ceramic Tiles 8mm
Ensuite / Kitchen/Living	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	2.51		No Insulation	Ceramic Tiles 8mm
Ensuite / Pantry	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	4.51		No Insulation	Ceramic Tiles 8mm
Void / Kitchen/Living	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	0.00		No Insulation	Carpet+Rubber Underlay 18mm



Location	Construction	Area [m ²]	Sub-floor ventilation	Added insulation [R-value]	Covering
Parent Retreat / Kitchen/Living	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	15.67		No Insulation	Carpet+Rubber Underlay 18mm
Hall / Kitchen/Living	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	2.46		No Insulation	Carpet+Rubber Underlay 18mm
Hall / Bath	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	0.22		No Insulation	Carpet+Rubber Underlay 18mm
Hall / Powder	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	2.30		No Insulation	Carpet+Rubber Underlay 18mm
Hall / Home Gym	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	0.38		No Insulation	Carpet+Rubber Underlay 18mm
Hall	Suspended 35mm Fibre-Reinforced Concrete Floor Timber Frame 42mm	4.10	Totally Open	Bulk Insulation in Contact with Floor R1	80/20 Carpet 10mm/Ceramic
WC / Bath	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard 42mm	1.66		No Insulation	Ceramic Tiles 8mm

Ceiling type

Location	Construction material/type	Bulk insulation R-value (may include edge batt values)	Reflective wrap* [yes/no]
Kitchen/Living	Plasterboard on Timber	Bulk Insulation R3	
Kitchen/Living	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard	No Insulation	
Pantry	Plasterboard on Timber	Bulk Insulation R3	
Pantry	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard	No Insulation	
Laundry	Plasterboard on Timber	Bulk Insulation R3	
Laundry	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard	No Insulation	
Bath	Plasterboard on Timber	Bulk Insulation R3	
Bath	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard	No Insulation	
Powder	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard	No Insulation	
Guest Bed	Plasterboard on Timber	Bulk Insulation R3	



Location	Construction material/type	Bulk insulation R-value (may include edge batt values)	Reflective wrap* [yes/no]
Guest Bed	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard	No Insulation	
Home Gym	35mm Fibre-Reinforced Concrete Timber Frame Above Plasterboard	No Insulation	
Storage	Plasterboard on Timber	Bulk Insulation R3	
Master Bed	Plasterboard on Timber	Bulk Insulation R3	
Rumpus	Plasterboard on Timber	Bulk Insulation R3	
Bedroom 2	Plasterboard on Timber	Bulk Insulation R3	
Bedroom 3	Plasterboard on Timber	Bulk Insulation R3	
Bedroom 4	Plasterboard on Timber	Bulk Insulation R3	
Bathroom	Plasterboard on Timber	Bulk Insulation R3	
Ensuite	Plasterboard on Timber	Bulk Insulation R3	
Void	Plasterboard on Timber	Bulk Insulation R3	
Parent Retreat	Plasterboard on Timber	Bulk Insulation R3	
Hall	Plasterboard on Timber	Bulk Insulation R3	
WC	Plasterboard on Timber	Bulk Insulation R3	

Ceiling penetrations*

Location	Quantity	Type	Diameter [mm]	Sealed/unsealed
Kitchen/Living	17	Downlights - LED	150	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed
Pantry	1	Downlights - LED	150	Sealed
Laundry	1	Downlights - LED	150	Sealed
Laundry	1	Exhaust Fans	300	Sealed
Bath	1	Downlights - LED	150	Sealed
Bath	1	Exhaust Fans	300	Sealed
Powder	1	Downlights - LED	150	Sealed
Powder	1	Exhaust Fans	300	Sealed
Guest Bed	3	Downlights - LED	150	Sealed
Home Gym	2	Downlights - LED	150	Sealed
Storage	1	Downlights - LED	150	Sealed
Master Bed	6	Downlights - LED	150	Sealed



Location	Quantity	Type	Diameter [mm]	Sealed/unsealed
Rumpus	7	Downlights - LED	150	Sealed
Bedroom 2	3	Downlights - LED	150	Sealed
Bedroom 3	2	Downlights - LED	150	Sealed
Bedroom 4	2	Downlights - LED	150	Sealed
Bathroom	1	Downlights - LED	150	Sealed
Bathroom	1	Exhaust Fans	300	Sealed
Ensuite	1	Downlights - LED	150	Sealed
Ensuite	1	Exhaust Fans	300	Sealed
Parent Retreat	3	Downlights - LED	150	Sealed

Ceiling fans

Location	Quantity	Diameter [mm]
Kitchen/Living	1	1800
Guest Bed	1	1400
Master Bed	1	1400
Rumpus	1	1800
Bedroom 2	1	1400
Bedroom 3	1	1400
Bedroom 4	1	1400

Roof type

Construction	Added insulation [R-value]	Solar absorptance	Roof shade [colour]
Corrugated Iron Timber Frame	Bulk, Reflective Side Down, No Air Gap Above R1.3	0.60	Medium

Thermal bridging schedule for steel frame elements

Building element	Steel section dimensions [height x width, mm]	Frame spacing [mm]	Steel thickness [BMT,mm]	Thermal break [R-value]
No Data Available				

Appliance schedule

(not applicable if a Whole of Home performance assessment is not conducted for this certificate)

Note: A flat assumption of 5W/m² is used for lighting, therefore lighting is not included in the appliance schedule.



Cooling system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available				

Heating system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available				

Hot water system

Appliance/ system type	Fuel type	Hot Water	Minimum efficiency /STC	Zone 3 STC	Zone 3 Substitution tolerance ranges		Assessed daily load [litres]
		CER Zone			lower limit	upper limit	
No Data Available							

Pool/spa equipment

Appliance/ system type	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available			

Onsite Renewable Energy Schedule

System Type	Orientation	System Size Or Generation Capacity
No Data Available		

Battery Schedule

System Type	Size [Battery Storage Capacity]
No Data Available	



Explanatory notes

About this report

NatHERS ratings are a reliable guide for comparing different dwelling designs and to demonstrate that designs meet the energy efficiency requirements in the National Construction Code.

NatHERS ratings use computer modelling to evaluate a home's energy efficiency and performance. They use localised climate data and standard assumptions on how people use their home to predict the heating and cooling energy loads and energy value* of the whole home. The thermal performance star rating uses the home's building specifications, layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings) to predict the heating and cooling energy loads. The Whole of Home performance rating uses information about the home's appliances and onsite energy generation and storage to estimate the home's energy value*.

The actual energy loads, cost and greenhouse gas emissions of a home may vary from that predicted. This is because the assumptions will not always match the actual occupant usage patterns. For example, the number of occupants and how people use their appliances will vary.

Energy efficient homes use less energy, are warmer on cool days, cooler on hot days and cost less to run.

Accredited assessors

For quality assured NatHERS Certificates, always use an accredited or licenced assessor registered with an Assessor Accrediting Organisation (AAO). AAOs have strict quality assurance processes, and professional development requirements ensuring consistently high standards for assessments.

Non-accredited assessors (Raters) have no ongoing training requirements and

are not quality assured.

Any queries about this report should be directed to the assessor. If the assessor is unable to address questions or concerns, contact the AAO specified on the front of this certificate.

Disclaimer

The NatHERS Certificate format is developed by the NatHERS Administrator. However, the content in the certificate is entered by the assessor. It is the assessor's responsibility to use NatHERS accredited software correctly and follow the NatHERS Technical Note to produce a NatHERS Certificate.

The predicted annual energy load, cost and greenhouse gas emissions in this NatHERS Certificate are an estimate based on an assessment of the dwelling's design by the assessor. It is not a prediction of actual energy use, cost or emissions. The information and ratings may be used to compare how other dwellings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, behaviour, appliance performance, indoor air temperature and local climate.

Not all assumptions made by the assessor using the NatHERS accredited software tool are presented in this report and further details or data files may be obtained from the assessor.

Glossary

AFRC	Australian Fenestration Rating Council
Annual energy load	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
Assessed floor area	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
Ceiling penetrations	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, range hoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
COP	Coefficient of performance
Conditioned	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
Custom windows	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
Default windows	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
EER	Energy Efficiency Ratio, measure of how much cooling can be achieved by an air conditioner for a single kWh of electricity input
Energy use	This is your home's rating without solar or batteries.
Energy value	The net cost to society including, but not limited to, costs to the building user, the environment and energy networks (as defined in the ABCB Housing Provisions Standard).
Entrance door	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
Exposure	see exposure categories below.
Exposure category – exposed	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
Exposure category – open	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
Exposure category – protected	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
Exposure category – suburban	terrain with numerous, closely spaced obstructions over 10 m e.g. city and industrial areas.
Horizontal shading feature	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
National Construction Code (NCC) Class	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at www.abcb.gov.au .
Net zero home	a home that achieves a net zero energy value*.
Opening percentage	the operability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
Provisional value	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at www.nathers.gov.au
Recommended capacity	this is the capacity or size of equipment that is recommended by NatHERS to achieve the desired comfort conditions in the zone or zones serviced. This is a recommendation and the final selection sizing should be confirmed by a suitably qualified person.
Reflective wrap (also known as foil)	can be applied to walls, roofs and ceilings. When combined with an appropriate airgap and emissivity value, it provides insulative properties.
Roof window	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
Shading features	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
Skylight (also known as roof lights)	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.
Solar heat gain coefficient (SHGC)	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
STCs	Small-scale Technology Certificates, certificates created by the REC registry for renewable energy technologies that may be bought and sold as part of the Small-scale Renewable Energy Scheme operated by the Clean Energy Regulator (CER)
Thermal breaks	are materials with an R-value greater than or equal to 0.2 that must separate the metal frame from the cladding. This includes, but is not limited to, materials such as timber battens greater than or equal to 20mm thick or continuous thermal breaks such as polystyrene insulation sheathing or plastic strips
U-value	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
Unconditioned	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions.
Vertical shading features	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).
Window shading device	device fixed to windows that provides shading e.g. window awnings or screens but excludes horizontal* or vertical shading features* (eg eaves and balconies)

* Refer to glossary.