BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A453795

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv Date of issue: Saturday, 30, April 2022 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project name	Clarke Belrose
Street address	17 Seeana Place Belrose 2086
Local Government Area	Northern Beaches Council
Plan type and number	Deposited Plan 237435
Lot number	20
Section number	
Project type	
Dwelling type	Separate dwelling house
Type of alteration and	My renovation work is valued at \$50,000 or more

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Neil Harvey

ABN (if applicable): 20628585478

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		\checkmark	~

Construction		Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements				
The applicant must construct the new or altered the table below, except that a) additional insula is not required for parts of altered construction	~	~	~	
Construction	Additional insulation required (R-value) Other specifications			
concrete slab on ground floor.	nil			
floor above existing dwelling or building.	nil			
external wall: cavity brick	nil			
external wall: brick veneer	R1.16 (or R1.70 including construction)			
flat ceiling, pitched roof	ceiling: R2.50 (up), roof: foil/sarking medium (solar absorptance 0.475 - 0.70)			

Glazing ı	requirements	5					Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows	and glazed	doors					I	1	
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.						~	~	~	
The following requirements must also be satisfied in relation to each window and glazed door:							\checkmark	\checkmark	
Each window or glazed door with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.								~	~
For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.							~	\checkmark	\checkmark
Pergolas v	with polycarbon	ate roof or s	similar tran	slucent mate	erial must have a shading coefficien	t of less than 0.35.		~	\checkmark
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.							\checkmark	\checkmark	
Overshadowing buildings or vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column in the table below.						\checkmark	\checkmark	\checkmark	
Window	s and glaze	d doors g	lazing r	equiremer	nts		-		
Window / no.	door Orientatio	on Area of glass inc. frame (m2)	Oversha Height (m)	dowing Distance (m)	Shading device	Frame and glass type			
W1	SW	1.44	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W2	SE	1.44	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W3	SE	1.44	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W4	NE	1.44	7	6	none	standard aluminium, single toned, (or U-value: 7.57, SHGC: 0.57)			

Glazing requirements								Show on CC/CDC Plans & specs	Certifier Check
Window / door Orientation Are			Area of Overshado		dowing Shading device Frame and glass type				
no.		glass inc. frame (m2)	Height (m)	Distance (m)					
W5	SW	1.44	0	0	eave/verandah/pergola/balcony >=750 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W6	SE	2.16	0	0	eave/verandah/pergola/balcony >=750 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W7	SE	2.16	0	0	eave/verandah/pergola/balcony >=750 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W8	NE	1.44	0	0	eave/verandah/pergola/balcony >=750 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
"
"
"
"
"
"
"
"
"
"
Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " / " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.