

# BASIX<sup>®</sup>Certificate

Building Sustainability Index [www.basix.nsw.gov.au](http://www.basix.nsw.gov.au)

## Single Dwelling

Certificate number: 1228573S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at [www.basix.nsw.gov.au](http://www.basix.nsw.gov.au)

Secretary

Date of issue: Tuesday, 21 December 2021

To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning,  
Industry &  
Environment

### Project summary

Project name	122 Riverview Avalon
Street address	122 Riverview Road Avalon 2107
Local Government Area	Northern Beaches Council
Plan type and plan number	deposited DP 24563
Lot no.	81
Section no.	-
Project type	separate dwelling house
No. of bedrooms	4

### Project score

Water	✓ 41	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 52	Target 50

### Certificate Prepared by

Name / Company Name: Interlock Construction

ABN (if applicable): 58631997763

# Description of project

## Project address

Project name	122 Riverview Avalon
Street address	122 Riverview Road Avalon 2107
Local Government Area	Northern Beaches Council
Plan type and plan number	Deposited Plan DP 24563
Lot no.	81
Section no.	-

## Project type

Project type	separate dwelling house
No. of bedrooms	4

## Site details

Site area (m <sup>2</sup> )	964
Roof area (m <sup>2</sup> )	209
Conditioned floor area (m <sup>2</sup> )	160.0
Unconditioned floor area (m <sup>2</sup> )	11.0
Total area of garden and lawn (m <sup>2</sup> )	579

## Assessor details and thermal loads

Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m <sup>2</sup> .year)	n/a
Area adjusted heating load (MJ/m <sup>2</sup> .year)	n/a
Ceiling fan in at least one bedroom	n/a
Ceiling fan in at least one living room or other conditioned area	n/a

## Project score

Water	✓ 41	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 52	Target 50

## Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<b>Landscape</b>			
The applicant must plant indigenous or low water use species of vegetation throughout 400 square metres of the site.	✓	✓	
<b>Fixtures</b>			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but ≤ 6 L/min plus spray force and/or coverage tests) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 5 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		✓	
<b>Alternative water</b>			
<b>Rainwater tank</b>			
The applicant must install a rainwater tank of at least 5000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rain runoff from at least 236 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		✓	✓
The applicant must connect the rainwater tank to: <ul style="list-style-type: none"> <li>at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.)</li> </ul>		✓	✓

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<b>General features</b>			
The dwelling must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
<b>Floor, walls and ceiling/roof</b>			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓

Construction	Additional insulation required (R-Value)	Other specifications
floor - suspended floor above open subfloor, 81 square metres, concrete	0.9 (or 1.5 including construction) (down)	
floor - above habitable rooms or mezzanine, 81 square metres, concrete	nil	
external wall - brick veneer	1.86 (or 2.40 including construction)	
external wall - framed (weatherboard, fibre cement, metal clad)	2.00 (or 2.40 including construction)	
internal wall shared with garage - plasterboard	nil	
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 4 (up), roof: foil backed blanket (100 mm)	framed; dark (solar absorptance > 0.70)

Note	• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<b>Windows, glazed doors and skylights</b>			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
<p>The following requirements must also be satisfied in relation to each window and glazed door:</p> <ul style="list-style-type: none"> <li>For the following glass and frame types, the certifier check can be performed by visual inspection. <ul style="list-style-type: none"> <li>- Aluminium single clear</li> <li>- Aluminium double (air) clear</li> <li>- Timber/uPVC/fibreglass single clear</li> <li>- Timber/uPVC/fibreglass double (air) clear</li> </ul> </li> <li>For other glass or frame types, each window and glazed door must be accompanied with certification showing a U value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range of those listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. Frame and glass types shown in the table below are for reference only.</li> <li>Vertical external louvres and blinds must fully shade the window or glazed door beside which they are situated when fully drawn or closed.</li> <li>Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column.</li> </ul>	✓	✓	✓ ✓     ✓
The applicant must install the skylights described in the table below, in accordance with the specifications listed in the table. Total skylight area must not exceed 3 square metres (the 3 square metre limit does not include the optional additional skylight of less than 0.7 square metres that does not have to be listed in the table).	✓	✓	✓

Skylight no.	Maximum area (square metres)	Type	Shading device
S01	1.30	aluminium, moulded plastic single clear	no shading

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
<b>North facing</b>					
WLG.02	800	5800	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	external louvre/vertical blind (adjustable)	>4 m high, 2-5 m away
WLG.03	800	3700	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	external louvre/vertical blind (adjustable)	>4 m high, 2-5 m away
<b>East facing</b>					
WLG.04	900	900	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	eave 400 mm, 2000 mm above head of window or glazed door	>4 m high, <2 m away
WLG.05	900	900	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	eave 400 mm, 2000 mm above head of window or glazed door	>4 m high, <2 m away
WG.03	1800	1200	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	eave 300 mm, 300 mm above head of window or glazed door	not overshadowed
WG.02	500	1400	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	eave 300 mm, 300 mm above head of window or glazed door	not overshadowed
WG.04	500	1400	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	eave 300 mm, 300 mm above head of window or glazed door	not overshadowed
<b>South facing</b>					
DG.09	380	1400	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	eave 100 mm, 400 mm above head of window or glazed door	not overshadowed
<b>West facing</b>					
DG.06	2100	2800	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	eave 700 mm, 0 mm above head of window or glazed door	2-4 m high, 8-12 m away
DG.07	2100	2800	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	eave 700 mm, 0 mm above head of window or glazed door	2-4 m high, 8-12 m away

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
DLG.01	2100	2500	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	eave 700 mm, 0 mm above head of window or glazed door	2-4 m high, 8-12 m away
DLG.02	2100	2500	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	eave 700 mm, 0 mm above head of window or glazed door	2-4 m high, 8-12 m away
WLG.01	2100	900	U-value: 3.7, SHGC: 0.342 - 0.418 (timber/UPVC/fibreglass, single, Lo-Tsol Low-e)	eave 700 mm, 0 mm above head of window or glazed door	2-4 m high, 8-12 m away

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<b>Hot water</b>			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric instantaneous.	✓	✓	✓
<b>Cooling system</b>			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: ceiling fans; Energy rating: n/a		✓	✓
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: ceiling fans; Energy rating: n/a		✓	✓
<b>Heating system</b>			
The living areas must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		✓	✓
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		✓	✓
<b>Ventilation</b>			
The applicant must install the following exhaust systems in the development: At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
<b>Natural lighting</b>			
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.	✓	✓	✓
<b>Alternative energy</b>			
The applicant must install a photovoltaic system with the capacity to generate at least 1.5 peak kilowatts of electricity as part of the development. The applicant must connect this system to the development's electrical system.	✓	✓	✓
<b>Other</b>			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		✓	





Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		✓	
The applicant must install a fixed outdoor clothes drying line as part of the development.		✓	

## Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.