

BASIX[®]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 957201S_08

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

This certificate is a revision of certificate number 957201S_05 lodged with the consent authority or certifier on 30 November 2018 with application DA2019/1905.

It is the responsibility of the applicant to verify with the consent authority that the original, or any revised certificate, complies with the requirements of Schedule 1 Clause 2A, 4A or 6A of the Environmental Planning and Assessment Regulation 2000

Secretary

Date of issue: Tuesday, 27 October 2020

To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning,
Industry &
Environment

Project summary

Project name	01416 Shanahan_08
Street address	145 Crescent Road Newport 2106
Local Government Area	Northern Beaches Council
Plan type and plan number	deposited 1229229
Lot no.	1
Section no.	-
Project type	separate dwelling house
No. of bedrooms	4

Project score

Water	✓ 41	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 50	Target 50

Certificate Prepared by

Name / Company Name: Midcoast Design & Drafting

ABN (if applicable): 34145976034

Description of project

Project address

Project name	01416 Shanahan_08
Street address	145 Crescent Road Newport 2106
Local Government Area	Northern Beaches Council
Plan type and plan number	Deposited Plan 1229229
Lot no.	1
Section no.	-

Project type

Project type	separate dwelling house
No. of bedrooms	4




Site details

Site area (m ²)	843
Roof area (m ²)	205
Conditioned floor area (m2)	174.0
Unconditioned floor area (m2)	14.1
Total area of garden and lawn (m2)	145

Assessor details and thermal loads

Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m ² .year)	n/a
Area adjusted heating load (MJ/m ² .year)	n/a

Project score

Water	 41	Target 40
Thermal Comfort	 Pass	Target Pass
Energy	 50	Target 50

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 3 star (> 7.5 but <= 9 L/min) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 3 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 3 star in each bathroom in the development.		✓	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 2000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rain runoff from at least 100 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		✓	✓
The applicant must connect the rainwater tank to: <ul style="list-style-type: none"> all toilets in the development the cold water tap that supplies each clothes washer in the development at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		✓ ✓ ✓	✓ ✓ ✓

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground, 37 square metres	nil	
floor - above habitable rooms or mezzanine, 78 square metres, concrete	nil	
floor - suspended floor above garage, concrete	nil	
external wall - framed (weatherboard, fibre cement, metal clad)	2.00 (or 2.40 including construction)	
external wall - concrete panel/plasterboard (concrete: 155 mm)	2.08 (or 2.40 including construction)	
ceiling and roof - flat ceiling / pitched roof	ceiling: 4.5 (up), roof: foil/sarking	unventilated; medium (solar absorptance 0.475-0.70)

Note	• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
<p>The following requirements must also be satisfied in relation to each window and glazed door:</p> <ul style="list-style-type: none"> For the following glass and frame types, the certifier check can be performed by visual inspection. <ul style="list-style-type: none"> Aluminium single clear Aluminium double (air) clear Timber/uPVC/fibreglass single clear Timber/uPVC/fibreglass double (air) clear Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column. 	✓	✓	✓ ✓
	✓	✓	✓

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
North facing					
W110	1200	2400	aluminium, single, clear	eave 750 mm, 400 mm above head of window or glazed door	not overshadowed
W111	2100	3600	aluminium, single, clear	eave 3000 mm, 750 mm above head of window or glazed door	not overshadowed
W112	1200	1800	aluminium, single, clear	eave 3000 mm, 750 mm above head of window or glazed door	not overshadowed
W113	1200	1800	aluminium, single, clear	eave 750 mm, 400 mm above head of window or glazed door	not overshadowed
East facing					
W08	1000	1500	aluminium, single, clear	none	>4 m high, 2-5 m away

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
W106	600	1200	aluminium, single, clear	eave 750 mm, 400 mm above head of window or glazed door	>4 m high, 2-5 m away
W107	1000	1500	aluminium, single, clear	eave 750 mm, 400 mm above head of window or glazed door	>4 m high, 2-5 m away
W108	1000	1500	aluminium, single, clear	eave 750 mm, 400 mm above head of window or glazed door	>4 m high, 2-5 m away
W109	1200	2400	aluminium, single, clear	eave 750 mm, 400 mm above head of window or glazed door	>4 m high, 2-5 m away
South facing					
W03	2000	900	aluminium, single, clear	solid overhang 800 mm, 500 mm above head of window or glazed door	not overshadowed
W04	2100	1800	aluminium, single, clear	solid overhang 800 mm, 500 mm above head of window or glazed door	not overshadowed
W05	600	1800	aluminium, single, clear	solid overhang 800 mm, 500 mm above head of window or glazed door	not overshadowed
W06	2100	1800	aluminium, single, clear	solid overhang 800 mm, 500 mm above head of window or glazed door	not overshadowed
W07	2000	900	aluminium, single, clear	solid overhang 800 mm, 500 mm above head of window or glazed door	not overshadowed
W102	2100	900	aluminium, single, clear	eave 1400 mm, 400 mm above head of window or glazed door	not overshadowed
W103	2100	1800	aluminium, single, clear	eave 1400 mm, 400 mm above head of window or glazed door	not overshadowed
W104	2100	4800	aluminium, single, clear	eave 4350 mm, 400 mm above head of window or glazed door	not overshadowed
W105	1800	600	aluminium, single, clear	eave 750 mm, 400 mm above head of window or glazed door	not overshadowed
West facing					


Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
W01	1200	2100	aluminium, single, clear	none	>4 m high, 5-8 m away
W02	600	2100	aluminium, single, clear	none	>4 m high, 5-8 m away
W114	2000	600	aluminium, single, clear	eave 750 mm, 400 mm above head of window or glazed door	>4 m high, 5-8 m away
W115	600	1500	aluminium, single, clear	eave 750 mm, 400 mm above head of window or glazed door	>4 m high, 5-8 m away
W101	600	2100	aluminium, single, clear	eave 750 mm, 400 mm above head of window or glazed door	>4 m high, 5-8 m away

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 5 stars.	✓	✓	✓
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: ceiling fans + 1-phase airconditioning; Energy rating: 3 star (average zone)		✓	✓
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: ceiling fans; Energy rating: n/a		✓	✓
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 3 star (average zone)		✓	✓
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		✓	✓
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: no mechanical ventilation (ie. natural); Operation control: n/a		✓	✓
Kitchen: no mechanical ventilation (ie. natural); Operation control: n/a		✓	✓
Laundry: natural ventilation only, or no laundry; Operation control: n/a		✓	✓
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
• at least 4 of the bedrooms / study; dedicated		✓	✓
• at least 3 of the living / dining rooms; dedicated		✓	✓
• the kitchen; dedicated		✓	✓


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	✓	✓	✓
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.	✓	✓	✓
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		✓	
The applicant must install a fixed outdoor clothes drying line as part of the development.		✓	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.