154,31 NS

-\$150 UPVC ELEVATED ALONG THE WAID3'

30.665

03'

600 X 600 INSPECTION OPENING

LYSAGHT TRASH SCREEN MAXIMESH

RH3030 OR EQUIVALENT HOT DIP

GALVANISED

WITH GALVANISED GRATE HINGED TO FRAME

ELEVATED ALONG THE WALL

Ø150 uPVC

Ø150 UPVC DUTLETY

 $^-$ ELEeeATED AL $_{
m ONG}$ THE WALL

-RHS (GALV.)

450×450 PIT

BENCH MARKS

RL 155.83 (AHD)

200 RC BLOCK WALL -

S12 @ 400 C/S VERTICAL-

S12 @ 400 C/S HORIZONTAL

SEDIMENT FENCE DETAIL

NAIL IN KERB 🛦 🗞

RA

TO EXISTING KERB & GUTTER

ELEVATED ALONG THE WALL

EXTENDED

DRIVEWAY

SL82 TOP

OSD TANK 5.0 X 3.0 X 1.0 = 15 m3

S12 @ 200 C/S BOTH WAYS

TEMPORARY CONSTRUCTION EXIT

155.89 NS

1.0 BONDECK (GALV.)

150 THICK SLAB

THIS DESIGN AND PRINT IS THE PROPERTY OF TED BENNETT AND MUST NOT BE USED, REPRODUCED OR COPIED WITHOUT WRITTEN PERMISSION FROM TED BENNETT.

152.81 DRN

Ø150 uPVC

-ELEVATED ALONG THE WALL

#LEVATED ALONG THE WALL

S.S. PLATE

ORIFICE PLATE DETAIL

HYDRAULIC NOTES

- H.1 ALL SERVICES ARE TO BE LOCATED IN THE FIELD IN CONJUNCTION WITH A RESPONSIBLE OFFICER OF EACH RELEVANT AUTHORITY PRIOR TO COMMENCEMENT OF CONSTRUCTION.
- H.2 DRAINAGE PITS ARE TO BE 450 mm SQUARE OR LARGER AND FITTED WITH A GALVANISED GRATE.
- H.3 DRAINAGE PIPE SIZES ARE \$\phi\$100 mm UNLESS NOTED.
- H.4 DRAINAGE PIPES SHALL BE SEWER GRADE PVC UNLESS NOTED.
- H.5 ALL BARE SOIL AREAS ARE TO BE PROTECTED FROM EROSION BY TEMPORARY MEASURES AND RE-VEGETATED AT CESSATION OF CONSTRUCTION.
- H.6 A SEDIMENT CATCHMENT POND IS TO BE PROVIDED AT THE RATE OF 120 m3 CAPACITY PER HECTARE DRAINED. THE DETENTION TANKS MAY BE USED FOR THIS PURPOSE, PROVIDED SUFFICIENT WATER IS RETAINED AS A POOL DURING CONSTRUCTION & ADEQUATE SAFETY FENCING IS PROVIDED.
- H.7 THE DOWNHILL BOUNDARY OF THE SITE IS TO BE PROTECTED BY HAY BALE OR FILTER FABRIC FENCE DURING CONSTRUCTION AS SHOWN IN ATTACHED DETAIL.
- H.8 THE STREET DRAINAGE PIT LOCATED DOWNHILL OF THE SITE SHALL BE PROTECTED FROM SEDIMENT WITH HAY BALES.
- H.9 A SINGLE CONSTRUCTION ENTRANCE SHALL BE ESTABLISHED IN THE MANNER SHOWN IN ATTACHED
- H.10 ALL EROSION PROTECTION MEASURES TO MEET THE REQUIREMENTS OF THE DEPT. OF CONSERVATION AND LAND MANAGEMENT AS OUTLINED IN 'URBAN EROSION & SEDIMENT CONTROL', SCS TECH. HANDBOOK No.2 1978 UNLESS SPECIFIED BY COUNCIL.


PIPE MAXIMUM FLOW	TABLE (BASED (ON Q = 0.065ETA &	MANNINGS $n = 0.012$)

FRICTION	100 mm PVC		150 mm PVC		225 mm PVC	
SLOPE (%)	Q (l/s)	EIA (m2)	Q (l/s)	EIA (m2)	Q (l/s)	El/
1.	5.6	85	16.5	260	48.6	75
2.	7.9	120	23.3	360	68.7	100
3.	9.7	150	28.6	440	84.2	130
4.	11.2	175	33.0	510	97.2	150
5.	12.5	190	36.9	570	109	168
10.	17.7	240	52.2	810	154	23

EIA = EQUIVALENT IMPERVIOUS AREA

SPECIAL NOTES

- 1. ALL PIPES TO BE LAID ON 75 mm SAND BED WITH THE BARRELS FULLY SUPPORTED ("B" CLASS BEDDING) PROVIDE "CLEANING EYES" TO ALL DOWN PIPES NOT DIRECTLY CONNECTED TO PITS.
- "HEAVY DUTY" GRATES AND COVERS ARE TO BE PROVIDED IN TRAFFICABLE AREAS.
- 4. THE SUMP IN THE DETENTION TANK SHALL BE DELETED. 5. ORIFICE PLATES USED TO RESTRICT THE OUTFLOW MUST BE MACHINED TO THE EXACT DIMENSION
- AS CALCULATED, FROM MINIMUM 3 mm THICK STAINLESS STEEL OR 3 mm THICK GALVANISED STEEL AFTER MACHINING. THEY MUST BE CAST IN THE PIT WALLS OR PERMANENTLY FIXED IN THE PIT BY SOME APPROVED METHOD SO THEY CANNOT BE EASILY REMOVED.
- 6. A PLAQUE MEASURING NO LESS THAN 400 mm X 200 mm SHALL BE IN SOME WAY PERMANENTLY ATTACHED AND PROMINENTLY DISPLAYED WITHIN THE IMMEDIATE VICINITY OF THE OSD DEVISE. THIS PLAQUE SHALL ADVISE OCCUPIERS OF THE PROPERTY OF THE EXISTENCE OF THE OSD DEVISE AND ALSO THAT THE DEVISE IS NOT IN ANY WAY TO BE TAMPERED WITH OR CHANGED WITHOUT PRIOR WTITTEN CONSENT OF COUNCIL.
- 7. THE CONSTRUCTED OSD INSTALLATION MUST BE APPROPRIATELY CERTIFIED BY A SUITABLY QUALIFIED AND EXPERIENCED CONSULTING ENGINEER (GENERALLY CP ENG. QUALIFICATION) WHO MUST STATE THAT IT COMPLIES WITH COUNCIL'S OSD POLICY, ALL RELEVANT CODES AND STANDARDS AND ALSO THAT IT IS GENERALLY IN ACCORDANCE WITH APPROVED PLANS.
- 8. UPON COMPLETION OF THE OSD WORKS, WORK-AS-EXECUTED (WAE) PLANS SHALL BE SUBMITTED TO THE COUNCIL BY THE CONSULTING ENGINEER/REGISTERED SURVEYOR TO VERIFY THAT THE VOLUME OF STORAGE HAS BEEN ATTAINED AND THAT CRITICAL WATER AND FLOOR LEVELS ARE IN ACCORDANCE WITH DESIGN REQUIREMENTS. ANY CHANGES OR VARIATIONS TO THE APPROVED PLANS SHALL BE
- 9. CERTIFICATION ON THE STANDARD FORM FOR ON-SITE DETENTION RECORD OF INSTALLATION ISSUED BY COUNCIL AND WAE PLANS SHALL BE SUBMITTED TOGETHER WITH THE COMPLIANCE CERTIFICATE.



SITE PARAMETERS	
SITE AREA	556.4 m2
EXISTING IMPERVIOUS AREA	233.52 m2
NEW IMPERVIOUS AREA	333.6 m2
ZONE	2
SLOPE	20%
REQUIRED VOLUME	14 m3
PROVIDED VOLUME	15 m3
ORIFICE DIAMETER	110 mm
1 YEAR POST DEV DISCHARGE	8 L/S
100 YEAR POST DEV DISCHARGE	22 L/S

SITE PARAMETERS	
SITE AREA	556.4 m2
EXISTING IMPERVIOUS AREA	233.52 m2
NEW IMPERVIOUS AREA	333.6 m2
ZONE	2
SLOPE	20%
REQUIRED VOLUME	14 m3
PROVIDED VOLUME	15 m3
ORIFICE DIAMETER	110 mm
1 YEAR POST DEV DISCHARGE	8 L/S
100 YEAR POST DEV DISCHARGE	22 L/S

SITE PARAMETER 1:50

TYPICAL SECTION THRU OSD TANK 600×600 INSPECTION OPENING ROUND HOLE Ø120 mm SQUARE MACHINE CUT

SCREEN DETAIL

600×600 INSPECTION OPENING 150 THICK BONDEK SLAB 1.0 BONDEK (GALV.) SL82 TOP EXTRA DIRECTION OF BONDECK

TANK $5.0 \times 3.0 \times 1.2 = 15m3$

PLAN ON TANK

GENERAL NOTES

- THESE NOTES SHALL BE READ IN CONJUNCTION WITH ALL ARCHITECTURAL AND OTHER CONSULTANTS DRAWINGS AND SPECIFICATIONS AND WITH SUCH OTHER WRITTEN INSTRUCTION AS ISSUED DURING THE COURSE OF THE CONTRACT. ALL DISCREPANCIES SHALL BE REFERED TO THE ARCHITECT OR ENGINEER BEFORE PROCEEDING WITH THE WORK.
- DIMENSIONS SHALL NOT BE OBTAINED BY SCALING THE STRUCTURAL DRAWINGS.
- G.3 SETTING OUT DIMENSIONS SHOWN ON THE DRAWINGS SHALL BE VERIFIED BY ON-SITE MEASUREMENT.
- DURING CONSTRUCTION THE STRUCTURE SHALL BE MAINTAINED IN A STABLE CONDITION AND NO PART SHALL BE OVERSTRESSED.
- G.5 ALL WORKMANSHIP AND MATERIALS SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF THE CURRENT EDITIONS OF THE SAA CODE AND THE BY-LAWS AND ORDINANCES OF THE RELATIVE
- BUILDING AUTHORITY. EXCAVATIONS SHALL NOT BE PERMITTED WITHIN 2 METRES OF AN EXISTING STRUCTURE WITHOUT
- PRIOR APPROVAL OR RECOMMENDATIONS FOR SHORING OR UNDERPINNING PROVIDED BY ENGINEER.
- FOOTINGS HAVE BEEN DESIGNED FOR AN ALLOWABLE INTENSITY OF BEARING PRESSURE OF 150kPa. THE BUILDER SHALL OBTAIN APPROVAL OF THE FOUNDATION MATERIAL BEFORE PLACING CONCRETE.
- F.2 FOOTINGS SHALL BE PLACED UNDER WALLS AND COLUMNS UNLESS OTHERWISE NOTED.

ALL WORKMANSHIP AND MATERIALS SHALL BE IN ACCORDANCE WITH AS 3600.

SG.1 UNDER ALL SLABS ON GRADE, WHETHER ON CUT OR FILL. REMOVE SOFT SPOTS AND REFILL BY COMPACTING CUT SURFACES OR FILL SURFACES IN LAYERS NOT EXCEEDING 200 mm TO 95%

CONCRETE WORK

DRY DENSITY, ENSURING MINIMUM SETTLEMENT TO SLABS.

CONCRETE QUALITY SHALL BE AS TABULATED AND SHALL BE VERIFIED BY TESTS.

LEMENT	SLUMP	MAX. SIZE AGG.	CEMENT TYPE	ADMIXTURE	mPa CONCRETE GRADE
ALL	80	20	A	NIL	32

C.3 CLEAR CONCRETE COVERS TO REINFORCEMENT SHALL BE AS FOLLOWS UNLESS OTHERWISE SHOWN.

CAST IN FOR			
ELEMENT	CONDITION 1 NOT TO BE EXPOSED TO WEATHER GROUND WATER OR FRESH WATER	CONDITION 2 TO BE EXPOSED TO WEATHER GROUND WATER OR FRESH WATER	CONDITION 3 CAST AGAINST OTHER FORMWORK OR THE GROUND
PAD FOOTINGS & PILE CAPS	-	65	75
STRIP FOOTINGS	-	50	65
SORE OR CAST PIERS	-	50	75
COLUMNS	40	50	75
WALLS, INCLUDING RETAINING WALLS	20	30	65
BEAMS	25	40	65
SLABS, INCLUDING JOISTS & HOLLOW BLOCK CONSTRUCTION	20	30	65
REINFORCEMENT ADJACENT TO HOLLOW BLOCKS INTEGRAL WITH STRUCTURE	5	-	-

- NOTE: 1. SLABS POURED OVER A MEMBRANE ON THE GROUND ARE INCLUDED AS CONDITION 2. 2. SLABS EXPOSED TO CORROSIVE VAPOURS, CORROSIVE GROUND WATER, SEA WATER OR SPRAY ARE TO HAVE REINFORCEMENT COVER AS NOTED OR NOT LESS THAN AS REQUIRED FOR CONDITION 3.
- C.4 SIZES OF ELEMENTS DO NOT INCLUDE THICKNESS OF APPLIED FINISHES.
- C.5 CONSTRUCTION JOINTS WHERE NOT SHOWN SHALL BE TO THE APPROVAL OF THE ENGINEER.
- C.6 BEAM DEPTHS ARE WRITTEN FIRST AND INCLUDE SLAB THICKNESS, IF ANY, UNO. NO HOLES OR CHASES OTHER THAN THOSE SHOWN ON THE STRUCTURAL DRAWINGS SHALL BE
- MADE IN CONCRETE ELEMENTS WITHOUT PRIOR APPROVAL OF THE ENGINEER. REINFORCEMENT IS REPRESENTED DIAGRAMATICALLY. IT IS NOT NECESSARLY SHOWN IN TRUE
- SPLICES IN REINFORCEMENT MADE IN POSITIONS OTHER THAN SHOWN SHALL BE TO THE APPROVAL
- OF THE ENGINEER. WHERE THE LAP LENGTH IS NOT SHOWN IT SHALL BE SUFFICIENT TO DEVELOP THE FULL STRENGTH OF THE REINFORCEMENT.
- WELDING OF REINFORCEMENT SHALL NOT BE PERMITTED UNLESS SHOWN ON THE STRUCTURAL
- C.11 PIPES OR CONDUITS SHALL NOT BE PLACED WITHIN THE CONCRETE COVER TO REINFORCEMENT WITHOUT THE APPROVAL OF THE ENGINEER.
- C.12 ALL REINFORCING BARS SHALL COMPLY WITH AS 1302. ALL FABRIC SHALL COMPLY WITH AS 1303 AND AS 1304 AND SHALL BE SUPPLIED IN FLAT SHEETS.
- REINFORCING SYMBOLS
- S GRADE 230S DEFORMED BAR C GRADE 410C COLD WORKED DEFORMED BAR
- Y GRADE 410R DEFORMED BAR R GRADE 230R PLAIN BAR
- F GRADE 450 WELDED WIRE FABRIC N GRADE 500 DEFORMED BAR
- THE NUMBER IMMEDIATELY FOLLOWING THESE SYMBOLS IS THE BAR DIAMETER IN MILLIMETRES FABRIC REINFORCEMENTTO BE LAPPED 300 MINIMUM AT ENDS AND SIDES UNO. LAPS IN
- POSITION OF MAXIMUM MOMENTARE NOT PERMITTED. ALL REINFORCEMENT SHALL BE FULLY SUPORTED ON INSULATED STEEL, PLASTIC OR CONCRETE
- CHAIRS SPACED AT 900 AND 750 CENTRES BOTH WAYS UNDER ROD AND FABRIC REINFORCEMENT RESPECTIVELY. RODS SHALL BE TIED AT ALTERNATE INTERSECTIONS.
- C.16 MINIMUM STRIPPING TIMES FOR FORMWORK SHALL BE AS RECOMMENDED IN AS 1509 OR AS DIRECTED BY ENGINEER.

CIVIL & STRUCTURAL ENGINEERING DESIGN SERVICES PTY. LTD. ACN. 051 307 852

CONSULTING STRUCTURAL, CIVIL, GEOTECHNICAL & ENVIRONMENTAL ENGINEERS

3 Wanniti Road BELRUSE 2085

PHONE 61-02 9975 3899 FAX 61-02 9975 1943 MOBILE 0407 753 899 EMAIL hited@bigpond.net.au

CLIENT: CARRY & HELEN SOCRATES PROJECT: STORMWATER MANAGEMENT PLAN FOR NEW DWELLING STRUCTURE AT 10 POULTON PARADE, FRENCHS FOREST

Drawi	n By:				Scale:	
		SD			AS SHOWN	
Checked	d By:				Drawing No.:	
E. 1	Α.	BENNETT	M.I.E.	Aust.	S-11-266837	
Date:					Amendment	
(21	/12/2018			_	

Registered Professional Engineer 198230 Mr Edward A. Bennett

....Date 21 / 12 / 2018

MIEAust CPEng

Signature.... Register on the NPER in the Category of Civil/Environmental/Structural/Geotechnical National Professional Engineers Register