

BASIX[®]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A430010

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Wednesday, 01, September 2021

To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning,
Industry &
Environment

Description of project

Project address	
Project name	George St Avalon
Street address	101 George Street Avalon 2107
Local Government Area	Northern Beaches Council
Plan type and number	Deposited Plan 558869
Lot number	1
Section number	
Project type	
Dwelling type	Separate dwelling house
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and does not include a pool (and/or spa).

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Jeff Karskens Designer

ABN (if applicable): 22452898480

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		✓	✓
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		✓	✓
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		✓	✓
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		✓	

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
The applicant must construct the new or altered construction (floor(s), walls, and ceilings/roofs) in accordance with the specifications listed in the table below, except that a) additional insulation is not required where the area of new construction is less than 2m ² , b) insulation specified is not required for parts of altered construction where insulation already exists.			✓	✓	✓
Construction	Additional insulation required (R-value)	Other specifications			
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				

Glazing requirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows and glazed doors								
<p>The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.</p> <p>The following requirements must also be satisfied in relation to each window and glazed door:</p> <p>Each window or glazed door with improved frames, or pyrolytic low-e glass, or clear/air gap/clear glazing, or toned/air gap/clear glazing must have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. The description is provided for information only. Alternative systems with complying U-value and SHGC may be substituted.</p> <p>For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.</p> <p>Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.</p> <p>Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.</p> <p>Pergolas with adjustable shading may have adjustable blades or removable shade cloth (not less than 80% shading ratio). Adjustable blades must overlap in plan view.</p>						✓	✓	✓
Windows and glazed doors glazing requirements								
Window / door no.	Orientation	Area of glass inc. frame (m ²)	Overshadowing		Shading device	Frame and glass type		
			Height (m)	Distance (m)				
AD1	NE	4.2	0	0	pergola (adjustable shade) >=900 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)	✓	✓
AD2	N	8.9	0	0	eave/verandah/pergola/balcony >=900 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)	✓	✓
AD3	SE	4.2	0	0	pergola (adjustable shade) >=900 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)	✓	✓
AD4	SE	4.5	0	0	eave/verandah/pergola/balcony	improved aluminium, single toned,	✓	✓

Glazing requirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Window / door no.	Orientation	Area of glass inc. frame (m ²)	Overshadowing		Shading device	Frame and glass type		
			Height (m)	Distance (m)				
					>=750 mm	(U-value: 6.39, SHGC: 0.56)		
AD5	SW	6.4	0	0	eave/verandah/ pergola/balcony >=750 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AD6	SW	1.8	0	0	eave/verandah/ pergola/balcony >=750 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AD7	NE	7	0	0	pergola (adjustable shade) >=900 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AD8	NE	12.4	0	0	pergola (adjustable shade) >=900 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AW1	NW	1.5	0	0	eave/verandah/ pergola/balcony >=900 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AW2	NW	0.7	0	0	eave/verandah/ pergola/balcony >=450 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AW3	NW	0.7	0	0	eave/verandah/ pergola/balcony >=450 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AW4	SW	1.6	0	0	eave/verandah/ pergola/balcony >=900 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AW5	SW	0.8	0	0	eave/verandah/ pergola/balcony >=750 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AW6	SW	0.8	0	0	eave/verandah/ pergola/balcony >=750 mm	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AW7	SE	0.8	0	0	none	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AW8	SE	0.8	0	0	none	improved aluminium, single toned, (U-value: 6.39, SHGC: 0.56)		
AW9	NE	1.2	0	0	pergola (adjustable shade) >=900	improved aluminium, single toned,		

Glazing requirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Window / door no.	Orientation	Area of glass inc. frame (m ²)	Overshadowing		Shading device	Frame and glass type		
			Height (m)	Distance (m)				
					mm	(U-value: 6.39, SHGC: 0.56)		

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a "✓" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "✓" in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "✓" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.