page 1/6

BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A399004

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv

Date of issue: Monday, 30, November 2020 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project address	
Project name	55 Carefree Rd, Nth Narrabeen
Street address	55 Carefree Road North Narrabeen 2101
Local Government Area	Northern Beaches Council
Plan type and number	Deposited Plan 11547
Lot number	20
Section number	
Project type	
Project type Dwelling type	Separate dwelling house

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: GRS Building Reports

ABN (if applicable): 33 077 900 497

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Fixtures	1		
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		\checkmark	~
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		\checkmark	~
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		\checkmark	

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
	ion is not required where the area of new cons	s) in accordance with the specifications listed in struction is less than 2m2, b) insulation specified	~	~	~
Construction	Additional insulation required (R-value)	Other specifications			
suspended floor with enclosed subfloor: framed (R0.7).	R0.60 (down) (or R1.30 including construction)				
floor above existing dwelling or building.	nil				
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				
internal wall shared with garage: plasterboard (R0.36)	nil				
flat ceiling, pitched roof	ceiling: R3.00 (up), roof: foil/sarking	medium (solar absorptance 0.475 - 0.70)			

	equirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Nindows a	and glazed do	oors							
					nading devices, in accordance with r each window and glazed door.	the specifications listed in the table below.	~	 	~
The following requirements must also be satisfied in relation to each window and glazed door:							\checkmark	\checkmark	
have a U-va	alue and a Solar	Heat Gair	n Coefficie	ent (SHGC) r		d glass may either match the description, or, le below. Total system U-values and SHGCs s.		~	~
					f each eave, pergola, verandah, bal than 2400 mm above the sill.	cony or awning must be no more than 500 mm	~	\checkmark	\checkmark
Porgolas wi	ith nalvoarhanat	o roof or c	imilar trar	slucent mate	erial must have a shading coefficien	t of less than 0.35.		~	\checkmark
r ergulas Wi	iin polycarbonaii			loidoont mate	0			_	
U					C C	situated when fully drawn or closed.		~	\checkmark
External lou Pergolas wi shades a pe	ivres and blinds ith fixed battens erpendicular win	must fully must have dow. The	shade th battens spacing b	e window or parallel to the petween batte	glazed door beside which they are s e window or glazed door above whi ens must not be more than 50 mm.		-	х х	~
External lou Pergolas wi shades a pe Windows	uvres and blinds ith fixed battens erpendicular win and glazed	must fully must have dow. The doors g	shade th battens spacing b lazing r	e window or parallel to the etween batte equireme l	glazed door beside which they are s e window or glazed door above whi ens must not be more than 50 mm. nts	situated when fully drawn or closed. ch they are situated, unless the pergola also		х х	<i>×</i> <i>×</i>
External lou Pergolas wi shades a pe Windows Window / d	ivres and blinds ith fixed battens erpendicular win	must fully must have dow. The doors g	shade th battens spacing b lazing r	e window or parallel to the etween batte equireme l	glazed door beside which they are s e window or glazed door above whi ens must not be more than 50 mm.	situated when fully drawn or closed.			~
External lou Pergolas wi shades a pe Windows Window / de no.	uvres and blinds ith fixed battens erpendicular win and glazed	must fully must have dow. The doors g Area of glass inc. frame	shade the battens spacing be battens spacing be battens spacing be backet by the backet backet be backet by the backet	e window or parallel to the etween batte equiremen adowing Distance	glazed door beside which they are s e window or glazed door above whi ens must not be more than 50 mm. nts	situated when fully drawn or closed. ch they are situated, unless the pergola also			~
External lou Pergolas wir shades a pe Windows Window / de no.	avres and blinds ith fixed battens erpendicular win and glazed loor Orientation	must fully must have dow. The doors g Area of glass inc. frame (m2)	shade the battens spacing b lazing r Oversha Height (m)	e window or parallel to the etween batte equireme adowing Distance (m)	glazed door beside which they are see window or glazed door above which they are see window or glazed door above which are smust not be more than 50 mm.	situated when fully drawn or closed. ch they are situated, unless the pergola also Frame and glass type timber or uPVC, single clear, (or U-value:			~
External lou Pergolas wir shades a pe Windows Window / da no. W1	ith fixed battens erpendicular win and glazed loor Orientation	must fully must have dow. The doors g Area of glass inc. frame (m2) 0.735	shade the battens spacing b lazing r Oversha Height (m) 0	e window or parallel to the between batte equireme adowing Distance (m) 0	glazed door beside which they are see window or glazed door above which smust not be more than 50 mm. nts Shading device eave/verandah/pergola/balcony >=900 mm eave/verandah/pergola/balcony	situated when fully drawn or closed. ch they are situated, unless the pergola also Frame and glass type timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66) timber or uPVC, single clear, (or U-value:			~
External lou Pergolas wi shades a pe Windows	ith fixed battens erpendicular win and glazed loor Orientation	must fully must have dow. The doors g Area of glass inc. frame (m2) 0.735	shade the battens spacing b lazing r Oversha Height (m) 0	e window or parallel to the between batte adowing Distance (m) 0	glazed door beside which they are see window or glazed door above while ens must not be more than 50 mm. nts Shading device eave/verandah/pergola/balcony >=900 mm eave/verandah/pergola/balcony >=900 mm	situated when fully drawn or closed. ch they are situated, unless the pergola also Frame and glass type timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66) timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66) timber or uPVC, single clear, (or U-value:			× ×

Glazing requirements								Show on CC/CDC Plans & specs	Certifier Check
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	dowing Distance (m)	Shading device	Frame and glass type			
						5.71, SHGC: 0.66)			
W8	S	7.98	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
D1	N	1.72	0	0	eave/verandah/pergola/balcony >=900 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
D2	S	14.28	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
D3	E	5.04	0	0	external louvre/blind (adjustable)	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.