


Hydrogeology Assessment and Groundwater Dewatering Management Plan

1-3 Gondola Road, North Narrabeen, NSW



Final Report

P2310036JR05V01

August 2024

Prepared For Brett Crowther

Project Details

Report Title	Hydrogeology Assessment and Groundwater Dewatering Management Plan: 1-3 Gondola Road, North Narrabeen, NSW
Client	Brett Crowther
Document	P2310036JR05V01
Director	Daniel Martens
Manager	Gray Taylor
Principal Author	Trystan Richards

Document History

Issue	Issue Date	Status	Description / Comment	Author	Reviewer	Approved
1	12/08/2024	Final	For development application	TR	BM	GT

© Copyright Martens & Associates Pty Ltd
 Suite 201, 20 George St, Hornsby, NSW 2077, Australia
 ACN 070 240 890 ABN 85 070 240 890
 P +61-2-9476-9999 | mail@martens.com.au | www.martens.com.au

Copyright Statement

Martens & Associates Pty Ltd (Publisher) is the owner of the copyright subsisting in this publication. Other than as permitted by the Copyright Act and as outlined in the Terms of Engagement, no part of this report may be reprinted or reproduced or used in any form, copied or transmitted, by any electronic, mechanical, or by other means, now known or hereafter invented (including microcopying, photocopying, recording, recording tape or through electronic information storage and retrieval systems or otherwise), without the prior written permission of Martens & Associates Pty Ltd. Legal action will be taken against any breach of its copyright. This report is available only as book form unless specifically distributed by Martens & Associates in electronic form. No part of it is authorised to be copied, sold, distributed or offered in any other form.

Contents

1	Introduction	6
1.1	Overview	6
1.2	Proposed Development.....	6
1.2.1	Overview	6
1.2.2	Basement Extent	6
1.3	Scope.....	6
1.3.1	Hydrogeological Assessment (HA).....	6
1.3.2	Groundwater Dewatering Management Plan (GDMP).....	7
1.4	Other Assessments	7
2	Hydrogeological Assessment	8
2.1	Site Details.....	8
2.2	Fieldworks	8
2.2.1	Well Installation and Development	8
2.2.2	Collection of Groundwater Samples	9
2.3	Groundwater Monitoring	9
2.3.1	Monitoring Methodology.....	9
2.3.2	Monitoring Results.....	9
2.4	Groundwater Quality Testing.....	11
2.4.1	Testing Methodology	11
2.4.2	Testing Results.....	11
2.5	Hydraulic Conductivity.....	12
3	Groundwater Dewatering Management Plan	13
3.1	Collection of Groundwater.....	13
3.2	Anticipated Extent of Groundwater Interception.....	13
3.3	Dewatering Volume.....	14
3.4	Anticipated Offsite Impacts.....	15
3.5	Dewatering Management.....	15
3.5.1	Treatment Requirements	15
3.5.2	Licensing Requirements	16
3.5.3	Monitoring Requirements	16
3.6	Comments	16
4	References	17
	Appendix A – Mapset	18
	Appendix B – Site Survey and Architectural Plans	20
	Appendix C – Borehole Logs.....	33
	Appendix D – Dewatering Modelling.....	40

Appendix F - Laboratory Summary Table	42
Appendix G - Laboratory Analytical Documentation	49

Tables

Table 1: Site detail summary.	8
Table 2: 'Dip' groundwater measurement summary.	9
Table 3: Monitoring data summary (7/03/2024 – 5/07/2024).	10
Table 4: Summary of pH, EC and Cl results.	11

Figures

Figure 1: Plot of groundwater level data.	10
Figure 2: Expected mean groundwater level.	14

1 Introduction

1.1 Overview

This report documents a Hydrogeology Assessment (**HA**) and Groundwater Dewatering Management Plan (**GDMP**) completed by Martens and Associates Pty Ltd (**MA**) on behalf of Brett Crowther (the **Client**), for proposed new three storey mixed use development with basement carpark with bulk excavation up to approximately 1.1m AHD at 1-3 Gondola Road, North Narrabeen, NSW (the **Site**).

This report has been prepared to support a development application (**DA**) to Northern Beach Council (**NBC**).

1.2 Proposed Development

1.2.1 Overview

MA understands from provided architectural plans that the development will include construction of a new three storey mixed-use building. The development will include one level of basement carpark with bulk excavation to approximately 1.1 m AHD with a lift well base level of approximately -0.1 m AHD.

1.2.2 Basement Extent

The proposal includes a single level basement with a finished floor level of 1.4 m AHD, equivalent to a bulk excavation of up to approximately 1.2 m below existing ground level (**mbgl**) to allow for a 300 mm slab to be constructed. The eastern portion of the basement contains a garage ramp from Minarto Lane, grading from a proposed level of 2 m AHD to the basement finished floor level at 1.4 m AHD. Two lifts are proposed as part of the development are expected to have lift well base levels of approximately -0.1 m AHD.

From review of preliminary structural plans provided by Mackenzie Architects International the ultimate basement construction is to include an OSD. Final structural details and methodology of OSD will be provided by the project structural engineer at the detailed design stage.

Development plans and the approximate extent of the proposed basement is shown in Appendix B.

1.3 Scope

1.3.1 Hydrogeological Assessment (HA)

The scope of the HA is noted as:

1. Undertake a desktop review of available site information including topography, geology, soil landscape and acid sulfate soils (**ASS**) risk.

2. Site inspection to assess the serviceability and condition of existing monitoring well (**MW01**).
3. Installation of one groundwater monitoring well (**MW02**) in conjunction with a geotechnical investigation.
4. Purging and development of installed monitoring wells approximately one week following Site inspection.
5. Collection of one groundwater sample from each monitoring well and subsequent laboratory analysis to assess groundwater quality.
6. Assessment of aquifer permeability characteristics through the completion of slug tests.
7. Manual measurement of groundwater levels in each monitoring well using an electronic dip meter, and monitoring of groundwater level using a data logger for a period of approximately one month.

1.3.2 Groundwater Dewatering Management Plan (GDMP)

The scope of the GDMP is as follows:

1. Assessment of anticipated groundwater interception by the proposed development
2. Calculation of predicted groundwater infiltration rates and dewatering volumes during basement and lift well construction (based on assumed timeframes).
3. Provide a monitoring plan for the duration of the construction dewatering in accordance with current Water NSW requirements.

1.4 Other Assessments

The following relevant assessments have been completed by MA for the Site:

- a. *Geotechnical, Hydrogeological and Acid Sulfate Soil Assessment: 3 Gondola Road, North Narrabeen, NSW.* Report ref: P2108694JR02V03 (**MA, 2022**).
- b. *Site Contamination Assessment: 1-3 Gondola Road, North Narrabeen NSW.* Report ref P2310036JR01V01 (**MA, 2024a**).
- c. *Geotechnical And Acid Sulfate Soil Assessment: 1 – 3 Gondola Road, North Narrabeen, NSW.* Report ref P2310036JR02V01 (**MA, 2024b**).
- d. *Acid Sulfate Management Plan: 1 – 3 Gondola Road, North Narrabeen, NSW.* Report ref P2310036JR04V01 (**MA, 2024c**).

Where required in this report, reference has been made to the findings of the above reports.

2 Hydrogeological Assessment

2.1 Site Details

A summary of Site details is provided in Table 1, with site locality plan provided in Appendix A.

Table 1: Site detail summary.

Item	Description
Site address	1-3 Gondola Road, North Narrabeen, NSW
Legal identifier	Lot 187 and 188 DP 16719 (Six Maps)
Surveyed area	1289.3 m ² (C & A Surveyors, 2024)
Topography	The Site is relatively flat with grades < 5%. 3 Gondola Rd elevation ranges from 5.61 mAHD in the centre to 1.95 mAHD along the northern boundary (C & A Surveyors, 2024). 1 Gondola Rd elevations range from 1.91 mAHD in the northeast corner to 2.15 mAHD at the centre of the western boundary (C & A Surveyors, 2024).
Geology	The Sydney 1:100,000 Geological Sheet 9030 (Herbert, 1983) describes site geology as silty peaty quartz sand, silt and clay. Ferruginous and humic cementation in places. Common shell layers
Soil landscape	The NSW Environment and Heritage eSPADE website identifies the site as having soils of the Warriewood landscape having soils of deep, well sorted, sandy humus podzols and dark, mottled siliceous sands, overlying buried acid peats in depressions; deep podzols and pale siliceous sands on sandy rises
Acid sulfate soils	The Pittwater Local Environment Plan 2014, Acid Sulfate Soil Map (Sheet ASS - 019), the site is located within Class 3 ASS risk

2.2 Fieldworks

2.2.1 Well Installation and Development

Site inspection and installation of groundwater wells was undertaken over two separate events on 14 July 2023 and 7 March, 2024, in conjunction with geotechnical and ASS investigations at the Site. The following works were undertaken:

- Detailed Site walkover inspection.
- Drilling of 10 boreholes (BH101 – BH102 and BH201 – BH208) to a maximum investigation depth of 10.00 mbgl.
- Installation of two groundwater monitoring wells (MW01 – MW02) at each BH201(part of previous works at 3 gondola road) and BH202, with flush mounted gatic covers.

- Development of each groundwater well.
- Installation of data logger in MW02 for continuous monitoring of groundwater levels and barometric pressure.

2.2.2 Collection of Groundwater Samples

Subsequent inspection of the Site was undertaken on 11 April 2024. The following works were undertaken:

- Manual measurement of groundwater levels in each monitoring well using an electronic dip meter.
- Field screening of groundwater quality parameters using a water quality meter at each monitoring well.
- Collection of representative groundwater samples from each monitoring well location for laboratory analysis.
- Installation of data logger in MW01 for continuous monitoring of groundwater levels.

2.3 Groundwater Monitoring

2.3.1 Monitoring Methodology

Groundwater monitoring was undertaken at MW02 between 7 March 2024 and 5 July, 2024 and MW01 between 11 April 2024 – 5 July 2024. Works undertaken included:

- Continuous monitoring using a data logger at 15 minute recording intervals.
- Manual dip meter measurements taken at the beginning and end of the continuous monitoring period.
- Efforts to perform rising and falling slug tests in each monitoring well for calculation of hydraulic conductivity (k) across the Site.

2.3.2 Monitoring Results

Dip meter measurements and continuous data logger recordings are summarised in Table 2 and Table 3 respectively, and a graphical plot of collected groundwater level data is provided in Figure 1.

Table 2: 'Dip' groundwater measurement summary.

Date	Groundwater levels			
	MW01		MW02	
	mbgl	mAHD	mbgl	mAHD
4 April, 2024	1.31	0.69	1.52	0.48

Date	Groundwater levels			
	MW01		MW02	
	mbgl	mAHD	mbgl	mAHD
11 April 2024	1.13	0.87	1.4	0.6
13 May 2024	1.15	0.85	1.45	0.55
13 June 2024	1.29	0.71	1.54	0.46
5 July 2024	1.19	0.81	1.41	0.59

Table 3: Monitoring data summary (7/03/2024 – 5/07/2024).

Monitoring Well	Surface Level (mAHD)	Groundwater Level (mbgl / mAHD)			Range (m)
		Minimum	Mean	Maximum	
MW01 ¹	2.00	-1.43 / 0.57	-1.22 / 0.78	-1.00 / 1.00	0.43
MW02	2.00	-1.78 / 0.22	-1.54 / 0.47	-1.01 / 0.99	0.78

¹ Note: MW01 was only monitored between 11 April 2024 – 5 July 2024.




Figure 1: Plot of groundwater level data.

Some amount of groundwater level variation was recorded throughout the monitoring period. Rapid groundwater level response was observed during heavy or prolonged rainfall with increases in groundwater levels closely reacting to rainfall recharge. It is noted that the monitoring period was conducted during a period of consistent and at times heavy rainfall which is likely the reason for observed groundwater level variance. During dry periods with little to no rainfall, Site groundwater levels would be expected to remain generally stable.

The groundwater gradient across the Site was observed to be relatively flat with a slight gradient to the east (noting only two monitoring wells).

2.4 Groundwater Quality Testing

2.4.1 Testing Methodology

Groundwater was sampled from each monitoring well to allow initial data assessment of groundwater quality in accordance with NSW DPIE (2022). All wells were sampled during Site inspection on 11 April, 2024.

Each well was purged using low flow peristaltic pump, with water quality parameters continually assessed through a flow cell unit until pH, EC, DO, turbidity and temperature measurements stabilised. Field screening of parameters was undertaken and groundwater samples were collected in laboratory supplied bottles with appropriate preservations.

Two groundwater samples were submitted to a NATA accredited laboratory (Envirolab Pty Ltd) and tested for the following:

- Ionic Balance (Ca, K, Mg, Na, OH, CO₃, HCO₃, total alkalinity, Cl, SO₄)
- Nutrients (N, NO_x, NH₃, P, PO₄)
- TOC
- Microbes (faecal coliforms, enterococci, E. coli)
- Hydrocarbons (BTEX, TRH, PAH)
- Physical Parameters (pH, EC, DO, SAR, TDS, TSS, turbidity)
- Heavy metals (aluminium, antimony, arsenic barium, beryllium, boron, cadmium, chromium, cobalt, copper, iron lead, lithium, manganese, mercury, molybdenum, nickel, selenium, silver, strontium, uranium, vanadium, zinc, silicon).

2.4.2 Testing Results

Laboratory results for pH, electrical conductivity (EC) and chloride (Cl) are summarised in Table 4.

Table 4: Summary of pH, EC and Cl results.

Monitoring well	pH	EC (µS / cm)	Chloride (mg / L)
MW01	7.0	12,000	3,900
MW02	7.2	2,300	420

Based on the above results, groundwater at the Site is brackish, and neutral.

Groundwater sampled for Site Contamination Assessment (MA, 2024a) were assessed against the ANZG (2018) marine water 95% guideline, based on the closest major water way from the Site being South Creek, which drains from Narrabeen Lagoon into the Pacific Ocean. To assess potential vapour risk from the adjacent service station (which may present an offsite risk to Site groundwater), results were also compared to health screening levels (**HSL**) provided in NEPM (2013). Laboratory results found concentrations of all COPC to meet the adopted testing criteria for all analytes.

All groundwater results were found to be below the adopted guideline criteria. Of note, contamination associated with services station use were reported below the laboratory detection limit.

A detailed table of results showing individual contaminant concentrations compared to adopted testing criteria is provided in Appendix E, and chain of custody documentation and laboratory certificates are provided in Appendix F.

2.5 Hydraulic Conductivity

Rising and falling head slug tests were attempted on MW01 and MW04 on 11 April and 13 May 2024. Slug tests were unable to provide reliable hydraulic conductivity (k) data for the Site. Therefore, using values taken from E. Scott Bair and Lahm, 2006 hydraulic conductivity of medium sand was estimated to be of the order 5 - 15 m / day.

3 Groundwater Dewatering Management Plan

3.1 Collection of Groundwater

Groundwater seepage into the basement excavation is expected to be collected via appropriately located spoon drains and sump(s). A submersible pump in the sump(s) shall direct water to Council stormwater provided baseline data confirmation (Section 2.4.2). During warmer / dry weather, evaporate loss may result in less groundwater being collected during construction.

3.2 Anticipated Extent of Groundwater Interception

Groundwater level data collected during the primary monitoring period (Section 2.3) indicate that the average groundwater level across the Site ranged from approximately 0.46 mAHD and 0.76 mAHD with upper bound levels in order of 0.99 mAHD and 1.00 mAHD.

Based on Site construction plans, bulk excavation for construction of the basement will be across the Site is to be taken to 1.1 mAHD, with excavation of lift wells expected to be to -0.1 mAHD. Analysis of rainfall and groundwater levels indicated bulk excavation is only expected to intercept groundwater with occurrences of high rainfall with groundwater quickly returning to Site averages in the following days (Figure 1). Excavation of lift wells is expected to intercept approximately 0.73 m into the groundwater table.

A diagram showing approximate mean groundwater elevations across the Site is provided in Figure 2.



Figure 2: Expected mean groundwater level.

3.3 Dewatering Volume

Dewatering is only expected to be required during the lift well construction works, including construction of lift wells slab and perimeter walling (including tanking). We anticipate that the dewatering timeframe will likely be in the order of one month. In light of this, we expect total construction dewatering volumes to be approximately 0.63 ML over the one month dewatering timeframe.

Groundwater dewatering volume calculations are provided in Appendix D. The following is noted:

- An inflow rate of approximately 7.52 ML / year is estimated for a maximum predicted groundwater take in the order of 0.63 ML over the dewatering timeframe of up to one month.
- Predicted volumes may depend somewhat on the rate of excavation progress and adjustment of groundwater profiles beyond the excavation as well as evaporation rates.
- Monitoring was completed following a period of significant rainfall; it is likely that actual groundwater table at the time of dewatering may be lower than predicted.

- Due to difficulties encountered during slug test attempts, hydraulic conductivity for medium sands are assumed and not Site specific.

3.4 Anticipated Offsite Impacts

Anticipated offsite impacts of groundwater dewatering have been assessed as follows:

1. Groundwater flow impacts including mounding and flow diversion are likely to be minimal given the scale of the proposed basement, local flat hydraulic gradient and the permeability of underlying sand.
2. A review of the Bureau of Meteorology (2019) *Groundwater Dependent Ecosystems Atlas* indicates that there are groundwater dependent ecosystems (GDE) within 100 m of the Site. Due to the minimal nature of the proposed dewatering and, partial cut off walls such as diaphragm walls or secant pile walls noted in MA, 2024b impact on nearby GDEs are expected to be negligible.
3. Two acid sulfate soils (ASS) assessments were undertaken for the Site and documented in MA 2022 and MA 2024b. Based on laboratory testing of Site soils, ASS indicators (acid / sulfur trails) were identified in soils collected from depths below 1.2 mbgl. Given the temporary nature of the proposed dewatering and cut off walls noted in MA 2024b, anticipated dewatering to a level of approximately - 0.1 mAHD, risk to actual or potential ASS from dewatering is considered minimal. Any material and groundwater collected during excavation and dewatering process is to be managed in accordance with Site ASS Management Plan (MA, 2024c).
4. Assessment of settlement as a result of dewatering has been documented in the geotechnical and acid sulfate soils assessment (MA, 2024b). Impacts are considered acceptable, subject to recommendations provided in MA (2024b).

3.5 Dewatering Management

3.5.1 Treatment Requirements

On the basis of the groundwater sampling undertaken (which indicates that groundwater is brackish, neutral and meets ANZG (2018) guidelines) the following options for disposal of groundwater from the dewatering process will need to be considered:

1. Discharge to stormwater.
2. Discharge of groundwater to sewer under a trade waste license.

We note resampling of all groundwater wells at the Site be taken to confirm groundwater characterisation, noting only one round of sampling has been completed to date.

3.5.2 Licensing Requirements

Under Section 92 of the Water Management Act (2000), a Water Supply Works (**WSW**) approval will be required for the construction works given the proposal will intercept the groundwater table.

As total groundwater take is expected to be less than 3 ML over dewatering timeframe of up to one month, a Water Access License (**WAL**) will not be required from WaterNSW under the Water Management Act (2000).

Applications for a WSW approval are to be submitted to WaterNSW for approval prior to construction dewatering being undertaken.

3.5.3 Monitoring Requirements

Monitoring of groundwater levels, groundwater discharge quality and groundwater take will be required to be undertaken in accordance with NSW DPIE (2022) requirements. The scope of monitoring will be contingent on the type of treatment and disposal that is implemented in light of our recommendations in Section 3.5.1. Monitoring requirements shall be included as part of the final dewatering management plan which will be required to be submitted to WaterNSW for the Water Supply Work approval.

3.6 Comments

Further works will need to be undertaken following development approval but prior to construction to meet the requirements of WaterNSW and NSW DPIE (2022) and to inform a WSW approval. This will include, but may not be limited to:




1. Appropriate monitoring and sampling of at least three monitoring wells prior to the commencement of construction works in accordance with NSW DPIE (2022) requirements.
2. Determination of baseline data.
3. Preparation of a detailed dewatering management and monitoring plan.

4 References

- Bureau of Meteorology (2019) *Groundwater Dependent Ecosystems Atlas*. <http://www.bom.gov.au/water/groundwater/gde/map.shtml>. Accessed July 2024.
- C & A Surveyors (2024) Detail & Boundary Identification Survey of Lot 187 & 188 in DP 16719, Located at No. 1-3 Gondola Road, North Narrabeen
- E. Scott Bair and Lahm, T.D. (2006). *Practical Problems in Groundwater Hydrology*. Prentice Hall.
- Herbert C (1983) Sydney 1:100 000 Geological Sheet 9130, 1st edition. Geological Survey of New South Wales, Sydney.
- Mackenzie Architects International (2024) *Multi Residential Development: 1 – 3 Gondola Rd North Narrabeen 2101*
- Martens and Associates (2022) *Geotechnical, Hydrogeological and Acid Sulfate Soil Assessment: 3 Gondola Road, North Narrabeen NSW* (ref: P2108694JR02V03).
- Martens and Associates (2024a) *Site Contamination Assessment: 1-3 Gondola Road, North Narrabeen NSW* (ref P2310036JR01V01).
- Martens and Associates (2024b) *Geotechnical and Acid Sulfate Soil Assessment: 1 – 3 Gondola Road, North Narrabeen, NSW* (ref P2310036JR02V01).
- Martens and Associates (2024c) *Acid Sulfate Management Plan: 1 – 3 Gondola Road, North Narrabeen, NSW* (ref P2310036JR04V01).
- NSW Department of Environment & Heritage (eSPADE, NSW soil and land information), www.environment.nsw.gov.au. Accessed 26/04/2024.
- NSW Department of Planning, Industry & Environment (2022) *Minimum requirements for building site groundwater investigations and reporting*. Referred to as NSW DPIE (2022)
- Water Quality Australia (2018) *Australian and New Zealand Guidelines for Fresh and Marine Water Quality*. Referred to as ANZG (2018).

Appendix A – Mapset

Legend

-  Monitoring Well Locations
-  Approximate Basement Extent
-  Site Boundary



0 6 12 18 24 30 m

Map Title / Figure:



Site Map

1:500 @ A4

Viewport A

Image: Nearmap (2024)
Data Source: ELVIS DEM

Appendix B – Site Survey and Architectural Plans





LEGEND:

AHD	AUSTRALIAN HEIGHT DATUM
AWN	AWNING
BM	BENCH MARK
BOW	BOTTOM OF WALL
BRW	BOTTOM OF RETAINING WALL
CONC	CONCRETE
CS	CONCRETE SURFACE
D/H/S	DIAMETER/HEIGHT/SPREAD
EB	EDGE OF BITUMEN
EC	EDGE OF CONCRETE
EG	EAVE & GUTTER
EP	ELECTRICAL BOX
FL	FLOOR LEVEL
HYD	HYDRANT
IC	INSPECTION COVER
INV	INVERT LEVEL
KO	KERB OUTLET
LH	LAMP HOLE
LIP	LIP OF KERB
NS	NATURAL SURFACE
PP	POWER POLE
RL	REDUCED LEVEL
RTK	ROLLING TOP OF KERB
SL	SURFACE LEVEL
SIP	SEWER INSPECTION POINT
SMH	SEWER MAN HOLE
SV	STOP VALE
TEL	TELSTRA PIT
TK	TOP OF KERB
TOW/TW	TOP OF WALL
TRW	TOP OF RETAINING WALL
VC	VEHICLE CROSSING
W-B	WALL TO BOUNDARY
WM	WATER METER

© THIS PLAN AND THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF C & A SURVEYORS NSW PTY LTD. IT MUST NOT BE COPIED IN WHOLE OR PART, AND IS NOT TO BE USED FOR ANY PURPOSE OTHER THAN FOR THAT WHICH IT HAS BEEN PREPARED, WITHOUT THE WRITTEN CONSENT OF C & A SURVEYORS NSW PTY LTD. THIS PLAN HAS BEEN PREPARED FOR THE SOLE USE OF THE INSTRUCTING PARTY.

C&A SURVEYORS
 30 Grose Street, Parramatta, NSW 2150
 Ph: 96309299 email: Operations@candasurveyors.com.au
 www.candasurveyors.com.au

DETAIL & BOUNDARY IDENTIFICATION SURVEY OF LOT 187 & 188 IN DP 16719, LOCATED AT No. 1-3, GONDOLA ROAD, NORTH NARRABEEN.



INSTRUCTING PARTY: Joseph El-Hage @ Mackenzie Architects International		SURVEYED BY: EH		DATUM: AHD	
LGA: NORTHERN BEACHES	AREA BY DP: LOT 187-645.0 m ² LOT 188-638.6 m ²	DRAWN BY: SU	CHECKED BY: KO		
SURVEY DATE: 29/02/2024	AREA BY CALC: LOT 187-650.5 m ² LOT 188-638.7 m ²	SCALE: 1:100@A1	REF NO: 31813-24 DET/ID		
DATE DRAWN: 8/03/2024	CONTOUR INTERVAL: 0.2 m	REV No: V1	SHEET: 1 OF 1		

THE SUBJECT TITLE NOTES : AS AT 28/02/2024 LOT 187 IN DP 16719
 1) RESERVATIONS AND CONDITIONS IN THE CROWN GRANT(S)
 2) D149502 COVENANT
 3) AT268282 CAVEAT BY CROWTHER INVESTMENTS (NSW) PTY LTD

THE SUBJECT TITLE NOTES : AS AT 28/02/2024 LOT 188 IN DP 16719
 1) RESERVATIONS AND CONDITIONS IN THE CROWN GRANT(S)
 2) D230687 COVENANT
 3) AP410549 LEASE TO MWP COMMUNITY AID LIMITED EXPIRES: 27/6/2022. OPTION OF RENEWAL: 2 YEARS.

NOTES:

A) BOUNDARIES OF THE SITE HAVE BEEN IDENTIFIED BY SURVEY SERVICES SHOWN HAVE BEEN DERIVED FROM VISUAL EVIDENCE APPARENT AT THE TIME OF SURVEY. SERVICES MAY EXIST WHICH ARE NOT SHOWN. THE RELEVANT SERVICE AUTHORITY SHOULD BE CONTACTED TO VERIFY THE EXISTENCE AND POSITION OF SERVICES PRIOR TO THE COMMENCEMENT OF ANY CONSTRUCTION OR EXCAVATION.

C) DIAMETER, HEIGHT & SPREAD OF TREES ARE APPROXIMATE ONLY.

D) LEVELS SHOWN ARE OF AUSTRALIAN HEIGHT DATUM. ORIGIN OF LEVELS : PM 5315, RL 1.631 (AHD), CLASS LC.



E) USE STATED DIMENSIONS. DO NOT SCALE.

F) THESE NOTES FORM PART OF THIS PLAN AND CANNOT BE REMOVED.


G) NO COVENANTS AND/OR RESTRICTIONS HAVE BEEN INVESTIGATED BY C & A SURVEYORS PTY LTD.

REVISION No	DESCRIPTION	DATE
V1	PLAN ISSUED	8/03/2024
V2
V3
V4

TRENT JAMES VELLA
 (REGISTERED SURVEYOR)
 SURVEYOR ID No. 8959



	<p>mackenzie architects international</p>	<p>736 PACIFIC HWY Gordon NSW 2072 Phone: (02) 9967 9966 Fax: (02) 9967 9977 www.mainternational.com.au info@mainternational.com.au</p>	<p>Nominated Architect No.6033 ABN 76 091 107 201 ACN 061107201</p>	<p>LEGEND DO NOT SCALE DRAWINGS VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCING WORK</p> <p>COPYRIGHT Mackenzie Architects International is the owner of the copyright subsisting in these drawings, plans, designs and specifications. They must not be used, reproduced or copied in whole or part without prior written consent of Mackenzie Architects International.</p>	<p>AMENDMENTS</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>REVISION</th> <th>BY</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>DA</td> <td>J.E</td> <td>03.04.2024</td> </tr> </tbody> </table>	No.	REVISION	BY	DATE	A	DA	J.E	03.04.2024	<p>PROJECT NORTH</p>	<p>MULTI RESIDENTIAL DEVELOPMENT PROJECT 1-3 Gondola Rd North Narrabeen 2101</p> <p>PROJECT NO. 15/19</p>	<p>DRAWING: SITE PLAN</p>	
					No.	REVISION	BY	DATE									
A	DA	J.E	03.04.2024														
<p>DRAWN BY J.E</p> <p>CHECKED BY D.M</p>	<p>SCALE: 1:200@A3</p>	<p>DRAWING NO.: A0005</p>	<p>ISSUE: A</p>														



mackenzie architects international

736 PACIFIC HWY
Gordon NSW 2072
Phone: (02) 9967 9966
Fax: (02) 9967 9977
www.mainternational.com.au
info@mainternational.com.au

WARNING
DO NOT SCALE DRAWINGS
VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCING WORK

COPYRIGHT
Mackenzie Architects International is the owner of the copyright subsisting in these drawings, plans, designs and specifications. They must not be used, reproduced or copied in whole or part without prior written consent of Mackenzie Architects International.



AMENDMENTS			
No.	REVISION	BY	DATE
A	DA	J.E	03.04.2024

PROJECT NORTH

MULTI RESIDENTIAL DEVELOPMENT
PROJECT
1-3 Gondola Rd North
Narrabeen 2101

PROJECT NO.
15/19

DRAWING: BASEMENT PLAN			
DRAWN BY	SCALE:	DRAWING NO.:	ISSUE:
J.E	1:200@A3	A1001	A
CHECKED BY			
D.M			



**mackenzie
architects
international**

736 PACIFIC HWY
Gordon NSW 2072
Phone: (02) 9967 9966
Fax: (02) 9967 9977
www.mainternational.com.au
info@mainternational.com.au

Nominated Architect No.6033
ABN 76 091 107 201
ACN 061107201

WARNING
DO NOT SCALE DRAWINGS
VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCING WORK

COPYRIGHT
Mackenzie Architects International is the owner of the copyright subsisting in these drawings, plans, designs and specifications. They must not be used, reproduced or copied in whole or part without prior written consent of Mackenzie Architects International.

AMENDMENTS

No.	REVISION	BY	DATE
A	DA	J.E	03.04.2024



PROJECT NORTH



MULTI RESIDENTIAL DEVELOPMENT
PROJECT
1-3 Gondola Rd North
Narrabeen 2101
PROJECT NO.
15/19

DRAWING:
GROUND FLOOR PLAN

DRAWN BY J.E	SCALE: 1:200@A3	DRAWING NO.: A1002	ISSUE: A
CHECKED BY D.M			




**mackenzie
architects
international**

736 PACIFIC HWY
Gordon NSW 2072
Phone: (02) 9967 9966
Fax: (02) 9967 9977
www.mainternational.com.au
info@mainternational.com.au

Nominated Architect No.6033
ABN 76 091 107 201
ACN 061107201



DO NOT SCALE DRAWINGS
VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCING WORK
COPYRIGHT
Mackenzie Architects International is the owner of the copyright subsisting in these drawings, plans, designs and specifications. They must not be used, reproduced or copied in whole or part without prior written consent of Mackenzie Architects International.

AMENDMENTS			
No.	REVISION	BY	DATE
A	DA	J.E	03.04.2024



PROJECT NORTH
MULTI RESIDENTIAL DEVELOPMENT
PROJECT
1-3 Gondola Rd North
Narrabeen 2101
PROJECT NO.
15/19

DRAWING: FIRST FLOOR PLAN			
DRAWN BY	SCALE:	DRAWING NO.:	ISSUE:
J.E	1:200@A3	A1003	A
CHECKED BY			
D.M			




**mackenzie
architects
international**

736 PACIFIC HWY
Gordon NSW 2072
Phone: (02) 9967 9966
Fax: (02) 9967 9977
www.mainternational.com.au
info@mainternational.com.au

Nominated Architect No.6033
ABN 76 091 107 201
ACN 061107201



DO NOT SCALE DRAWINGS
VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCING WORK
COPYRIGHT
Mackenzie Architects International is the owner of the copyright subsisting in these drawings, plans, designs and specifications. They must not be used, reproduced or copied in whole or part without prior written consent of Mackenzie Architects International.

AMENDMENTS			
No.	REVISION	BY	DATE
A	DA	J.E	03.04.2024





PROJECT NORTH
MULTI RESIDENTIAL DEVELOPMENT
PROJECT
1-3 Gondola Rd North
Narrabeen 2101
PROJECT NO.
15/19

DRAWING: SECOND FLOOR PLAN			
DRAWN BY J.E	SCALE: 1:200@A3	DRAWING NO.: A1004	ISSUE: A
CHECKED BY D.M			



	mackenzie architects international 736 PACIFIC HWY Gordon NSW 2072 Phone: (02) 9967 9966 Fax: (02) 9967 9977 www.mainternational.com.au info@mainternational.com.au	Nominated Architect No.6033 ABN 76 091 107 201 ACN 061107201	AMENDMENTS <table border="1"> <thead> <tr> <th>No.</th> <th>REVISION</th> <th>BY</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>DA</td> <td>J.E</td> <td>03.04.2024</td> </tr> </tbody> </table>	No.	REVISION	BY	DATE	A	DA	J.E	03.04.2024	PROJECT NORTH 	MULTI RESIDENTIAL DEVELOPMENT PROJECT 1-3 Gondola Rd North Narrabeen 2101 PROJECT NO. 15/19	DRAWING: COS FLOOR PLAN DRAWN BY J.E CHECKED BY D.M	SCALE: 1:200@A3	DRAWING NO.: A1005	ISSUE: A
				No.	REVISION	BY	DATE										
A	DA	J.E	03.04.2024														



	mackenzie architects international	736 PACIFIC HWY Gordon NSW 2072 Phone: (02) 9967 9966 Fax: (02) 9967 9977 www.mainternational.com.au info@mainternational.com.au	Nominated Architect No.6033 ABN 76 091 107 201 ACN 061107201	AMENDMENTS		PROJECT NORTH 	MULTI RESIDENTIAL DEVELOPMENT PROJECT 1-3 Gondola Rd North Narrabeen 2101 PROJECT NO. 15/19	DRAWING: ROOF PLAN				
				<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>REVISION</th> <th>BY</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>DA</td> <td>J.E</td> <td>03.04.2024</td> </tr> </tbody> </table>	No.	REVISION		BY	DATE	A	DA	J.E
No.	REVISION	BY	DATE									
A	DA	J.E	03.04.2024									



NORTH ELEVATION



EAST ELEVATION



mackenzie
architects
international

736 PACIFIC HWY
Gordon NSW 2072
Phone: (02) 9967 9966
Fax: (02) 9967 9977
www.mainternational.com.au
info@mainternational.com.au


Nominated Architect No.6033
ABN 76 091 107 201
ACN 061107201

LEGEND
DO NOT SCALE DRAWINGS
VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCING WORK
COPYRIGHT
Mackenzie Architects International is the owner of the copyright subsisting in these drawings, plans, designs and specifications. They must not be used, reproduced or copied in whole or part without prior written consent of Mackenzie Architects International.


AMENDMENTS			
No.	REVISION	BY	DATE
A	DA	J.E	03.04.2024

MULTI RESIDENTIAL DEVELOPMENT
PROJECT
1-3 Gondola Rd North
Narrabeen 2101
PROJECT NO.
15/19

DRAWING: NORTH & EAST ELEVATIONS
DRAWN BY
J.E
CHECKED BY
D.M
SCALE:
1:200@A3
DRAWING NO.:
A2001
ISSUE:
A



SOUTH ELEVATION



WEST ELEVATION



mackenzie
architects
international

736 PACIFIC HWY
Gordon NSW 2072
Phone: (02) 9967 9966
Fax: (02) 9967 9977
www.mainternational.com.au
info@mainternational.com.au


Nominated Architect No.6033
ABN 76 091 107 201
ACN 061107201

LEGEND
DO NOT SCALE DRAWINGS
VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCING WORK
COPYRIGHT
Mackenzie Architects International is the owner of the copyright subsisting in these drawings, plans, designs and specifications. They must not be used, reproduced or copied in whole or part without prior written consent of Mackenzie Architects International.


AMENDMENTS			
No.	REVISION	BY	DATE
A	DA	J,E	03.04.2024

MULTI RESIDENTIAL DEVELOPMENT
PROJECT
1-3 Gondola Rd North
Narrabeen 2101
PROJECT NO.
15/19

DRAWING: SOUTH & WEST ELEVATIONS
DRAWN BY
J.E
CHECKED BY
D.M
SCALE:
1:200@A3
DRAWING NO.:
A2002
ISSUE:
A



SECTION AA



SECTION BB



mackenzie
architects
international

736 PACIFIC HWY
Gordon NSW 2072
Phone: (02) 9967 9966
Fax: (02) 9967 9977
www.mainternational.com.au
info@mainternational.com.au


Nominated Architect No.6033
ABN 76 091 107 201
ACN 061107201

LEGEND
DO NOT SCALE DRAWINGS
VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCING WORK
COPYRIGHT
Mackenzie Architects International is the owner of the copyright subsisting in these drawings, plans, designs and specifications. They must not be used, reproduced or copied in whole or part without prior written consent of Mackenzie Architects International.

AMENDMENTS			
No.	REVISION	BY	DATE
A	DA	J.E	03.04.2024

MULTI RESIDENTIAL DEVELOPMENT
PROJECT
1-3 Gondola Rd North
Narrabeen 2101
PROJECT NO.
15/19

DRAWING: SECTIONS			
DRAWN BY J.E	SCALE: 1:200@A3	DRAWING NO.: A2101	ISSUE: A
CHECKED BY D.M			



LIFT SECTION CC



**mackenzie
architects
international**

736 PACIFIC HWY
Gordon NSW 2072
Phone: (02) 9967 9966
Fax: (02) 9967 9977
www.mainternational.com.au
info@mainternational.com.au

Nominated Architect No.6033
ABN 76 091 107 201
ACN 091107201



LEGEND
DO NOT SCALE DRAWINGS
VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCING WORK

COPYRIGHT
Mackenzie Architects International is the owner of the copyright subsisting in these drawings, plans, designs and specifications. They must not be used, reproduced or copied in whole or part without prior written consent of Mackenzie Architects International.

AMENDMENTS

No.	REVISION	BY	DATE

PROJECT NORTH

MULTI RESIDENTIAL DEVELOPMENT

PROJECT
1-3 Gondola Rd North
Narrabeen 2101

PROJECT NO.
15/19

DRAWING:

LIFT SECTION

DRAWN BY
J.E
CHECKED BY
D.M

SCALE:
1:200@A3

DRAWING NO.:

ISSUE:

Appendix C – Borehole Logs

CLIENT	Brett Crowther	COMMENCED	07/03/2024	COMPLETED	07/03/2024	REF BH201	
PROJECT	Geotechnical & ASS Assessment	LOGGED	AH/RM	CHECKED	WB	Sheet 1 OF 1	
SITE	1-3 Gondola Road, North Narrabeen, NSW	GEOLOGY	Quaternary deposits	VEGETATION	Grass	PROJECT NO. P2310036	
EQUIPMENT	4WD truck-mounted hydraulic drill rig	LONGITUDE	151.29571	RL SURFACE	2 m	DATUM	AHD
EXCAVATION DIMENSIONS	ø100 mm x 8.50 m depth	LATITUDE	-33.70815	ASPECT	North/Northeast	SLOPE	< 2 %

Drilling			Sampling			Field Material Description							
METHOD	PENETRATION RESISTANCE	WATER	DEPTH (metres)	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	USCS / ASCS CLASSIFICATION	SOIL/ROCK MATERIAL DESCRIPTION	MOISTURE CONDITION	CONSISTENCY	DENSITY	STRUCTURE AND ADDITIONAL OBSERVATIONS	
ADV			2.00	0.1-0.2/S/1 D	█	⊗	SP	FILL: SAND; medium grained; brown; trace gravels (road base and sandstone); trace plastic fragments; inferred poorly compacted.	D			FILL	
			0.30 1.70	0.10-0.20 m			SP						SAND; fine to medium grained; dark brown, black.
				1	0.8-0.9/S/1 D 0.80-0.90 m SPT 1.00-1.45 m 2, 2, 2 N = 4 1.0-1.45/SPT/1 1.3-1.4/S/1 D 1.30-1.40 m	█							
				2	2.0/S/1 D 2.00 m	█							
				2.50 -0.50	SPT 2.50-2.95 m 0, 1, 2 N = 3 2.5-2.95/SPT/1	█		SP	SAND; fine to medium grained; dark brown, black; trace shells, organics.				
				4	SPT 4.00-4.45 m 3, 5, 6 N = 11 4.0-4.45/SPT/1	█							
WB			5										
			5.80 -3.80	SPT 5.50-5.95 m 4, 8, 8 N = 16 5.5-5.95/SPT/1	█			Black, dark grey, black brown.					
			8.50										
				9				Hole Terminated at 8.50 m (Target depth reached)					
			10										

EXCAVATION LOG TO BE READ IN CONJUNCTION WITH ACCOMPANYING REPORT NOTES AND ABBREVIATIONS

MARTENS 2.00 LIB.GLB Log MARTENS BOREHOLE P2310036BH01-103.GPJ <-DrawingFile>> 02/04/2024 10:12 10:02:00.04 D:\git\Lab and In Situ Tool - DGD\ Lib: Martens 2.00 2016-11-13 Proj: Martens 2.00 2016-11-13



(C) Copyright Martens & Associates Pty. Ltd.

MARTENS & ASSOCIATES PTY LTD
 Suite 201, 20 George St. Hornsby, NSW 2077 Australia
 Phone: (02) 9476 9999 Fax: (02) 9476 8767
 mail@martens.com.au WEB: http://www.martens.com.au

**Engineering Log -
BOREHOLE**

CLIENT	Brett Crowther	COMMENCED	07/03/2024	COMPLETED	07/03/2024	REF BH202	
PROJECT	Geotechnical & ASS Assessment	LOGGED	AH/RM	CHECKED	WB	Sheet 1 OF 1	
SITE	1-3 Gondola Road, North Narrabeen, NSW	GEOLOGY	Quaternary deposits	VEGETATION	Grass	PROJECT NO. P2310036	
EQUIPMENT	4WD truck-mounted hydraulic drill rig	LONGITUDE	151.29583	RL SURFACE	2 m	DATUM	AHD
EXCAVATION DIMENSIONS	ø100 mm x 10.00 m depth	LATITUDE	-33.70785	ASPECT	North/Northeast	SLOPE	< 2 %

Drilling			Sampling			Field Material Description								
METHOD	PENETRATION RESISTANCE	WATER	DEPTH (metres)	DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	USCS / ASCS CLASSIFICATION	SOIL/ROCK MATERIAL DESCRIPTION	MOISTURE CONDITION	CONSISTENCY	DENSITY	STRUCTURE AND ADDITIONAL OBSERVATIONS	
ADV			2.00					SP	FILL: SAND; medium grained; brown; trace gravels (road base and sandstone); trace plastic fragments; inferred poorly compacted.				FILL	
			0.40		0.2-0.3/S/1 D 0.20-0.30 m			SP	SAND; fine to medium grained; brown, orange brown.				MARINE DEPOSITS	
			1.10		0.8-0.9/S/1 D 0.80-0.90 m SPT 1.00-1.45 m 2, 3, 5 N = 8			SP	SAND; fine to medium grained; black.		D	L		
			1.50		1.0-1.45/SPT/1			SP	SAND; fine to medium grained; pale brown, grey.					
			2.00		2.0/S/1 D 2.00 m			SP	SAND; fine to medium grained; grey, dark grey.					
				3		SPT 2.50-2.95 m 1, 0, 2 N = 2 2.5-2.95/SPT/1							VL	
				4		SPT 4.00-4.45 m 1, 2, 4 N = 6 4.0-4.45/SPT/1							L	
				5						Inferred medium dense.				
				6									W	
				7									MD	
			10.00						Hole Terminated at 10.00 m (Target depth reached)					

EXCAVATION LOG TO BE READ IN CONJUNCTION WITH ACCOMPANYING REPORT NOTES AND ABBREVIATIONS

MARTENS 2.00.LIB.GLB Log MARTENS BOREHOLE P2310036BH101-103.GPJ <-DrawingFile>> 02/04/2024 10:12 10:02:00.04 D:\git\Lab and In Situ Tool - DGD [Lib: Martens 2.00 2016-11-13 Proj: Martens 2.00 2016-11-13



(C) Copyright Martens & Associates Pty. Ltd.

MARTENS & ASSOCIATES PTY LTD
 Suite 201, 20 George St. Hornsby, NSW 2077 Australia
 Phone: (02) 9476 9999 Fax: (02) 9476 8767
 mail@martens.com.au WEB: http://www.martens.com.au


**Engineering Log -
BOREHOLE**

CLIENT	Brett Crowther	COMMENCED	07/03/2024	COMPLETED	07/03/2024	REF BH202/MW02 Sheet 1 OF 1 PROJECT NO. P2310036	
PROJECT	Geotechnical & ASS Assessment	LOGGED	AH/RM	CHECKED	WB		
SITE	1-3 Gondola Road, North Narrabeen, NSW	GEOLOGY	Quaternary deposits	VEGETATION	Grass		
EQUIPMENT	4WD truck-mounted hydraulic drill rig	LONGITUDE	151.29583	RL SURFACE	2 m	DATUM	AHD
EXCAVATION DIMENSIONS	Ø100 mm x 10.00 m depth	LATITUDE	-33.70785	ASPECT	North/Northeast	SLOPE	< 2 %

Drilling			Sampling		Field Material Description							
METHOD	PENETRATION RESISTANCE	WATER	DEPTH (metres)	DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	USCS / ASCS CLASSIFICATION	SOIL/ROCK MATERIAL DESCRIPTION	MOISTURE CONDITION	CONSISTENCY	PIEZOMETER DETAILS
												ID Static Water Level MW02
			2.00					SP	FILL: SAND; medium grained; brown; trace gravels (road base and sandstone); trace plastic fragments; inferred poorly compacted.			Concrete
			0.40		0.2-0.3/S/1 D			SP	SAND; fine to medium grained; brown, orange brown.			Bentonite
			1.60		0.8-0.9/S/1 D			SP	SAND; fine to medium grained; black.	D		Casing.
		Inflow	1.10		0.80-0.90 m SPT 1.00-1.45 m 2, 3, 5 N = 8			SP	SAND; fine to medium grained; pale brown, grey.	L		
			1.50		1.0-1.45/SPT/1			SP	SAND; fine to medium grained; grey, dark grey.			Screen.
			2.00		2.0/S/1 D 2.00 m			SP				
			3		SPT 2.50-2.95 m 1, 0, 2 N = 2 2.5-2.95/SPT/1			VL				
			4		SPT 4.00-4.45 m 1, 2, 4 N = 6 4.0-4.45/SPT/1			L				Sand
		L Inflow	5					W				
			6									
			7									
			8									
			9									
			10		10.00			MD				
									Hole Terminated at 10.00 m			

EXCAVATION LOG TO BE READ IN CONJUNCTION WITH ACCOMPANYING REPORT NOTES AND ABBREVIATIONS

MARTENS 2.00 LIB.GLB Log: MARTENS BOREHOLE: P2310036BH01-103.GPJ <-DrawingFile>> 02/04/2024 10:12:10:02:00.04 Digilog Lib and In Situ Tool - DGIJ Lib: Martens 2.00 2016-11-13 Proj: Martens 2.00 2016-11-13

 (C) Copyright Martens & Associates Pty. Ltd.	MARTENS & ASSOCIATES PTY LTD Suite 201, 20 George St. Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767 mail@martens.com.au WEB: http://www.martens.com.au	Engineering Log - TEST
---	--	-----------------------------------

CLIENT	Brett Crowther	COMMENCED	07/03/2024	COMPLETED	07/03/2024	REF BH203	
PROJECT	Geotechnical & ASS Assessment	LOGGED	AH/RM	CHECKED	WB	Sheet 1 OF 1	
SITE	1-3 Gondola Road, North Narrabeen, NSW	GEOLOGY	Quaternary deposits	VEGETATION	Grass	PROJECT NO. P2310036	
EQUIPMENT	4WD truck-mounted hydraulic drill rig	LONGITUDE	151.29586	RL SURFACE	2 m	DATUM	AHD
EXCAVATION DIMENSIONS	ø100 mm x 5.00 m depth	LATITUDE	-33.70801	ASPECT	North/Northeast	SLOPE	< 2 %

Drilling			Sampling			Field Material Description								
METHOD	PENETRATION RESISTANCE	WATER	DEPTH (metres)	DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	USCS / ASCS CLASSIFICATION	SOIL/ROCK MATERIAL DESCRIPTION	MOISTURE CONDITION	CONSISTENCY	DENSITY	STRUCTURE AND ADDITIONAL OBSERVATIONS	
ADV	L	Inflow	2.00					SP	FILL: SAND; medium grained; brown; trace gravels (road base and sandstone); trace plastic fragments; inferred poorly compacted.				FILL	
			0.5/S/1 D 0.50 m											
			1	1.20		1.0/S/1 D 1.00 m			SP	SAND; fine to medium grained; brown, dark brown; inferred very loose to loose.	D			MARINE DEPOSITS
			0.80											
			1.50						SP	SAND; fine to medium grained; brown, dark brown; trace organics; inferred very loose to loose.				
			2	2.50		2.5/S/1 D 2.50 m								
				-0.50				SP	SAND; fine to medium grained; brown, orange; trace shells; inferred very loose to loose.					
			3			3.0/S/1 D 3.00 m				M	VL - L			
			4	4.00		4.0/S/1 D 4.00 m								
				-2.00				SP	SAND; fine to medium grained; dark brown, orange; trace organics; inferred very loose to loose.					
			5	5.00		5.0/S/1 D 5.00 m								
									Hole Terminated at 5.00 m (Target depth reached)					
			6											
			7											
			8											
			9											
			10											

EXCAVATION LOG TO BE READ IN CONJUNCTION WITH ACCOMPANYING REPORT NOTES AND ABBREVIATIONS



(C) Copyright Martens & Associates Pty. Ltd.

MARTENS & ASSOCIATES PTY LTD
Suite 201, 20 George St. Hornsby, NSW 2077 Australia
Phone: (02) 9476 9999 Fax: (02) 9476 8767
mail@martens.com.au WEB: http://www.martens.com.au

**Engineering Log -
BOREHOLE**

MARTENS 2.00 LIB.GLB Log MARTENS BOREHOLE P2310036BH101-103.GPJ <DrawingFile>> 02/04/2024 10:12 10:02:00.04 D:\g\l\l\l and In Situ Tool - DGD [Lib: Martens 2.00 2016-11-13 Proj: Martens 2.00 2016-11-13

CLIENT	Mackenzie Architects International Pty Ltd	COMMENCED	14/07/2023	COMPLETED	14/07/2023	REF BH201	
PROJECT	Preliminary Site Investigation	LOGGED	WX	CHECKED		Sheet 1 OF 1	
SITE	3 Gondola Road, North Narrabeen, NSW	GEOLOGY	Quaternary	VEGETATION	Nil	PROJECT NO. P2108694	
EQUIPMENT	4WD truck-mounted hydraulic drill rig	LONGITUDE		RL SURFACE	m	DATUM	AHD
EXCAVATION DIMENSIONS	ø100 mm x 7.70 m depth	LATITUDE		ASPECT	North	SLOPE	<2%

Drilling			Sampling			Field Material Description							
METHOD	PENETRATION RESISTANCE	WATER	DEPTH (metres)	DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	USCS / ASCS CLASSIFICATION	SOIL/ROCK MATERIAL DESCRIPTION	MOISTURE CONDITION	CONSISTENCY	DENSITY	STRUCTURE AND ADDITIONAL OBSERVATIONS
			0.25		0.3-0.5/S/Dupe02 D 0.30-0.50 m	■	■	SM	CONCRETE.				PAVEMENT
			1		0.7-0.8/S/1 D 0.70-0.80 m	■	■	SM	FILL: Silty SAND; medium grained; brown; with shell inclusions.				FILL
		Inflow ▽	1.50					SP	SAND; brown, dark brown; with trace silt, trace shells.				MARINE DEPOSITS
			4	4.00					Grey / brown.				
			6	6.00					Grey, occasional blackish grey / brown.				
			7.70						Hole Terminated at 7.70 m (Target depth reached)				

EXCAVATION LOG TO BE READ IN CONJUNCTION WITH ACCOMPANYING REPORT NOTES AND ABBREVIATIONS

MARTENS 2.00 LIB.GLB Log MARTENS BOREHOLE P2108694BH201-MW01.GPJ ->DrawingFile-> 17/07/2023 14:55 10.02.00.04 D:\git\Lab and In Situ Tool - DGD | Lib: Martens 2.00 2016-11-13 Proj: Martens 2.00 2016-11-13

HSA



(C) Copyright Martens & Associates Pty. Ltd.

MARTENS & ASSOCIATES PTY LTD
 Suite 201, 20 George St. Hornsby, NSW 2077 Australia
 Phone: (02) 9476 9999 Fax: (02) 9476 8767
 mail@martens.com.au WEB: http://www.martens.com.au

**Engineering Log -
BOREHOLE**

CLIENT	Mackenzie Architects International Pty Ltd	COMMENCED	14/07/2023	COMPLETED	14/07/2023	REF BH201/MW01	
PROJECT	Preliminary Site Investigation	LOGGED	WX	CHECKED		Sheet 1 OF 1	
SITE	3 Gondola Road, North Narrabeen, NSW	GEOLOGY	Quaternary	VEGETATION	Nil	PROJECT NO. P2108694	
EQUIPMENT	4WD truck-mounted hydraulic drill rig	LONGITUDE		RL SURFACE	m	DATUM	AHD
EXCAVATION DIMENSIONS	ø100 mm x 7.70 m depth	LATITUDE		ASPECT	North	SLOPE	<2%

Drilling			Sampling			Field Material Description							
METHOD	PENETRATION RESISTANCE	WATER	DEPTH (metres)	DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	USCS / ASCS CLASSIFICATION	SOIL/ROCK MATERIAL DESCRIPTION	MOISTURE CONDITION	CONSISTENCY	DENSITY	PIEZOMETER DETAILS
													ID MW01 Static Water Level
				0.25	0.3-0.5/S/Dupe02 D 0.30-0.50 m			SM	CONCRETE.				Concrete
				1	0.7-0.8/S/1 D 0.70-0.80 m				FILL: Silty SAND; medium grained; brown; with shell inclusions.				Casing, Cuttings
				1.50				SP	SAND; brown, dark brown; with trace silt, trace shells.				Bentonite
		Inflow		4					Grey / brown.				Sand
				6.00					Grey, occasional blackish grey / brown.				Screen.
				7.70					Hole Terminated at 7.70 m (Target depth reached)				
				8									
				9									

EXCAVATION LOG TO BE READ IN CONJUNCTION WITH ACCOMPANYING REPORT NOTES AND ABBREVIATIONS

MARTENS 2.00 LIB.GLB Log MARTENS BOREHOLE P2108694BH201-MW01.GPJ ->DrawingFile--> 17/07/2023 14:55 10.02.00.04 D:\git\Lab and In Situ Tool - DGD | Lib: Martens 2.00 2016-11-13 Proj: Martens 2.00 2016-11-13

HSA



MARTENS & ASSOCIATES PTY LTD
 Suite 201, 20 George St. Hornsby, NSW 2077 Australia
 Phone: (02) 9476 9999 Fax: (02) 9476 8767
 mail@martens.com.au WEB: http://www.martens.com.au

**Engineering Log -
TEST**

Appendix D – Dewatering Modelling

4.000

Method ST-na Revised 20.1.2022

PROJECT DETAILS


Site: **1-3 Gondola Road, North Narrabeen**
 Project: **Mixed use development**
 Project Ref: **P2310036**

Date: **5-Jul-24**
 Assessor: **TR**
 Reviewer: **BM**

SIDEWALL INFLOW

Method: **Dupuit solution, Bear (1979)**


FACTOR	Enter Data	Unit
H - Average static head outside excavation	0.720	m
h_d - Head in excavation (0 if dry)	0.000	m
R_o - Equivalent excavation radius	1.450	m
R - Equivalent radius to constant head boundary	29.910	m
K - Hydraulic conductivity	15.000	m/d
Qs - Sidewall inflow	8.071	m ³ /d



EXCAVATION BASE INFLOW

Method: **Forchheimer (1914)**

FACTOR	Enter Data	Unit
H - Average static head outside excavation	0.720	m
h_d - Head in excavation (0 if dry)	0.000	m
$r_w (=R_o)$ - Equivalent excavation radius	1.450	m
Kh:Kv ratio	0.200	-
K - Hydraulic conductivity	3.000	m/d
S_w - Head difference in excavation	0.720	m
Qb - Base inflow	12.528	m ³ /d



SUMMARY

Qs - Sidewall inflow	8.071	m ³ /d
Qb - Base inflow	12.528	m ³ /d
Qtotal	20.599	m ³ /d
	7.519	ML/year

Head Office

Suite 201/20 George St
 Hornsby, NSW 2077
 Ph: (02) 9476 9999

>mail@martens.com.au
 www.martens.com.au
 MARTENS & ASSOCIATES PTY LTD

Appendix E – Laboratory Summary Table

	BTEX						TRH							Other				
	Naphthalene (VOC) mg/L	Benzene µg/L	Toluene µg/L	Ethylbenzene µg/L	Xylene (m & p) µg/L	Xylene (o) µg/L	C6-C10 Fraction (F1) µg/L	C6-C10 (F1 minus BTEX) µg/L	>C10-C16 Fraction (F2) µg/L	>C10-C16 Fraction (F2 minus Naphthalene) µg/L	>C16-C34 Fraction (F3) µg/L	>C34-C40 Fraction (F4) µg/L	>C10-C40 Fraction (Sum) µg/L	Benzo(b+j+k)fluoranthene mg/L	Acenaphthene µg/L	Acenaphthylene µg/L	Anthracene µg/L	Benzo(a)anthracene µg/L
EQL	0.001	1	1	1	2	1	10	10	50	50	100	100	50	0.0002	0.1	0.1	0.1	0.1
ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)	0.07	700	180	80													0.4	
NEPM 2013 Table 1A(4) Comm/Ind HSL D GW for Vapour Intrusion, Sand		5,000 5,000 5,000						6,000 6,000 7,000										

Field ID	Location Code	Date	<0.001	<1	<1	<1	<2	<1	<10	<10	<50	<50	<100	<100	<50	<0.0002	<0.1	<0.1	<0.1	<0.1
MW01		11 Apr 2024	<0.001	<1	<1	<1	<2	<1	<10	<10	<50	<50	<100	<100	<50	<0.0002	<0.1	<0.1	<0.1	<0.1
MW02		11 Apr 2024	<0.001	<1	<1	<1	<2	<1	<10	<10	<50	<50	<100	<100	<50	<0.0002	<0.1	<0.1	<0.1	<0.1

Statistics																				
Number of Detects	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Maximum Concentration	<0.001	<1	<1	<1	<2	<1	<10	<10	<50	<50	<100	<100	<50	<0.0002	<0.1	<0.1	<0.1	<0.1	<0.1	
Average Concentration *	0.0005	0.5	0.5	0.5	1	0.5	5	5	25	25	50	50	25	0.0001	0.05	0.05	0.05	0.05	0.05	
Median Concentration *	0.0005	0.5	0.5	0.5	1	0.5	5	5	25	25	50	50	25	0.0001	0.05	0.05	0.05	0.05	0.05	
Standard Deviation *	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	

* A Non Detect Multiplier of 0.5 has been applied.

Environmental Standards

ANZG, July 2023, ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)
2013, NEPM 2013 Table 1A(4) Comm/Ind HSL D GW for Vapour Intrusion, Sand

	PAH											TPH					
	Benzo(a) pyrene µg/L	Benzo(g,h,i)perylene µg/L	Chrysene µg/L	Dibenz(a,h)anthracene µg/L	Fluoranthene µg/L	Fluorene µg/L	Indeno(1,2,3-c,d)pyrene µg/L	Naphthalene µg/L	Phenanthrene µg/L	Pyrene µg/L	Benzo(a)pyrene TEQ mg/L	PAHs (Sum of positives) mg/L	C6-C9 Fraction µg/L	C10-C14 Fraction µg/L	C15-C28 Fraction µg/L	C29-C36 Fraction µg/L	C10-C36 Fraction (Sum) µg/L
EQL	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.0005	0.0001	10	50	100	100	50
ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)	0.2				1.4			70	2								
NEPM 2013 Table 1A(4) Comm/Ind HSL D GW for Vapour Intrusion, Sand																	

Field ID	Location Code	Date	Benzo(a) pyrene µg/L	Benzo(g,h,i)perylene µg/L	Chrysene µg/L	Dibenz(a,h)anthracene µg/L	Fluoranthene µg/L	Fluorene µg/L	Indeno(1,2,3-c,d)pyrene µg/L	Naphthalene µg/L	Phenanthrene µg/L	Pyrene µg/L	Benzo(a)pyrene TEQ mg/L	PAHs (Sum of positives) mg/L	C6-C9 Fraction µg/L	C10-C14 Fraction µg/L	C15-C28 Fraction µg/L	C29-C36 Fraction µg/L	C10-C36 Fraction (Sum) µg/L
MW01		11 Apr 2024	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.0005	<0.0001	<10	<50	<100	<100	<50
MW02		11 Apr 2024	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.0005	<0.0001	<10	<50	<100	<100	<50

Statistics																			
Number of Detects	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Maximum Concentration	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.0005	<0.0001	<10	<50	<100	<100	<50
Average Concentration *	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.00025	0.00005	5	25	50	50	25
Median Concentration *	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.00025	0.00005	5	25	50	50	25
Standard Deviation *	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

* A Non Detect Multiplier of 0.5 has been applied.

Environmental Standards

ANZG, July 2023, ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)
2013, NEPM 2013 Table 1A(4) Comm/Ind HSL D GW for Vapour Intrusion, Sand

	Biological			Inorganics																
	Faecal Coliforms	E. Coli	Enterococci	Hardness (filtered)	Electrical Conductivity (Non Compensated)	Reactive Silica	Alkalinity (Bicarbonate as CaCO3)	Alkalinity (Carbonate as CaCO3)	Alkalinity (Hydroxide) as CaCO3	Alkalinity (total) as CaCO3	Ammonia as N (filtered)	Chloride	Dissolved Oxygen (Lab)	Ionic Balance	Kjeldahl Nitrogen Total	Nitrate (as N) (filtered)	Nitrite (as N) (filtered)	Organic Nitrogen as N	Nitrogen (Total Oxidised)	
	CFU/100mL	cfu/100 ml	org/100ml	mg/L	µS/cm	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	%	mg/L	mg/L	mg/L	mg/L	mg/L	
EQL	1	1	1	3	1	0.1	5	5	5	5	0.005	1	0.1		0.1	0.005	0.005	0.2	0.005	
ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)											0.91									
NEPM 2013 Table 1A(4) Comm/Ind HSL D GW for Vapour Intrusion, Sand																				

Field ID	Location Code	Date																			
MW01		11 Apr 2024	500	500		1,300	12,000	14	240	<5	<5	240	0.21	3,900	8.3	0	6.0	1.4	0.052	5.8	1.5
MW02		11 Apr 2024	<1,000	<1,000	<10	610	2,300	12	490	<5	<5	490	0.040	420	8.4	-3.0	0.4	8.0	0.036	0.4	8.1

Statistics																					
Number of Detects	1	1	0	2	2	2	2	0	0	2	2	2	2	2	2	2	2	2	2	2	
Maximum Concentration	<1,000	<1,000	<10	1,300	12,000	14	490	<5	<5	490	0.21	3,900	8.4	0	6	8	0.052	5.8	8.1		
Average Concentration *	500	500		955	7,150	13	365	2.5	2.5	365	0.12	2,160	8.4	-1.5	3.2	4.7	0.044	3.1	4.8		
Median Concentration *	500	500	5	955	7,150	13	365	2.5	2.5	365	0.125	2,160	8.35	-1.5	3.2	4.7	0.044	3.1	4.8		
Standard Deviation *	0	0		488	6,859	1.4	177	0	0	177	0.12	2,461	0.071	2.1	4	4.7	0.011	3.8	4.7		

* A Non Detect Multiplier of 0.5 has been applied.

Environmental Standards

ANZG, July 2023, ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)
2013, NEPM 2013 Table 1A(4) Comm/Ind HSL D GW for Vapour Intrusion, Sand

	Nitrogen (Total)	pH (Lab)	Total Phosphorus (Organic Phosphate)	Reactive Phosphorus as P (Orthophosphate as P) (filtered)	Sodium (filtered)	Sodium Absorption Ratio	Sulphate	Total Dissolved Solids (Lab)	Total Suspended Solids (Lab)	Turbidity (Lab)	Organic
	mg/L	-	mg/L	mg/L	mg/L	-	mg/L	mg/L	mg/L	NTU	mg/L
EQL	0.1	-	0.05	0.005	0.5	0.01	1	5	5	0.1	1
ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)											
NEPM 2013 Table 1A(4) Comm/Ind HSL D GW for Vapour Intrusion, Sand											

Field ID	Location Code	Date											
MW01		11 Apr 2024	7.5	7.0	0.4	<0.005	2,300	27	590	8,800	90	120	9
MW02		11 Apr 2024	8.5	7.2	1.4	0.11	230	3.9	94	1,800	120	210	15

Statistics													
Number of Detects	2	2	2	1	2	2	2	2	2	2	2	2	2
Maximum Concentration	8.5	7.2	1.4	0.11	2,300	27	590	8,800	120	210	15		
Average Concentration *	8	7.1	0.9	0.056	1,265	15	342	5,300	105	165	12		
Median Concentration *	8	7.1	0.9	0.05625	1,265	15.45	342	5,300	105	165	12		
Standard Deviation *	0.71	0.14	0.71	0.076	1,464	16	351	4,950	21	64	4.2		

* A Non Detect Multiplier of 0.5 has been applied.

Environmental Standards

ANZG, July 2023, ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)
2013, NEPM 2013 Table 1A(4) Comm/Ind HSL D GW for Vapour Intrusion, Sand

	Metals																			
	Aluminium (filtered)	Antimony (filtered)	Arsenic (filtered)	Barium (filtered)	Beryllium (filtered)	Boron (filtered)	Cadmium (filtered)	Chromium (III+VI) (filtered)	Cobalt (filtered)	Copper (filtered)	Iron (filtered)	Lead (filtered)	Lithium (filtered)	Manganese (filtered)	Mercury (filtered)	Molybdenum (filtered)	Nickel (filtered)	Selenium (filtered)	Silicon	
	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	µg/L
EQL	0.01	0.001	0.001	0.001	0.0005	0.02	0.0001	0.001	0.001	0.001	0.01	0.001	0.001	0.005	0.00005	0.001	0.001	0.001		200
ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)							0.0055		0.001	0.0013		0.0044			0.0004		0.07			

Field ID	Location Code	Date	Aluminium (filtered)	Antimony (filtered)	Arsenic (filtered)	Barium (filtered)	Beryllium (filtered)	Boron (filtered)	Cadmium (filtered)	Chromium (III+VI) (filtered)	Cobalt (filtered)	Copper (filtered)	Iron (filtered)	Lead (filtered)	Lithium (filtered)	Manganese (filtered)	Mercury (filtered)	Molybdenum (filtered)	Nickel (filtered)	Selenium (filtered)	Silicon
MW01		11 Apr 2024	<0.01	0.001	<0.001	0.056	<0.0005	0.52	<0.0001	<0.001	0.001	<0.001	<0.01	<0.001	0.027	0.25	<0.00005	0.003	<0.001	<0.001	3,900
MW02		11 Apr 2024	<0.01	0.002	0.005	0.023	<0.0005	0.07	<0.0001	<0.001	<0.001	0.001	0.02	<0.001	0.007	0.01	<0.00005	0.004	<0.001	<0.001	3,000

Statistics																					
Number of Results	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Number of Detects	0	2	1	2	0	2	0	0	0	1	1	1	0	2	2	0	2	0	0	0	2
Minimum Detect	ND	0.001	0.005	0.023	ND	0.07	ND	ND	0.001	0.001	0.02	ND	0.007	0.01	ND	0.003	ND	ND	ND	3,000	
Maximum Concentration	<0.01	0.002	0.005	0.056	<0.0005	0.52	<0.0001	<0.001	0.001	0.001	0.02	<0.001	0.027	0.25	<0.00005	0.004	<0.001	<0.001	<0.001	3,900	
Maximum Detect	ND	0.002	0.005	0.056	ND	0.52	ND	ND	0.001	0.001	0.02	ND	0.027	0.25	ND	0.004	ND	ND	ND	3,900	
Median Concentration *	0.005	0.0015	0.00275	0.0395	0.00025	0.295	0.00005	0.0005	0.00075	0.00075	0.0125	0.0005	0.017	0.13	0.000025	0.0035	0.0005	0.0005	0.0005	3,450	
Standard Deviation *	0	0.00071	0.0032	0.023	0	0.32	0	0	0.00035	0.00035	0.011	0	0.014	0.17	0	0.00071	0	0	0	636	

* A Non Detect Multiplier of 0.5 has been applied.

Environmental Standards

ANZG, July 2023, ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)

	Silver (filtered)	Strontium (filtered)	Uranium (filtered)	Vanadium (filtered)	Zinc (filtered)
	mg/L	mg/L	µg/L	mg/L	mg/L
EQL	0.001	0.001	0.5	0.001	0.001
ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)	0.0014			0.1	0.008

Field ID	Location Code	Date					
MW01		11 Apr 2024	<0.001	1.6	1.2	<0.001	0.003
MW02		11 Apr 2024	<0.001	1.5	3.2	0.012	<0.001

Statistics

Number of Results	2	2	2	2	2
Number of Detects	0	2	2	1	1
Minimum Detect	ND	1.5	1.2	0.012	0.003
Maximum Concentration	<0.001	1.6	3.2	0.012	0.003
Maximum Detect	ND	1.6	3.2	0.012	0.003
Median Concentration *	0.0005	1.55	2.2	0.00625	0.00175
Standard Deviation *	0	0.071	1.4	0.0081	0.0018

* A Non Detect Multiplier of 0.5 has been applied.

Environmental Standards

ANZG, July 2023, ANZG Marine Water Toxicant DGVs LOSP 95% (July 2023)

Appendix F – Laboratory Analytical Documentation

CHAIN OF CUSTODY FORM

Water Testing													
Name	P2310036 – 1-3 Gondola Road, North Narrabeen												
Martens Contact Officer	Trystan Richards					Contact Email	trichards@martens.com.au						
Sampling and Shipping	Sample Date	11/04/2024			Dispatch Date	11/04/2024		Turnaround Time	standard				
	Our Reference	P2310036COC03V01				Shipping Method (X)	Hand		Post		Courier	X	
	On Ice (X)	X	No Ice (X)		Other (X)								
Laboratory													
Name	Envirolab												
Sample Delivery Address	12 Ashley Street, Chatswood												
Delivery Contact	Name				Phone	9910 6200		Fax			Email	samplereceipt@envirolabservices.com.au	
Please Send Report By (X)	Post		Fax		Email	X		Reporting Email Address	trichardsi@martens.com.au				
									gtaylor@martens.com.au				
									bmcgiffin@martens.com.au				

Sample ID	Ionic Balance	Nutrient Suite	Microbiology suite	Dissolved HM*	TRH, BTEXN, PAH	Dissolved SiO ₂	TSS	TOC	Turbidity	TDS	pH	EC	DO	SAR
MW01	X	X	X	X	X	X	X	X	X	X	X	X	X	X
MW02	X	X	X	X	X	X	X	X	X	X	X	X	X	X

Note: *Please filter for HM from non-preservative bottles.



Envirolab Services
 12 Ashley St
 Chatswood NSW 2067
 Ph: (02) 9910 6200

Job No: 348642

Date Received: 11/4/24

Time Received: 1655

Received By: ew

Temp: Cool Ambient

Cooling: Ice Icepack

Security: Intact/Broken/None

Head Office
 Suite 201, 20 George St
 Hornsby NSW 2077, Australia
 Ph 02 9476 9999 Fax 02 9476 8767

> mail@martens.com.au
 > www.martens.com.au
 MARTENS & ASSOCIATES P/L
 ABN 85 070 240 890 ACN 070 240 890

CERTIFICATE OF ANALYSIS 348642

Client Details

Client	Martens & Associates Pty Ltd
Attention	Trystan Richards
Address	Suite 201, 20 George St, Hornsby, NSW, 2077

Sample Details

Your Reference	<u>P2310036 - 1-3 Gondola Road, North Narrabeen</u>
Number of Samples	2 Water
Date samples received	11/04/2024
Date completed instructions received	11/04/2024

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.
 Samples were analysed as received from the client. Results relate specifically to the samples as received.
 Results are reported on a dry weight basis for solids and on an as received basis for other matrices.
Please refer to the last page of this report for any comments relating to the results.

Report Details

Date results requested by	18/04/2024
Date of Issue	19/04/2024
NATA Accreditation Number 2901. This document shall not be reproduced except in full.	
Accredited for compliance with ISO/IEC 17025 - Testing. Tests not covered by NATA are denoted with *	

Results Approved By

Diego Bigolin, Inorganics Supervisor
 Dragana Tomas, Senior Chemist
 Greta Petzold, Operation Manager
 Hannah Nguyen, Metals Supervisor
 Loren Bardwell, Development Chemist
 Nick Sarlamis, Assistant Operation Manager
 Timothy Toll, Senior Chemist

Authorised By

Nancy Zhang, Laboratory Manager

vTRH(C6-C10)/BTEXN in Water			
Our Reference		348642-1	348642-2
Your Reference	UNITS	MW01	MW02
Date Sampled		11/04/2024	11/04/2024
Type of sample		Water	Water
Date extracted	-	14/04/2024	14/04/2024
Date analysed	-	15/04/2024	15/04/2024
TRH C ₆ - C ₉	µg/L	<10	<10
TRH C ₆ - C ₁₀	µg/L	<10	<10
TRH C ₆ - C ₁₀ less BTEX (F1)	µg/L	<10	<10
Benzene	µg/L	<1	<1
Toluene	µg/L	<1	<1
Ethylbenzene	µg/L	<1	<1
m+p-xylene	µg/L	<2	<2
o-xylene	µg/L	<1	<1
Naphthalene	µg/L	<1	<1
Surrogate Dibromofluoromethane	%	131	130
Surrogate Toluene-d8	%	114	114
Surrogate 4-Bromofluorobenzene	%	91	91

svTRH (C10-C40) in Water			
Our Reference		348642-1	348642-2
Your Reference	UNITS	MW01	MW02
Date Sampled		11/04/2024	11/04/2024
Type of sample		Water	Water
Date extracted	-	15/04/2024	15/04/2024
Date analysed	-	16/04/2024	16/04/2024
TRH C ₁₀ - C ₁₄	µg/L	<50	<50
TRH C ₁₅ - C ₂₈	µg/L	<100	<100
TRH C ₂₉ - C ₃₆	µg/L	<100	<100
Total +ve TRH (C10-C36)	µg/L	<50	<50
TRH >C ₁₀ - C ₁₆	µg/L	<50	<50
TRH >C ₁₀ - C ₁₆ less Naphthalene (F2)	µg/L	<50	<50
TRH >C ₁₆ - C ₃₄	µg/L	<100	<100
TRH >C ₃₄ - C ₄₀	µg/L	<100	<100
Total +ve TRH (>C10-C40)	µg/L	<50	<50
Surrogate o-Terphenyl	%	93	86

PAHs in Water			
Our Reference		348642-1	348642-2
Your Reference	UNITS	MW01	MW02
Date Sampled		11/04/2024	11/04/2024
Type of sample		Water	Water
Date extracted	-	15/04/2024	15/04/2024
Date analysed	-	16/04/2024	16/04/2024
Naphthalene	µg/L	<0.1	<0.1
Acenaphthylene	µg/L	<0.1	<0.1
Acenaphthene	µg/L	<0.1	<0.1
Fluorene	µg/L	<0.1	<0.1
Phenanthrene	µg/L	<0.1	<0.1
Anthracene	µg/L	<0.1	<0.1
Fluoranthene	µg/L	<0.1	<0.1
Pyrene	µg/L	<0.1	<0.1
Benzo(a)anthracene	µg/L	<0.1	<0.1
Chrysene	µg/L	<0.1	<0.1
Benzo(b,j+k)fluoranthene	µg/L	<0.2	<0.2
Benzo(a)pyrene	µg/L	<0.1	<0.1
Indeno(1,2,3-c,d)pyrene	µg/L	<0.1	<0.1
Dibenzo(a,h)anthracene	µg/L	<0.1	<0.1
Benzo(g,h,i)perylene	µg/L	<0.1	<0.1
Benzo(a)pyrene TEQ	µg/L	<0.5	<0.5
Total +ve PAH's	µg/L	<0.1	<0.1
Surrogate <i>p</i> -Terphenyl-d14	%	87	94

HM in water - dissolved			
Our Reference		348642-1	348642-2
Your Reference	UNITS	MW01	MW02
Date Sampled		11/04/2024	11/04/2024
Type of sample		Water	Water
Date prepared	-	17/04/2024	17/04/2024
Date analysed	-	17/04/2024	17/04/2024
Arsenic-Dissolved	µg/L	<1	5
Cadmium-Dissolved	µg/L	<0.1	<0.1
Chromium-Dissolved	µg/L	<1	<1
Copper-Dissolved	µg/L	<1	1
Lead-Dissolved	µg/L	<1	<1
Mercury-Dissolved	µg/L	<0.05	<0.05
Nickel-Dissolved	µg/L	<1	<1
Zinc-Dissolved	µg/L	3	<1

Metals in Waters - Acid extractable			
Our Reference		348642-1	348642-2
Your Reference	UNITS	MW01	MW02
Date Sampled		11/04/2024	11/04/2024
Type of sample		Water	Water
Date prepared	-	15/04/2024	15/04/2024
Date analysed	-	16/04/2024	16/04/2024
Phosphorus - Total	mg/L	0.4	1.4

Miscellaneous Inorganics			
Our Reference		348642-1	348642-2
Your Reference	UNITS	MW01	MW02
Date Sampled		11/04/2024	11/04/2024
Type of sample		Water	Water
Date prepared	-	11/04/2024	11/04/2024
Date analysed	-	11/04/2024	11/04/2024
Ammonia as N in water	mg/L	0.21	0.040
Nitrate as N in water	mg/L	1.4	8.0
Nitrite as N in water	mg/L	0.052	0.036
NOx as N in water	mg/L	1.5	8.1
Total Nitrogen in water	mg/L	7.5	8.5
TKN in water	mg/L	6.0	0.4
Phosphate as P in water	mg/L	<0.005	0.11
Organic Nitrogen as N	mg/L	5.8	0.4
Total Organic Carbon	mg/L	9	15
Total Suspended Solids	mg/L	90	120
Turbidity	NTU	120	210
Sodium Adsorption Ratio	-	27	3.9
Total Dissolved Solids (grav)	mg/L	8,800	1,800
pH	pH Units	7.0	7.2
Electrical Conductivity	µS/cm	12,000	2,300
Dissolved Oxygen*	mg/L	8.3	8.4
Silica (Reactive - SiO ₂)	mg/L	14	12

Ion Balance			
Our Reference		348642-1	348642-2
Your Reference	UNITS	MW01	MW02
Date Sampled		11/04/2024	11/04/2024
Type of sample		Water	Water
Date prepared	-	11/04/2024	11/04/2024
Date analysed	-	11/04/2024	11/04/2024
Calcium - Dissolved	mg/L	150	180
Potassium - Dissolved	mg/L	76	7.3
Sodium - Dissolved	mg/L	2,300	230
Magnesium - Dissolved	mg/L	230	38
Hardness (calc) equivalent CaCO ₃	mg/L	1,300	610
Hydroxide Alkalinity (OH ⁻) as CaCO ₃	mg/L	<5	<5
Bicarbonate Alkalinity as CaCO ₃	mg/L	240	490
Carbonate Alkalinity as CaCO ₃	mg/L	<5	<5
Total Alkalinity as CaCO ₃	mg/L	240	490
Sulphate, SO ₄	mg/L	590	94
Chloride, Cl	mg/L	3,900	420
Ionic Balance	%	0	-3.0

Microbiological Testing			
Our Reference		348642-1	348642-2
Your Reference	UNITS	MW01	MW02
Date Sampled		11/04/2024	11/04/2024
Type of sample		Water	Water
Date of testing	-	12/04/2024	12/04/2024
Faecal Coliforms	cfu/100mL	500	<1000
E. coli	cfu/100mL	500	<1000
Enterococci	cfu/100mL	30 A	<10

Method ID	Methodology Summary
Ext-008	Subcontracted to Sonic Food & Water Testing. NATA Accreditation No. 4034.
Inorg-001	pH - Measured using pH meter and electrode. Please note that the results for water analyses are indicative only, as analysis outside of the APHA storage times.
Inorg-002	Conductivity and Salinity - measured using a conductivity cell.
Inorg-006	Alkalinity - determined titrimetrically in accordance with APHA latest edition, 2320-B.
Inorg-018	Total Dissolved Solids - determined gravimetrically. The solids are dried at 180+/-10°C. NOTE: Where the EC of the sample is <100µS/cm, the TDS will typically be below 70mg/L (as the sample is very likely to be at least drinking water quality). Therefore to ensure data quality for TDS, the TDS is typically calculated as per the equation below:- TDS = EC * 0.6
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.
Inorg-022	Turbidity - measured nephelometrically using a turbidimeter, in accordance with APHA latest edition, 2130-B.
Inorg-040	The concentrations of the major ions (mg/L) are converted to milliequivalents and summed. The ionic balance should be within +/- 15% ie total anions = total cations +/-15%.
Inorg-055	Nitrate - determined colourimetrically. Waters samples are filtered on receipt prior to analysis. Soils are analysed following a water extraction.
Inorg-055	Nitrite - determined colourimetrically based on APHA latest edition NO2- B. Waters samples are filtered on receipt prior to analysis. Soils are analysed following a water extraction.
Inorg-055/062/127	Total Nitrogen - Calculation sum of TKN and oxidised Nitrogen. Alternatively analysed by combustion and chemiluminescence.
Inorg-057	Ammonia - determined colourimetrically, based on APHA latest edition 4500-NH3 F. Waters samples are filtered on receipt prior to analysis. Soils are analysed following a KCl extraction.
Inorg-060	Phosphate determined colourimetrically based on EPA365.1 and APHA latest edition 4500 P E. Waters samples are filtered on receipt prior to analysis. Soils are analysed following a water extraction.
Inorg-062	TKN - determined colourimetrically based on APHA latest edition 4500 Norg. Alternatively, TKN can be derived from calculation (Total N - NOx).
Inorg-079	TOC determined using a TOC analyser using the combustion method. Dissolved requires filtering prior to determination. Analysis using APHA latest edition 5310B.
Inorg-081	Anions - a range of Anions are determined by Ion Chromatography, in accordance with APHA latest edition, 4110-B. Waters samples are filtered on receipt prior to analysis. Alternatively determined by colourimetry/turbidity using Discrete Analyser.
Inorg-112	Dissolved Oxygen using membrane electrode. Note this analysis should ideally be carried out immediately after sampling.
INORG-120	Reactive Silica (SiO2) determined colorimetrically. Waters samples are filtered on receipt prior to analysis.
Metals-020	Determination of various metals by ICP-AES.
Metals-020	Calcium and Magnesium analysed by ICP-AES and SAR calculated.
Metals-021	Determination of Mercury by Cold Vapour AAS.

Method ID	Methodology Summary
Metals-022	Determination of various metals by ICP-MS. Please note for Bromine and Iodine, any forms of these elements that are present are included together in the one result reported for each of these two elements. Salt forms (e.g. FeO, PbO, ZnO) are determined stoichiometrically from the base metal concentration.
Org-020	Soil samples are extracted with Dichloromethane/Acetone and waters with Dichloromethane and analysed by GC-FID. F2 = (>C10-C16)-Naphthalene as per NEPM B1 Guideline on Investigation Levels for Soil and Groundwater (HSLs Tables 1A (3, 4)). Note Naphthalene is determined from the VOC analysis.
Org-022/025	Soil samples are extracted with Dichloromethane/Acetone and waters with Dichloromethane and analysed by GC-MS/GC-MSMS. Benzo(a)pyrene TEQ as per NEPM B1 Guideline on Investigation Levels for Soil and Groundwater - 2013.
Org-023	Water samples are analysed directly by purge and trap GC-MS.
Org-023	Soil samples are extracted with methanol and spiked into water prior to analysing by purge and trap GC-MS. Water samples are analysed directly by purge and trap GC-MS. F1 = (C6-C10)-BTEX as per NEPM B1 Guideline on Investigation Levels for Soil and Groundwater.

Client Reference: P2310036 - 1-3 Gondola Road, North Narrabeen

QUALITY CONTROL: vTRH(C6-C10)/BTEXN in Water					Duplicate			Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W5	[NT]
Date extracted	-			14/04/2024	[NT]	[NT]	[NT]	[NT]	14/04/2024	[NT]
Date analysed	-			15/04/2024	[NT]	[NT]	[NT]	[NT]	15/04/2024	[NT]
TRH C ₆ - C ₉	µg/L	10	Org-023	<10	[NT]	[NT]	[NT]	[NT]	107	[NT]
TRH C ₆ - C ₁₀	µg/L	10	Org-023	<10	[NT]	[NT]	[NT]	[NT]	107	[NT]
Benzene	µg/L	1	Org-023	<1	[NT]	[NT]	[NT]	[NT]	116	[NT]
Toluene	µg/L	1	Org-023	<1	[NT]	[NT]	[NT]	[NT]	111	[NT]
Ethylbenzene	µg/L	1	Org-023	<1	[NT]	[NT]	[NT]	[NT]	103	[NT]
m+p-xylene	µg/L	2	Org-023	<2	[NT]	[NT]	[NT]	[NT]	103	[NT]
o-xylene	µg/L	1	Org-023	<1	[NT]	[NT]	[NT]	[NT]	105	[NT]
Naphthalene	µg/L	1	Org-023	<1	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
Surrogate Dibromofluoromethane	%		Org-023	121	[NT]	[NT]	[NT]	[NT]	107	[NT]
Surrogate Toluene-d8	%		Org-023	113	[NT]	[NT]	[NT]	[NT]	100	[NT]
Surrogate 4-Bromofluorobenzene	%		Org-023	96	[NT]	[NT]	[NT]	[NT]	94	[NT]

Client Reference: P2310036 - 1-3 Gondola Road, North Narrabeen

QUALITY CONTROL: svTRH (C10-C40) in Water					Duplicate			Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	348642-1
Date extracted	-			15/04/2024	[NT]	[NT]	[NT]	[NT]	15/04/2024	15/04/2024
Date analysed	-			15/04/2024	[NT]	[NT]	[NT]	[NT]	15/04/2024	16/04/2024
TRH C ₁₀ - C ₁₄	µg/L	50	Org-020	<50	[NT]	[NT]	[NT]	[NT]	112	121
TRH C ₁₅ - C ₂₈	µg/L	100	Org-020	<100	[NT]	[NT]	[NT]	[NT]	104	112
TRH C ₂₉ - C ₃₆	µg/L	100	Org-020	<100	[NT]	[NT]	[NT]	[NT]	86	95
TRH >C ₁₀ - C ₁₆	µg/L	50	Org-020	<50	[NT]	[NT]	[NT]	[NT]	112	121
TRH >C ₁₆ - C ₃₄	µg/L	100	Org-020	<100	[NT]	[NT]	[NT]	[NT]	104	112
TRH >C ₃₄ - C ₄₀	µg/L	100	Org-020	<100	[NT]	[NT]	[NT]	[NT]	86	95
Surrogate o-Terphenyl	%		Org-020	91	[NT]	[NT]	[NT]	[NT]	90	93

Client Reference: P2310036 - 1-3 Gondola Road, North Narrabeen

QUALITY CONTROL: PAHs in Water				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W2	348642-1
Date extracted	-			15/04/2024	[NT]	[NT]	[NT]	[NT]	15/04/2024	15/04/2024
Date analysed	-			16/04/2024	[NT]	[NT]	[NT]	[NT]	16/04/2024	16/04/2024
Naphthalene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	87	83
Acenaphthylene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
Acenaphthene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	78	76
Fluorene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	91	80
Phenanthrene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	75	74
Anthracene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
Fluoranthene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	79	78
Pyrene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	94	83
Benzo(a)anthracene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
Chrysene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	72	71
Benzo(b,j+k)fluoranthene	µg/L	0.2	Org-022/025	<0.2	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
Benzo(a)pyrene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	86	87
Indeno(1,2,3-c,d)pyrene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
Dibenzo(a,h)anthracene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
Benzo(g,h,i)perylene	µg/L	0.1	Org-022/025	<0.1	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
Surrogate p-Terphenyl-d14	%		Org-022/025	84	[NT]	[NT]	[NT]	[NT]	99	92

Client Reference: P2310036 - 1-3 Gondola Road, North Narrabeen

QUALITY CONTROL: HM in water - dissolved				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			17/04/2024	[NT]	[NT]	[NT]	[NT]	17/04/2024	[NT]
Date analysed	-			17/04/2024	[NT]	[NT]	[NT]	[NT]	17/04/2024	[NT]
Arsenic-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	103	[NT]
Cadmium-Dissolved	µg/L	0.1	Metals-022	<0.1	[NT]	[NT]	[NT]	[NT]	104	[NT]
Chromium-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	104	[NT]
Copper-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	105	[NT]
Lead-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	106	[NT]
Mercury-Dissolved	µg/L	0.05	Metals-021	<0.05	[NT]	[NT]	[NT]	[NT]	97	[NT]
Nickel-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	106	[NT]
Zinc-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	99	[NT]

Client Reference: P2310036 - 1-3 Gondola Road, North Narrabeen

QUALITY CONTROL: Metals in Waters - Acid extractable					Duplicate			Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	348642-2
Date prepared	-			15/04/2024	[NT]	[NT]	[NT]	[NT]	15/04/2024	15/04/2024
Date analysed	-			16/04/2024	[NT]	[NT]	[NT]	[NT]	16/04/2024	16/04/2024
Phosphorus - Total	mg/L	0.05	Metals-020	<0.05	[NT]	[NT]	[NT]	[NT]	89	89

Client Reference: P2310036 - 1-3 Gondola Road, North Narrabeen

QUALITY CONTROL: Miscellaneous Inorganics				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			11/04/2024	1	11/04/2024	11/04/2024		11/04/2024	[NT]
Date analysed	-			11/04/2024	1	11/04/2024	11/04/2024		11/04/2024	[NT]
Ammonia as N in water	mg/L	0.005	Inorg-057	<0.005	1	0.21	[NT]		103	[NT]
Nitrate as N in water	mg/L	0.005	Inorg-055	<0.005	1	1.4	[NT]		99	[NT]
Nitrite as N in water	mg/L	0.005	Inorg-055	<0.005	1	0.052	[NT]		101	[NT]
NOx as N in water	mg/L	0.005	Inorg-055	<0.005	1	1.5	[NT]		99	[NT]
Total Nitrogen in water	mg/L	0.1	Inorg-055/062/127	<0.1	1	7.5	[NT]		87	[NT]
TKN in water	mg/L	0.1	Inorg-062	<0.1	1	6.0	[NT]		[NT]	[NT]
Phosphate as P in water	mg/L	0.005	Inorg-060	<0.005	1	<0.005	[NT]		115	[NT]
Organic Nitrogen as N	mg/L	0.2	Inorg-055/062/127	<0.2	1	5.8	[NT]		[NT]	[NT]
Total Organic Carbon	mg/L	1	Inorg-079	<1	1	9	[NT]		84	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	1	90	83	8	97	[NT]
Turbidity	NTU	0.1	Inorg-022	<0.1	1	120	[NT]		100	[NT]
Sodium Adsorption Ratio	-	0.01	Metals-020	<0.01	1	27	[NT]		96	[NT]
Total Dissolved Solids (grav)	mg/L	5	Inorg-018	<5	1	8800	[NT]		102	[NT]
pH	pH Units		Inorg-001	[NT]	1	7.0	[NT]		99	[NT]
Electrical Conductivity	µS/cm	1	Inorg-002	<1	1	12000	[NT]		100	[NT]
Dissolved Oxygen*	mg/L	0.1	Inorg-112	<0.1	1	8.3	[NT]		[NT]	[NT]
Silica (Reactive - SiO ₂)	mg/L	0.1	INORG-120	<0.1	1	14	[NT]		95	[NT]

Client Reference: P2310036 - 1-3 Gondola Road, North Narrabeen

QUALITY CONTROL: Ion Balance				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			11/04/2024	[NT]	[NT]	[NT]	[NT]	11/04/2024	[NT]
Date analysed	-			11/04/2024	[NT]	[NT]	[NT]	[NT]	11/04/2024	[NT]
Calcium - Dissolved	mg/L	0.5	Metals-020	<0.5	[NT]	[NT]	[NT]	[NT]	103	[NT]
Potassium - Dissolved	mg/L	0.5	Metals-020	<0.5	[NT]	[NT]	[NT]	[NT]	96	[NT]
Sodium - Dissolved	mg/L	0.5	Metals-020	<0.5	[NT]	[NT]	[NT]	[NT]	97	[NT]
Magnesium - Dissolved	mg/L	0.5	Metals-020	<0.5	[NT]	[NT]	[NT]	[NT]	104	[NT]
Hydroxide Alkalinity (OH ⁻) as CaCO ₃	mg/L	5	Inorg-006	<5	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
Bicarbonate Alkalinity as CaCO ₃	mg/L	5	Inorg-006	<5	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
Carbonate Alkalinity as CaCO ₃	mg/L	5	Inorg-006	<5	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
Total Alkalinity as CaCO ₃	mg/L	5	Inorg-006	<5	[NT]	[NT]	[NT]	[NT]	105	[NT]
Sulphate, SO ₄	mg/L	1	Inorg-081	<1	[NT]	[NT]	[NT]	[NT]	117	[NT]
Chloride, Cl	mg/L	1	Inorg-081	<1	[NT]	[NT]	[NT]	[NT]	114	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Where matrix spike recoveries fall below the lower limit of the acceptance criteria (e.g. for non-labile or standard Organics <60%), positive result(s) in the parent sample will subsequently have a higher than typical estimated uncertainty (MU estimates supplied on request) and in these circumstances the sample result is likely biased significantly low.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.

Report Comments

Microbiology analysed by Sonic Food & Water Testing. Report No. W2408699 & W2408700

A: Approximate

The time between collection and the commencement of testing should not exceed 24 hours. Samples tested outside this time may have their results compromised

Dissolved Metals: no filtered, preserved sample was received, therefore the unpreserved sample was filtered through 0.45µm filter at the lab.

Note: there is a possibility some elements may be underestimated.

CERTIFICATE OF ANALYSIS 348642-A

Client Details

Client	Martens & Associates Pty Ltd
Attention	Trystan Richards
Address	Suite 201, 20 George St, Hornsby, NSW, 2077

Sample Details

Your Reference	<u>P2310036 - 1-3 Gondola Road, North Narrabeen</u>
Number of Samples	Additional analysis
Date samples received	11/04/2024
Date completed instructions received	26/04/2024

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.
 Samples were analysed as received from the client. Results relate specifically to the samples as received.
 Results are reported on a dry weight basis for solids and on an as received basis for other matrices.
Please refer to the last page of this report for any comments relating to the results.

Report Details

Date results requested by	03/05/2024
Date of Issue	26/04/2024
NATA Accreditation Number 2901. This document shall not be reproduced except in full.	
Accredited for compliance with ISO/IEC 17025 - Testing. Tests not covered by NATA are denoted with *	

Results Approved By

Hannah Nguyen, Metals Supervisor

Authorised By

Nancy Zhang, Laboratory Manager

All metals in water-dissolved			
Our Reference		348642-A-1	348642-A-2
Your Reference	UNITS	MW01	MW02
Date Sampled		11/04/2024	11/04/2024
Type of sample		Water	Water
Date prepared	-	17/04/2024	17/04/2024
Date analysed	-	17/04/2024	17/04/2024
Aluminium-Dissolved	µg/L	<10	<10
Antimony-Dissolved	µg/L	1	2
Arsenic-Dissolved	µg/L	<1	5
Barium-Dissolved	µg/L	56	23
Beryllium-Dissolved	µg/L	<0.5	<0.5
Boron-Dissolved	µg/L	520	70
Cadmium-Dissolved	µg/L	<0.1	<0.1
Chromium-Dissolved	µg/L	<1	<1
Cobalt-Dissolved	µg/L	1	<1
Copper-Dissolved	µg/L	<1	1
Iron-Dissolved	µg/L	<10	20
Lead-Dissolved	µg/L	<1	<1
Lithium-Dissolved	µg/L	27	7
Manganese-Dissolved	µg/L	250	10
Mercury-Dissolved	µg/L	<0.05	<0.05
Molybdenum-Dissolved	µg/L	3	4
Nickel-Dissolved	µg/L	<1	<1
Selenium-Dissolved	µg/L	<1	<1
Silver-Dissolved	µg/L	<1	<1
Strontium-Dissolved	µg/L	1,600	1,500
Uranium-Dissolved	µg/L	1.2	3.2
Vanadium-Dissolved	µg/L	<1	12
Zinc-Dissolved	µg/L	3	<1

Metals in Water - Dissolved			
Our Reference		348642-A-1	348642-A-2
Your Reference	UNITS	MW01	MW02
Date Sampled		11/04/2024	11/04/2024
Type of sample		Water	Water
Date digested	-	17/04/2024	17/04/2024
Date analysed	-	17/04/2024	17/04/2024
Silicon*- Dissolved	mg/L	3.9	3.0

Method ID	Methodology Summary
Metals-020	Determination of various metals by ICP-AES.
Metals-021	Determination of Mercury by Cold Vapour AAS.
Metals-022	Determination of various metals by ICP-MS. Please note for Bromine and Iodine, any forms of these elements that are present are included together in the one result reported for each of these two elements. Salt forms (e.g. FeO, PbO, ZnO) are determined stoichiometrically from the base metal concentration.

Client Reference: P2310036 - 1-3 Gondola Road, North Narrabeen

QUALITY CONTROL: All metals in water-dissolved				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			17/04/2024	[NT]	[NT]	[NT]	[NT]	17/04/2024	[NT]
Date analysed	-			17/04/2024	[NT]	[NT]	[NT]	[NT]	17/04/2024	[NT]
Aluminium-Dissolved	µg/L	10	Metals-022	<10	[NT]	[NT]	[NT]	[NT]	102	[NT]
Antimony-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	99	[NT]
Arsenic-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	103	[NT]
Barium-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	110	[NT]
Beryllium-Dissolved	µg/L	0.5	Metals-022	<0.5	[NT]	[NT]	[NT]	[NT]	95	[NT]
Boron-Dissolved	µg/L	20	Metals-022	<20	[NT]	[NT]	[NT]	[NT]	119	[NT]
Cadmium-Dissolved	µg/L	0.1	Metals-022	<0.1	[NT]	[NT]	[NT]	[NT]	104	[NT]
Chromium-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	104	[NT]
Cobalt-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	107	[NT]
Copper-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	105	[NT]
Iron-Dissolved	µg/L	10	Metals-022	<10	[NT]	[NT]	[NT]	[NT]	105	[NT]
Lead-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	106	[NT]
Lithium-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	106	[NT]
Manganese-Dissolved	µg/L	5	Metals-022	<5	[NT]	[NT]	[NT]	[NT]	106	[NT]
Mercury-Dissolved	µg/L	0.05	Metals-021	<0.05	[NT]	[NT]	[NT]	[NT]	97	[NT]
Molybdenum-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	104	[NT]
Nickel-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	106	[NT]
Selenium-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	97	[NT]
Silver-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	82	[NT]
Strontium-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	105	[NT]
Uranium-Dissolved	µg/L	0.5	Metals-022	<0.5	[NT]	[NT]	[NT]	[NT]	99	[NT]
Vanadium-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	105	[NT]
Zinc-Dissolved	µg/L	1	Metals-022	<1	[NT]	[NT]	[NT]	[NT]	99	[NT]

Client Reference: P2310036 - 1-3 Gondola Road, North Narrabeen

QUALITY CONTROL: Metals in Water - Dissolved				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date digested	-			17/04/2024	[NT]	[NT]	[NT]	[NT]	17/04/2024	[NT]
Date analysed	-			17/04/2024	[NT]	[NT]	[NT]	[NT]	17/04/2024	[NT]
Silicon*- Dissolved	mg/L	0.2	Metals-020	<0.2	[NT]	[NT]	[NT]	[NT]	98	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Where matrix spike recoveries fall below the lower limit of the acceptance criteria (e.g. for non-labile or standard Organics <60%), positive result(s) in the parent sample will subsequently have a higher than typical estimated uncertainty (MU estimates supplied on request) and in these circumstances the sample result is likely biased significantly low.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.

Report Comments

Dissolved Metals: no filtered, preserved sample was received, therefore the unpreserved sample was filtered through 0.45µm filter at the lab.

Note: there is a possibility some elements may be underestimated.

SAMPLE RECEIPT ADVICE

Client Details

Client	Martens & Associates Pty Ltd
Attention	Trystan Richards

Sample Login Details

Your reference	P2310036 - 1-3 Gondola Road, North Narrabeen
Envirolab Reference	348642
Date Sample Received	11/04/2024
Date Instructions Received	11/04/2024
Date Results Expected to be Reported	18/04/2024

Sample Condition

Samples received in appropriate condition for analysis	Yes
No. of Samples Provided	2 Water
Turnaround Time Requested	Standard
Temperature on Receipt (°C)	1
Cooling Method	Ice
Sampling Date Provided	YES

Comments

Microbiology suite assumed as Faecal Coliforms, E.Coli, Enterococci as previous jobs

Please direct any queries to:

Aileen Hie

Phone: 02 9910 6200
Fax: 02 9910 6201
Email: ahie@envirolab.com.au

Jacinta Hurst

Phone: 02 9910 6200
Fax: 02 9910 6201
Email: jhurst@envirolab.com.au

Analysis Underway, details on the following page:



Sample ID	VTRH(C6-C10)/BTEXN in Water	svTRH (C10-C40) in Water	PAHs in Water	HM in water - dissolved	Metals in Waters -Acid extractable	Ammonia as N in water	Nitrate as N in water	Nitrite as N in water	NOx as N in water	Total Nitrogen in water	TKN in water	Phosphate as P in water	Organic Nitrogen as N	Total Organic Carbon	Total Suspended Solids	Turbidity	Sodium Adsorption Ratio	Total Dissolved Solids(grav)	pH	Electrical Conductivity	Dissolved Oxygen*	Silica (Reactive - SiO2)	Calcium - Dissolved	Potassium - Dissolved	Sodium - Dissolved	Magnesium - Dissolved	Hardness (calc) equivalent CaCO3	Hydroxide Alkalinity (OH-) as CaCO3	Bicarbonate Alkalinity as CaCO3	Carbonate Alkalinity as CaCO3	Total Alkalinity as CaCO3	Sulphate, SO4	Chloride, Cl	Ionic Balance	Microbiological Testing			
MW01	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
MW02	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

The '✓' indicates the testing you have requested. **THIS IS NOT A REPORT OF THE RESULTS.**

Additional Info

Sample storage - Waters are routinely disposed of approximately 1 month and soils approximately 2 months from receipt.

Requests for longer term sample storage must be received in writing.

Please contact the laboratory immediately if observed settled sediment present in water samples is to be included in the extraction and/or analysis (exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, Total Recoverable metals and PFAS analysis where solids are included by default.

TAT for Micro is dependent on incubation. This varies from 3 to 6 days.