BASIX°Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A378097 04

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

This certificate is a revision of certificate number A378097_03 lodged with the consent authority or certifier on 09 Jul 2020 with application DA2020/0758.

It is the responsibility of the applicant to verify with the consent authority that the original, or any revised certificate, complies with the requirements of Sch 1 Cl 2A, 4A or 6A of the Environmental Planning and Assessment Regulation 2000

Secretary

Date of issue: Monday, 01, February 2021

To be valid, this certificate must be lodged within 3 months of the date of issue.



Description of project

| Project address | |
|-----------------------|--|
| Project name | 25 The Outlook_04 |
| Street address | 25 The Outlook Road Bilgola Plateau 2107 |
| Local Government Area | Northern Beaches Council |
| Plan type and number | Deposited Plan 16902 |
| Lot number | 190 |
| Section number | |
| Project type | |
| | |
| Dwelling type | Separate dwelling house |

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Daniel Raymond Architect

ABN (if applicable): 612713425

BASIX Certificate number: A378097_04 page 2 / 6

| Fixtures and systems | Show on DA Plans | Show on CC/CDC Plans & specs | Certifier Check |
|--|---------------------|---------------------------------------|--------------------|
| Lighting | | | |
| The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps. | | ✓ | ✓ |
| Fixtures | | | |
| The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating. | | ✓ | ✓ |
| The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating. | | ✓ | ✓ |
| The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating. | | ✓ | |

BASIX Certificate number: A378097_04 page 3 / 6

| Construction | | | Show on DA Plans | Show on CC/CDC Plans & specs | Certifier Check | | |
|--|---|----------|---------------------|---------------------------------------|--------------------|--|--|
| Insulation requirements | | | | | | | |
| The applicant must construct the new or altered the table below, except that a) additional insular is not required for parts of altered construction | √ | √ | ✓ | | | | |
| Construction | onstruction Additional insulation required (R-value) Other specifications | | | | | | |
| suspended floor with open subfloor: framed (R0.7). | R0.8 (down) (or R1.50 including construction) | | | | | | |
| external wall: cavity brick | nil | | | | | | |
| external wall: framed (weatherboard, fibro, metal clad) | R1.30 (or R1.70 including construction) | | | | | | |

BASIX Certificate number: A378097_04 page 4 / 6

| Glazing requ | uirements | | | | | | Show on DA Plans | Show on CC/CDC Plans & specs | Certifier Check |
|---|---------------|-------------------------------|--------------------------|-----------------|---|---|---------------------|---------------------------------------|--------------------|
| Windows and | d glazed do | ors | | | | | | | |
| | | | | | nading devices, in accordance with reach window and glazed door. | the specifications listed in the table below. | ✓ | ✓ | ✓ |
| The following requirements must also be satisfied in relation to each window and glazed door: | | | | | | | ✓ | ✓ | |
| have a U-value | and a Solar | Heat Gair | n Coefficie | ent (SHGC) n | | d glass may either match the description, or, le below. Total system U-values and SHGCs | | ✓ | ✓ |
| | | | | | f each eave, pergola, verandah, bal than 2400 mm above the sill. | cony or awning must be no more than 500 mm | ✓ | ✓ | ✓ |
| Pergolas with | oolycarbonate | roof or si | milar tran | slucent mate | erial must have a shading coefficien | t of less than 0.35. | | ✓ | ✓ |
| | | | | | e window or glazed door above which should be more than 50 mm. | ch they are situated, unless the pergola also | | ✓ | ✓ |
| Windows a | | doors g | lazing r | equireme | | | | | |
| Window / door no. | Orientation | Area of glass inc. frame (m2) | Oversha Height (m) | Distance (m) | Shading device | Frame and glass type | | | |
| W01 | S | 1 | 0 | 0 | awning (adjustable) >=900 mm | standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) | | | |
| W02 | N | 0.8 | 0 | 0 | awning (adjustable) >=900 mm | standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) | | | |
| W03 | E | 2.7 | 0 | 0 | eave/verandah/pergola/balcony >=900 mm | standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) | | | |
| W04 | Е | 1.5 | 0 | 0 | eave/verandah/pergola/balcony >=900 mm | standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) | | | |
| W05 | E | 1.5 | 0 | 0 | eave/verandah/pergola/balcony >=900 mm | standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) | | | |

BASIX Certificate number: A378097_04 page 5 / 6

| Glazing requ | irements | | | | | | Show on DA Plans | Show on CC/CDC Plans & specs | Certifier Check |
|-------------------|-------------|-------------------------------|--------------------------|---------------------------|---|--|---------------------|---------------------------------------|--------------------|
| Window / door no. | Orientation | Area of glass inc. frame (m2) | Oversha Height (m) | dowing Distance (m) | Shading device | Frame and glass type | | | |
| D01 | Е | 3.2 | 0 | 0 | eave/verandah/pergola/balcony >=900 mm | standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) | | | |
| D02 | Е | 7.3 | 0 | 0 | eave/verandah/pergola/balcony >=900 mm | timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66) | | | |

BASIX Certificate number: A378097_04 page 6 / 6

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a "

"" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.