BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A409912 06

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Thursday, 08, July 2021

To be valid, this certificate must be lodged within 3 months of the date of issue.



_

| | Project address | |
|---|---------------------------------|---|
| | Project name | 20129_9 Suffolk Avenue Collaroy_06 |
| 1 | Street address | 9 Suffolk Avenue Collaroy 2097 |
| | Local Government Area | Northern Beaches Council |
| | Plan type and number | Deposited Plan DP380519 |
| | Lot number | Α |
| | Section number | |
| | Project type | |
| | Dwelling type | Separate dwelling house |
| 1 | Type of alteration and addition | My renovation work is valued at \$50,000 or more, and includes a pool (and/or spa). |

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Designed 2 You

ABN (if applicable): 84697799721

BASIX Certificate number: A409912_06 page 2 / 7

| Pool and Spa | Show on DA Plans | Show on CC/CDC Plans & specs | Certifier Check |
|---|---------------------|---------------------------------------|--------------------|
| Rainwater tank | | | |
| The applicant must install a rainwater tank of at least 3937 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities. | < | ~ | ~ |
| The applicant must configure the rainwater tank to collect rainwater runoff from at least 110 square metres of roof area. | | ✓ | ✓ |
| The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the outdoor spa. | | ✓ | ✓ |
| Outdoor spa | | | |
| The spa must not have a capacity greater than 8.15 kilolitres. | ~ | ✓ | ✓ |
| The spa must have a spa cover. | | ✓ | ✓ |
| The applicant must install a spa pump timer. | | ✓ | ✓ |
| The applicant must install the following heating system for the outdoor spa that is part of this development: gas. | | ✓ | ✓ |

BASIX Certificate number: A409912_06 page 3 / 7

| Fixtures and systems | Show on DA Plans | Show on CC/CDC Plans & specs | Certifier Check |
|--|---------------------|---------------------------------------|--------------------|
| Lighting | | | |
| The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps. | | ✓ | ~ |
| Fixtures | | | |
| The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating. | | ✓ | ✓ |
| The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating. | | ✓ | ✓ |
| The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating. | | ✓ | |

BASIX Certificate number: A409912_06 page 4 / 7

| Construction | | | Show on DA Plans | Show on CC/CDC Plans & specs | Certifier Check |
|--|---|---|---------------------|---------------------------------------|--------------------|
| Insulation requirements | | | | | |
| the table below, except that a) additional insu | applicant must construct the new or altered construction (floor(s), walls, and ceilings/roofs) in accordance with the specifications listed in able below, except that a) additional insulation is not required where the area of new construction is less than 2m2, b) insulation specified trequired for parts of altered construction where insulation already exists. Additional insulation required (R-value) Other specifications | | | | |
| suspended floor with enclosed subfloor: framed (R0.7). | R0.60 (down) (or R1.30 including construction) | | | | |
| external wall: brick veneer | R1.16 (or R1.70 including construction) | | | | |
| flat ceiling, pitched roof | ceiling: R3.00 (up), roof: foil/sarking | medium (solar absorptance 0.475 - 0.70) | | | |

BASIX Certificate number: A409912_06 page 5 / 7

| Glazing re | quirements | | | | | | Show on DA Plans | Show on CC/CDC Plans & specs | Certifier Check |
|---|--------------------------------------|-----------------------|-------------------------|---------------------------------|--|---|---------------------|---------------------------------------|--------------------|
| Windows a | ınd glazed do | ors | | | | | | | |
| | | | | | nading devices, in accordance with reach window and glazed door. | the specifications listed in the table below. | ✓ | ~ | ~ |
| The following | g requirements | must also | be satisf | ied in relation | n to each window and glazed door: | | | ✓ | ✓ |
| have a U-val | lue and a Solar culated in accord | Heat Gai dance wit | n Coeffici h Nationa | ent (SHGC) r Il Fenestration | no greater than that listed in the table | ar glazing, or toned/air gap/clear glazing must le below. Total system U-values and SHGCs . The description is provided for information | | ~ | ~ |
| | | | | | f each eave, pergola, verandah, bal than 2400 mm above the sill. | cony or awning must be no more than 500 mm | ✓ | ✓ | ✓ |
| Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35. | | | | | | | ✓ | ✓ | |
| | | | | | e window or glazed door above which which some which was not be more than 50 mm. | ch they are situated, unless the pergola also | | ✓ | ✓ |
| Windows | and glazed | doors g | lazing ı | equireme | nts | | | | |
| | oor Orientation | | | Distance (m) | Shading device | Frame and glass type | | | |
| W01 | N | 1.4 | 0 | 0 | eave/verandah/pergola/balcony >=450 mm | improved aluminium, single pyrolytic low-e, (U-value: 4.48, SHGC: 0.46) | | | |
| W02 | N | 4.5 | 0 | 0 | eave/verandah/pergola/balcony >=900 mm | improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75) | | | |
| D01 | W | 10.6 | 0 | 0 | eave/verandah/pergola/balcony >=900 mm | improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75) | | | |
| D02 | N | 6.9 | 0 | 0 | eave/verandah/pergola/balcony >=750 mm | improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75) | | | |

BASIX Certificate number: A409912_06 page 6 / 7

BASIX Certificate number: A409912_06 page 7 / 7

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"" in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.