# **BASIX** Certificate

Building Sustainability Index www.basix.nsw.gov.au

## **Alterations and Additions**

Certificate number: A367252

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

### Secretary

Date of issue: Monday, 23, December 2019

To be valid, this certificate must be lodged within 3 months of the date of issue.



# Description of project

Project address						
Project name	Dougheney					
Street address	19 Cooleena Road Elanora Heights 2101					
Local Government Area	Northern Beaches Council					
Plan type and number	Deposited Plan 17397					
Lot number	2					
Section number						
Project type						
Dwelling type	Separate dwelling house					
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and does not include a pool (and/or spa).					

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Contour Landscape Architecture

ABN (if applicable): 55631020776

BASIX Certificate number: A367252 page 2 / 6

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		<b>✓</b>	<b>✓</b>
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		<b>✓</b>	✓
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		<b>✓</b>	<b>✓</b>
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		<b>✓</b>	

BASIX Certificate number: A367252 page 3 / 6

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check	
Insulation requirements						
the table below, except that a) additional insula	The applicant must construct the new or altered construction (floor(s), walls, and ceilings/roofs) in accordance with the specifications listed in the table below, except that a) additional insulation is not required where the area of new construction is less than 2m2, b) insulation specified is not required for parts of altered construction where insulation already exists.					
Construction	Additional insulation required (R-value)	Other specifications				
suspended floor with open subfloor: framed (R0.7).	R0.8 (down) (or R1.50 including construction)					
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)					
flat ceiling, flat roof: framed	ceiling: R3.00 (up), roof: foil/sarking	medium (solar absorptance 0.475 - 0.70)				

BASIX Certificate number: A367252 page 4 / 6

Glazing i	equirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows	and glazed	doors							
					hading devices, in accordar r each window and glazed	ance with the specifications listed in the table below. door.	<b>~</b>	<b>✓</b>	<b>✓</b>
The followi	ing requirement	ts must als	o be satisf	fied in relatior	n to each window and glaz	red door:		<b>✓</b>	✓
have a U-v	alue and a Sol	ar Heat Ga	in Coeffici	ent (SHGC) ı		ar or toned glass may either match the description, or, in the table below. Total system U-values and SHGCs conditions.		<b>✓</b>	<b>✓</b>
	owing buildings on the 'overshad				ht and distance from the c	entre and the base of the window and glazed door, as	<b>~</b>	✓	<b>✓</b>
Windows	s and glazed	d doors	glazing ı	requireme	nts				
	/ door Orientation Area of Overshadowing Shading device Frame and glass type								
	door Orientation	on Area of	Oversh	adowing		Frame and glass type			
Window / o	door Orientatio					Frame and glass type			
	door Orientation	on Area of glass inc. frame	Oversh Height	adowing Distance		standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
no.		on Area of glass inc. frame	Oversha Height (m)	adowing Distance (m)	Shading device	standard aluminium, single clear, (or			
no.	E	on Area of glass inc. frame (m2)	Overshamed Height (m)	adowing Distance (m) 0.3	Shading device none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or			
no. W1 W2	E E	on Area of glass inc. frame (m2)  1  0.45	Overshall Height (m)  0.4  0.7	adowing  Distance (m)  0.3	Shading device  none  none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or			
<ul><li>mo.</li><li>W1</li><li>W2</li><li>W3</li></ul>	E E	on Area of glass inc. frame (m2)  1  0.45	Overshall Height (m)  0.4  0.7	Distance (m)  0.3  0.3	none none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			

BASIX Certificate number: A367252 page 5 / 6

Glazing require	ements			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
The applicant mus	st install the skyligh	ts in accordance with the specifications	s listed in the table below.	<b>V</b>	<b>✓</b>	<b>✓</b>
The following requ	The following requirements must also be satisfied in relation to each skylight:					
Each skylight may the table below.	y either match the d	escription, or, have a U-value and a Sc	olar Heat Gain Coefficient (SHGC) no greater than that listed in		<b>✓</b>	<b>✓</b>
External awnings	External awnings and louvres must fully shade the skylight above which they are situated when fully drawn or closed.					<b>✓</b>
Skylights glaz	zing requiremer	nts				
Skylight number	Area of glazing inc. frame (m2)	Shading device	Frame and glass type			
S1	1.32	external fixed awning or blind	aluminium, moulded plastic single clear, (or U-value: 6.21, SHGC: 0.808)			
S2	1.32	external fixed awning or blind	aluminium, moulded plastic single clear, (or U-value: 6.21, SHGC: 0.808)			
S3	1.32	external fixed awning or blind	aluminium, moulded plastic single clear, (or U-value: 6.21, SHGC: 0.808)			

BASIX Certificate number: A367252 page 6 / 6

### Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a "

"" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.