



Sekisui House Proposed Residential Development

To be built at Lot 12, Road NO.1, Frenchs Forest, NSWc 2086

Issue	File Ref	Description	Author	Date
A	#2401171	NatHERS Thermal Comfort and BASIX Assessment	JF/SS	28/04/2025

This report has been prepared by Efficient Living Pty Ltd on behalf of our client Sekisui House. Efficient Living prepares all reports in accordance with the BASIX Thermal Comfort Protocol and is backed by professional indemnity insurance. This report takes into account our Client's instructions and preferred building inclusions.

If there is a change to this specification during design or construction phases, please contact Efficient Living and quote the above file reference for advice, and to obtain an updated Certificate if required.



BASIX Inclusions – extra notes:

There are a few inclusions set in the BASIX Portal which are not showing correctly in the BASIX Certificate. These items have been flagged with BASIX as errors. The correct inclusions should be as follows (shown in bold text):

Ventilation

At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: interlocked to light / timer off

Nationwide House Energy Rating Scheme®

NatHERS® Certificate No. #HR-MWIX7M-01

Generated on 24 Apr 2025 using Hero 4.1 (Chenath v3.23)

Property

Address Lot 12, Road No.1, Frenchs Forest, NSW, 2086
Lot/DP 12/unreg
NCC Class* 1a
Floor/all Floors 1 of 2 floors
Type New

Plans

Main Plan NM105571 REV10 14.03.2025
Prepared by SEKISUI HOUSES SERVICES (NSW) PTY LIMITED

Construction and environment

Assessed floor area (m²)*	Exposure Type
Conditioned* 191.4	Suburban
Unconditioned* 17.7	NatHERS climate zone
Total 248.0	56 - Mascot AMO
Garage 38.9	



Accredited assessor

Name Haylea Edwards
Business name haylea@efficientliving.com.au
Email haylea@efficientliving.com.au
Phone +61 9970 6181
Accreditation No. 10213
Assessor Accrediting Organisation HERA
Declaration of interest No Conflict of Interest

NCC Requirements

BCA provisions Volume 2
State/Territory variation Yes


National Construction Code (NCC) requirements

The NCC allows the use of NatHERS accredited software to comply with the energy efficiency requirements for houses (Class 1 buildings) and apartments (Class 2 sole-occupancy units and Class 4 parts of buildings). The applicable requirements for houses are detailed in Specification 42 of NCC Volume Two. For apartments the requirements are detailed in clauses J2D2(2)(a) and (3) of NCC Volume One.

NCC 2022 includes enhanced thermal performance requirements for houses and apartments. It also includes a new whole-of-home annual energy use budget which applies to the major equipment in the home.

The NCC, and associated ABCB Standards and support material, can be accessed at www.abcb.gov.au.

Thermal performance star rating



Thermal performance (MJ/m²)

Limits taken from ABCB Standard 2022

	Heating	Cooling
Modelled	12.2	16.2
Load limits	25	18

Features determining load limits

Floor type (lowest conditioned area) CSOG
NCC climate zone 1 or 2 N
Outdoor living area N
Outdoor living area ceiling fan N

Whole of Home performance rating

No Whole of Home performance rating generated for this certificate.

Verification

To verify this certificate, scan the QR code or visit
<http://www.hero-software.com.au/pdf/HR-MWIX7M-01>.

When using either link, ensure you are visiting <http://www.hero-software.com.au>



Note, variations and additions to the NCC energy efficiency requirements may apply in some states and territories.

Thermal performance rating

NatHERS thermal software models the expected heating and cooling energy loads using information about the design, construction, climate and common patterns of household use. The thermal performance rating (shown as a star rating on this Certificate) does not take into account appliances, apart from the airflow impacts from ceiling fans.

Whole of Home performance rating

NatHERS Whole of Home software uses the heating and cooling energy loads combined with the energy performance of the home's appliances (heating, cooling, hot water, lighting, pool/spa pump and onsite renewable energy generation and storage) and models the expected energy value* of the whole home. The Whole of Home performance rating is shown as a score out of 100 on this Certificate.

Heating and Cooling Load Limits

Additional information

In some locations under the NCC NatHERS pathway, separate heating and cooling load limits may apply. Minimum required star ratings in northern parts of Australia may also be affected by the presence or absence of an outdoor living area and/or an outdoor living area ceiling fan. Refer to the *ABCB Standard: NatHERS heating and cooling load limits* for details or contact the relevant local building regulating authority, noting that State and Territory variations may also apply.

Setting options:

Floor type:

- CSOG - Concrete Slab on Ground
- SF - Suspended Floor (or a mixture of CSOG and SF)
- NA - Not Applicable

NCC climate Zone 1 or 2:

- Yes
- No
- NA - Not Applicable

Outdoor living area:

- Yes
- No
- NA - Not Applicable

Outdoor living area ceiling fan:

- Yes
- No
- NA - Not Applicable



Predicted onsite renewable energy impact

No Whole of Home performance assessment conducted for this certificate.

Predicted Whole of Home annual impact by appliance

Shows the contribution each appliance has on the home's annual energy use, greenhouse gas emissions and cost without solar.

Energy use:

No Whole of Home performance assessment conducted for this certificate.

Greenhouse gas emissions:

No Whole of Home performance assessment conducted for this certificate.

Cost:

No Whole of Home performance assessment conducted for this certificate.

Certificate check

The checklist covers important items impacting the dwelling's ratings.

It is recommended that the accuracy of the whole certificate is checked.

Note: The boxes indicate when and who should check each item.

It is not mandatory to complete this checklist.

Approval stage		Construction stage		
Assessor checked	Consent authority/ surveyor checked	Builder checked	Consent authority/ surveyor checked	Occupancy/other

Genuine certificate check

Does this Certificate match the one available at the web address or QR code verification link on the front page?

☐☐☐☐

Does the NatHERS certificate number on the NatHERS-stamped plans match the number on this Certificate?

☐☐☐☐

Thermal performance check

Windows and glazed doors

Does the window size, opening type and location shown on the NatHERS-stamped plans or as installed match what is shown in 'Window and glazed door schedule' and 'Roof window schedule' tables on this Certificate?

☐☐☐☐☐

Does the installed windows meet the substitution tolerances (AFRC* based SHGC* and U-values*) as shown in the 'Window and glazed door type and performance' and 'Roof window type and performance' tables on this Certificate?

☐☐☐

External walls

Does the external wall bulk insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'External wall type table' on this Certificate?

☐☐☐☐☐

Does the external wall shade (colour) match what is shown in the 'External wall type' table on this Certificate?

☐☐☐☐☐

Floor

Does the floor insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Floor type' table on this certificate?

☐☐☐☐☐

Ceiling penetrations*

Does the 'quantity' and 'type' of ceiling penetrations* (e.g. downlights, exhaust fans, etc) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling penetrations' table on this Certificate?

☐☐☐☐☐

Ceiling

Does the ceiling insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling type' table on this Certificate?

☐☐☐☐☐

Roof

Does the external roof shade (colour) on the NatHERS stamped plans or as installed match what is shown in the 'Roof type' table on this Certificate?

☐☐☐☐☐

Apartment entrance doors (NCC Class 2 assessments only)

Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.

☐☐☐☐

Exposure*

Has the appropriate exposure type (terrain) (shown on page 1) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".

☐☐☐☐

Heating and cooling load limits*

Do the load limits settings (shown on page 1) match what is shown on the NatHERS-stamped plans?

☐☐☐☐☐

* Refer to glossary.

Certificate check

Continued

Approval stage		Construction stage		
Assessor checked	Consent authority/ surveyor checked	Builder checked	Consent authority/ surveyor checked	Occupancy/other

Additional NCC requirements for thermal performance (not included in the NatHERS assessment)

Thermal bridging

Does the dwelling meet the NCC requirement for thermal bridging?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--	--------------------------	--------------------------	--------------------------	--------------------------

Insulation installation method

Has the insulation been installed according to the NCC requirements?			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--	--	--------------------------	--------------------------	--------------------------

Building sealing

Does the dwelling meet the NCC requirements for Building Sealing?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
---	--	--------------------------	--------------------------	--------------------------	--------------------------

Whole of Home performance check (not applicable if a Whole of Home assessment is not conducted)

Appliances

Does the cooling appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
---	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the heating appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed, match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the hot water system type and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the pool pump efficiency/performance shown on the NatHERS-stamped plans or as installed match the minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
---	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the onsite renewable energy system type, orientation and system size or generation capacity shown on the NatHERS stamped plans or installed match the 'Onsite Renewable Energy schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Additional NCC Requirements for Services (not included in the NatHERS assessment)

Does the lighting meet the artificial lighting requirements specified in the NCC?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
---	--	--------------------------	--------------------------	--------------------------	--------------------------

Does the hot water system meet the additional requirements specified in the NCC?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--	--------------------------	--------------------------	--------------------------	--------------------------

Provisional values* check

Have provisional values* been used in the assessment and, if so, are they noted in 'Additional notes' table below?	<input type="checkbox"/>	<input type="checkbox"/>			
--	--------------------------	--------------------------	--	--	--

Other NCC requirements

Note: This Certificate only covers the energy efficiency requirements in the NCC. Additional requirements that must also be satisfied include, but are not limited to: condensation, structural and fire safety requirements and any state or territory variations to the NCC energy efficiency requirements.



Additional Notes

Provisional Inclusions:

Roof default colour medium

Default colour modelled to external walls, windows frames and floor finishes

Waffle pod 225mm thick

Sealed and insulated Downlights 1 per 5m² ceiling penetration diameter 150mm

Sealed and insulated Exhaust fans ceiling penetration diameter 200mm

Windows modelled as a proxy to match window manufacturer U-value and SHGC

Floor coverings: bare concrete to garage, carpet to bedrooms and first floor living areas, tiles to remainder of the house

Page 2 - Whole of home and Appliance check list on this NatHERS Certificate is not applicable in NSW as energy is covered by BASIX.

Insulation is applied to the conditioned envelope of the house; this includes; external walls of habitable rooms, the wall between the garage and the house and any vertical walls adjacent to roof space. Unless noted otherwise garage external walls do not require insulation.

- Windows areas may be split into varying sash types in the model
- Raked ceilings under 10 degrees are modelled as flat ceiling
- Sisalation / sarking is only shown in certificate where it provides a reflective air-space
- No insulation clearance modeled as IC rated downlights are nominated

Room schedule

Room	Zone Type	Area (m ²)
LOUNGE	Living	8.23
GST BATH	Unconditioned	5.49
GUEST ROOM	Bedroom	11.99
KITCHBN/LIVING	Kitchen/Living	53.76
ENTRY	Day Time	10.50
PANTRY	Day Time	4.89
laundry	Unconditioned	5.54
GARAGE	Garage	38.88
bed 3	Bedroom	9.50
wir 3	Night Time	2.85
wc	Day Time	2.39
bath	Unconditioned	6.67
BED4	Bedroom	12.53
BED1	Bedroom	16.85
WIR	Night Time	3.15
wir	Night Time	3.14



Room schedule

Room	Zone Type	Area (m²)
ensuite	Night Time	9.81
bed 2	Bedroom	11.67
family	Living	31.56

Window and glazed door type and performance

Default* windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

Custom* windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
WID-101-032	Horizon Awning Window	3.97	0.58	0.55	0.61
WID-102-018	Horizon Sliding Window	3.96	0.61	0.58	0.64
WID-106-017	Horizon Fixed Window	3.10	0.71	0.68	0.75
WID-122-017	Paragon Entry Door	3.92	0.51	0.49	0.54
WID-124-018	Paragon Stacking Door	4.05	0.58	0.55	0.61

Window and glazed door schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orient-ation	Shading device*
BED1	WID-101-032	W205	1030	3010	Awning	10	E	None
BED4	WID-101-032	W201	1030	3000	Awning	10	W	None
BED4	WID-106-017	W202	1030	610	Fixed	0	S	None
GST BATH	WID-101-032	W107	1030	610	Awning	90	N	None
GUEST ROOM	WID-102-018	W106	1030	1810	Sliding	45	N	None
KITCHBN/LIVING	WID-101-032	W105	2400	2400	Awning	25	E	None
KITCHBN/LIVING	WID-106-017	W103	600	2410	Fixed	0	S	None
KITCHBN/LIVING	WID-124-018	D103	2850	3580	Sliding Door	59	E	None

* Refer to glossary.



Window and glazed door *schedule*

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orient-ation	Shading device*
LOUNGE	WID-101-032	W102	2050	610	Awning	60	W	None
LOUNGE	WID-101-032	W101	2050	610	Awning	60	W	None
PANTRY	WID-101-032	W104	2400	610	Awning	64	E	None
bath	WID-101-032	W208	395	1570	Awning	45	N	None
bed 2	WID-101-032	W207	860	2410	Awning	10	N	None
bed 3	WID-101-032	W209	860	2410	Awning	10	N	None
ensuite	WID-101-032	W206	1030	1570	Awning	45	N	None
family	WID-106-017	W204	1030	1810	Fixed	0	S	None
family	WID-102-018	W203	600	3010	Sliding	42	S	None
laundry	WID-122-017	D102	2120	900	Casement	90	S	None

Roof window *type and performance value*

Default* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

Custom* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

Roof window *schedule*

Location	Window ID	Window no.	Opening %	Height (mm)	Width (mm)	Orient-ation	Outdoor shade	Indoor shade
None								

Skylight *type and performance*

Skylight ID	Skylight description
None	

Skylight schedule

Location	Skylight ID	Skylight No.	Skylight shaft length (mm)	Area (m ²)	Orientation	Outdoor shade	Diffuser	Shaft Reflectance
None								

External door schedule

Location	Height (mm)	Width (mm)	Opening %	Orientation
ENTRY	2360	1275	90	W
GARAGE	2265	4817	90	W

External wall type

Wall ID	Wall Type	Solar absorptance	Wall Colour	Bulk insulation (R-value)	Reflective wall wrap*
CONC-100-PB	Precast 100mm Concrete - Plasterboard Internally	0.50	Medium	0.00	No
Sekisui Nichiha Cladding Walls-A	Sekisui Nichiha Cladding Walls - Fibre-Cement Clad Battened (Refl Cavity) Stud Wall	0.50	Medium	3.10	Yes
Sekisui Nichiha Cladding Walls-B	Sekisui Nichiha Cladding Walls - Fibre-Cement Clad Battened (Refl Cavity) Stud Wall	0.50	Medium	0.00	Yes

External wall schedule

Location	Wall ID	Height (mm)	Width (mm)	Orientation	Horizontal shading feature* projection (mm)	Vertical shading feature
BED1	Sekisui Nichiha Cladding Walls-A	1780	3605	E	460	No
BED4	Sekisui Nichiha Cladding Walls-A	2135	2580	S	460	Yes
BED4	Sekisui Nichiha Cladding Walls-A	2510	3480	W	459	No
BED4	Sekisui Nichiha Cladding Walls-A	2510	1020	S	460	Yes
ENTRY	Sekisui Nichiha Cladding Walls-A	2510	1658	W		Yes
GARAGE	Sekisui Nichiha Cladding Walls-B	2510	5880	S	237	Yes
GARAGE	Sekisui Nichiha Cladding Walls-B	2510	5881	W	1236	Yes
GST BATH	Sekisui Nichiha Cladding Walls-A	2510	2280	N	240	Yes
GUEST ROOM	Sekisui Nichiha Cladding Walls-A	2510	3781	N	240	Yes
KITCHBN/LIVING	Sekisui Nichiha Cladding Walls-A	2850	3088	E	200	Yes

External wall *schedule*

Location	Wall ID	Height (mm)	Width (mm)	Orientation	Horizontal shading feature* projection (mm)	Vertical shading feature
KITCHBN/LIVING	Sekisui Nichiha Cladding Walls-A	2850	4695	S	176	Yes
KITCHBN/LIVING	Sekisui Nichiha Cladding Walls-A	2850	4695	N	240	Yes
KITCHBN/LIVING	Sekisui Nichiha Cladding Walls-A	2850	5601	E	3186	Yes
KITCHBN/LIVING	CONC-100-PB	340	3307	W		No
KITCHBN/LIVING	CONC-100-PB	2400	1318	N		No
KITCHBN/LIVING	CONC-100-PB	2400	4188	W		No
LOUNGE	Sekisui Nichiha Cladding Walls-A	2510	3187	N	240	Yes
LOUNGE	Sekisui Nichiha Cladding Walls-A	2510	1217	S	6567	Yes
LOUNGE	Sekisui Nichiha Cladding Walls-A	2510	2579	W	1175	Yes
PANTRY	Sekisui Nichiha Cladding Walls-A	2850	2881	N	5543	Yes
PANTRY	Sekisui Nichiha Cladding Walls-A	2850	1699	E	196	Yes
PANTRY	Sekisui Nichiha Cladding Walls-A	2850	2879	S	175	Yes
WIR	Sekisui Nichiha Cladding Walls-A	2135	2280	S	460	Yes
WIR	Sekisui Nichiha Cladding Walls-A	2135	600	W	2223	Yes
bath	Sekisui Nichiha Cladding Walls-A	1955	1695	N	460	Yes
bed 2	Sekisui Nichiha Cladding Walls-A	1955	3780	N	460	Yes
bed 3	Sekisui Nichiha Cladding Walls-A	1955	3075	N	460	Yes
bed 3	Sekisui Nichiha Cladding Walls-A	2510	3091	W	1059	Yes
ensuite	Sekisui Nichiha Cladding Walls-A	1955	3173	N	460	Yes
ensuite	Sekisui Nichiha Cladding Walls-A	2510	1991	E	460	No
ensuite	Sekisui Nichiha Cladding Walls-A	1780	1100	E	460	No
family	Sekisui Nichiha Cladding Walls-A	2135	2400	S	1060	Yes
family	Sekisui Nichiha Cladding Walls-A	2135	600	E	2223	Yes
family	Sekisui Nichiha Cladding Walls-A	2135	3391	S	460	Yes
laundry	Sekisui Nichiha Cladding Walls-A	2850	2269	S	191	Yes

* Refer to glossary.

External wall *schedule*

Location	Wall ID	Height (mm)	Width (mm)	Orient-ation	Horizontal shading feature* projection (mm)	Vertical shading feature
laundry	CONC-100-PB	340	2070	W		No
laundry	CONC-100-PB	340	1295	N		No
laundry	CONC-100-PB	340	801	W		No
wc	Sekisui Nichiha Cladding Walls-A	1955	1531	N	460	Yes
wir	Sekisui Nichiha Cladding Walls-A	1780	1380	E	460	No
wir	Sekisui Nichiha Cladding Walls-A	2135	2273	S	460	Yes
wir 3	Sekisui Nichiha Cladding Walls-A	2510	600	N	3641	Yes
wir 3	Sekisui Nichiha Cladding Walls-A	2510	1500	W	459	Yes

Internal wall *type*

Wall ID	Wall Type	Area (m ²)	Bulk insulation
INT-PB	Internal Plasterboard Stud Wall	142.9	0.00
INT-PB	Internal Plasterboard Stud Wall	32.8	2.50
INT-PB-EXP1	Internal Plasterboard Stud Wall (exposed 1 side)	17.1	3.10

Floor *type*

Location	Construction	Area (m ²)	Sub-floor ventilation	Added insulation (R-value)	Covering
BED1	TIMB-001: Suspended Timber Floor	16.8	N/A	0.15	Carpet
BED4	TIMB-001: Suspended Timber Floor	8.4	N/A	4.00	Carpet
BED4	TIMB-002: Suspended Timber Floor - Lined Below	4.1	N/A	4.00	Carpet
ENTRY	WAFFLE-85: Concrete Waffle Pod Slab on Ground (85mm)	10.5	N/A	0.59	Tile (8mm)
GARAGE	WAFFLE-85: Concrete Waffle Pod Slab on Ground (85mm)	38.9	N/A	0.59	Tile (8mm)
GST BATH	WAFFLE-85: Concrete Waffle Pod Slab on Ground (85mm)	5.5	N/A	0.59	Tile (8mm)
GUEST ROOM	WAFFLE-85: Concrete Waffle Pod Slab on Ground (85mm)	12.0	N/A	0.59	Carpet
KITCHBN/LIVING	WAFFLE-85: Concrete Waffle Pod Slab on Ground (85mm)	53.8	N/A	0.59	Tile (8mm)
LOUNGE	WAFFLE-85: Concrete Waffle Pod Slab on Ground (85mm)	8.2	N/A	0.59	Tile (8mm)



Floor type

Location	Construction	Area (m ²)	Sub-floor ventilation	Added insulation (R-value)	Covering
PANTRY	WAFFLE-85: Concrete Waffle Pod Slab on Ground (85mm)	4.9	N/A	0.59	Tile (8mm)
WIR	TIMB-001: Suspended Timber Floor	3.1	N/A	0.15	Carpet
bath	TIMB-001: Suspended Timber Floor	6.7	N/A	0.15	Tile (8mm)
bed 2	TIMB-001: Suspended Timber Floor	11.7	N/A	0.15	Carpet
bed 3	TIMB-001: Suspended Timber Floor	8.6	N/A	0.15	Carpet
bed 3	TIMB-002: Suspended Timber Floor - Lined Below	0.8	N/A	4.00	Carpet
ensuite	TIMB-001: Suspended Timber Floor	9.8	N/A	0.15	Tile (8mm)
family	TIMB-001: Suspended Timber Floor	9.7	N/A	0.15	Carpet
family	TIMB-001: Suspended Timber Floor	22.0	N/A	4.00	Carpet
laundry	WAFFLE-85: Concrete Waffle Pod Slab on Ground (85mm)	5.5	N/A	0.59	Tile (8mm)
wc	TIMB-001: Suspended Timber Floor	2.3	N/A	0.15	Tile (8mm)
wir	TIMB-001: Suspended Timber Floor	3.1	N/A	0.15	Carpet
wir 3	TIMB-001: Suspended Timber Floor	0.2	N/A	0.15	Carpet
wir 3	TIMB-001: Suspended Timber Floor	0.8	N/A	4.00	Carpet
wir 3	TIMB-002: Suspended Timber Floor - Lined Below	1.9	N/A	4.00	Carpet

Ceiling type

Location	Construction	Bulk insulation (R-value)	Reflective wrap*
BED1	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
BED4	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
GARAGE	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	0.00	Yes
GST BATH	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
GUEST ROOM	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
KITCHBN/LIVING	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
LOUNGE	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes

* Refer to glossary.

Ceiling type

Location	Construction	Bulk insulation (R-value)	Reflective wrap*
PANTRY	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
WIR	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
bath	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
bed 2	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
bed 3	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
ensuite	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
family	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
laundry	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
wc	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
wir	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes
wir 3	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	6.00	Yes

Ceiling penetrations*

Location	Quantity	Type	Diameter (mm)	Sealed /unsealed
BED1	3	Downlight	150	Sealed
BED4	3	Downlight	150	Sealed
ENTRY	3	Downlight	150	Sealed
GST BATH	1	Downlight	150	Sealed
GST BATH	1	Exhaust Fan	200	Sealed
GUEST ROOM	2	Downlight	150	Sealed
KITCHBN/LIVING	10	Downlight	150	Sealed
KITCHBN/LIVING	1	Exhaust Fan	200	Sealed
LOUNGE	2	Downlight	150	Sealed
PANTRY	1	Downlight	150	Sealed
WIR	1	Downlight	150	Sealed

* Refer to glossary.

Ceiling penetrations*

Location	Quantity	Type	Diameter (mm)	Sealed /unsealed
bath	1	Downlight	150	Sealed
bath	1	Exhaust Fan	200	Sealed
bed 2	2	Downlight	150	Sealed
bed 3	2	Downlight	150	Sealed
ensuite	2	Downlight	150	Sealed
ensuite	1	Exhaust Fan	200	Sealed
family	6	Downlight	150	Sealed
laundry	1	Downlight	150	Sealed
wc	1	Downlight	150	Sealed
wc	1	Exhaust Fan	200	Sealed
wir	1	Downlight	150	Sealed
wir 3	1	Downlight	150	Sealed

Ceiling fans

Location	Quantity	Diameter (mm)
BED1	1	1200
BED4	1	1200
GUEST ROOM	1	1200
bed 2	1	1200
bed 3	1	1200

Roof type

Construction	Added insulation (R-value)	Solar absorptance	Roof Colour
ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	1.80	0.50	Medium

Thermal bridging schedule for steel frame elements

Building element	Steel section dimensions (height x width, mm)	Frame spacing (mm)	Steel thickness (BMT mm)	Thermal Break (R-value)
None				



Appliance *schedule*

(not applicable if a Whole of Home performance assessment is not conducted for this certificate)

Cooling system

Type	Location	Fuel Type	Minimum efficiency / performance	Recommended capacity
------	----------	-----------	----------------------------------	----------------------

No Whole of Home Data

Heating system

Type	Location	Fuel Type	Minimum efficiency / performance	Recommended capacity
------	----------	-----------	----------------------------------	----------------------

No Whole of Home Data

Hot water system

Type	Fuel type	Hot Water CER Zone	Minimum efficiency / STC	Assessed daily load [litres]
------	-----------	--------------------	--------------------------	------------------------------

No Whole of Home Data

Pool / spa equipment

Type	Fuel type	Minimum efficiency / performance	Recommended capacity
------	-----------	----------------------------------	----------------------

No Whole of Home Data

Onsite Renewable Energy *schedule*

Type	Orientatation	Generation Capacity [kW]
------	---------------	--------------------------

No Whole of Home Data

Battery *schedule*

Type	Storage Capacity [kWh]
------	------------------------

No Whole of Home Data

Explanatory Notes

About this report

NatHERS ratings are a reliable guide for comparing different dwelling designs and to demonstrate that designs meet the energy efficiency requirements in the National Construction Code.

NatHERS ratings use computer modelling to evaluate a home's energy efficiency and performance. They use localised climate data and standard assumptions on how people use their home to predict the heating and cooling energy loads and energy value* of the whole home. The thermal performance star rating uses the home's building specifications, layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings) to predict the heating and cooling energy loads. The Whole of Home performance rating uses information about the home's appliances and onsite energy generation and storage to estimate the home's energy value*.

The actual energy loads, cost and greenhouse gas emissions of a home may vary from that predicted. This is because the assumptions will not always match the actual occupant usage patterns. For example, the number of occupants and how people use their appliances will vary.

Energy efficient homes use less energy, are warmer on cool days, cooler on hot days and cost less to run.

Accredited assessors

For quality assured NatHERS Certificates, always use an accredited or licenced assessor registered with an Assessor Accrediting Organisation (AAO). AAOs have strict quality assurance processes, and professional development requirements ensuring consistently high standards for assessments.

Non-accredited assessors (Raters) have no ongoing training requirements and

are not quality assured.

Any queries about this report should be directed to the assessor. If the assessor is unable to address questions or concerns, contact the AAO specified on the front of this certificate.

Disclaimer

The NatHERS Certificate format is developed by the NatHERS Administrator. However, the content in the certificate is entered by the assessor. It is the assessor's responsibility to use NatHERS accredited software correctly and follow the NatHERS Technical Note to produce a NatHERS Certificate.

The predicted annual energy load, cost and greenhouse gas emissions in this NatHERS Certificate are an estimate based on an assessment of the dwelling's design by the assessor. It is not a prediction of actual energy use, cost or emissions. The information and ratings may be used to compare how other dwellings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, behaviour, appliance performance, indoor air temperature and local climate.

Not all assumptions made by the assessor using the NatHERS accredited software tool are presented in this report and further details or data files may be obtained from the assessor.

Glossary

Annual energy load	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
AFRC	Australian Fenestration Rating Council
Assessed floor area	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
Ceiling penetrations	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, range hoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
Conditioned	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
COP	Coefficient of performance
Custom windows	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
Default windows	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
EER	Energy Efficiency Ratio, measure of how much cooling can be achieved by an air conditioner for a single kWh of electricity input
Energy use	This is your home's rating without solar or batteries.
Energy value	The net cost to society including, but not limited to, costs to the building user, the environment and energy networks (as defined in the ABCB Housing Provisions Standard).
Entrance door	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
Exposure	see exposure categories below
Exposure category - exposed	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
Exposure category - open	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
Exposure category - suburban	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
Exposure category - protected	terrain with numerous, closely spaced obstructions over 10 m e.g. city and industrial areas.
Horizontal shading feature	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
National Construction Code (NCC) Class	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at www.abcb.gov.au .
Net zero home	a home that achieves a net zero energy value*.
Opening percentage	the openability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
Provisional value	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at www.nathers.gov.au
Recommended capacity	this is the capacity or size of equipment that is recommended by NatHERS to achieve the desired comfort conditions in the zone or zones serviced. This is a recommendation and the final selection sizing should be confirmed by a suitably qualified person.
Reflective wrap (also known as foil)	can be applied to walls, roofs and ceilings. When combined with an appropriate airgap and emissivity value, it provides insulative properties.
Roof window	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
Shading features	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
Solar heat gain coefficient (SHGC)	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
Skylight (also known as roof lights)	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.
STCs	Small-scale Technology Certificates, certificates created by the REC registry for renewable energy technologies that may be bought and sold as part of the Small-scale Renewable Energy Scheme operated by the Clean Energy Regulatory
Thermal breaks	are materials with an R-value greater than or equal to 0.2 that must separate the metal frame from the cladding. This includes, but is not limited to, materials such as timber battens greater than or equal to 20mm thick, continuous thermal breaks such as polystyrene insulation sheeting, plastic strips or furring channels.
U-value	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
Unconditioned	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions
Vertical shading features	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).
Window shading device	a device fixed to windows that provides shading e.g. window awnings or screens but excludes horizontal* or vertical shading features* (eg eaves and balconies)

* Refer to glossary.