BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A281022 04

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Sunday, 03, February 2019

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project address Project name Jacobsen Residence 04 Street address 13 Dress Circle Road Avalon Beach 2107 Local Government Area Pittwater Council Deposited Plan 102459 Plan type and number В Lot number Section number 0 Project type Separate dwelling house Dwelling type Type of alteration and My renovation work is valued at \$50,000 or more, addition and does not include a pool (and/or spa).

escriptio

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Michael Airey Building Design & Drafting

ABN (if applicable): 26 769 291 556

BASIX Certificate number: A281022_04 page 2 / 5

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
The applicant must construct the new or altere the table below, except that a) additional insula is not required for parts of altered construction	✓	✓	<		
Construction	Additional insulation required (R-value)	Other specifications			
concrete slab on ground floor.	nil				
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				
flat ceiling, pitched roof	ceiling: R1.45 (up), roof: foil backed blanket (55 mm)	medium (solar absorptance 0.475 - 0.70)			

BASIX Certificate number: A281022_04 page 3 / 5

Glazing re	equirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows a	and glazed d	oors							
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.							~	✓	✓
The following requirements must also be satisfied in relation to each window and glazed door:							✓	✓	
Each window or glazed door with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.								✓	✓
For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.							✓	✓	✓
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.							✓	✓	
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.							✓	✓	
Overshadowing buildings or vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column in the table below.						✓	✓	✓	
Windows	and glazed	doors g	lazing r	equireme	nts				
Window / do	oor Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	Distance (m)	Shading device	Frame and glass type			
W1	SW	4.5	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
W2	SW	0.6	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
W3	SE	1.5	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
W4	NE	1.5	4	4.2	eave/verandah/pergola/balcony >=600 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			

BASIX Certificate number: A281022_04 page 4 / 5

Glazing requirements								Show on CC/CDC Plans & specs	Certifier Check
Window / door Orientation Area of O			• Overshadowing		Shading device	Frame and glass type			
no.		glass inc. frame (m2)	Height (m)	Distance (m)					
W5	SE	1.5	8	1.6	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
D1	SW	1.89	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
D2	SW	3.78	0	0	eave/verandah/pergola/balcony >=600 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
D3	NE	3.78	7	9	eave/verandah/pergola/balcony >=600 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
D4	NE	10.29	0	0	eave/verandah/pergola/balcony >=600 mm	timber or uPVC, single toned, (or U-value: 5.67, SHGC: 0.49)			
D5	NE	6.47	0	0	eave/verandah/pergola/balcony >=900 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
D6	NE	10.29	0	0	eave/verandah/pergola/balcony >=600 mm	timber or uPVC, single toned, (or U-value: 5.67, SHGC: 0.49)			

BASIX Certificate number: A281022_04 page 5 / 5

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
" in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.