page 1/4

BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A487711 02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv

Date of issue: Wednesday, 05, April 2023 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project address				
Project name	103 King_02			
Street address	103 King Street Manly Vale 2093Northern Beaches CouncilDeposited Plan 2455972			
Local Government Area				
Plan type and number				
Lot number				
Section number				
Project type				
Project type Dwelling type	Separate dwelling house			

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Nick Gordon

ABN (if applicable): N/A

Glazing r	equirements	_					Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows	and glazed do	ors					l	l	
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.						~	~	~	
The following requirements must also be satisfied in relation to each window and glazed door:						\checkmark	\checkmark		
have a U-v	alue and a Solar	Heat Gair	n Coefficie	ent (SHGC) ı		ed glass may either match the description, or, le below. Total system U-values and SHGCs s.		~	~
For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.					\checkmark	~	~		
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.						\checkmark	\checkmark		
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.						\checkmark	\checkmark		
Windows	s and glazed o	doors g	lazing r	equireme	nts		-		
	door Orientation		Overshadowing		Shading device	Frame and glass type			
no.		glass inc. frame (m2)	Height (m)	Distance (m)					
W1	N	1.44	0	0	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W2	S	1.08	0	0	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W3	W	1.68	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
D1	W	9.66	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
D2	N	0.5	0	0	eave/verandah/pergola/balcony	standard aluminium, single clear, (or		1	

BASIX Certificate number: A487711_02

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.