

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1051030S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Tuesday, 15 October 2019

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary	
Project name	11 Farnell Street, Curl Curl
Street address	11 Farnell Street Curl Curl 2096
Local Government Area	Northern Beaches Council
Plan type and plan number	deposited 595584
Lot no.	867
Section no.	n/a
Project type	attached dwelling house
No. of bedrooms	2
Project score	
Water	✓ 40 Target 40
Thermal Comfort	✓ Pass Target Pass
Energy	✓ 50 Target 50

Certificate	Prepared	by
-------------	-----------------	----

Name / Company Name: Certified Energy

ABN (if applicable): 95164564210

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1051030S Tuesday, 15 October 2019 page 1/9

Description of project

Project address				
Project name	11 Farnell Street, Curl Curl			
Street address	11 Farnell Street Curl Curl 2096			
Local Government Area	Northern Beaches Council			
Plan type and plan number	Deposited Plan 595584			
Lot no.	867			
Section no.	n/a			
Project type				
Project type	attached dwelling house			
No. of bedrooms 2				
Site details				
Site area (m²)	505			
Roof area (m²)	98			
Conditioned floor area (m2)	69.0			
Unconditioned floor area (m2)	6.0			
Total area of garden and lawn (m2)	20			

Assessor details and thermal loads							
Assessor number	n/a						
Certificate number	n/a						
Climate zone	n/a						
Area adjusted cooling load (MJ/m².year)	n/a						
Area adjusted heating load (MJ/m².year)	n/a						
Project score							
Water	✓ 40	Target 40					
Thermal Comfort	Pass	Target Pass					
Energy	V 50	Target 50					

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1051030S Tuesday, 15 October 2019 page 2/9

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 3 star (> 4.5 but <= 6 L/min) in all showers in the development.		✓	V
The applicant must install a toilet flushing system with a minimum rating of 3 star in each toilet in the development.		~	V
The applicant must install taps with a minimum rating of 3 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 3 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 2000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	→	~
The applicant must configure the rainwater tank to collect rain runoff from at least 60 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	V
The applicant must connect the rainwater tank to:			
all toilets in the development		✓	•
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	V

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1051030S Tuesday, 15 October 2019 page 3/9

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	V	~	-
The conditioned floor area of the dwelling must not exceed 300 square metres.	V	~	V
The dwelling must not contain open mezzanine area exceeding 25 square metres.	V	~	V
The dwelling must not contain third level habitable attic room.	V	V	V
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	V	V	V

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground, 41 square metres	nil	
floor - suspended floor above enclosed subfloor, 32 square metres, concrete	1.20 (or 1.8 including construction) (down)	
external wall - cavity brick	0.50 (or 1.17 including construction)	
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 5 (up), roof: foil/sarking	framed; medium (solar absorptance 0.475-0.70)

Note	Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1051030S Tuesday, 15 October 2019 page 4/9

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	V	~	V
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	>	V
The following requirements must also be satisfied in relation to each window and glazed door:	V	✓	V
 For the following glass and frame types, the certifier check can be performed by visual inspection. 			-
- Aluminium single clear			
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			
• Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.		~	V
 Unless they have adjustable shading, pergolas must have fixed battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not exceed the height of the battens. 		~	~
 Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column. 	V	~	V

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North facing					
G9	1040	800	aluminium, single, clear	none	>4 m high, <2 m away
G10	2100	900	aluminium, single, clear	pergola (fixed battens) 9000 mm, 100 mm above head of window or glazed door	>4 m high, <2 m away
East facing		1			

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1051030S Tuesday, 15 October 2019 page 5/9

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
G1	2100	3200	aluminium, single, clear	solid overhang 3800 mm, 150 mm above head of window or glazed door	not overshadowed
G2	2100	3200	aluminium, single, clear	solid overhang 3800 mm, 150 mm above head of window or glazed door	not overshadowed
South facing					
G3	1040	1800	aluminium, single, clear	none	>4 m high, <2 m away
G4	1040	1800	aluminium, single, clear	none	>4 m high, <2 m away
G5	1040	1800	aluminium, single, clear	none	>4 m high, <2 m away

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1051030S Tuesday, 15 October 2019 page 6/9

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water		<u>'</u>	
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 6 stars.	•	✓	V
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 5 Star		→	V
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 5 Star		y	V
The cooling system must provide for day/night zoning between living areas and bedrooms.		✓	V
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 5 Star		→	V
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 5 Star		V	V
The heating system must provide for day/night zoning between living areas and bedrooms.		~	V
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, not ducted; Operation control: manual switch on/off		✓	-
Kitchen: individual fan, not ducted; Operation control: manual switch on/off		•	-
Laundry: individual fan, not ducted; Operation control: manual switch on/off		•	-
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
at least 2 of the bedrooms / study; dedicated		_	

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1051030S Tuesday, 15 October 2019 page 7/9

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
at least 1 of the living / dining rooms; dedicated		~	~
• the kitchen; dedicated		~	V
all bathrooms/toilets; dedicated		_	_
the laundry; dedicated			
all hallways; dedicated			V
Natural lighting			
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.		~	V
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		→	
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.			

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1051030S Tuesday, 15 October 2019 page 8/9

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

BASIX Planning & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_10_0 Certificate No.: 1051030S Tuesday, 15 October 2019 page 9/9