

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1350189S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

BASIX

Date of issue: Thursday, 15 December 2022

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary			
Project name	27 PHILIP ROAD, MONA VALE		
Street address	27 Philip Road Mona Vale 2103		
Local Government Area	Northern Beaches Council		
Plan type and plan number	deposited 200907		
Lot no.	2		
Section no.	-		
Project type	separate dwelling house - secondary dwelling		
No. of bedrooms	1		
Project score			
Water	√ 40 Target 40		
Thermal Comfort	✓ Pass Target Pass		
Energy	✓ 50 Target 50		

Certificate Prepared by
Name / Company Name: rkdesigns
ABN (if applicable): 39330033053

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1350189S Thursday, 15 December 2022 page 1/9

Description of project

BASIX

Project address	
Project name	27 PHILIP ROAD, MONA VALE
Street address	27 Philip Road Mona Vale 2103
Local Government Area	Northern Beaches Council
Plan type and plan number	Deposited Plan 200907
Lot no.	2
Section no.	-
Project type	
Project type	separate dwelling house - secondary dwelling
No. of bedrooms	1
Site details	
Site area (m²)	1809
Roof area (m²)	94
Conditioned floor area (m2)	46.0
Unconditioned floor area (m2)	12.0
Total area of garden and lawn (m2)	40
Roof area (m2) of the existing dwelling	230
No. of bedrooms in the existing dwelling	4

Assessor details and thermal le	oads	
Assessor number	n/a	
Certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m².year)	n/a	
Area adjusted heating load (MJ/m².year)	n/a	
Ceiling fan in at least one bedroom	n/a	
Ceiling fan in at least one living room or other conditioned area	n/a	
Project score		
Water	✓ 40	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 50	Target 50

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1350189S Thursday, 15 December 2022 page 2/9

Schedule of BASIX commitments

BASIX

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	V
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		~	V
The applicant must install taps with a minimum rating of 6 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 6 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 1500 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	V
The applicant must configure the rainwater tank to collect rain runoff from at least 230 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	V
The applicant must connect the rainwater tank to:			
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	V

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1350189S Thursday, 15 December 2022 page 3/9

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	V	✓	-
The conditioned floor area of the dwelling must not exceed 300 square metres.	V	V	V
The dwelling must not contain open mezzanine area exceeding 25 square metres.	V	V	V
The dwelling must not contain third level habitable attic room.	~	~	V
Floor, walls and ceiling/roof		'	
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	-

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - other/undecided	2.40 (including construction)	
ceiling and roof - raked ceiling / pitched or skillion roof, framed	ceiling: 3.5 (up), roof: foil/sarking	framed; medium (solar absorptance 0.475-0.70)

Note	Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1350189S Thursday, 15 December 2022 page 4/9

BASIX

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	~	~
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	V
The following requirements must also be satisfied in relation to each window and glazed door:	~	V	V
• For the following glass and frame types, the certifier check can be performed by visual inspection.			-
- Aluminium single clear			
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North-East facing					
W01	600	1450	aluminium, single, clear	eave 450 mm, 849 mm above head of window or glazed door	not overshadowed
South-East facing					
W02	700	2200	aluminium, single, clear	eave 450 mm, 912 mm above head of window or glazed door	not overshadowed
South-West facing					
W03	400	1450	aluminium, single, clear	eave 450 mm, 693 mm above head of window or glazed door	not overshadowed
W04	400	1210	aluminium, single, clear	eave 450 mm, 1018 mm above head of window or glazed door	not overshadowed
W05	400	1450	aluminium, single, clear	eave 450 mm, 864 mm above head of window or glazed door	not overshadowed
North-West facing	1	1		1	

BASIX

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1350189S Thursday, 15 December 2022 page 5/9

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
W06	1800	1000	aluminium, single, clear	eave 450 mm, 495 mm above head of window or glazed door	not overshadowed
W07	2100	3030	aluminium, single, clear	eave 2450 mm, 934 mm above head of window or glazed door	not overshadowed
W08	1800	1000	aluminium, single, clear	eave 450 mm, 495 mm above head of window or glazed door	not overshadowed

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1350189S Thursday, 15 December 2022 page 6/9

BASIX

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric heat pump with a performance of 36 to 40 STCs or better.	~	~	
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: ceiling fans + 1-phase airconditioning; Energy rating: EER 3.5 - 4.0		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: ceiling fans; Energy rating: n/a		~	V
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: EER 3.5 - 4.0		~	~
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	V
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	-
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		~	~
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		V	V
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
at least 2 of the bedrooms / study; dedicated		_	V
at least 1 of the living / dining rooms; dedicated		•	V
the kitchen; dedicated			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1350189S Thursday, 15 December 2022 page 7/9

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
all bathrooms/toilets; dedicated		•	V
• the laundry; dedicated		✓	-
all hallways; dedicated		✓	•
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	-	→	-
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.	-	•	-
Other			
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		-	
The applicant must install a fixed outdoor clothes drying line as part of the development.		→	
The applicant must install a fixed indoor or sheltered clothes drying line as part of the development.			

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1350189S Thursday, 15 December 2022 page 8/9

BASIX

Legend

BASIX

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1350189S Thursday, 15 December 2022 page 9/9