
CIVIL WORKS PACKAGE FOR 4 MINNA CLOSE, BELROSE NSW 2085 DEVELOPMENT APPLICATION

GENERAL	
22-1016-DAC000	COVER SHEET AND LOCALITY PLAN
22-1016-DAC001	GENERAL NOTES
22-1016-DAC002	EXISTING SITE PLAN
22-1016-DAC003	GENERAL ARRANGMENT PLAN
22-1016-DAC004	BULK EARTHWORKS PLAN
SITE SECTIONS	
22-1016-DAC010	SITE SECTIONS
SITEWORKS DRAINAGE	
22-1016-DAC020	SITEWORKS AND STORMWATER DRAINAGE PLAN
22-1016-DAC025	SITEWORKS AND STORMWATER DETAILS SHEET 1
22-1016-DAC026	SITEWORKS AND STORMWATER DETAILS SHEET 2
22-1016-DAC027	SITEWORKS AND STORMWATER DETAILS SHEET 3
PAVEMENT	
22-1016-DAC030	PAVEMENT PLAN
STORMWATER DRAINAGE	
22-1016-DAC042	OSD PLAN AND SECTIONS
22-1016-DAC045	STORMWATER DRAINAGE LONGITUDINAL SECTIONS
22-1016-DAC050	STORMWATER DRAINAGE CATCHMENT PLAN
22-1016-DAC055	MUSIC CATCHMENT PLAN
EROSION AND SEDIMENT CONTROL	
22-1016-DAC060	SEDIMENTATION AND EROSION CONTROL PLAN
22-1016-DAC065	SEDIMENTATION AND EROSION CONTROL DETAILS

		Bar Scales
В	ISSUE FOR APPROVAL	17-04-2024
А	ISSUE FOR APPROVAL	17-05-2023
Issue	Description	Date
		100mm on Original



	Client		Scales		Drawn	JS	Projec
THIS DRAWING CANNOT BE				NTS	Designed	SM	1
			Grid	GDA2020	Checked	SM	1
ANY FORM OR USED FOR ANY OTHER PURPOSE OTHER THAN		WU PROPERTIES	Height Datum	AHD	Approved	GJ	Title
THAT ORIGINALLY INTENDED WITHOUT THE WRITTEN PERMISSION OF AT&L							Three

F:\22-1016 4 Minna Close Belrose\6.0 Drgs\Civil\Final\22-1016-DAC000.dwg

Project - Drawing No.

22-1016-DAC000

Issue

В

SURVEY NOTES

THE EXISTING SITE CONDITIONS SHOWN ON THE FOLLOWING DRAWINGS HAVE BEEN INVESTIGATED BY SDG, BEING

REGISTERED SURVEYORS. THE INFORMATION IS SHOWN TO PROVIDE A BASIS FOR DESIGN. AT & L DOES NOT GUARANTEE THE ACCURACY OR COMPLETENESS OF THE SURVEY BASE OR ITS SUITABILITY AS A BASIS FOR CONSTRUCTION DRAWINGS.

SHOULD DISCREPANCIES BE ENCOUNTERED DURING CONSTRUCTION BETWEEN THE SURVEY DATA AND ACTUAL FIELD DATA, CONTACT AT & L.

THE FOLLOWING NOTES HAVE BEEN TAKEN DIRECTLY FROM THE ORIGINAL SURVEY DOCUMENTS.

GENERAL NOTES

- ONLY TREES GREATER THAN 3.5 METRES IN HEIGHT ARE SHOWN ON THIS PLAN AND THEIR POSITIONS ARE DIAGRAMMATIC ONLY AND MAY REQUIRE ADDITIONAL SURVEY WHERE CRITICAL TO DESIGN.
- CONTOURS ARE INDICATIVE AT GROUND FORM ONLY. SPOT LEVELS ONLY SHOULD BE USED FOR CALCULATIONS OF QUANTITIES WITH CAUTION.
- LEVELS ARE ON AUSTRALIAN HEIGHT DATUM (AHD).
- ALL SETOUT LEVELS MUST BE REFERRED TO THE BENCH MARK
- SHOWN ON THIS PLAN.

BOUNDARY NOTES

- A BASIC BOUNDARY SURVEY HAS BEEN DONE SUITABLE FOR DA LODGEMENT PURPOSES.
- BOUNDARIES HAVE NOT BEEN MARKED.
- SURVEY INFORMATION NOTES
- THE ORIGIN OF COORDINATES COMES FROM SSM88206 E333954.228 N6269239.469 CLASS C POSITIONAL UNCERTAINTY (PU) N/A (MGA2020) ADOPTED FROM SCIMS DATED 08/06/2021.
- THE ORIGIN OF LEVELS COMES FROM SSM75296 RL179.240 CLASS LC POSITIONAL UNCERTAINTY (PU) N/A ADOPTED FROM SCIMS DATED 08/06/2021.
- THE ORIENTATION OF THIS PLAN IS MGA NORTH WHICH HAS BEEN 10 DETERMINED BY A COORDINATE JOIN BETWEEN SSM88206 AND SSM75296.

CERTIFICATE OF TITLE NOTES

- THE FOLLOWING INFORMATION RELATES TO THE RESPECTIVE CERTIFICATE OF TITLE OF EACH LOTS:
- LOT 502 IN DP875858 (CT EDITION 9 DATED 18/10/2019 SEARCH DATE 01/06/2021) AFFECTED BY:
- RIGHT OF CARRIAGEWAY 4.0 WIDE (AE960449) RESTRICTION ON THE USE OF LAND (DP265029, DP852750,
- DP875858 & O897327) COVENANT (1909898 & DP265029)
- BENEFITED BY BY:
- EASEMENT FOR ACCESS AND DRAINAGE AND WATER MANAGEMENT (DP807013)
- COVENANTS AND RESTRICTIONS NOTED ON THE TITLE HAVE NOT BEEN INVESTIGATED. THESE SHOULD BE INVESTIGATED PRIOR TO DESIGN TO ENSURE ANY FUTURE DEVELOPMENT COMPLIES.

SERVICES NOTES

- 17. ONLY THOSE SERVICES VISIBLE AT THE TIME OF SURVEY HAVE BEEN LOCATED AND ARE QUALITY LEVEL A AS DEFINED BY AS 5488.1:2019.
- UNDERGROUND SERVICES HAVE BEEN PLOTTED FROM 'DIAL-BEFORE'YOU-DIG' PLANS, ARE QUALITY LEVEL D AS DEFINED BY AS 5488.1:2019 AND ARE ONLY CURRENT AT THE DATE OF SFARCH
- ALL RELEVANT AUTHORITIES MUST BE CONTACTED TO DETERMINE THE FULL EXTENT OF SERVICES PRIOR TO ANY PLANNING OR WORKS NEAR THE SITE.

EXISTING UNDERGROUND SERVICES NOTES

THE LOCATIONS OF UNDERGROUND SERVICES SHOWN IN THIS SET OF DRAWINGS HAVE BEEN PLOTTED FROM SURVEY INFORMATION AND SERVICE AUTHORITY INFORMATION. THE SERVICE INFORMATION HAS BEEN PREPARED ONLY TO SHOW THE APPROXIMATE POSITIONS OF ANY KNOWN SERVICES AND MAY NOT BE AS CONSTRUCTED OR ACCURATE. AT & L CAN NOT GUARANTEE THAT THE SERVICES INFORMATION SHOWN ON THESE DRAWINGS ACCURATELY

INDICATES THE PRESENCE OR ABSENCE OF SERVICES OR THEIR LOCATION AND WILL ACCEPT NO LIABILITY FOR INACCURACIES IN THE SERVICES INFORMATION SHOWN FROM ANY CAUSE WHATSOEVER. CONTRACTORS SHALL TAKE DUE CARE WHEN EXCAVATING ONSITE INCLUDING

HAND EXCAVATION WHERE NECESSARY

CONTRACTORS ARE TO CONTACT THE RELEVANT SERVICE AUTHORITY PRIOR TO COMMENCEMENT OF EXCAVATION WORKS.

CONTRACTORS ARE TO UNDERTAKE A SERVICES SEARCH, PRIOR TO COMMENCEMENT OF WORKS ON SITE. SEARCH RESULTS ARE TO BE KEPT ON SITE AT ALL TIMES.

SITEWORKS NOTES

- 1. ORIGIN OF LEVELS:- REFER SURVEY NOTES
- 2. CONTRACTOR MUST VERIFY ALL DIMENSIONS AND EXISTING LEVELS ON SITE PRIOR TO COMMENCEMENT OF WORK. ANY DISCREPANCIES TO BE REPORTED TO AT & L.
- 3. MAKE SMOOTH CONNECTION WITH EXISTING WORKS.
- 4. ALL TRENCH BACKFILL MATERIAL SHALL BE COMPACTED TO THE SAME DENSITY AS THE ADJACENT MATERIAL
- 5. ALL SERVICE TRENCHES UNDER VEHICULAR PAVEMENTS SHALL BE BACKFILLED WITH SAND TO 300mm ABOVE PIPE. WHERE PIPE IS UNDER PAVEMENTS BACKFILL REMAINDER OF TRENCH TO UNDERSIDE OF PAVEMENT WITH SAND OR APPROVED GRANULAR MATERIAL COMPACTED IN 150mm LAYERS TO MINIMUM 98% MODIFIED MAXIMUM DRY DENSITY IN ACCORDANCE WITH AS 1289 5.2.1. (OR A DENSITY INDEX OF NOT LESS THAN 75)
- 6. PROVIDE 10mm WIDE EXPANSION JOINTS BETWEEN BUILDINGS AND ALL CONCRETE OR UNIT PAVEMENTS.
- 7. ASPHALTIC CONCRETE SHALL CONFORM TO RMS. SPECIFICATION R116.
- 8. ALL BASECOURSE MATERIAL SHALL BE IGNEOUS ROCK QUARRIED MATERIAL TO COMPLY WITH RMS. FORM 3051 (UNBOUND), RMS. FORM 3052 (BOUND) COMPACTED TO MINIMUM 98% MODIFIED DENSITY IN ACCORDANCE WITH AS 1289 5.2.1 FREQUENCY OF COMPACTION TESTING SHALL NOT BE LESS THAN 1 TEST PER 50m³ OF BASECOURSE MATERIAL PLACED.
- 9. ALL SUB-BASE COURSE MATERIAL SHALL BE IGNEOUS ROCK QUARRIED MATERIAL TO COMPLY WITH RMS. FORM 3051, 3051.1 AND COMPACTED TO MINIMUM 98% MODIFIED DENSITY IN ACCORDANCE WITH A.S 1289 5.2.1 FREQUENCY OF COMPACTION TESTING SHALL NOT BE LESS THAN 1 TEST PER 50m OF SUB-BASE COURSE MATERIAL PLACED.
- 10. AS AN ALTERNATIVE TO THE USE OF IGNEOUS ROCK AS A SUB-BASE MATERIAL IN (9) A CERTIFIED RECYCLED CONCRETE MATERIAL COMPLYING WITH RMS. FORM 3051 AND 3051.1 WILL BE CONSIDERED. SUBJECT TO MATERIAL SAMPLES AND APPROPRIATE CERTIFICATIONS BEING PROVIDED TO THE SATISFACTION OF AT & L.
- 11. SHOULD THE CONTRACTOR WISH TO USE A RECYCLED PRODUCT THIS SHALL BE CLEARLY INDICATED IN THEIR TENDER AND THE PRICE DIFFERENCE BETWEEN AN IGNEOUS PRODUCT AND A RECYCLED PRODUCT SHALL BE CLEARLY INDICATED.
- 12. WHERE NOTED ON THE DRAWINGS THAT WORKS ARE TO BE CARRIED BY OTHERS, (eg. ADJUSTMENT OF SERVICES), THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CO-ORDINATION OF THESE WORKS.

- 2. ALL KERBS, GUTTERS, DISH DRAINS AND CROSSINGS TO BE CONSTRUCTED ON 100mm GRANULAR BASECOURSE COMPACTED TO MINIMUM 95% MODIFIED DRY DENSITY (AS 1289 5.2.1).
- 3. EXPANSION JOINTS (E.J) TO BE FORMED FROM 10mm COMPRESSIBLE CORK FILLER BOARD FOR THE FULL DEPTH OF THE SECTION AND CUT TO PROFILE. EXPANSION JOINTS TO BE LOCATED AT DRAINAGE PITS, ON TANGENT POINTS OF CURVES AND ELSEWHERE AT MAX 12m CENTRES EXCEPT FOR INTEGRAL KERBS WHERE THE EXPANSION JOINTS ARE TO MATCH THE JOINT LOCATIONS IN THE SLABS.

- EXISTING KERB AND GUTTER IS TO BE COMPLETELY REMOVED WHERE NEW KERB AND GUTTER IS SHOWN.

- 1% AEP 5% AFP

			Bar Sc
В	ISSUE FOR APPROVAL	17-04-2024	
Α	ISSUE FOR APPROVAL	17-05-2023	
ssue	Description	Date	
	100mm on Original		

KERBING NOTES

- 1. ALL CONCRETE TO HAVE A MINIMUM COMPRESSIVE STRENGTH OF 25 MPa U.N.O IN REINFORCED CONCRETE NOTES.
- 4. WEAKENED PLANE JOINTS TO BE MIN 3mm WIDE AND LOCATED AT 3m CENTRES EXCEPT FOR INTEGRAL KERBS WHERE THE WEAKENED PLANE JOINTS ARE TO MATCH THE JOINT LOCATIONS IN THE SLABS.
- 5. BROOMED FINISH TO ALL RAMPED AND VEHICULAR CROSSINGS. ALL OTHER KERBING OR DISH DRAINS TO BE STEEL FLOAT FINISHED.
- 6. IN THE REPLACEMENT OF KERB AND GUTTER : EXISTING ROAD PAVEMENT IS TO BE SAWCUT 900mm U.N.O FROM THE LIP OF GUTTER. UPON COMPLETION OF THE NEW KERB AND GUTTER NEW BASECOURSE AND SURFACE TO BE LAID 600mm WIDE U.N.O.
- EXISTING ALLOTMENT DRAINAGE PIPES ARE TO BE BUILT INTO THE NEW KERB AND GUTTER WITH 100mm DIA HOLE.

STORMWATER DRAINAGE NOTES


1. STORMWATER DESIGN CRITERIA

- (A) AVERAGE RECURRENCE INTERVAL: ROOFED AREAS TO SURCHARGE PIT EXTERNAL PAVEMENTS
- (B) RAINFALL INTENSITIES: TIME OF CONCENTRATION: 5 MINUTES 1% AEP = 269 mm/hr
- 5 % AEP = 210 mm/hr
- (C) RUNOFF COEFFICIENTS: C 100 ROOF AREAS: =10
- EXTERNAL PAVEMENTS: C 20 =0.95 . PIPES 300 DIA. AND LARGER TO BE REINFORCED CONCRETE CLASS '4'
- APPROVED SPIGOT AND SOCKET WITH RUBBER RING JOINTS. U.N.O. B. PIPES UP TO 300 DIA SHALL BE SEWER GRADE uPVC WITH SOLVENT
- WELDED JOINTS.
- EQUIVALENT STRENGTH VCP OR FRC PIPES MAY BE USED. 5. ALL STORMWATER DRAINAGE LINES UNDER PROPOSED BUILDING SLABS TO BE uPVC PRESSURE PIPE GRADE 6. ENSURE ALL VERTICALS AND DOWNPIPES ARE uPVC PRESSURE PIPE, GRADE 6 FOR A MIN OF 3.0m
- IN HEIGHT. 5. PIPES TO BE INSTALLED TO TYPE HS3 (ROAD) HS2 (LOTS) SUPPORT IN ACCORDANCE WITH AS 3725 (2007) IN ÀLL CASES BACKFILL TRENCH WITH SAND TO 300mm ABOVE PIPE. WHÉRE PIPE IS UNDER PAVEMENTS BACKFILL REMAINDER OF TRENCH TO UNDERSIDE OF PAVEMENT WITH SAND OR APPROVED GRANULAR MATERIAL COMPACTED IN 150mm LAYERS TO MINIMUM 98% STANDARD MAXIMUM DRY DENSITY IN ACCORDANCE WITH AS 1289 5.2.1. (OR A DENSITY INDEX OF NOT LESS THAN 75)
- ALL INTERNAL WORKS WITHIN PROPERTY BOUNDARIES ARE TO COMPLY WITH THE REQUIREMENTS OF AS 3500 3.1 (2006) AND AS/NZS 3500 3.2
- 8. PRECAST PITS MAY BE USED EXTERNAL TO THE BUILDING SUBJECT TO APPROVAL BY AT & L.
- 9. ENLARGERS, CONNECTIONS AND JUNCTIONS TO BE PREFABRICATED FITTINGS WHERE PIPES ARE LESS THAN 300 DIA.
- 10. WHERE SUBSOIL DRAINS PASS UNDER FLOOR SLABS AND VEHICULAR PAVEMENTS, UNSLOTTED uPVC SEWER GRADE PIPE IS TO BE USED.
- 11. CARE IS TO BE TAKEN WITH LEVELS OF STORMWATER LINES. GRADES SHOWN ARE NOT TO BE REDUCED WITHOUT APPROVAL. 12. GRATES AND COVERS SHALL CONFORM TO AS 3996.
- 13. ALL INTERNAL PIT DIMENSIONS TO CONFORM TO AS3500.3 TABLE 7.5.2.1
- 14. AT ALL TIMES DURING CONSTRUCTION OF STORMWATER PITS, ADEQUATE SAFETY PROCEDURES SHALL BE TAKEN TO ENSURE AGAINST THE
- POSSIBILITY OF PERSONNEL FALLING DOWN PITS. 5. ALL EXISTING STORMWATER DRAINAGE LINES AND PITS THAT ARE TO REMAIN ARE TO BE INSPECTED AND CLEANED. DURING THIS PROCESS ANY PART OF THE STORMWATER DRAINAGE SYSTEM THAT WARRANTS REPAIR SHALL BE REPORTED TO THE SUPERINTENDENT/ENGINEER FOR FURTHER DIRECTIONS.


JOINTING NOTES

PEDESTRIAN PAVEMENT JOINTS

- 1. ALL PEDESTRIAN PAVEMENTS ARE TO BE JOINTED AS FOLLOWS. (U.N.O) 2. EXPANSION JOINTS ARE TO BE LOCATED WHERE POSSIBLE AT TANGENT
- POINTS OF CURVES AND ELSEWHERE AT MAX. 6.0m CENTRES. 3. WEAKENED PLANE JOINTS ARE TO BE LOCATED AT A MAX. SPACING OF
- 1.5 x WIDTH OF THE PAVEMENT.
- 4. WHERE POSSIBLE JOINTS SHOULD BE LOCATED TO MATCH KERBING AND OR ADJACENT PAVEMENT JOINTS.
- 5. PEDESTRIAN PAVEMENT JOINT DETAIL



- VEHICULAR PAVEMENT JOINTS
- 6. ALL VEHICULAR PAVEMENTS TO BE JOINTED AS FOLLOWS. (U.N.O) 7. KEYED CONSTRUCTION JOINTS SHOULD GENERALLY BE LOCATED AT A MAX OF 6.0m CENTRES
- 8. SAWN JOINTS SHOULD GENERALLY BE LOCATED AT A MAX OF 6.0m CENTRES WITH DOWELED EXPANSION JOINTS AT MAX 18.0m CENTRES
- 9. VEHICULAR PAVEMENT JOINT DETAIL



CONCRETE NOTES

- 1. ALL WORKMANSHIP AND MATERIALS SHALL BE IN ACCORDANCE WITH AS 3600 CURRENT EDITION WITH AMENDMENTS, EXCEPT WHERE VARIED BY THE CONTRACT DOCUMENTS.
- 2. CONCRETE QUALITY
- ALL REQUIREMENTS OF THE CURRENT ACSE CONCRETE SPECIFICATION DOCUMENT 1 SHALL APPLY TO THE FORMWORK, REINFORCEMENT AND CONCRETE UNLESS NOTED OTHERWISE.

ELEMENT	AS 3600 F'c MPa AT 28 DAYS	SPECIFIED SLUMP	NOMINAL AGG. SIZE
VEHICULAR BASE	32	60	20
KERBS, PATHS, AND PITS	32	80	20

- WITH AS 1379.
- 3. NO ADMIXTURES SHALL BE USED IN CONCRETE UNLESS APPROVED IN WRITING BY AT & L.
- 4. CLEAR CONCRETE COVER TO ALL REINFORCEMENT FOR DURABILITY SHALL BE 40mm TOP AND 70mm FOR EXTERNAL EDGES UNLESS NOTED OTHERWISE.
- 5. ALL REINFORCEMENT SHALL BE FIRMLY SUPPORTED ON MILD STEEL PLASTIC TIPPED CHAIRS, PLASTIC CHAIRS OR CONCRETE CHAIRS AT NOT GREATER THAN 1m CENTRES BOTH WAYS. BARS SHALL BE TIED AT ALTERNATE INTERSECTIONS.
- COMPLETELY FILLING THE FORMWORK. THOROUGHLY EMBEDDING THE REINFORCEMENT AND FREE OF STONE POCKETS. ALL CONCRETE INCLUDING SLABS ON GROUND AND FOOTINGS SHALL BE COMPACTED AND CURED IN ACCORDANCE WITH R.M.S. SPECIFICATION R83.
- 7. REINFORCEMENT SYMBOLS:
- N DENOTES GRADE 450 N BARS TO AS/NZS 4671 GRADE N R DENOTES 230 R HOT ROLLED PLAIN BARS TO AS/NZS 4671
- SL DENOTES HARD-DRAWN WIRE REINFORCING FABRIC TO AS/NZS 4671 NUMBER OF BARS E AND TYPE

17 N 20250

NOMINAL BAR SIZE IN mm _____ L_SPACING IN mm

THE FIGURE FOLLOWING THE FABRIC SYMBOL SL IS THE REFERENCE NUMBER FOR FABRIC TO AS/NZS 4671.

8. FABRIC SHALL BE LAPPED IN ACCORDANCE WITH THE FOLLOWING DETAIL:

LAP TWO WIRES

EROSION AND SEDIMENT CONTROL NOTES

GENERAL INSTRUCTIONS

- 1. THE SITE SUPERINTENDENT/ENGINEER WILL ENSURE THAT ALL SOIL AND WATER MANAGEMENT WORKS ARE LOCATED AS DOCUMENTED.
- 2. ALL WORK SHALL BE GENERALLY CARRIED OUT IN ACCORDANCE WITH a. LOCAL AUTHORITY REQUIREMENTS **b. EPA REQUIREMENTS** c. NSW DEPARTMENT OF HOUSING MANUAL "MANAGING URBAN STORMWATER, SOILS AND CONSTRUCTION", 4th EDITION, MARCH
- 3. MAINTAIN THE EROSION CONTROL DEVICES TO THE SATISFACTION OF THE SUPERINTENDENT AND THE LOCAL AUTHORITY.
- 4. WHEN STORMWATER PITS ARE CONSTRUCTED. PREVENT SITE RUNOFF ENTERING UNLESS SEDIMENT FENCES ARE ERECTED AROUND PITS.
- 5. CONTRACTOR IS TO ENSURE ALL EROSION & SEDIMENT CONTROL DEVICES ARE MAINTAINED IN GOOD WORKING ORDER AND OPERATE EFFECTIVELY, REPAIRS AND OR MAINTENANCE SHALL BE UNDERTAKEN AS REQUIRED, PARTICULARLY FOLLOWING STORM EVENTS.

LAND DISTURBANCE

2004

- 6. WHERE PRACTICAL, THE SOIL EROSION HAZARD ON THE SITE WILL BE KEPT AS LOW AS POSSIBLE. TO THIS END, WORKS SHOULD BE UNDERTAKEN IN THE FOLLOWING SEQUENCE:
- (A) INSTALL A WIND FENCE ALONG THE BOUNDARIES AS SHOWN ON PLAN. REFER DETAIL.
- (B) INSTALL A SEDIMENT FENCE ALONG THE BOUNDARIES AS SHOWN ON PLAN. REFER DETAIL.
- (C) CONSTRUCT STABILISED CONSTRUCTION ENTRANCE TO LOCATION AS DETERMINED BY SUPERINTENDENT/ENGINEER. REFER DETAIL.
- (D) INSTALL SEDIMENT BASIN AS SHOWN ON PLAN
- (E) INSTALL SEDIMENT TRAPS AS SHOWN ON PLAN.
- (F) UNDERTAKE SITE DEVELOPMENT WORKS IN ACCORDANCE WITH THE ENGINEERING PLANS. WHERE POSSIBLE, PHASE DEVELOPMENT SO THAT LAND DISTURBANCE IS CONFINED TO AREAS OF WORKABLE SIZE.

EROSION CONTROL

- 7. DURING WINDY WEATHER, LARGE, UNPROTECTED AREAS WILL BE KEPT MOIST (NOT WET) BY SPRINKLING WITH WATER TO KEEP DUST UNDER CONTROL.
- 8. FINAL SITE LANDSCAPING WILL BE UNDERTAKEN AS SOON AS POSSIBLE AND WITHIN 20 WORKING DAYS FROM COMPLETION OF CONSTRUCTION ACTIVITIES.

SEDIMENT CONTROL

- 9. STOCKPILES WILL NOT BE LOCATED WITHIN 2 METRES OF HAZARD AREAS, INCLUDING LIKELY AREAS OF CONCENTRATED OR HIGH VELOCITY FLOWS SUCH AS WATERWAYS. WHERE THEY ARE BETWEEN 2 AND 5 METRES FROM SUCH AREAS. SPECIAL SEDIMENT CONTROL MEASURES SHOULD BE TAKEN TO MINIMISE POSSIBLE POLLUTION TO DOWNSLOPE WATERS, E.G. THROUGH INSTALLATION OF SEDIMENT FENCING
- 10. ANY SAND USED IN THE CONCRETE CURING PROCESS (SPREAD OVER THE SURFACE) WILL BE REMOVED AS SOON AS POSSIBLE AND WITHIN 10 WORKING DAYS FROM PLACEMENT.
- 11. WATER WILL BE PREVENTED FROM ENTERING THE PERMANENT DRAINAGE SYSTEM UNLESS IT IS RELATIVELY SEDIMENT FREE, I.E. THE CATCHMENT AREA HAS BEEN PERMANENTLY LANDSCAPED AND/OR ANY LIKELY SEDIMENT HAS BEEN FILTERED THROUGH AN APPROVED STRUCTURE.
- 12. TEMPORARY SOIL AND WATER MANAGEMENT STRUCTURES WILL BE REMOVED ONLY AFTER THE LANDS THEY ARE PROTECTING ARE REHABILITATED.

OTHER MATTERS

- 13. ACCEPTABLE RECEPTORS WILL BE PROVIDED FOR CONCRETE AND MORTAR SLURRIES, PAINTS, ACID WASHINGS, LIGHT-WEIGHT WASTE MATERIALS AND LITTER.
- 14. ANY EXISTING TREES WHICH FORM PART OF THE FINAL LANDSCAPING PLAN WILL BE PROTECTED FROM CONSTRUCTION ACTIVITIES BY:
- (A) PROTECTING THEM WITH BARRIER FENCING OR SIMILAR MATERIALS INSTALLED OUTSIDE THE DRIP LINE
- (B) ENSURING THAT NOTHING IS NAILED TO THEM (C) PROHIBITING PAVING, GRADING, SEDIMENT WASH OR PLACING OF STOCKPILES WITHIN THE DRIP LINE EXCEPT UNDER THE FOLLOWING CONDITIONS.
- (I) ENCROACHMENT ONLY OCCURS ON ONE SIDE AND NO CLOSER TO THE TRUNK THAN EITHER 1.5 METRES OR HALF THE DISTANCE BETWEEN THE OUTER EDGE OF THE DRIP LINE AND THE TRUNK, WHICH EVER IS THE GREATER
- (II) A DRAINAGE SYSTEM THAT ALLOWS AIR AND WATER TO CIRCULATE THROUGH THE ROOT ZONE (E.G. A GRAVEL BED) IS PLACED UNDER ALL FILL LAYERS OF MORE THAN 300 MILLIMETRES DEPTH
- (III) CARE IS TAKEN NOT TO CUT ROOTS UNNECESSARILY NOR TO COMPACT THE SOIL AROUND THEM.

	Client	Scales	NTO	Drawn	JS	Project
THIS DRAWING CANNOT BE			NTS	Designed	SM	1
COPIED OR REPRODUCED IN		Grid	GDA2020	Checked	SM	1
ANY FORM OR USED FOR ANY OTHER PURPOSE OTHER THAN	WU PROPERTIES	Height Datum	AHD	Approved	GJ	
THAT ORIGINALLY INTENDED WITHOUT THE WRITTEN PERMISSION OF AT&L						Title

- CEMENT TYPE SHALL BE (ACSE SPECIFICATION) TYPE SL - PROJECT CONTROL TESTING SHALL BE CARRIED OUT IN ACCORDANCE

- 6. THE FINISHED CONCRETE SHALL BE A DENSE HOMOGENEOUS MASS.

EROSION AND SEDIMENT CONTROL NOTES (CONTINUED)

STAGING

SUITABLE EROSION AND SEDIMENT CONTROLS SHALL BE PROVIDED AND MAINTAINED BY THE CONTRACTOR THROUGHOUT ALL STAGES OF WORKS, INCLUDING AT COMPLETION OF THE BULK EARTHWORKS WHERE SHOWN ON AT&L DRAWINGS OR WHERE DIRECTED BY THE SUPERINTENDENT OR NORTHERN BEACHES COUNCIL'S ENGINEERS. THE CONTRACTOR IS RESPONSIBLE FOR DESIGNING, DOCUMENTING, INSTALLING AND MAINTAINING THE SEDIMENT AND EROSION CONTROLS REQUIRED TO SUIT THE SELECTED CONSTRUCTION STAGING. THIS IS TO BE DOCUMENTED IN THE FORM OF A SOIL AND WATER MANAGEMENT PLAN TO BE DEVELOPED BY THE CONTRACTOR AND APPROVED BY THE SUPERINTENDENT PRIOR TO CONSTRUCTION COMMENCEMENT.

SUCH CONTROLS SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF THE PROTECTION OF THE ENVIRONMENT OPERATIONS ACT, NORTHERN BEACHES COUNCIL'S SPECIFICATIONS AND THE OFFICE OF ENVIRONMENT AND HERITAGE'S 'MANAGING URBAN STORMWATER: SOILS AND CONSTRUCTION. LANDCOM, (4TH EDITION) MARCH 2004 (REPRINTED 2006) (THE "BLUE BOOK"). VOLUME 1 AND VOLUME 2.

CONSTRUCTION SPECIFICATION

THESE DRAWINGS SHOULD BE READ IN CONJUCTION WITH NORTHERN BEACHES COUNCIL'S LATEST DRAWINGS AND SPECIFICATIONS.

- 2. WHERE THERE IS A CONFLICT THE FOLLOWING IS TO OCCUR
- 2.1. NOTIFY THE DESIGN ENGINEER AND/OR SUPERINTENDENT 2.2. THE NORTHERN BEACHES COUNCIL'S SPECIFICATION TAKES PRECEDENT



CONTRACTOR SHALL CALL; DIAL BEFORE YOU DIG 1100 PRIOR TO COMMENCEMENT OF WORK TO OBTAIN ALL CURRENT SERVICE AUTHORITY PLANS


Civil Engineers and Project Managers


4 MINNA CLOSE BELROSE NSW 2085	ABN 96 130 882 4 Tel: 02 9439 17 Fax: 02 9923 10 www.atl.net.au	N 2060 105 177
GENERAL NOTES	Status FOR APPROVAL NOT TO BE USED FOR CONSTRUCTION	A1
	Project - Drawing No.	Issue
	22-1016-DAC001	В




F:\22-1016 4 Minna Close Belrose\6.0 Drgs\Civil\Final\22-1016-DAC002.dwg

-			
and the second second			
Service Tran			
and a second			
1000			
NZAMPA			
1.000			
- Burdle			
and the second			
ALC: NO			
1000			
33.000			
10083			
the most in			
Salar 1 To			
Carlos and Salar			
776 643			
1000			
DATE .			
Contraction of the second			
1.0000.0			
200 181	A Charling		
Contraction of the			
ALC: N			
Sec. 6			A CONTRACTOR
S			5 MINNA CL
55.00			MINNA CL
1723 Ba			
S. 10 1000			
Red Barry			Learn T
MICONK.			
a state of the			
• • • • • • • • • • • • • • • • • • •		marine	and within
1000			16 Bar Con
1 40 1			100 C 10
A			
Ab			
	ABANG MAY		
100 C	Gh		638-00.75 GRAWMATER Tr689-00.776 - 176.89-00.77
100 Ca. /	AF		o g Li
and the state			
1 Acres 64			
1000			
10000			
Autoria			
1000			
A STATE OF A STATE			
C. Marine .			
man			
and the second			
and the second second			
Sale Street Land			
		Bar Scales	
		0	10 20 30 40
C ISSUE FOR APPROVA		0	10 20 30 40 1 : 400 @ A1
B ISSUE FOR APPROVA	L	19-05-2023	
	L		











F:\22-1016 4 Minna Close Belrose\6.0 Drgs\Civil\Final\22-1016-DAC010.dwg









	SCALE: 1:20		REFER NOTE A BELOW	▶ <mark> </mark>	- REFER NOTE
			PIPE TRE	ENCH BELOW	LANDSC
				N.T.S <u>NOTE</u> A. ≥0.2D OR 0.3m (WHI B. 100mm FOR PIPE DI	S. IICHEVER IS GREA
MORTAR BEDDING	150 150 230 100 MIN	R5 R10 - 450 COG 150	NOMINAL KERB LINE R20 C.J. OPTIONAL -SETOUT POINT 4N12 R6-600	PAVEMENT AS SPECIFIED	
DETAIL "E" SCALE 1:10	<u>IN</u>	TEGRAL KERB WIT	H THICKENED ED	<u> 3E (IKO)</u>	
THIS DRAWING CANNOT BE COPIED OR REPRODUCED II ANY FORM OR USED FOR AN	N		Scales AS SHOWN Grid GDA2020	Drawn JS Designed SM Checked SM	М
OTHER PURPOSE OTHER THA THAT ORIGINALLY INTENDED WITHOUT THE WRITTEN PERMISSION OF AT&L		OPERTIES	Height AHD Datum	Approved _{GJ}	J Title S


_____ 2.5De (Lc) REFER BELOW De ≤ 300 > 300 ≤ 450 >450 ≤ 900




F:\22-1016 4 Minna Close Belrose\6.0 Drgs\Civil\Final\22-1016-DAC025.dwg



	Bar Scales		Client	Scales		Drawn	JS	Project	Civil Engineers and Project Managers	
		THIS DRAWING CANNOT BE			NTS	Designed	SM	4 MINNA CLOSE	Level 7, 153 Walk North Sydney NS	
		COPIED OR REPRODUCED IN ANY FORM OR USED FOR ANY		Grid	GDA2020	Checked	SM	BELROSE NSW 2085	ABN 96 130 882 4 Tel: 02 9439 17 Fax: 02 9923 10	405 1777 1055
		OTHER PURPOSE OTHER THAN			AHD	Approved	GJ	Title	www.atl.net.au info@atl.net.au	
B ISSUE FOR APPROVAL	17-04-2024	THAT ORIGINALLY INTENDED WITHOUT THE WRITTEN PERMISSION OF AT&L						SITEWORKS AND STORMWATER DETAILS	Status FOR APPROVAL NOT TO BE USED FOR CONSTRUCTION	A1
A ISSUE FOR APPROVAL ' Issue Description	Date							SHEET 2	Project - Drawing No. 22-1016-DAC026	Issue B



F:\22-1016 4 Minna Close Belrose\6.0 Drgs\Civil\Final\22-1016-DAC026.dwg



Date

Description

100mm on Original

	Client		Scales		Drawn	JS	Proje
THIS DRAWING CANNOT BE				NTS	Designed	SM	
COPIED OR REPRODUCED IN			Grid	GDA2020	Checked	SM	
ANY FORM OR USED FOR ANY OTHER PURPOSE OTHER THAN		WU PROPERTIES	Height Datum	AHD	Approved	GJ	Title
THAT ORIGINALLY INTENDED WITHOUT THE WRITTEN PERMISSION OF AT&L							Title SI

GN TAB	LE			
	INSTALLED. CIFIED STRUCTURE(S)			
	. FLOW, AND SELF-CLE			
690	460	31		
840	600	60		
820 1.6	590 1.1	44 0.		
0.9	0.46	0.3		
	SITE SPECIF			
	A REQUIREN			
ICTURE ID		1	1	
	TRIDGES REQ'D]	
	(310 / 460 / 690)	[]	
A TYPE (ZPO	G / PSORB)	[]	
	FLOW RATE (L/S)]]]	
RAULIC CAP				
DATA:	I.L. MA		AMETER	
[PIPE #1 [PIPE #2][]	
FIFE #2		<u>ן ן</u> ז ר]]	
ET PIPE][]	
AST PIT WE	IGHT	TBA		
/EIGHT		TBA		
ERT ELEVATI	XIMUM EARTH COVER ON. CERTIFYING ENG E IN ACCORDANCE WI	INEER TO	ID A	
g Engineer, Required.	EXCEEDS THE PEAK	HYDRAULIC	;	
INTENANCE. ENTS.	REFER TO OPERATIO	N AND		
CEMENT OF C	DRDER.			
SIONS ARE SI	TE-SPECIFIC DESIGN	CONSIDERA	TIONS	
TING AND REALLY).	CH CAPACITY TO LIF	FAND SET T	ΉE	
E, INSTALL AN	ID GROUT INLET AND	OUTLET PIF	PES.	
	EAN PROTECT	R SVSI	-ЕМ	
	00 x 900 PIT			
-	ICATION DRAW	NG		
		I .		
roject			JIVII Engineer	rs and Project Managers
	MINNA CLOSE .ROSE NSW 2085		at	North Sydney NSW 2060 ABN 96 130 882 405 Tel: 02 9439 1777


TEWORKS AND STORMWATER Status DETAILS SHEET 3

0 882 405 9439 1777 02 9923 1055 Fax: www.atl.net.au info@atl.net.au FOR APPROVAL A1 NOT TO BE USED FOR CONSTRUCTION Project - Drawing No. Issue

В


F:\22-1016 4 Minna Close Belrose\6.0 Drgs\Civil\Final\22-1016-DAC027.dwg

22-1016-DAC027





PAVEMENT TYPE 1 - CONCRETE HARDSTAND TO BE CONFIRMED BY STRUCTURAL ENGINEER DURING DETAILED DESIGN
PAVEMENT TYPE 2 - FOOTPATH 80mm THICK CONCRETE FOOTPATH ON 75mm THICK DGB20 ON COMPACTED SUBGRADE TO MIN. CBR 4% REFER NBC STANDARD DWG NO. 4
PAVEMENT TYPE 3 - VEHICLE CROSSING 180mm THICK 32MPa CONCRETE CROSSING WITH SL82 MESH WITH 30mm TOP COVER ON 100mm THICK COMPACTED DGB20 OR AS APPROVED BY COUNCIL ON COMPACTED SUBGRADE TO MIN. CBR 4% REFER WARRINGAH COUNCIL DWG 2276/B
PAVEMENT TYPE 4 - LANDSCAPING REFER TO LANDSCAPE ARCHITECTS DRAWINGS FOR DETAILS
PAVEMENT TYPE 5 - CONCRETE DRIVEWAY 180mm THICK 32MPa CONCRETE CROSSING WITH SL82 MESH WITH 30mm TOP COVER 100mm THICK COMPACTED DGB20 ON COMPACTED SUBGRADE TO MIN. CBR 4%



100mm on Original

		Client	Scales	4.50	Drawn	JS	Project
	THIS DRAWING CANNOT BE			1:50	Designed	SM	1
	COPIED OR REPRODUCED IN		Grid	GDA2020	Checked	SM	1
	ANY FORM OR USED FOR ANY OTHER PURPOSE OTHER THAN THAT ORIGINALLY INTENDED WITHOUT THE WRITTEN PERMISSION OF AT&L	WU PROPERTIES	TIES Height Datum	AHD	Approved	GJ	Title
							nue

F:\22-1016 4 Minna Close Belrose\6.0 Drgs\Civil\Final\22-1016-DAC042.dwg




			Bar Scales
В	ISSUE FOR APPROVAL	17-04-2024	
А	ISSUE FOR APPROVAL	17-05-2023	
Issue	Description	Date	
	100mm on Original		

E333918.569 N6269272.957 N6269272.957 N6269272.957 N6269272.957 N6269272.957 N6269272.957 N6269275.951 N6269276.919 N6269276.919 N6269276.919 N6269286.919 N6269286.894 N6269286.894 N6269286.894 N6269286.894 N6269286.894	E333935.522 N6269231.227 B333933.945 N6269220.746 C-0 E333932.536 N6269220.746
	EXISTING COMMS SHOWN INDICATIVELY WITH STANDARD 450mm COVER, EXACT DEPTH TBC DURING DETAILED DESIGN.
SURFACE INLET PIT, 0.5% GRADE SURFACE INLET PIT, 0.5% GRADE	OSD TANK OSD TANK KERB INLET PIT. REFER DAC027
$\begin{array}{c c c c c c c c c c c c c c c c c c c $	0.03 1 1 0.1 2.6 0375 RFJ RCP 4 2.7% 170.00 1901 PS 00 1901 PS 00 1
Line A Line B Line C 0 1 2 3 4 5m 1:50 @ A1 1:100 @ A3 Client Client Grid GDA2020 1:50 @ A1 1:100 @ A3 THIS DRAWING CANNOT BE COPIED OR REPRODUCED IN ANY FORM OR USED FOR ANY OTHER PURPOSE OTHER THAN Client WU PROPERTIES Grid GDA2020 1:500 @ A1 1:100 @ A3 THAT ORIGINALLY INTENDED WITHOUT THE WRITTEN PERMISSION OF AT&L WU PROPERTIES Grid GDA2020	LINE D Drawn JS Project Civil Engineers and Project Managers Designed SM 4 MINNA CLOSE Civil Engineers and Project Managers Checked SM 4 MINNA CLOSE Civil Engineers and Project Managers

Nalker Street / NSW 2060 882 405 439 1777 923 1055 A1 Issue В 22-1016-DAC045

F:\22-1016 4 Minna Close Belrose\6.0 Drgs\Civil\Final\22-1016-DAC045.dwg







Civil Engineers and Project Managers Level 7, 153 Walker Street North Sydney NSW 2060 4 MINNA CLOSE ABN 96 130 882 405 Tel: 02 9439 1777 Fax: 02 9923 1055 **BELROSE NSW 2085** www.atl.net.au info@atl.net.au STORMWATER DRAINAGE Status FOR APPROVAL A1 CATCHMENT PLAN Project - Drawing No. Issue 22-1016-DAC050 В

F:\22-1016 4 Minna Close Belrose\6.0 Drgs\Civil\Final\22-1016-DAC050.dwg



MONA VALE ROAD

rate RL:186.64 IL185.84 Ø0 225

SELP

OFI F

UNDISTURBED LAND EXCLUDED FROM CALCULATIONS

ENVIRONMENTAL CONSERVATION ZONE LAND TO REMAIN UNDISTURBED

LANDSCAPE 0.381 ha ['MIXED - 0% IMP.]


MINNA CLOSE


WU PROPERTIES

Client


THIS DRAWING CANNOT BE COPIED OR REPRODUCED IN ANY FORM OR USED FOR ANY OTHER PURPOSE OTHER THAN THAT ORIGINALLY INTENDED WITHOUT THE WRITTEN PERMISSION OF AT&L

Scales Drawn Project JS 1: 250 Designed SM Checked GDA2020 Grid SM Height Datum Approved AHD GJ Title












LEGEND


-00	SEDIMENT FENCE (SD 6-8)
>>	CATCH DRAIN
——— В ———	BARRIER FENCE
\frown	MESH AND GRAVEL INLET FILTER (SD 6-11)
\boxtimes	GEOTEXTILE INLET (SD 6-12)
	STABILISED SITE ACCESS AND TRUCK WASH DOWN AREA (SD 6-14)
\bigcirc	PROPOSED SITE ACCESS GATE

INSTALL TEMPORARY GEOTEXTILE

Civil Engineers and Project Managers Level 7, 153 Walker Street North Sydney NSW 2060 4 MINNA CLOSE ABN 96 130 882 405 Tel: 02 9439 1777 Fax: 02 9923 1055 **BELROSE NSW 2085** www.atl.net.au info@atl.net.au Status FOR APPROVAL A1 SEDIMENTATION AND NOT TO BE USED FOR CONSTRUCTION **EROSION CONTROL** Project - Drawing No. Issue PLAN 22-1016-DAC060 В

F:\22-1016 4 Minna Close Belrose\6.0 Drgs\Civil\Final\22-1016-DAC060.dwg





NTS

	Bar Scales		Client	Scales		Drawn	JS	Project	Civil Engineers and Project Managers	
	 0 100 200 400 600 800 1000mm	THIS DRAWING CANNOT BE COPIED OR REPRODUCED IN ANY FORM OR USED FOR ANY OTHER PURPOSE OTHER THAN	COPIED OR REPRODUCED IN		1	: 250	Designed	SM	4 MINNA CLOSE	Level 7, 153 Walker Street North Sydney NSW 2060
					Grid GD	DA2020	Checked	SM	BELROSE NSW 2085	ABN 96 130 882 405 Tel: 02 9439 1777 Fax: 02 9923 1055
	1 : 10 @ A1 1 : 20 @ A3			Height Datum	AHD	Approved	GJ	Title	www.atl.net.au info@atl.net.au	
B ISSUE FOR APPROVAL 17-04-202	24 0 1 2 3 4 5m	THAT ORIGINALLY INTENDED WITHOUT THE WRITTEN PERMISSION OF AT&L						SEDIMENTATION AND	Status FOR APPROVAL NOT TO BE USED FOR CONSTRUCTION	
A ISSUE FOR APPROVAL 17-05-202 Issue Description Date	1 : 50 @ A1 1 : 100 @ A3	I ERMISSION OF ATRE						EROSION CONTROL	Project - Drawing No. Issue 22-1016-DAC065 B	
F:\22-1016 4 Minna Close Belrose\6.0 Drgs\Civil\Final\22-1016-DAC065.dwg										