# **BASIX** Certificate

Building Sustainability Index www.basix.nsw.gov.au

## Alterations and Additions

Certificate number: A380895

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

#### Secretary

Date of issue: Monday, 22, June 2020

To be valid, this certificate must be lodged within 3 months of the date of issue.



1

Project address								
Project name	42 Upper Clifford Ave							
Street address	42 Upper Clifford Avenue Fairlight 2094							
Local Government Area	Northern Beaches Council							
Plan type and number	Deposited Plan 313797							
Lot number	Α							
Section number								
Project type								
Dwelling type	Separate dwelling house							
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and does not include a pool (and/or spa).							

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Jean Stewart P/L

ABN (if applicable): 88093135570

BASIX Certificate number: A380895 page 2 / 6

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		<b>✓</b>	~
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		<b>✓</b>	✓
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		<b>✓</b>	✓
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		<b>✓</b>	

BASIX Certificate number: A380895 page 3 / 6

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
The applicant must construct the new or altered the table below, except that a) additional insular is not required for parts of altered construction	<b>V</b>	<b>V</b>	<b>V</b>		
Construction	Additional insulation required (R-value)	Other specifications			
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				

BASIX Certificate number: A380895

Glazing requirements							Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows and	d glazed do	ors							
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.							<b>✓</b>	<b>~</b>	<b>✓</b>
The following r	The following requirements must also be satisfied in relation to each window and glazed door:							<b>✓</b>	✓
Each window or glazed door with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.								<b>✓</b>	✓
Each window or glazed door with improved frames, or pyrolytic low-e glass, or clear/air gap/clear glazing, or toned/air gap/clear glazing must have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. The description is provided for information only. Alternative systems with complying U-value and SHGC may be substituted.								~	✓
For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.						✓	✓	<b>✓</b>	
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.							<b>✓</b>	<b>✓</b>	
External louvres and blinds must fully shade the window or glazed door beside which they are situated when fully drawn or closed.							✓	✓	
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.							<b>✓</b>	<b>✓</b>	
Windows a	nd glazed (	doors g	lazing r	equireme	nts				
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	dowing Distance (m)	Shading device	Frame and glass type			
D3	S	15.91	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W2	W	1.49	0	0	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single pyrolytic low-e, (U-value: 5.7, SHGC: 0.47)			
W3	Е	0.91	0	0	eave/verandah/pergola/balcony	standard aluminium, single clear, (or			

BASIX Certificate number: A380895 page 5 / 6

Glazing requirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check	
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	dowing Distance (m)	Shading device	Frame and glass type			
					>=450 mm	U-value: 7.63, SHGC: 0.75)			
W4	Е	2.06	0	0	external louvre/blind (adjustable)	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W5	W	2.06	0	0	external louvre/blind (adjustable)	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			

BASIX Certificate number: A380895

### Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a "

"" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.