BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A428186 05

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Wednesday, 19, October 2022

To be valid, this certificate must be lodged within 3 months of the date of issue.



Description of project

Project address							
Project name	759B - 61B Wandeen Rd Clareville_05						
Street address	61B Wandeen Road Clareville 2107						
Local Government Area	Northern Beaches Council						
Plan type and number	Deposited Plan 236667						
Lot number	19						
Section number							
Project type							
Dwelling type	Separate dwelling house						
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and includes a pool (and/or spa).						

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: ECOMODE Design

ABN (if applicable): 79845824261

BASIX Certificate number: A428186_05 page 2 / 8

Pool and Spa	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Rainwater tank			
The applicant must install a rainwater tank of at least 896 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	~
The applicant must configure the rainwater tank to collect rainwater runoff from at least 50 square metres of roof area.		✓	✓
The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool.		✓	✓
Outdoor swimming pool			1
The swimming pool must be outdoors.	✓	✓	✓
The swimming pool must not have a capacity greater than 25 kilolitres.	✓	✓	✓
The swimming pool must have a pool cover.		✓	✓
The applicant must install a pool pump timer for the swimming pool.		✓	✓
The applicant must install the following heating system for the swimming pool that is part of this development: electric heat pump.		✓	✓

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		✓	✓
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		✓	~
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		✓	✓
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		✓	

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements				•	
The applicant must construct the new or altered the table below, except that a) additional insulat is not required for parts of altered construction v	V	V	~		
Construction	Additional insulation required (R-value)	Other specifications			
concrete slab on ground floor.	nil				
suspended floor with open subfloor: concrete (R0.6).	R0.9 (down) (or R1.50 including construction)				
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				
external wall: brick veneer	R1.16 (or R1.70 including construction)				
internal wall shared with garage: plasterboard (R0.36)	nil				
raked ceiling, pitched/skillion roof: structural panel >125 mm	ceiling: nil (up), roof: none	medium (solar absorptance 0.475 - 0.70)			

Glazing requ	irements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows and	l glazed do	ors							
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.								~	✓
The following re	equirements	must also	be satisfic	ed in relation	to each window and gla	azed door:		✓	✓
have a U-value	and a Solar	Heat Gair	n Coefficie	ent (SHGC) r		ear or toned glass may either match the description, or, d in the table below. Total system U-values and SHGCs conditions.		✓	✓
					each eave, pergola, ver han 2400 mm above the	randah, balcony or awning must be no more than 500 mm e sill.	✓	✓	✓
Pergolas with p	olycarbonate	e roof or s	imilar tran	slucent mate	erial must have a shading	g coefficient of less than 0.35.		✓	✓
					e window or glazed door ens must not be more tha	above which they are situated, unless the pergola also an 50 mm.		✓	✓
Overshadowing specified in the					nt and distance from the	centre and the base of the window and glazed door, as	✓	✓	✓
Windows ar	nd glazed	doors g	lazing re	equireme	nts				
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	dowing Distance (m)	Shading device	Frame and glass type			
WL01	SW	7.4	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
DL01	SW	2.8	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
DL02	SW	2.8	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
DL03	SW	2.3	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			

BASIX Certificate number: A428186_05 page 6 / 8

Glazing requirements								Show on CC/CDC Plans & specs	Certifier Check
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	Distance (m)	Shading device	Frame and glass type			
WG01	SW	6.7	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
WG02	SW	1.5	0	0	eave/verandah/pergola/balcony >=900 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
WG03	SW	4.2	0	0	eave/verandah/pergola/balcony >=900 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
WG04	SW	0.4	0	0	eave/verandah/pergola/balcony >=900 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
WG05	SW	1.5	0	0	eave/verandah/pergola/balcony >=900 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
WG06	SW	4.2	0	0	eave/verandah/pergola/balcony >=900 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
WG07	SW	0.4	0	0	eave/verandah/pergola/balcony >=900 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
WG08	SW	1.1	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
WG09	SW	33.7	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
WG10	SW	0.9	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
WG11	NE	4.1	2.5	2.8	eave/verandah/pergola/balcony >=450 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
DG01	NE	2.6	0	0	eave/verandah/pergola/balcony >=900 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
DG02	SW	8.2	0	0	eave/verandah/pergola/balcony >=900 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			

Glazing requ	irements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Window / door no.	Orientation	Area of glass inc. frame (m2)	Overshad Height (m)	dowing Distance (m)	Shading device	Frame and glass type			
DG03	SE	1.8	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			

BASIX Certificate number: A428186_05 page 8 / 8

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.