# **BASIX** Certificate

Building Sustainability Index www.basix.nsw.gov.au

## **Alterations and Additions**

Certificate number: A367317

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

### Secretary

Date of issue: Saturday, 28, December 2019

To be valid, this certificate must be lodged within 3 months of the date of issue.



# Description of project

Project address					
Project name	13 Wirringulla Avenue				
Street address	13 Wirringulla Avenue Elvina Bay 2105				
Local Government Area	Northern Beaches Council				
Plan type and number	Deposited Plan 224643				
Lot number	1				
Section number					
Project type					
Dwelling type	Separate dwelling house				
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and does not include a pool (and/or spa).				

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Ironbark Architecture + Design

ABN (if applicable): 14992060818

BASIX Certificate number: A367317 page 2 / 5

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		<b>✓</b>	<b>✓</b>
Fixtures		ı	
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		<b>✓</b>	✓
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		<b>✓</b>	✓
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		<b>✓</b>	

BASIX Certificate number: A367317 page 3 / 5

Glazing requ	uirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows and	d glazed do	ors							
					nading devices, in accord r each window and glaze	dance with the specifications listed in the table below. d door.	<b>~</b>	<b>~</b>	<b>~</b>
The following r	equirements	must also	be satisfi	ed in relatior	n to each window and gla	azed door:		✓	<b>✓</b>
have a U-value	and a Solar	Heat Gair	n Coefficie	ent (SHGC) r		ear or toned glass may either match the description, or, d in the table below. Total system U-values and SHGCs conditions.		<b>✓</b>	~
					f each eave, pergola, ver than 2400 mm above the	randah, balcony or awning must be no more than 500 mm sill.	✓	✓	✓
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.								<b>✓</b>	✓
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.								<b>✓</b>	<b>✓</b>
Overshadowin specified in the					nt and distance from the	centre and the base of the window and glazed door, as	✓	✓	✓
Windows a	nd glazed	doors g	lazing r	equireme	nts				
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	dowing Distance (m)	Shading device	Frame and glass type			
DINING	W	12.1	20	8.3	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
DINING	N	8	30	3	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
HIGHLIGHT	N	1.17	28	3	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
HIGHLIGHT	N	1.17	28	3	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			

BASIX Certificate number: A367317 page 4 / 5

Glazing requirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check	
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	Distance (m)	Shading device	Frame and glass type			
LIVING	Е	9.08	0	0	eave/verandah/pergola/balcor >=900 mm	y timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
KITCHEN	S	4.33	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
ENSUITE	W	1.17	10	10	eave/verandah/pergola/balcor >=600 mm	y timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
BED 1	Е	2.77	10	2	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
Skylights									
The applicant n	nust install th	e skylight	s in acco	dance with th	ne specifications listed in the tab	le below.	<b>✓</b>	✓	✓
The following re	equirements i	must also	be satisf	ied in relation	to each skylight:			<b>✓</b>	✓
Each skylight may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below.						✓	✓		
Skylights glazing requirements									
Skylight number	Skylight number Area of glazing inc. frame (m2)  Shading device Frame and glass type								
S1	1		no shad	ling	timber,	double clear/air fill, (or U-value: 4.3, SHGC: 0.5)			

BASIX Certificate number: A367317 page 5 / 5

### Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.