

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1106409S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

BASIX

Date of issue: Monday, 13 July 2020

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary					
Project name	15 PRINCES PROM	15 PRINCES PROMENADE SEAFORTH			
Street address	15 PRINCES Prome	nade SEAFORTH 2092			
Local Government Area	Northern Beaches C	ouncil			
Plan type and plan number	deposited DP4889				
Lot no.	139				
Section no.	-				
Project type	separate dwelling ho	separate dwelling house			
No. of bedrooms	2				
Project score					
Water	₩ 40	Target 40			
Thermal Comfort	✓ Pass	Target Pass			
Energy	> 50	Target 50			

Certificate Prepared by
Name / Company Name: rkdesigns
ABN (if applicable): 39330033053

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1106409S Monday, 13 July 2020 page 1/9

Description of project

BASIX

Project address			
Project name	15 PRINCES PROMENADE SEAFORTH		
Street address	15 PRINCES Promenade SEAFORTH 2092		
Local Government Area	Northern Beaches Council		
Plan type and plan number	Deposited Plan DP4889		
Lot no.	139		
Section no.	-		
Project type			
Project type	separate dwelling house		
No. of bedrooms	2		
Site details			
Site area (m²)	1353		
Roof area (m²)	146		
Conditioned floor area (m2)	52.1		
Unconditioned floor area (m2)	5.16		
Total area of garden and lawn (m2)	50		

Assessor details and thermal loads							
Assessor number	n/a						
Certificate number	n/a						
Climate zone	n/a						
Area adjusted cooling load (MJ/m².year)	n/a						
Area adjusted heating load (MJ/m².year)	n/a						
Project score							
Water	✓ 40 Target 40						
Thermal Comfort	✓ Pass Target Pass						
Energy	✓ 50 Target 50						

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1106409S Monday, 13 July 2020 page 2/9

Schedule of BASIX commitments

BASIX

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 5 star in each toilet in the development.		~	V
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		V	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 3000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	•	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 146.14 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	V
The applicant must connect the rainwater tank to:			
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		✓	V

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1106409S Monday, 13 July 2020 page 3/9

Thermal Comfort Commitments		Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	V	~	-
The conditioned floor area of the dwelling must not exceed 300 square metres.	V	V	V
The dwelling must not contain open mezzanine area exceeding 25 square metres.	V	V	V
The dwelling must not contain third level habitable attic room.	~	V	V
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	V	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - other/undecided	2.40 (including construction)	
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 3.5 (up), roof: foil/sarking	framed; medium (solar absorptance 0.475-0.70)

Note	Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1106409S Monday, 13 July 2020 page 4/9

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check			
Windows, glazed doors and skylights						
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	~	~			
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	V	~	V			
The following requirements must also be satisfied in relation to each window and glazed door:	V	~	V			
• For the following glass and frame types, the certifier check can be performed by visual inspection.			-			
- Aluminium single clear						
- Aluminium double (air) clear						
- Timber/uPVC/fibreglass single clear						
- Timber/uPVC/fibreglass double (air) clear						
• Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column.	V	~	V			

neight (mm)	(mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
1200	1450	aluminium, single, clear	eave 450 mm, 461 mm above head of window or glazed door	>4 m high, 5-8 m away
600	2410	aluminium, single, clear	eave 450 mm, 461 mm above head of window or glazed door	>4 m high, 5-8 m away
150	1450	aluminium, single, clear	eave 450 mm, 202 mm above head of window or glazed door	>4 m high, 5-8 m away
150	1450	aluminium, single, clear	eave 450 mm, 202 mm above head of window or glazed door	>4 m high, 5-8 m away
1 50	1450	aluminium, single, clear	eave 450 mm, 202 mm above head of window or glazed door	>4 m high, 5-8 m away
15	50 50	00 2410 50 1450 50 1450	2410 aluminium, single, clear 1450 aluminium, single, clear 1450 aluminium, single, clear	of window or glazed door 2410 aluminium, single, clear eave 450 mm, 461 mm above head of window or glazed door 300 1450 aluminium, single, clear eave 450 mm, 202 mm above head of window or glazed door 300 1450 aluminium, single, clear eave 450 mm, 202 mm above head of window or glazed door 300 1450 aluminium, single, clear eave 450 mm, 202 mm above head of window or glazed door 300 2410 aluminium, single, clear eave 450 mm, 202 mm above head

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1106409S Monday, 13 July 2020 page 5/9

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
W06	1200	1450	aluminium, single, clear	eave 450 mm, 958 mm above head of window or glazed door	>4 m high, 8-12 m away
South-West facing					
W07	2100	2688	aluminium, single, clear	eave 450 mm, 246 mm above head of window or glazed door	>4 m high, 5-8 m away
W08	1029	1210	aluminium, single, clear	eave 450 mm, 246 mm above head of window or glazed door	>4 m high, 5-8 m away
North-West facing					
W09	400	1600	aluminium, single, clear	eave 450 mm, 1422 mm above head of window or glazed door	not overshadowed

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1106409S Monday, 13 July 2020 page 6/9

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric heat pump with a performance of 31 to 35 STCs or better.	~	V	
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: EER 3.5 - 4.0		~	~
The bedrooms must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		~	-
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: EER 3.5 - 4.0		~	~
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	-
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		~	-
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		•	V
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		~	-
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
at least 2 of the bedrooms / study; dedicated		-	V
at least 1 of the living / dining rooms; dedicated		V	V
the kitchen; dedicated		J	

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1106409S Monday, 13 July 2020 page 7/9

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
all bathrooms/toilets; dedicated		~	~
the laundry; dedicated		•	-
all hallways; dedicated		✓	-
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	-	→	V
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	-	~	V
Other			
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		•	
The applicant must install a fixed outdoor clothes drying line as part of the development.		~	
The applicant must install a fixed indoor or sheltered clothes drying line as part of the development.		V	

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1106409S Monday, 13 July 2020 page 8/9

Legend

BASIX

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1106409S Monday, 13 July 2020 page 9/9