BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1185612S_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

This certificate is a revision of certificate number 1185612S lodged with the consent authority or certifier on 31 March 2021 with application pan86774.

It is the responsibility of the applicant to verify with the consent authority that the original, or any revised certificate, complies with the requirements of Schedule 1 Clause 2A, 4A or 6A of the Environmental Planning and Assessment Regulation 2000

Secretary

Date of issue: Monday, 12 April 2021 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project summary				
Project name	33 Wollstonecraft Ave_02			
Street address	33 Wollstonecraft Avenue avalon 2107			
Local Government Area	Northern Beaches Council			
Plan type and plan number	deposited 12074			
Lot no.	76			
Section no.	-			
Project type	separate dwelling house - secondary dwelling			
No. of bedrooms	2			
Project score				
Water	V 40 Target 40			
Thermal Comfort	V Pass Target Pass			
Energy	✓ 50 Target 50			

Name / Company Name: Trevor Stephens

ABN (if applicable): N/A

Description of project

Project address

•				
Project name	33 Wollstonecraft Ave_02			
Street address	33 Wollstonecraft Avenue avalon 2107			
Local Government Area	Northern Beaches Council			
Plan type and plan number	Deposited Plan 12074			
Lot no. 76				
Section no.	-			
Project type				
Project type	separate dwelling house - secondary dwelling			
No. of bedrooms	2			
Site details				
Site area (m²)	209			
Roof area (m ²)	71			
Conditioned floor area (m2)	52.48			
Unconditioned floor area (m2)	7.06			
Total area of garden and lawn (m2)	77			
Roof area (m2) of the existing dwelling	129			
No. of bedrooms in the existing dwelling	4			
L	· · · · · · · · · · · · · · · · · · ·			

Assessor details and thermal lo	bads
Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m ² .year)	n/a
Area adjusted heating load (MJ/m².year)	n/a
Ceiling fan in at least one bedroom	n/a
Ceiling fan in at least one living room or other conditioned area	n/a
Project score	
Water	V 40 Target 40
Thermal Comfort	V Pass Target Pass
Energy	V 50 Target 50

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 68 square metres of the site.	~	~	
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 6 but <= 7.5 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 4 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 4 star in each bathroom in the development.		 	
Alternative water	1		
Rainwater tank			
The applicant must install a rainwater tank of at least 3000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 79 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		 Image: A set of the set of the	~

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - suspended floor above open subfloor, framed	1.3 (or 2 including construction) (down)	
external wall - framed (weatherboard, fibre cement, metal clad)	3.00 (or 3.40 including construction)	
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 5 (up), roof: foil backed blanket (75 mm)	framed; dark (solar absorptance > 0.70)

Note	• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check			
Windows, glazed doors and skylights						
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the pecifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	~	~			
he dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	~			
The following requirements must also be satisfied in relation to each window and glazed door:	~	~	~			
 For the following glass and frame types, the certifier check can be performed by visual inspection. 			~			
- Aluminium single clear						
- Aluminium double (air) clear						
- Timber/uPVC/fibreglass single clear						
- Timber/uPVC/fibreglass double (air) clear						
 For other glass or frame types, each window and glazed door must be accompanied with certification showing a U value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range of those listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. Frame and glass types shown in the table below are for reference only. 			~			
 Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column. 	~	~	v			

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North-East facing					
W01	1200	2650	U-value: 5.4, SHGC: 0.522 - 0.638 (aluminium, single, Hi-Tsol Low-e)	solid overhang 800 mm, 100 mm above head of window or glazed door	not overshadowed
South-East facing					
W04	1200	1210	U-value: 5.4, SHGC: 0.522 - 0.638 (aluminium, single, Hi-Tsol Low-e)	eave 300 mm, 625 mm above head of window or glazed door	not overshadowed

Window/glazed door no.	Maximum	Maximum width	Tura	Shading Device (Dimension within	Overshadowing
window/giazed door no.	height (mm)	(mm)	Туре	10%)	Oversnadowing
W02	1974	850	aluminium, single, clear	solid overhang 1000 mm, 200 mm above head of window or glazed door	not overshadowed
W06	1200	1210	U-value: 5.4, SHGC: 0.522 - 0.638 (aluminium, single, Hi-Tsol Low-e)	eave 300 mm, 320 mm above head of window or glazed door	not overshadowed
South-West facing					
W03	1200	700	U-value: 5.4, SHGC: 0.522 - 0.638 (aluminium, single, Hi-Tsol Low-e)	eave 300 mm, 760 mm above head of window or glazed door	>4 m high, 8-12 m away
W05	1200	1210	U-value: 5.4, SHGC: 0.522 - 0.638 (aluminium, single, Hi-Tsol Low-e)	eave 300 mm, 470 mm above head of window or glazed door	>4 m high, 8-12 m away
North-West facing					
W11	600	2400	U-value: 5.4, SHGC: 0.522 - 0.638 (aluminium, single, Hi-Tsol Low-e)	eave 300 mm, 730 mm above head of window or glazed door	1-2 m high, <1.5 m away
W10	600	1570	U-value: 5.4, SHGC: 0.522 - 0.638 (aluminium, single, Hi-Tsol Low-e)	eave 300 mm, 220 mm above head of window or glazed door	1-2 m high, <1.5 m away
W08	1030	610	U-value: 5.4, SHGC: 0.522 - 0.638 (aluminium, single, Hi-Tsol Low-e)	eave 300 mm, 200 mm above head of window or glazed door	2-4 m high, 2 m away
W09	610	600	U-value: 5.4, SHGC: 0.522 - 0.638 (aluminium, single, Hi-Tsol Low-e)	eave 300 mm, 220 mm above head of window or glazed door	2-4 m high, 2-5 m away
W07	1030	610	U-value: 5.4, SHGC: 0.522 - 0.638 (aluminium, single, Hi-Tsol Low-e)	eave 300 mm, 200 mm above head of window or glazed door	2-4 m high, 2 m away

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous.	~	v	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: ceiling fans; Energy rating: n/a		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: ceiling fans; Energy rating: n/a		~	~
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: gas fixed flued heater; Energy rating: 4 Star		 ✓ 	~
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		 	~
Ventilation			-
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: no mechanical ventilation (ie. natural); Operation control: n/a		~	~
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		~	~
Laundry: natural ventilation only, or no laundry; Operation control: n/a		 Image: A second s	~
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
 at least 2 of the bedrooms / study; dedicated 		 ✓ 	~
 at least 1 of the living / dining rooms; dedicated 		 Image: A second s	~
the kitchen; dedicated			

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
all bathrooms/toilets; dedicated		~	~
the laundry; dedicated		~	~
all hallways; dedicated		~	~
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.	~	~	~
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.		~	
The applicant must install a fixed indoor or sheltered clothes drying line as part of the development.		~	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a vi in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a vi in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a vi in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.