

BASIX™ Certificate

Building Sustainability Index

www.planningportal.nsw.gov.au/development-and-assessment/basix

Single Dwelling

Certificate number: 1792797S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.planningportal.nsw.gov.au/definitions

Secretary

Date of issue: Thursday, 24 April 2025

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



Project summary

Project name	Dee Why 37 Bushey Place
Street address	37 BUSHEY Place DEE WHY 2099
Local Government Area	Northern Beaches Council
Plan type and plan number	Deposited Plan DP737235
Lot no.	52
Section no.	-
Project type	dwelling house (attached) - secondary dwelling
No. of bedrooms	1

Project score

Water	✓ 45	Target 40
Thermal Performance	✓ Pass	Target Pass
Energy	✓ 100	Target 68
Materials	✓ -100	Target n/a





Certificate Prepared by

Name / Company Name: The Trustee for Studio Lykke

ABN (if applicable):

Description of project

Project address	
Project name	Dee Why 37 Bushey Place
Street address	37 BUSHEY Place DEE WHY 2099
Local Government Area	Northern Beaches Council
Plan type and plan number	Deposited Plan DP737235
Lot no.	52
Section no.	-
Project type	
Project type	dwelling house (attached) - secondary dwelling
No. of bedrooms	1
Site details	
Site area (m ²)	598
Roof area (m ²)	53
Conditioned floor area (m ²)	34.0
Unconditioned floor area (m ²)	4.0
Total area of garden and lawn (m ²)	5
Roof area of the existing dwelling (m ²)	160
Number of bedrooms in the existing dwelling	3

Assessor details and thermal loads		
NatHERS assessor number	n/a	
NatHERS certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/ m².year)	n/a	
Area adjusted heating load (MJ/ m².year)	n/a	
Project score		
Water	 45	Target 40
Thermal Performance	 Pass	Target Pass
Energy	 100	Target 68
Materials	 -100	Target n/a

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 6 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 6 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 6 star in each bathroom in the development.		✓	
Alternative water			
Greywater diversion system			
The applicant must install a greywater diversion system on the site. This system must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.		✓	✓
The applicant must configure the greywater diversion system so that greywater for diversion is collected from: <ul style="list-style-type: none"> each bathroom (but not the toilets) 		✓	✓
The applicant must connect the greywater diversion system to: <ul style="list-style-type: none"> a sub-surface irrigation system (Note: NSWHealth does not recommend that greywater be used to irrigate edible plants which are consumed raw.) 		✓	✓

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Do-it-yourself Method			
General features			
The dwelling must be a Class 1 dwelling according to the National Construction Code, and must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓
The applicant must adopt one of the options listed in the tables below to address thermal bridging in metal framed floor(s), walls and ceiling/roof of the dwelling.	✓	✓	✓
The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the tables below.			✓

Construction	Area - m ²	Additional insulation required	Options to address thermal bridging	Other specifications
floor - concrete slab on ground, conventional slab.	45	nil;not specified	nil	
floor - suspended floor above garage, concrete - suspended; frame: light steel frame.	33	nil;fibreglass batts or roll	nil	
garage floor - concrete slab on ground.	43	none	nil	

Construction	Area - m ²	Additional insulation required	Options to address thermal bridging	Other specifications
external wall: cavity brick; frame: light steel frame.	6	0.50 (or 1.20 including construction) with one of the measures to address thermal bridging; rockwool batts, roll or pump-in	• Install • Install	wall colour: Light (solar absorptance < 0.48)
external wall: framed (fibre cement sheet or boards); frame: timber - H2 treated softwood.	70	2.50 (or 3.00 including construction); fibreglass batts or roll	nil	wall colour: Light (solar absorptance < 0.48)
external garage wall: cavity brick; frame: light steel frame.	70	rockwool batts, roll or pump-in	nil	
internal wall shared with garage: cavity brick wall; frame: light steel frame.	4	nil; fibreglass batts or roll	nil	
internal wall: plasterboard; frame: light steel frame.	70	none	nil	
internal wall: plasterboard; frame: timber - H2 treated softwood.	70	rockwool batts, roll or pump-in	nil	
ceiling and roof - flat ceiling / flat roof, framed - metal roof, timber - H2 treated softwood.	52	ceiling: 5.7 (up), roof: foil/sarking; ceiling: fibreglass batts or roll; roof: foil/sarking.	nil	roof colour: light (solar absorptance < 0.38); 0.5 to ≤ 1.0% of ceiling area uninsulated

Note	• Insulation specified in this Certificate must be installed in accordance with the ABCB Housing Provisions (Part 13.2.2) of the National Construction Code.
Note	• If the additional ceiling insulation listed in the table above is greater than R3.0, refer to the ABCB Housing Provisions (Part 13.2.3 (6)) of the National Construction Code.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.
Note	• Thermal breaks must be installed in metal framed walls and applicable roofs in accordance with the ABCB Housing Provisions of the National Construction Code.

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Ceiling fans			
The applicant must install at least one ceiling fan in at least one daytime habitable space, such as living room.	✓	✓	✓
<ul style="list-style-type: none"> The minimum number and diameter of ceiling fans in a daytime habitable space must be installed in accordance with the ABCB Housing Provisions (Part 13.5.2) of the National Construction Code . 	✓	✓	✓

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Glazed windows, doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each glazed window and door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
The following requirements must also be satisfied in relation to each window and glazed door:	✓	✓	✓
<ul style="list-style-type: none"> The applicant must install windows and glazed doors in accordance with the height and width, frame and glazing types listed in the table. 	✓	✓	✓
<ul style="list-style-type: none"> Each window and glazed door must have a U- value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. 		✓	✓
The applicant must install the skylights described in the table below, in accordance with the specifications listed in the table. Total skylight area must not exceed 3 square metres (the 3 square metre limit does not include the optional additional skylight of less than 0.7 square metres that does not have to be listed in the table).	✓	✓	✓

Skylight no.	Maximum area (m²)	Skylight specification	Shading device
SK.02	0.90	thermally broken aluminium, double/argon fill clear (U: <=3.5, SHGC: 0.21 - 0.24)	no shading
SK.01	0.90	thermally broken aluminium, double/argon fill clear (U: <=3.5, SHGC: 0.21 - 0.24)	no shading

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing
North facing					
WG02	1200.00	2100.00	timber, single glazed (U-value: Undecided, SHGC: Undecided)	eave 600 mm, 450 mm above head of window or glazed door	not overshadowed
East facing					

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing
WG03	1200.00	2100.00	timber, single glazed (U-value: Undecided, SHGC: Undecided)	eave 600 mm, 450 mm above head of window or glazed door	not overshadowed
WG.04	1200.00	2100.00	timber, single glazed (U-value: Undecided, SHGC: Undecided)	eave 600 mm, 450 mm above head of window or glazed door	not overshadowed
South facing					
WG05	1400.00	1400.00	timber, single glazed (U-value: Undecided, SHGC: Undecided)	eave 600 mm, 450 mm above head of window or glazed door	not overshadowed
WG06	1400.00	1400.00	timber, single glazed (U-value: Undecided, SHGC: Undecided)	eave 600 mm, 450 mm above head of window or glazed door	not overshadowed
West facing					
WG01	1200.00	600.00	timber, single glazed (U-value: Undecided, SHGC: Undecided)	eave 600 mm, 450 mm above head of window or glazed door	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric boosted solar.	✓	✓	✓
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning - non ducted; Energy rating: EER > 4.0		✓	✓
The bedrooms must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		✓	✓
Heating system			
The living areas must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		✓	✓
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		✓	✓
Ventilation			
The applicant must install the following exhaust systems in the development: At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: please select		✓	✓
Kitchen: individual fan, ducted to façade or roof; Operation control: interlocked to light		✓	✓
Laundry: individual fan, ducted to façade or roof; Operation control: interlocked to light		✓	✓
Artificial lighting			
The applicant must ensure that a minimum of 80% of light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		✓	✓
Natural lighting			
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	✓	✓	✓

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Alternative energy			
The applicant must install a photovoltaic system as part of the development. The applicant must connect this system to the development's electrical system.	✓	✓	✓
<p>The photovoltaic system must consist of:</p> <ul style="list-style-type: none"> photovoltaic collectors with the capacity to generate at least 10 peak kilowatts of electricity, installed at an angle between 0 degrees and 10 degrees to the horizontal facing north 	✓	✓	✓

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.