BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A341996

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Friday, 26, April 2019

To be valid, this certificate must be lodged within 3 months of the date of issue.



Pro Pro Stre Loc Plai Lot Sec Pro Dwe Typ add

Project address							
Project name	39B ocean Road						
Street address	39B Ocean Road Palm Beach 2108						
Local Government Area	Northern Beaches Council						
Plan type and number	Deposited Plan 712236						
Lot number	1						
Section number							
Project type							
Dwelling type	Separate dwelling house						
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and does not include a pool (and/or spa).						

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Cadence & Co Design Pty Ltd

ABN (if applicable): 12168714752

BASIX Certificate number: A341996 page 2 / 6

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Hot water			
The applicant must install the following hot water system in the development: gas instantaneous.	✓	~	✓
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		~	✓
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		✓	✓
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		✓	

BASIX Certificate number: A341996 page 3 / 6

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
The applicant must construct the new or altered the table below, except that a) additional insula is not required for parts of altered construction	~	~	~		
Construction	Additional insulation required (R-value)	Other specifications			
suspended floor with open subfloor: framed (R0.7).	R0.8 (down) (or R1.50 including construction)				
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				
raked ceiling, pitched/skillion roof: framed	ceiling: R2.24 (up), roof: foil backed blanket (55 mm)	dark (solar absorptance > 0.70)			

BASIX Certificate number: A341996 page 4 / 6

	equirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows a	and glazed do	ors							
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.							~	~	~
The following requirements must also be satisfied in relation to each window and glazed door:							✓	~	
Each window or glazed door with improved frames, or pyrolytic low-e glass, or clear/air gap/clear glazing, or toned/air gap/clear glazing must have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. The description is provided for information only. Alternative systems with complying U-value and SHGC may be substituted.								✓	~
For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.							✓	✓	✓
Pergolas with adjustable shading may have adjustable blades or removable shade cloth (not less than 80% shading ratio). Adjustable blades must overlap in plan view.								~	~
musi ovena	p p.a v.ov.								
Overshadov					nt and distance from the centre and t	the base of the window and glazed door, as	✓	✓	~
Overshadow specified in	wing buildings or the 'overshadow	ring' colun doors g	nn in the t lazing r	table below.	nts		✓	✓	✓
Overshadow specified in	wing buildings or the 'overshadow	doors g Area of glass inc. frame	nn in the t lazing r	table below.		the base of the window and glazed door, as Frame and glass type	✓	~	✓
Overshadow specified in Windows Window / do	wing buildings or the 'overshadow	doors g Area of glass inc.	lazing r Oversha	table below. equirement adowing Distance	nts		✓	~	✓
Overshadow specified in Windows Window / do no.	wing buildings or the 'overshadow and glazed (oor Orientation	doors g Area of glass inc. frame (m2)	lazing r Oversha Height (m)	requirements adowing Distance (m)	nts Shading device	Frame and glass type improved aluminium, single pyrolytic low-e,	✓	~	✓
Overshadow specified in Windows Window / do no.	wing buildings or the 'overshadow and glazed (oor Orientation	Area of glass inc. frame (m2)	lazing r Oversha Height (m)	requirement adowing Distance (m) 2.5	nts Shading device none	Frame and glass type improved aluminium, single pyrolytic low-e, (U-value: 4.48, SHGC: 0.46) improved aluminium, single pyrolytic low-e,	~	~	~
Overshadow specified in Windows Window / do no.	wing buildings or the 'overshadow and glazed (oor Orientation	Area of glass inc. frame (m2) 1.71 2.16	Iazing r Oversha Height (m) 5	requirements adowing Distance (m) 2.5	nts Shading device none none	improved aluminium, single pyrolytic low-e, (U-value: 4.48, SHGC: 0.46) improved aluminium, single pyrolytic low-e, (U-value: 4.48, SHGC: 0.46) improved aluminium, single pyrolytic low-e, (U-value: 4.48, SHGC: 0.46)	*	~	\

BASIX Certificate number: A341996 page 5 / 6

Glazing requirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Window / door Orientati no.	n Area of glass inc. frame (m2)	Oversha Height (m)	Distance (m)	Shading device	Frame and glass type			
					(U-value: 4.48, SHGC: 0.46)			

BASIX Certificate number: A341996 page 6 / 6

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a "v" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "" in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "
" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.