BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A472776

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Friday, 25, November 2022

To be valid, this certificate must be lodged within 3 months of the date of issue.



Pro Pro Stre Loc Plan Lot Sec Pro Dwe

Project address	
Project name	Chris and Philippa
Street address	29 WARRLE Avenue FAIRLIGHT 2094
Local Government Area	Northern Beaches Council
Plan type and number	Deposited Plan 11828
Lot number	36
Section number	
Project type	
Dwelling type	Separate dwelling house
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and does not include a pool (and/or spa).

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: JJDrafting AUSTRALIA PTY LTD

ABN (if applicable): 651693346

BASIX Certificate number: A472776 page 2 / 6

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		✓	~
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		✓	✓
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		✓	✓
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		✓	

BASIX Certificate number: A472776 page 3 / 6

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check		
Insulation requirements							
The applicant must construct the new or altere the table below, except that a) additional insula is not required for parts of altered construction	√	√	~				
Construction	truction Additional insulation required (R-value) Other specifications						
concrete slab on ground floor.	nil						
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)						
external wall: other/undecided	R1.70 (including construction)						
flat ceiling, pitched roof	ceiling: R1.45 (up), roof: foil backed blanket (55 mm)	medium (solar absorptance 0.475 - 0.70)					

BASIX Certificate number: A472776 page 4 / 6

Glazing requ	irements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows and	glazed do	ors							
					nading devices, in accordance with each window and glazed door.	the specifications listed in the table below.	✓	✓	~
The following re	equirements	must also	be satisfi	ed in relation	to each window and glazed door:			✓	✓
have a U-value	and a Solar	Heat Gair	n Coefficie	ent (SHGC) r		d glass may either match the description, or, le below. Total system U-values and SHGCs s.		✓	✓
					each eave, pergola, verandah, bal han 2400 mm above the sill.	cony or awning must be no more than 500 mm	✓	✓	✓
For projections least that show			he ratio of	the projection	on from the wall to the height above	the window or glazed door sill must be at	✓	✓	✓
Pergolas with p	olycarbonate	roof or s	imilar tran	slucent mate	erial must have a shading coefficien	t of less than 0.35.		✓	✓
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.							✓	✓	
Windows ar	nd glazed o	doors g	lazing r	equiremer	nts		-		
Window / door	Orientation		Oversha	dowing	Shading device	Frame and glass type			
no.		glass inc. frame (m2)	Height (m)	Distance (m)					
W1	W	1.8	0	0	projection/height above sill ratio >=0.36	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W2	S	1.44	0	0	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W3	S	1.44	0	0	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W4	S	3.58	0	0	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			

BASIX Certificate number: A472776 page 5 / 6

Glazing requ	irements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	Distance (m)	Shading device	Frame and glass type			
W5	Е	0.66	0	0	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W6	N	0.66	0	0	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
D1	S	8.09	0	0	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			

PASIX Certificate number: A472776 page 6 / 6

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.