page 1/6

BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A431953 02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv

Date of issue: Thursday, 13, January 2022 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

| Project address | |
|--------------------------------|----------------------------------|
| Project name | 21022_02 |
| Street address | 7 ROUNCE Avenue FORESTVILLE 2087 |
| Local Government Area | Northern Beaches Council |
| Plan type and number | Deposited Plan 200198 |
| Lot number | 11 |
| | |
| Section number | |
| Section number Project type | |
| | Separate dwelling house |

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: RenovatePlans

ABN (if applicable): 16617139296

| Fixtures and systems | Show on DA Plans | Show on CC/CDC Plans & specs | Certifier Check |
|--|---------------------|---------------------------------------|--------------------|
| Lighting | | | |
| The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps. | | ~ | ~ |
| Fixtures | 1 | | |
| The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating. | | \checkmark | \checkmark |
| The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating. | | \checkmark | \checkmark |
| The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating. | | \checkmark | |

| Construction | | | Show on DA Plans | Show on CC/CDC Plans & specs | Certifier Check |
|---|--|----------------------|---------------------|---------------------------------------|--------------------|
| nsulation requirements | | | | | |
| The applicant must construct the new or altere the table below, except that a) additional insul is not required for parts of altered construction | × | ~ | ~ | | |
| Construction | Additional insulation required (R-value) | Other specifications | | | |
| suspended floor with enclosed subfloor: framed (R0.7). | R0.60 (down) (or R1.30 including construction) | | | | |
| | | | | | |
| external wall: framed (weatherboard, fibro, metal clad) | R1.30 (or R1.70 including construction) | | | | |

| | requirements | | | | | | Show on DA Plans | Show on CC/CDC Plans & specs | Certifier Check |
|---|--|---|--|---|---|--|---------------------|---------------------------------------|--------------------|
| Windows | and glazed do | ors | | | | | | | |
| | | | | | nading devices, in accordance with t r each window and glazed door. | the specifications listed in the table below. | ~ | ~ | ~ |
| The follow | ving requirements | must also | be satisf | ied in relatior | n to each window and glazed door: | | | \checkmark | \checkmark |
| have a U-v | value and a Solar | Heat Gair | n Coefficie | ent (SHGC) r | | d glass may either match the description, or, e below. Total system U-values and SHGCs | | ~ | ~ |
| | | | | | each eave, pergola, verandah, balo han 2400 mm above the sill. | cony or awning must be no more than 500 mm | ~ | \checkmark | \checkmark |
| Pergolas v | with polycarbonate | e roof or s | imilar trar | slucent mate | erial must have a shading coefficient | t of less than 0.35. | | ~ | \checkmark |
| External louvres and blinds must fully shade the window or glazed door beside which they are situated when fully drawn or closed. | | | | | | | | _ | |
| | Surves and billings | must fully | snade th | e window or | glazed door beside which they are s | situated when fully drawn or closed. | | \checkmark | \checkmark |
| Pergolas v shades a p | with fixed battens perpendicular wine | must have dow. The | e battens spacing b | parallel to the between batte | e window or glazed door above whic ens must not be more than 50 mm. | situated when fully drawn or closed. ch they are situated, unless the pergola also | - | ~ | <i>✓</i> |
| Pergolas v shades a p Window | with fixed battens perpendicular wind /s and glazed (| must have dow. The doors g | e battens spacing b lazing r | parallel to the between batter equireme l | e window or glazed door above whic ens must not be more than 50 mm. nts | ch they are situated, unless the pergola also | - | ~ | ~ |
| Pergolas v shades a p Window | with fixed battens perpendicular wine | must have dow. The doors g | e battens spacing b lazing r | parallel to the between batter equireme l | e window or glazed door above whic ens must not be more than 50 mm. | | | ~ | ~ |
| Pergolas v shades a p Window / | with fixed battens perpendicular wind /s and glazed (| must have dow. The doors g Area of glass inc. frame | e battens spacing b lazing r Oversha Height | parallel to the between batter equirement adowing Distance | e window or glazed door above whic ens must not be more than 50 mm. nts | ch they are situated, unless the pergola also | | ~ | ~ |
| Pergolas v shades a p Window Window / no. | with fixed battens perpendicular wind /s and glazed door Orientation | must have dow. The doors g Area of glass inc. frame (m2) | e battens spacing b lazing r Oversha Height (m) | parallel to the between batter equiremen adowing Distance (m) | e window or glazed door above whic ens must not be more than 50 mm. nts Shading device | ch they are situated, unless the pergola also Frame and glass type standard aluminium, single clear, (or | | | ~ |
| Pergolas v shades a p Window / No. | with fixed battens perpendicular wind /s and glazed (door Orientation S | must have dow. The doors g Area of glass inc. frame (m2) 0.9 | e battens spacing b lazing r Oversha Height (m) 0 | parallel to the between batter adowing Distance (m) 0 | e window or glazed door above which ens must not be more than 50 mm. nts Shading device none | ch they are situated, unless the pergola also Frame and glass type standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or | | | ~ |
| Pergolas v shades a p Window / no. W1 W2 | with fixed battens perpendicular wind /s and glazed (door Orientation S S | must have dow. The doors g Area of glass inc. frame (m2) 0.9 3.9 | e battens spacing b lazing r Oversha Height (m) 0 0 | parallel to the between batter adowing Distance (m) 0 | e window or glazed door above whice ens must not be more than 50 mm. nts Shading device none none | ch they are situated, unless the pergola also Frame and glass type standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or | | | |

| Glazing requirements | | | | | | | | Show on CC/CDC Plans & specs | Certifier Check |
|----------------------|-------------|---|--------------------------|---------------------------|---|---|--|---------------------------------------|--------------------|
| Window / door no. | Orientation | Area of glass inc. frame (m2) | Oversha Height (m) | dowing Distance (m) | Shading device | Frame and glass type | | | |
| | | | | | | U-value: 7.63, SHGC: 0.75) | | | |
| W7 | W | 1.24 | 0 | 0 | eave/verandah/pergola/balcony >=900 mm | standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) | | | |
| GD1 | N | 6.5 | 0 | 0 | eave/verandah/pergola/balcony >=900 mm | standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) | | | |
| GD2 | E | 5.04 | 0 | 0 | external louvre/blind (adjustable) | standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) | | | |
| GD3 | S | 4.3 | 0 | 0 | none | standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) | | | |

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.