

Lege	nd				
•	Existing trees to be (see sheet 3 & Arb report)				
\bigcirc	Existing trees on a properties	djoining			
	Existing trees as pr Arborist Report	er			
$\overline{\mathbf{\cdot}}$	Proposed evergreen trees				
	Proposed Deciduous tree				
	Palm				
	Succulents				
	Tree Ferms				
	Low shrubs / ornar	nental grasses			
	Screen plants				
	Steps up				
	Private open space	paving			
	Common area pavi	ng			
	Common area line	ar paving			
+ + + + + + + + + + + + + + + + + + +	Groundcovers				
	Turfed areas				
	Timber decking / s	eating			
	Balustrading/fence				
	Water				
	Strip drainage grate Drainage pit	9			
	Stone clad walls				
4	Concrete				
	Walls				
21.29	Proposed levels				
124.55	Survey layer unde	r			
PAUL SCRIVENER					
<u> </u>	LANDS				
PO Box 813 ABN: 627 1	NEWPORT NSW 2 21 448	2106			
PHONE: 02 9907 8011 www.scrivener-design.com Email: Paul@scrivener-design.com					
	Retail & Reside 28 Lockwood Av Belrose, NSW	NTIAL DEVELOPMENT AT VE,			
Dwg:	Landscape Site	Plan			
2	29.11.19 19/2110 D	Scale: 1:200 @A1 Sheet No: 1 of 7			
Figures sintensions sho Olsovinght sithe proce Albini, day azh 44 8 The ilchited sites ghy	c mensions of the site before it on the build be used in preference to those so why of Ramildone Phylical IV- Paul So details and information described in the	ales off. Manar Lancs Sana The clawing are compright. Other than for the our ose			
A disprover under the Co or or written bern ission AM ENDM ENT	coyrgn1∔d,no ca1of 1 may n any	forn or on any means on used or neo odulad a hour NORTH			
	22				





Irrigation notes Automatic drip line watering system to be selected. To extend to all garden areas nominated on the hatched areas on sheet 3 and is to include all raised planter boxes over slab structures. Water supply tap hosecocks to each isolated planterbox for separate irrigation lines with battery timers. (To be coordinated with Hydraulic engineer's details). Dripline supply system only to be incorporated.

following requirements.

Planting schedule

Angophora costata

Banksia serrata

Casuarina glauca Elaeocarpus reticulatus

Pyrus ussariensis

Shrubs / small feature trees

Syzygium leuhmanni

Eriostemon australasius

Bambusa guangxiensis

Ferns / Palms / Succulents / ornamental bamboos

Syzygium 'Superior'

Aga∨e attenuata

Cyathea australe

Cycas revolutum

Draceana draco

Clivea miniata Crinum pedunculatum

Dianella caerulea

Lomandra 'Tanika'

Groundcovers/Climbers

Livistona australis

Dicksonia antarctica

Hardenbergia violacea

Pandorea jasminoides

Trachelospermum asiaticum

Ornamental grasses/strappy leaved plants

Liriope Evergreen Giant

Glochidion ferdinandii

Liriodendron tulifipifera 'Fastgiata' Upright Tulip Tree (vertical med-tall tree)

Archontophoenix cunninghmaniana Bangalow Palm (Tropical style tall palm)

Symbol Botanical name

Canopy trees ANO

BAS

CAG

GLO LTF

PYR

SYL

EOM

AGV

ARC

BGU

CAA

CYR

DA

DRD

LAV

HVI

TJA

CM

CRP

DIC

LIM

LOT

SPP

Generally: Supply an automatic drip line irrigation system. To include all piping to solenoids either PVC lines and/or class 12 pressure pipe or low density, rubber modified polypropeyline reticulation as required to provide water supply to the nominated areas. To be coordinated with Hydraulic engineers plans. To include all bends, junctions, ends, ball valves, solenoids and all other ancillary equipment. Backwash valve: An approved backwash prevention valve is to be located at the primary water source for top up valves to rainwater tanks (where applicable).

Contractor is to provide an irrigation design to meet the

Irrigation system to be supplied from rainwater tanks as nominated on the Hydraulic Engineer's plans with town water top up system.

<u>Chemical</u> root control: Provide standard chemical root inhibiting chemical cartridge. These are to be indust standard, in-line replaceable cartridges located for easy access for replacement cartridge installation

Automatic Controller: Provide automatic 2 week timer with hourly multi-cycle operation for each zone as noted on the irrigation areas plan on sheet 2.

Performance: It shall be the Landscape Contractor's responsibility to ensure and guarantee satisfactory operation of the irrigation system. The system is to be fit for the purpose and should utilize sufficient solenoids to provide for the varying watering requirements of landscape areas to allow all plants and lawn areas to thrive and attain long term viability.

Testing: After the system has been installed to the satisfaction of the project manager, the installation shall be tested under working conditions. Acceptance of the installed plant and equipment shall be subject to these being satisfactory.

Warranty: A twelve month warranty is to be provided in writing by the Landscape Contractor, which shall commit the Landscape Contractor to rectify the system (the items they have installed) to the satisfaction of the project manager or nominated representative. This will apply should any fault develop, or the capacity or efficiency fall below that guaranteed, or should the discharge or pressure be inadequate, or should defects develop in the filter unit or control heads, or any blockages that may develop in the system.

Approvals: The Landscape Contractor is to liaise as necessary, to ensure that the irrigation system conforms with all Water Board, Council and Australian standards (AS)

Detail 6.

Typical planter box drainage detail n.t.s



1. Site preparation Any existing trees and vegetation to be retained shall be preserved and protected from damage of any sort during the execution of landscape work. In particular, root systems of existing plants must not be disturted if possible. Any nearby site works should be carried carefully using hand tools. To ensure the survival and growth of existing trees during landscaping works, protect by fencing or armoring where necessary. Trees shall not be removed or lopped unless specific written approval to do so is given or is indicated on plan. Storage of materials, mixing of materials, vehicle parking, disposal of liquids, machinery repairs and refueling, site office and sheds, and the lighting of fires shall not occur within three (3) metres of any existing trees. Do not stockpile soil, rubble or other debris cleared from the site, or building materials, within the dripline of existing trees. Vehicular access shall not be permitted within three (3) metres of any tree.

2. Soil preparation All proposed planting areas to be deep ripped to 200mm (where possible) and clay soils to be treated with clay breaker.. Apply at least 200mm depth good quality garden soil mix to all garden planting areas. To comply with AS 4419 Turfed areas to be Soft leaf Buffalo or Soft Leaf Buffalo to be laid over 150mm good quality turf underlay over existing soil which is to be deep ripped to 200mm depth prior to installation. To be worked in with rotary hoe except where tree root damage would otherwise occur. In such situations care to be taken to hand cultivate in any area where existing tree roots exist to preserve health of trees and to comply with the requirements of the Arborist's report. Where planting is to occur in existing soil profiles ensute soil conditioners and compots worked into the top 200mm profile. To comply with AS 4454:1999.

3. New plantings Newly planted trees and large shrubs should be secured to stakes with hessian ties to prevent rocking by wird. Planting holes for plant material should be large enough in size to take root ball with additional space to take back filling of good quality planting mix. (Please note mature heights of planting as shown on planting schedule can vary due to site conditions, locations in constricted deep soil or over slab planters and so forth) Also shallow soils in certain locations may affect planting heights. Nominated heights for plantings in raised planters over slabs are nominated as less than their normal expected heights in acknowledgement of the contained soil environment. For other deep soil trees heights are subject to particular site conditions, and intended hedging or pruning for functional requ as available planting width, intended access under branches and solar access.

4. Planter boxes & waterproofing. All slab areas to be waterproofed and 'Atlantis' drainage cell installed with geotextile fabric Refer Engineer's details for structural details for all planter box construction. All internal planter slab levels to fall to drainage outlets as detailed by Engineer. Ensure min 50mm cavity between planter box and building wherever planter joins building with drainage provided. Keep cavity clear of debris by providing capping row butted against building. Exterior finishes as per Architect's detail. Ensure base of cavity is able to drain via drain outlet points in event water seeps into cavity so as to not build up against building wall. Containers to be at height as indicated on Architects' drawing. All planting containers to have the following: • Waterproofing to Engineer's specification and construction details

- of developmen
- Planter box soil mix or equivalet to comply with AS 4419 and AS 3743
- waterproofing of the planter boxes structures prior to slab pour. 5. Mulching
- 6. Fertliser

7. Staking

into ground to a depth able to achieve rigid support. 8. Lawn edging

All ground level garden beds adjacent to site boundary or paved areas to have 150mm raised concrete edging as nominated on the plans. 9. Turfing

10. Structural All structural details whatsoever to Engineer's details

Detail 7. Tree protection measure Type 2 n.t.s. Primary Route 800mm high cyclone mesh fence Zone where possib mounted on steel posts @ approx 1500 intervals. 100mm leaf litter mulch to 2000mm radius around tree to be kept moist with temporary sprinkler system during construction period.



	Common name	Cont. size	Staking	Mature height	No req.
	Sydney Red Gum (large native tree. Striking bark colour)	45Lt	3x50x50x1800	16-25.0M	2
	Old Man Banksia (Small native. Gnarled trunk & serrated leaves)		3x50x50x1800	4-6.0M	2
	Swamp She-Oak (IMed native tree)	45Lt	3x50x50x1800	18-13.0M	5
	Blueberry Ash (indigenous small tree)	45Lt	3x50x50x1800	6-8.0M	6
	Cheese Tree (Indigenous medium tree)	75Lt	3x50x50x1800	8-10.0M	1
a'	Upright Tulip Tree (vertical med-tall tree)	75Lt	3x50x50x1800	10-15.0M	2
	Manchurian Pear (medium deciduous tree)	75Lt	2x50x50x1800	9-12.0M	1
	Small Leaved Lilly Pilly (native screen tree)	75Lt	3x38x38x1800	8-10.0M	10
	Pink Wax Flower (flowering native shrub)	200mm	nil	2.0M	2
	Superior Lilly Pilly (flowering screen plant Can be hedged)	200mm	hedged to req.height	1.6-2.8M	14
I	bamboos				
	Century plant (striking spiky leaved succulent)	200mm	nil	0.5M	12
	Bangalow Palm (Tropical style tall palm)	Semi adv.	wire guys	8-12M	2
	Dwarf Chinese Bamboo (ornamental bamboo can be hedged)	200mm	nil	2-3.5M	12
	Tree Fern (Native tree ferns)	300mm	nil	2-4.0M	10
	Sago Palm (striking native low palm like)	300mm	nil	1-1.2M	5
	Soft Tree Fern (shade tolerant tree fern)	300mm	nil	4.0M	4
	Dragon Tree (striking feature plant)	semi adv.		2.5-3.5M	1
	Cabbage Palm (tall indigenous palm)	semi adv	wire guys	8-12.0M	5
	Native sarsaparilla (native groundcover)	200mm	nil	2.0M	50
	Bower Plant (native climbing/cascading groundcover)	200mm	wire supports on fence	2.5M	10
	Flatmat Star Jasmine (FT01 Ozbbreed hyvrid groundcover)	200mm	nil	0.2M	8
n	ts			0.514	
	Kaffir Lily (shade tolerant groundcover)	200mm	nil	0.5M	28
	Swamp Lily (native mass planted groundcover)	200mm	nil	0.5-0.7	22
	Blue Flax Lily (native grass like plant)	100mm	nil	0.4M	90
	Turf Lily (shade tolerant groundcover)	150mm	nil	0.4M	98
	Dwarf Mat Rush (native mass planted groundcover)	150mm	nil	0.4M	30

Planting schedule species to be sourced from local nurseries supplying plants of local provenance wherever possible. Landscape contractor is to check plant numbers on plan against the schedule prior to submitting tender price. Contact landscape architect if any number discrepancies are found. Council compliance controls require that any substitution of species variety or container size MUST be confirmed with landscape architect to ensure a compliance certificate can be issued that's meets the specific development consent conditions of the project.

General installation notes

• Impervious waterproof membrare along base and to continue up to top of soil level of conttainers • Atlantis' drainage cell (or engineers specified equivalent at base to be connected to drainage system

• Contractor to install all planter box finishes after other site works are completed to ensure no deterioration of waterproof membrane Contractor to be responsible for the integrity of the • All planter boxes are to have automatic dripline irrigation system. Connecting pipes to installed in slab

All planting areas to be mulched with a minimum 75mm thick cover of recycled hard wood chip mulch and then all plant areas to be thoroughly soaked with water. To comply with AS 4454

All planting areas to be fertilised wth 9 month 'NPK' slow release fertiliser.

To those plants indicated on the planting schedules provide: hardwood stakes as nominated and driven

Turfed nature strip areas to be Soft leaf Buffalo or Soft Leaf Buffalo 'shademaster' to be laid over 100mm good quality turf underlay over existing soil which is to be deep ripped to 200mm depth prior to nstallation. 300mm soil underlay over slab areas as per detail 7 sheet 4

Refer to Arborists report prepared by Mark Bury Consulting





Symbo	ol Botanical name	Common name	Cont. size
Canop	y trees		
PLU	Plumeria acutifolia	Frangipani (small flowering deciduous tree)	45Lt
Shrub	s / small feature trees		
SYC	Syzygium 'Cascade'	Cascade Lilly Pilly (flowering screen plant. Can be hedged)	200mm
Ferns	/ Palms / Succulents / ornament	al bamboos	
AGV	Aga∨e attenuata	Century plant (striking spiky leaved succulent)	200mm
ALR	Alacanatarea 'Rubra'	Giant Bromeliade (Large succulent leaved ornamental plant)	300mm
YUC	Yucca elaphantipes	Giant Yucca (multi trunked spiky feature plant)	300mm
Groun	dcovers/Climbers		
MYP	Myoprum par∨ifolium	Creeping Boobliala (native cascading groundcover)	150mm
TJA	Trachelospermum asiaticum	Flatmat Star Jasmine (FT01 Ozbbreed hyvrid groundcover)	200mm
WIS	Wisteria sinensis	Chinese Wisteria (deciduous climber over pergola)	300mm



Symbol	Botanical name	Common name	Cont. size	Stakiı
Canopy (PLU	trees Plumeria acutifolia	Frangipani (small flowering deciduous tree)	45Lt	2x50x5
Shruhe (small feature trees			
MLG	Magnolia 'Little Gem'	Little Gem (small omamental standard tree)	300mm	2x50x5
SYC	Syzygium 'Cascade'	Cascade Lilly Pilly (flowering screen plant. Can be hedged)	200mm	hedged
Ferns / P	Palms / Succulents / ornament	al bamboos		
AGV	Agave attenuata	Century plant (striking spiky leaved succulent)	200mm	nil
ALR	Alacanatarea 'Rubra'	Giant Bromeliade (Large succulent leaved ornamental plant)	300mm	nil
DRD	Draceana draco	Dragon Tree (striking feature plant)	semi adv.	nil
YUC	Yucca elaphantipes	Giant Yucca (multi trunked spiky feature plant)	300mm	nil
Groundc	overs/Climbers	· · · · · · · · · · · · · · · · · · ·	1	
HIS	Hibbertia scandens	Guinea Flower (flowering climber / groundcover)	200mm	nil
MYP	Myoprum parvifolium	Creeping Boobliala (native cascading groundcover)	150mm	nil
TJA	Trachelospermum asiaticum	Flatmat Star Jasmine (FT01 Ozbbreed hyvrid groundcover)	200mm	nil
WIS	Wisteria sinensis	Chinese Wisteria (deciduous climber over pergola)	300mm	over pe

50x1800 3-4.0M 2 50x1800 2.5-3.0M 3 4 to req.height 1.6-2.8M 16 0.5M 6 1.0M 2 2.5-3.5M 1 1.5M 8	ng	Mature height	No req.
to req.height 1.6-2.8M 16 0.5M 6 1.0M 2 2.5-3.5M 1 1.5M 8	50x1 80 0	3-4.0M	2
1.0M 2 2.5-3.5M 1 1.5M 8			
		1.0M 2.5-3.5M	2 1
0.3M 17 0.2M 9 0.2M 18 ergola 5.0M 6	ergola	0.2M	18

+ Proposed evergreen trees Proposed X Deciduous tree + + + + + + + + + + Cascading + + + + + + + + + + groundcovers Succulent Private open space paving Walls See sheet 7 for planter pot types See Arborists report prepared by Mark Bury Consulting PAUL SCRIVENER LANDSCAPE PO BOX 813 NEWPORT NSW 2106 ABN: 627 121 448 Phone: 02 9907 8011 WWW.SCRIVENER-DESIGN.COM EMAIL: PAUL@SCRIVENER-DESIGN.COM PROJECT: RETAIL & RESIDENTIAL DEVELOPMENT AT 28 Lockwood Ave, Belrose, NSW Level 2 Detail plan Dwg: DATE: 29.11.19 Scale: 1:150 @A1 Job Ref: 19/2110 Sheet No: 5 of 7 ISSUE: D Builder must verlig all o mens chs of the site before work commences. Figured o mens chs should be used in preference to those scalad off. Schoping at is the oncoding of Radi Johe Phylic, 14: Paul Schweier Lancstade A.B.M. 35 y 2014 The Incoments Casign, catalus and information castroad in the dawing are congright. Other than for the publica onestroad incent the Coopinghi Act, no bail of it may in any form program means be used or who could distribut or or with the orthoad school school of the standard of the standard school and the standard school of the AMENDMENTS North

Legend























Large format pots schedule - Sizes and type (or approved alternative makes)

Туре	Make & model	Size (mm)	
A	Quatro pots – Tall U Bowl	2200 dia x 1000(h)	
В	Quatro pots - 2000 Square Tall Civic Planter	2000 x 2000 x 1000(h)	
с	Quatro pots - 1200 Square Tall Civic Planter	1200 x 1200 x 800(h)	
D	Quatro pots - 2000 Narrow Tall Planter	2000 x 500 x 1000(h)	
E	Quatro pots - 2200 Tall Civic Trough Planter	2200 x 1000 x 800(h)	

With low foot supports to allow free surface water drainage under. All drainage points on terraces to stormwater engineers details

All pots to have concealed poly dripline irrigation run behind pots and up through base drainage holes. Connect to automatic timer. To be detailed in Construction Certificate drawings

All planters to have approved specified planter box mix min 400mm over B horizon soil fill. To be detailed in Construction Certificate drawings.

800mm high planters to have 200mm high foot risers with no toe holds to ensure min. 1000mm non-climbable faces. To be confirmed by BCA consultant prior to purchase and installation.

All fixed seating benches to be min. 1000mm from any balustrading or planter adjacent to balustrading. To be confirmed by BCA consultant prior to purchase and installation.







JOB/ PLATINUV PROPERTY / BELROSE / 2110



