# **BASIX**°Certificate

Building Sustainability Index www.basix.nsw.gov.au

## **Alterations and Additions**

Certificate number: A401786

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

### Secretary

Date of issue: Thursday, 17, December 2020

To be valid, this certificate must be lodged within 3 months of the date of issue.



# Description of project

Project address						
Project name	Unit 3, 19-21 The Corso, Manly NSW 2095					
Street address	19-21 The Corso Street Manly 2095					
Local Government Area	Manly Council					
Plan type and number	Strata Plan 12989					
Lot number	1,2-13					
Section number						
Project type						
Dwelling type	Unit					
Type of alteration and addition	My renovation work is valued at \$50,000 or more.					

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: JN Consulting

ABN (if applicable): 51003316032

BASIX Certificate number: A401786 page 2 / 5

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check				
Lighting							
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		<b>✓</b>	<b>✓</b>				
Fixtures							
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		<b>✓</b>	<b>~</b>				
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		<b>✓</b>	<b>✓</b>				
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		<b>✓</b>					

BASIX Certificate number: A401786 page 3 / 5

Glazing requ	uirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows an									
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.								<b>V</b>	<b>~</b>
The following requirements must also be satisfied in relation to each window and glazed door:								✓	✓
Each window or glazed door with improved frames, or pyrolytic low-e glass, or clear/air gap/clear glazing, or toned/air gap/clear glazing must have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. The description is provided for information only. Alternative systems with complying U-value and SHGC may be substituted.								<b>~</b>	<b>~</b>
Overshadowing buildings or vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column in the table below.								<b>✓</b>	✓
Windows a	nd glazed	l doors g	lazing r	equireme	nts				
	w / door Orientation Area of Overshadowing Shading device Frame and glass type				Frame and glass type				
no.		glass inc. frame (m2)	Height (m)	Distance (m)					
W1	SW	2.45	3.5	1.2	none	standard aluminium, clear/air gap/clear, (U-value: 5.34, SHGC: 0.67)			
W2	SW	1.22	3.5	1.2	none	standard aluminium, clear/air gap/clear, (U-value: 5.34, SHGC: 0.67)			
W3	SW	1	3.5	1.2	none	standard aluminium, clear/air gap/clear, (U-value: 5.34, SHGC: 0.67)			
W4	NW	1.4	5.5	6.5	none	standard aluminium, toned/air gap/clear, (U-value: 5.31, SHGC: 0.48)			
W5	SE	3.3	0	0	none	timber or uPVC, clear/air gap/clear, (U-value: 3.67, SHGC: 0.59)			
W6	SE	3.5	0	0	none	timber or uPVC, clear/air gap/clear, (U-value: 3.67, SHGC: 0.59)			
W7	SE	3	0	0	none	timber or uPVC, clear/air gap/clear, (U-value: 3.67, SHGC: 0.59)			

BASIX Certificate number: A401786 page 4 / 5

BASIX Certificate number: A401786 page 5 / 5

### Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.