

# Nationwide House Energy Rating Scheme®

## NatHERS® Certificate No. 0011784899

Generated on 14 Mar 2025 using BERS Pro v5.2.4 (3.23)

### Property

**Address** Unit 22A, 22 22 Karingal Crescent,  
FRENCHS FOREST , NSW , 2086

**Lot/DP** Lot 108A DP 36755

**NCC class\*** 1a

**Floor/all Floors** G of 2 floors

**Type** New Home

### Plans

**Main plan** A

**Prepared by** MHDP Architects

### Construction and environment

<b>Assessed floor area [m2]*</b>		<b>Exposure type</b>
Conditioned*	205.4	Suburban
Unconditioned*	5.6	
Total	233.6	<b>NatHERS climate zone</b>
Garage	22.6	56 Mascot (Sydney Airport)



### Accredited assessor

**Name** Adriana Segovia

**Business name** ESD Synergy Pty Ltd

**Email** adrianas@esdsynergy.com

**Phone** 0413591688

**Accreditation No.** 20754

**Assessor Accrediting Organisation** ABSA

**Declaration of interest** Declaration completed: no conflicts

### NCC Requirements

**NCC provisions** Volume Two

**State/Territory variation** Yes

### National Construction Code (NCC) requirements


The NCC allows the use of NatHERS accredited software to comply with the energy efficiency requirements for houses (Class 1 buildings) and apartments (Class 2 sole-occupancy units and Class 4 parts of buildings). The applicable requirements for houses are detailed in Specification 42 of NCC Volume Two. For apartments the requirements are detailed in clauses J3D3 and J3D15 of NCC Volume One.

NCC 2022 includes enhanced thermal performance requirements for houses and apartments. It also includes a new whole-of-home annual energy use budget which applies to the major equipment in the home.

The NCC, and associated ABCB Standards and support material, can be accessed at [www.abcb.gov.au](http://www.abcb.gov.au).

Note, variations and additions to the NCC energy efficiency requirements may apply in some states and territories.

### Thermal performance Star rating



### Thermal performance [MJ/m²]

Limits taken from ABCB Standard 2022

	Heating	Cooling
<b>Modelled</b>	16.3	11.0
<b>Load limits</b>	N/A	N/A
<b>Features determining load limits</b>		
Floor Type (lowest conditioned area)		CSOG
NCC climate zone 1 or 2		No
Outdoor living area		No
Outdoor living area ceiling fan		No

### Whole of Home performance rating

No Whole of Home  
performance rating  
generated for this  
certificate.

### Verification

To verify this certificate,  
scan the QR code or visit  
[hstar.com.au/QR/Generate?](http://hstar.com.au/QR/Generate?p=VKKMCLCDU)  
[p=VKKMCLCDU](http://hstar.com.au/QR/Generate?p=VKKMCLCDU).  
When using either link,  
ensure you are visiting  
[hstar.com.au](http://hstar.com.au)



## About the ratings

### Thermal performance rating

NatHERS thermal software models the expected heating and cooling energy loads using information about the design, construction, climate and common patterns of household use. The thermal performance rating (shown as a star rating on this Certificate) does not take into account appliances, apart from the airflow impacts from ceiling fans.

### Whole of Home performance rating

NatHERS Whole of Home software uses the heating and cooling energy loads combined with the energy performance of the home's appliances (heating, cooling, hot water, lighting, pool/spa pump and onsite renewable energy generation and storage) and models the expected energy value\* of the whole home. The Whole of Home performance rating is shown as a score out of 100 on this Certificate.

## Heating & Cooling Load Limits

### Additional information

In some locations under the NCC NatHERS pathway, separate heating and cooling load limits may apply. Minimum required star ratings in northern parts of Australia may also be affected by the presence or absence of an outdoor living area and/or an outdoor living area ceiling fan. Refer to the *ABC Standard 2022: NatHERS heating and cooling load limits* for details or contact the relevant local building regulating authority, noting that State and Territory variations may also apply.

### Setting Options:

Floor Type:

CSOG – Concrete Slab on Ground  
SF – Suspended Floor (or a mixture of CSOG and SF)  
NA – Not Applicable

NCC Climate Zone 1 or 2:

Yes  
No  
NA – Not Applicable

Outdoor Living Area:

Yes  
No  
NA – Not Applicable

Outdoor Living Area Ceiling Fan:

Yes  
No  
NA – Not Applicable



## Predicted onsite renewable energy impact

No Whole of Home performance assessment conducted for this certificate.

## Predicted Whole of Home annual impact by appliance

### Energy use

No Whole of Home performance assessment conducted for this certificate

### Greenhouse gas emissions

No Whole of Home performance assessment conducted for this certificate

### Cost

No Whole of Home performance assessment conducted for this certificate

## Certificate check

The checklist covers important items impacting the dwelling's ratings. It is recommended that the accuracy of the whole certificate is checked.

Note: The boxes indicate when and by whom each item should be checked. It is not mandatory to complete this checklist.

	Approval Stage		Construction Stage		Occupancy/Other
	Assessor checked	Consent Authority/ Surveyor checked	Builder checked	Consent Authority Surveyor checked	
<b>Genuine certificate check</b>					
Does this Certificate match the one available at the web address or QR code verification link on the front page?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the NatHERS certificate number on the NatHERS-stamped plans match the number on this Certificate?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Thermal performance check</b>					
<b>Windows and glazed doors</b>					
Does the window size, opening type and location shown on the NatHERS-stamped plans or as installed match what is shown in 'Window and glazed door schedule' and 'Roof window schedule' tables on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the installed windows meet the substitution tolerances (AFRC* based SHGC* and U-values*) as shown in the 'Window and glazed door type and performance' and 'Roof window type and performance' tables on this Certificate?			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>External walls</b>					
Does the external wall bulk insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the External wall type table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the external wall shade (colour) match what is shown in the 'External wall type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Floor</b>					
Does the floor insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Floor type' table on this certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Ceiling penetrations*</b>					
Does the 'quantity' and 'type' of ceiling penetrations* (e.g. downlights, exhaust fans, etc) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling penetrations' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Ceiling</b>					
Does the ceiling insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Roof</b>					
Does the external roof shade (colour) on the NatHERS stamped plans or as installed match what is shown in the 'Roof type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Apartment entrance doors (NCC Class 2 assessments only)</b>					
Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>
<b>Exposure*</b>					
Has the appropriate exposure type (terrain) (shown on page 1) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>
<b>Heating and cooling load limits*</b>					
Do the load limits settings (shown on page 1) match what is shown	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

## Certificate check

Continued

	Approval Stage		Construction Stage		
	Assessor checked	Consent Authority/ Surveyor checked	Builder checked	Consent Authority Surveyor checked	

### Additional NCC requirements for thermal performance (not included in the NatHERS assessment)

#### Thermal bridging

Does the dwelling meet the NCC requirement for thermal bridging?

☐ ☐ ☐ ☐

#### Insulation installation method

Has the insulation been installed according to the NCC requirements?

☐ ☐ ☐

#### Building sealing

Does the dwelling meet the NCC requirements for Building Sealing?

☐ ☐ ☐ ☐

### Whole of Home performance check (not applicable if a Whole of Home performance assessment is not conducted)

#### Appliances

Does the cooling appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the Appliance schedule on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the heating appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or installed, match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the hot water system type and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the pool pump efficiency/performance shown on the NatHERS-stamped plans or as installed match the minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the onsite renewable energy system type, orientation and system size or generation capacity shown on the NatHERS stamped plans or installed match the 'Onsite Renewable Energy schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

### Additional NCC Requirements for Services (not included in the NatHERS assessment)

Does the lighting meet the artificial lighting requirements specified in the NCC?

☐ ☐ ☐ ☐

Does the hot water system meet the additional requirements specified in the NCC?

☐ ☐ ☐ ☐

#### Provisional values\* check

Have provisional values\* been used in the assessment and, if so, are they noted in 'Additional notes' table below?

☐ ☐ ☐ ☐

#### Other NCC requirements

Note: This Certificate only covers the energy efficiency requirements in the NCC. Additional requirements that must also be satisfied include, but are not limited to: condensation, structural and fire safety requirements and any state or territory variations to the NCC energy efficiency requirements.

#### Additional notes

No lighting plan available. Certificate to be revised once lighting plan is available

Default sealed exhaust fans to kitchen, bathrooms, ensuites and laundry

Floor coverings: Tiles to wet areas only, Carpet to Bedrooms, Timber Elsewhere

Studs &amp; rafters: Timber

## Room schedule

Room	Zone Type	Area [m <sup>2</sup> ]
MP	Living	14.34
Kitchen/Living1	Kitchen/Living	50.15
Laundry	Bedroom	3.62
Bath1	Unconditioned	5.63
Garage 1	Garage	22.57
G Hall	Daytime	20.57
Bedroom 1	Bedroom	34.75
Bedroom 2	Bedroom	10.62
Bedroom 3	Bedroom	11.96
Bedroom 4	Bedroom	10.95
WIR	Nighttime	7.56
Ens	Nighttime	7.46
Store	Daytime	1.79
Bath2	Daytime	7.75
WC	Daytime	2.06
L1 Hall	Daytime	23.67

## Window and glazed door type and performance

### Default windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
ATB-003-04 B	AI Thermally Broken A	3.1	0.27	0.26	0.28
	DG Air Fill Low Solar				
	Gai				
ATB-004-04 B	AI Thermally Broken B	3.1	0.27	0.26	0.28
	DG Air Fill Low Solar				
	Gai				

### Custom windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
BRZ-006-008	Aluminium Louvre Window SG 6LE	4.3	0.48	0.45	0.50

\* Refer to glossary.



## Window and glazed door *schedule*

Location	Window ID	Window no.	Height [mm]	Width [mm]	Window type	Opening %	Orientation	Window shading device*
MP	ATB-003-04 B	W8	2150	500	Awning	90	E	No
MP	ATB-003-04 B	W11	2150	500	Awning	90	E	No
MP	ATB-003-04 B	W6	2150	500	Awning	90	NW	No
Kitchen/Living1	BRZ-006-008-001	W10	2250	700	Louvre	90	NE	No
Kitchen/Living1	ATB-004-04 B	W9	2700	2700	Sliding	60	NW	Yes
Kitchen/Living1	ATB-004-04 B	W18	2700	2700	Sliding	60	NW	Yes
Bath1	ATB-003-04 B	n/a	500	500	Awning	90	NE	No
Bath1	ATB-003-04 B	n/a	500	500	Awning	90	NE	No
G Hall	ATB-004-04 B	W20	2700	500	Fixed	00	SE	No
G Hall	ATB-004-04 B	W19	2700	700	Fixed	00	SE	No
G Hall	ATB-003-04 B	W21	1700	1200	Awning	45	NE	No
Bedroom 1	BRZ-006-008-001	W12	1400	600	Louvre	90	NE	No
Bedroom 1	BRZ-006-008-001	W13	1400	600	Louvre	90	NE	No
Bedroom 1	ATB-004-04 B	n/a	1650	4000	Sliding	10	SE	Yes
Bedroom 2	BRZ-006-008-001	W17	2250	650	Louvre	90	NE	No
Bedroom 2	ATB-004-04 B	W16	2250	650	Fixed	00	NE	No
Bedroom 3	ATB-003-04 B	n/a	1350	1000	Awning	10	NW	No
Bedroom 3	ATB-003-04 B	n/a	1350	1000	Awning	10	NW	No
Bedroom 3	ATB-003-04 B	n/a	1350	1000	Awning	10	NW	No
Bedroom 4	ATB-003-04 B	n/a	1350	1000	Awning	10	NW	No
Bedroom 4	ATB-003-04 B	n/a	1350	1000	Awning	10	NW	No
Bedroom 4	ATB-003-04 B	n/a	1350	1000	Awning	10	NW	No
Ens	ATB-003-04 B	n/a	500	900	Awning	90	NE	No
Ens	ATB-003-04 B	W14	500	900	Awning	90	NE	No
L1 Hall	ATB-004-04 B	W15	600	2500	Fixed	00	NE	No

\* Refer to glossary.



## Roof window\* type and performance value

### Default roof windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

### Custom roof windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
VEL-011-01 W	VELUX FS - Fixed Skylight DG 3mm LoE 366 / 8.5mm Argon Gap / 5.36mm Clear La	2.6	0.24	0.23	0.25

## Roof window\* schedule

Location	Window ID	Window no.	Opening %	Height [mm]	Width [mm]	Orientation	Outdoor shade	Indoor shade
Bath2	VEL-011-01 W	S4	0	800	800	NW	Yes	Yes
L1 Hall	VEL-011-01 W	S7	0	1100	1100	NW	Yes	Yes
L1 Hall	VEL-011-01 W	S8	0	700	550	NW	Yes	Yes

## Skylight\* type and performance

Skylight ID	Skylight description	Skylight shaft reflectance
No Data Available		

## Skylight\* schedule

Location	Skylight ID	Skylight No.	Skylight shaft length [mm]	Area [m <sup>2</sup> ]	Orientation	Outdoor shade	Diffuser
No Data Available							

## External door schedule

Location	Height [mm]	Width [mm]	Opening %	Orientation
Garage 1	2200	2700	90	SE
G Hall	2700	1300	90	SE



## External wall type

Wall ID	Wall type	Solar absorptance	Wall shade [colour]	Bulk insulation [R-value]	Reflective wall wrap*
EW-1	Timber Stud Frame Brick Veneer	0.50		Foil reflective both sides of the Bulk Insulation R2.3	Yes
EW-2	Timber Stud Frame Brick Veneer	0.85		Foil reflective both sides of the Bulk Insulation R2.3	Yes
EW-3	Timber Stud Frame Brick Veneer	0.30		Foil reflective both sides of the Bulk Insulation R2.3	Yes
EW-4	Weatherboard Timber Stud Frame Panel Direct Fix	0.85		Foil reflective both sides of the Bulk Insulation R2.3	Yes
EW-5	Fibro Timber Stud Frame Panel Direct Fix	0.85		Foil reflective both sides of the Bulk Insulation R2.3	Yes
EW-6	Weatherboard Timber Stud Frame Panel Direct Fix	0.30		Foil reflective both sides of the Bulk Insulation R2.3	Yes

## External wall schedule

Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature [yes/no]
MP	EW-1	2700	4916	E	0	No
MP	EW-1	2700	400	SE	0	No
MP	EW-1	2700	800	NW	0	No
Kitchen/Living1	EW-1	2700	6995	NE	0	No
Kitchen/Living1	EW-1	2700	7200	NW	0	Yes
Bath1	EW-1	2700	3290	NE	0	No
Garage 1	EW-1	2700	3595	SE	2100	No
G Hall	EW-2	2701	200	SE	0	No
G Hall	EW-3	2700	2600	SE	1000	No
G Hall	EW-2	2701	800	SE	500	No
G Hall	EW-3	2700	1600	SW	3600	No
G Hall	EW-1	2700	1895	NE	0	No
Bedroom 1	EW-4	900	4195	NE	0	No
Bedroom 1	EW-5	1800	4195	NE	0	No
Bedroom 1	EW-4	900	1600	SE	0	No
Bedroom 1	EW-5	1801	1600	SE	0	No
Bedroom 1	EW-4	900	4200	SE	0	No
Bedroom 1	EW-5	1800	4200	SE	400	No

\* Refer to glossary.





Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature [yes/no]
Bedroom 1	EW-6	2701	1400	SE	0	No
Bedroom 2	EW-6	2700	2995	NE	0	No
Bedroom 2	EW-6	2700	600	SE	10100	No
Bedroom 3	EW-6	2700	3995	NE	0	No
Bedroom 3	EW-6	2700	3295	NW	400	No
Bedroom 4	EW-6	2700	3895	NW	400	Yes
Ens	EW-4	900	3195	NE	0	No
Ens	EW-5	1800	3195	NE	0	No
Ens	EW-4	900	600	NW	0	No
Ens	EW-5	1800	600	NW	10100	No
L1 Hall	EW-4	2700	2690	NE	600	No

## Internal wall type

Wall ID	Wall type	Area [m <sup>2</sup> ]	Bulk insulation
IW-001	Timber Stud Frame, Direct Fix Plasterboard	46.98	Bulk Insulation, No Air Gap R2.5
IW-002	Timber Stud Frame, Direct Fix Plasterboard	174.15	No insulation
IW-003	Cavity brick, plasterboard	46.17	No Insulation
IW-004	Cavity brick	0.00	No Insulation

## Floor type

Location	Construction	Area [m <sup>2</sup> ]	Sub-floor ventilation	Added insulation [R-value]	Covering
MP	Concrete Slab on Ground 150mm	14.30	None	Bulk Insulation in Contact with Floor R2.3	Cork Tiles or Parquetry 8mm
Kitchen/Living1	Concrete Slab on Ground 150mm	50.15	None	Bulk Insulation in Contact with Floor R2.3	Cork Tiles or Parquetry 8mm
Laundry	Concrete Slab on Ground 150mm	3.62	None	Bulk Insulation in Contact with Floor R2.3	Ceramic Tiles 8mm



Location	Construction	Area [m <sup>2</sup> ]	Sub-floor ventilation	Added insulation [R-value]	Covering
Bath1	Concrete Slab on Ground 150mm	5.63	None	Bulk Insulation in Contact with Floor R2.3	Ceramic Tiles 8mm
Garage 1	Concrete Slab on Ground 150mm	22.57	None	Bulk Insulation in Contact with Floor R2.3	Bare
G Hall	Concrete Slab on Ground 150mm	20.57	None	Bulk Insulation in Contact with Floor R2.3	Cork Tiles or Parquetry 8mm
Bedroom 1 / Bath1	Timber Framed Timber Above Plasterboard 19mm	3.78		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 1 / Garage 1	Timber Framed Timber Above Plasterboard 19mm	11.34		Bulk Insulation R2.5	Carpet+Rubber Underlay 18mm
Bedroom 1 / G Hall	Timber Framed Timber Above Plasterboard 19mm	13.22		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 1	Suspended Floor Timber Frame 19mm	5.44	Totally Open	Bulk Insulation in Contact with Floor R1.5	Carpet+Rubber Underlay 18mm
Bedroom 2 / Kitchen/Living1	Timber Framed Timber Above Plasterboard 150mm	10.62		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 3 / Kitchen/Living1	Timber Framed Timber Above Plasterboard 150mm	11.96		No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 4 / Kitchen/Living1	Timber Framed Timber Above Plasterboard 150mm	10.95		No Insulation	Carpet+Rubber Underlay 18mm
WIR / Garage 1	Timber Framed Timber Above Plasterboard 150mm	7.20		Bulk Insulation R2.5	Carpet+Rubber Underlay 18mm
Ens / MP	Timber Framed Timber Above Plasterboard 150mm	5.05		No Insulation	Ceramic Tiles 8mm
Ens / Bath1	Timber Framed Timber Above Plasterboard 150mm	1.78		No Insulation	Ceramic Tiles 8mm
Store / Laundry	Timber Framed Timber Above Plasterboard 150mm	0.43		No Insulation	Cork Tiles or Parquetry 8mm
Store / Garage 1	Timber Framed Timber Above Plasterboard 150mm	1.19		Bulk Insulation R2.5	Cork Tiles or Parquetry 8mm
Bath2 / Kitchen/Living1	Timber Framed Timber Above Plasterboard 150mm	7.75		No Insulation	Ceramic Tiles 8mm



Location	Construction	Area [m <sup>2</sup> ]	Sub-floor ventilation	Added insulation [R-value]	Covering
WC / Kitchen/Living1	Timber Framed Timber Above Plasterboard 150mm	2.06		No Insulation	Ceramic Tiles 8mm
L1 Hall / MP	Timber Framed Timber Above Plasterboard 150mm	2.23		No Insulation	Cork Tiles or Parquetry 8mm
L1 Hall / Kitchen/Living1	Timber Framed Timber Above Plasterboard 150mm	3.25		No Insulation	Cork Tiles or Parquetry 8mm
L1 Hall / Laundry	Timber Framed Timber Above Plasterboard 150mm	0.41		No Insulation	Cork Tiles or Parquetry 8mm
L1 Hall / Garage 1	Timber Framed Timber Above Plasterboard 150mm	0.21		Bulk Insulation R2.5	Cork Tiles or Parquetry 8mm
L1 Hall / G Hall	Timber Framed Timber Above Plasterboard 150mm	5.17		No Insulation	Cork Tiles or Parquetry 8mm

## Ceiling type

Location	Construction material/type	Bulk insulation R-value (may include edge batt values)	Reflective wrap* [yes/no]
MP	Plasterboard on Timber	Bulk Insulation R2.5	
MP	Timber Framed Timber Above Plasterboard	No Insulation	
Kitchen/Living1	Timber Framed Timber Above Plasterboard	No Insulation	
Laundry	Timber Framed Timber Above Plasterboard	No Insulation	
Bath1	Timber Framed Timber Above Plasterboard	No Insulation	
Garage 1	Timber Framed Timber Above Plasterboard	Bulk Insulation R2.5	
G Hall	Timber Framed Timber Above Plasterboard	No Insulation	
Bedroom 1	Plasterboard on Timber	Bulk Insulation R5	
Bedroom 2	Plasterboard on Timber	Bulk Insulation R5	
Bedroom 3	Plasterboard on Timber	Bulk Insulation R5	
Bedroom 4	Plasterboard on Timber	Bulk Insulation R5	
WIR	Plasterboard on Timber	Bulk Insulation R5	
Ens	Plasterboard on Timber	Bulk Insulation R5	
Store	Plasterboard on Timber	Bulk Insulation R5	
Bath2	Plasterboard on Timber	Bulk Insulation R5	
WC	Plasterboard on Timber	Bulk Insulation R5	
L1 Hall	Plasterboard on Timber	Bulk Insulation R5	

## Ceiling penetrations\*

Location	Quantity	Type	Diameter [mm]	Sealed/unsealed
Kitchen/Living1	1	Exhaust Fans	300	Sealed
Laundry	1	Exhaust Fans	300	Sealed
Bath1	1	Exhaust Fans	300	Sealed
Ens	1	Exhaust Fans	300	Sealed
Bath2	1	Exhaust Fans	300	Sealed
WC	1	Exhaust Fans	300	Sealed

## Ceiling fans

Location	Quantity	Diameter [mm]
No Data Available		

## Roof type

Construction	Added insulation [R-value]	Solar absorptance	Roof shade [colour]
Corrugated Iron Timber Frame	Bulk, Reflective Side Down, No Air Gap Above R2.3	0.50	Medium
Corrugated Iron Timber Frame	No Insulation, Only an Air Gap	0.50	Medium

## Thermal bridging schedule for steel frame elements

Building element	Steel section dimensions [height x width, mm]	Frame spacing [mm]	Steel thickness [BMT,mm]	Thermal break [R-value]
No Data Available				

## Appliance schedule

(not applicable if a Whole of Home performance assessment is not conducted for this certificate)

Note: A flat assumption of 5W/m<sup>2</sup> is used for lighting, therefore lighting is not included in the appliance schedule.

### Cooling system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available				



## Heating system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available				

## Hot water system

Appliance/ system type	Fuel type	Hot Water CER Zone	Minimum efficiency /STC	Zone 3 STC	Zone 3 Substitution tolerance ranges		Assessed daily load [litres]
					lower limit	upper limit	
No Data Available							

## Pool/spa equipment

Appliance/ system type	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available			

## Onsite Renewable Energy Schedule

System Type	Orientation	System Size Or Generation Capacity
No Data Available		

## Battery Schedule

System Type	Size [Battery Storage Capacity]
No Data Available	



## Explanatory notes

### About this report

NatHERS ratings are a reliable guide for comparing different dwelling designs and to demonstrate that designs meet the energy efficiency requirements in the National Construction Code.

NatHERS ratings use computer modelling to evaluate a home's energy efficiency and performance. They use localised climate data and standard assumptions on how people use their home to predict the heating and cooling energy loads and energy value\* of the whole home. The thermal performance star rating uses the home's building specifications, layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings) to predict the heating and cooling energy loads. The Whole of Home performance rating uses information about the home's appliances and onsite energy generation and storage to estimate the home's energy value\*.

The actual energy loads, cost and greenhouse gas emissions of a home may vary from that predicted. This is because the assumptions will not always match the actual occupant usage patterns. For example, the number of occupants and how people use their appliances will vary.

Energy efficient homes use less energy, are warmer on cool days, cooler on hot days and cost less to run.

### Accredited assessors

For quality assured NatHERS Certificates, always use an accredited or licenced assessor registered with an Assessor Accrediting Organisation (AAO). AAOs have strict quality assurance processes, and professional development requirements ensuring consistently high standards for assessments.

Non-accredited assessors (Raters) have no ongoing training requirements and

are not quality assured.

Any queries about this report should be directed to the assessor. If the assessor is unable to address questions or concerns, contact the AAO specified on the front of this certificate.

### Disclaimer

The NatHERS Certificate format is developed by the NatHERS Administrator. However, the content in the certificate is entered by the assessor. It is the assessor's responsibility to use NatHERS accredited software correctly and follow the NatHERS Technical Note to produce a NatHERS Certificate.

The predicted annual energy load, cost and greenhouse gas emissions in this NatHERS Certificate are an estimate based on an assessment of the dwelling's design by the assessor. It is not a prediction of actual energy use, cost or emissions. The information and ratings may be used to compare how other dwellings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, behaviour, appliance performance, indoor air temperature and local climate.

Not all assumptions made by the assessor using the NatHERS accredited software tool are presented in this report and further details or data files may be obtained from the assessor.

## Glossary

<b>AFRC</b>	Australian Fenestration Rating Council
<b>Annual energy load</b>	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
<b>Assessed floor area</b>	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
<b>Ceiling penetrations</b>	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, range hoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
<b>COP</b>	Coefficient of performance
<b>Conditioned</b>	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
<b>Custom windows</b>	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
<b>Default windows</b>	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
<b>EER</b>	Energy Efficiency Ratio, measure of how much cooling can be achieved by an air conditioner for a single kWh of electricity input
<b>Energy use</b>	This is your home's rating without solar or batteries.
<b>Energy value</b>	The net cost to society including, but not limited to, costs to the building user, the environment and energy networks (as defined in the ABCB Housing Provisions Standard).
<b>Entrance door</b>	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
<b>Exposure</b>	see exposure categories below.
<b>Exposure category – exposed</b>	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
<b>Exposure category – open</b>	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
<b>Exposure category – protected</b>	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
<b>Exposure category – suburban</b>	terrain with numerous, closely spaced obstructions over 10 m e.g. city and industrial areas.
<b>Horizontal shading feature</b>	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
<b>National Construction Code (NCC) Class</b>	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at <a href="http://www.abcb.gov.au">www.abcb.gov.au</a> .
<b>Net zero home</b>	a home that achieves a net zero energy value*.
<b>Opening percentage</b>	the operability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
<b>Provisional value</b>	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at <a href="http://www.nathers.gov.au">www.nathers.gov.au</a>
<b>Recommended capacity</b>	this is the capacity or size of equipment that is recommended by NatHERS to achieve the desired comfort conditions in the zone or zones serviced. This is a recommendation and the final selection sizing should be confirmed by a suitably qualified person.
<b>Reflective wrap</b> (also known as foil)	can be applied to walls, roofs and ceilings. When combined with an appropriate airgap and emissivity value, it provides insulative properties.
<b>Roof window</b>	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
<b>Shading features</b>	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
<b>Skylight</b> (also known as roof lights)	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.
<b>Solar heat gain coefficient (SHGC)</b>	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
<b>STCs</b>	Small-scale Technology Certificates, certificates created by the REC registry for renewable energy technologies that may be bought and sold as part of the Small-scale Renewable Energy Scheme operated by the Clean Energy Regulator (CER)
<b>Thermal breaks</b>	are materials with an R-value greater than or equal to 0.2 that must separate the metal frame from the cladding. This includes, but is not limited to, materials such as timber battens greater than or equal to 20mm thick or continuous thermal breaks such as polystyrene insulation sheathing or plastic strips
<b>U-value</b>	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
<b>Unconditioned</b>	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions.
<b>Vertical shading features</b>	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).
<b>Window shading device</b>	device fixed to windows that provides shading e.g. window awnings or screens but excludes horizontal* or vertical shading features* (eg eaves and balconies)

\* Refer to glossary.